


Programming Languages – Functional Languages

Mahmoud Abdelsalam

Functional Programming

- Recall – In functional programming, you can write programs **ONLY** using pure functions and immutable values.
 - This is, however, not how it works in many cases.
- 


Functional Programming concepts

- Pure functions & side effects
- Referential transparency
- First class functions & higher order functions
- Immutability
- Recursion & tail-recursion
- Lambda functions
- Strict and lazy evaluation
- Pattern matching

Functional Programming concepts

- Pure functions & side effects
- Referential transparency
- First class functions & higher order functions
- Immutability
- Recursion & tail-recursion
- Lambda functions
- Strict and lazy evaluation
- Pattern matching

Pure Functions & Side Effects

- Pure functions, just **maps** input to output.
 - No I/O operations
 - No input modifications
 - No console reads/prints
 - No database calls
 - No global variable usage/modifications
- 

Pure Functions & Side Effects

- Pure functions, just **maps** input to output.
 - No I/O operations
 - No input modifications
 - No console reads/prints
 - No database calls
 - No global variable usage/modifications

Simply: It can't affect the outside world in anyway since this will be a **side effect**!

Referential Transparency

Referential transparency can be used to
check if a function is pure!

HOW?



Referential Transparency

Referential transparency can be used to
check if a function is pure!


HOW?



If you can replace an expression with its value
without changing the program behavior

Referential Transparency - Examples

```
def add1(i: Int) : Int = {  
    i + 1  
}
```



```
def add1(i: Int): Int = {  
    println(i)  
    i + 1  
}
```

Referential Transparency - Examples

```
def add1(i: Int) : Int = {  
    i + 1  
}
```

Replace add1(x) with the value of x + 1.
Does it change the program behavior?

```
def add1(i: Int): Int = {  
    println(i)  
    i + 1  
}
```

Referential Transparency - Examples

```
def add1(i: Int) : Int = {  
    i + 1  
}
```



Replace `add1(x)` with the value of `x + 1`.
Does it change the program behavior?

```
def add1(i: Int): Int = {  
    println(i)  
    i + 1  
}
```

Referential Transparency - Examples

```
def add1(i: Int) : Int = {  
    i + 1  
}
```



Replace `add1(x)` with the value of `x + 1`.
Does it change the program behavior?

```
def add1(i: Int): Int = {  
    println(i)  
    i + 1  
}
```



Referential Transparency - Examples

Math.sqrt(4.0)



Referential Transparency - Examples

Math.sqrt(4.0)

Can you replace *Math.sqrt(4.0)* with 2.0
without changing the program behavior?



Referential Transparency - Examples

Math.sqrt(4.0)

Can you replace *Math.sqrt(4.0)* with 2.0
without changing the program behavior?



Referential Transparency - Examples

Math.sqrt(4.0)

Can you replace *Math.sqrt(4.0)* with 2.0
without changing the program behavior?



var i: Int = 1

def addi(j: Int): Int = i + j

Referential Transparency - Examples

Math.sqrt(4.0)

Can you replace *Math.sqrt(4.0)* with 2.0
without changing the program behavior?



var i: Int = 1

def addi(j: Int): Int = i + j

Can you replace *addi(10)* with it's
corresponding value everywhere in the
program without changing it's behavior?

Referential Transparency - Examples

Math.sqrt(4.0)

Can you replace *Math.sqrt(4.0)* with 2.0
without changing the program behavior?




var i: Int = 1

def addi(j: Int): Int = i + j

Can you replace *addi(10)* with it's
corresponding value everywhere in the
program without changing it's behavior?



Recall – Why Pure functions?

- Safe programming – no side effects
 - Easy to test
 - Composable
 - Results can be cached
 - Can be lazy (discussed later)
- 
- A solid red square is located on the left side of the slide, below the list of bullet points.

Functional Programming concepts

- Pure functions & side effects
- Referential transparency
- First class functions & higher order functions
- Immutability
- Recursion & tail-recursion
- Lambda functions
- Strict and lazy evaluation
- Pattern matching

First Class Functions & Higher Order Functions

- First class functions:
 - NOT ONLY declared and called, but CAN also be used in every segment of the language as any other data type.
 - Everything a variable can do, a function can do.



First Class Functions & Higher Order Functions

- First class functions:
 - NOT ONLY declared and called, but CAN also be used in every segment of the language as any other data type.
 - Everything a variable can do, a function can do.
 - 1) Created in literal form without ever having been assigned an identifier

First Class Functions & Higher Order Functions

- First class functions:
 - NOT ONLY declared and called, but CAN also be used in every segment of the language as any other data type.
 - Everything a variable can do, a function can do.
 - 1) Created in literal form without ever having been assigned an identifier
 - 2) Can be stored in a container such as a variable

First Class Functions & Higher Order Functions

- First class functions:
 - NOT ONLY declared and called, but CAN also be used in every segment of the language as any other data type.
 - Everything a variable can do, a function can do.
 - 1) Created in literal form without ever having been assigned an identifier
 - 2) Can be stored in a container such as a variable
 - 3) Can be used as a parameter to another function

First Class Functions & Higher Order Functions

- First class functions:
 - NOT ONLY declared and called, but CAN also be used in every segment of the language as any other data type.
 - Everything a variable can do, a function can do.
 - 1) Created in literal form without ever having been assigned an identifier
 - 2) Can be stored in a container such as a variable
 - 3) Can be used as a parameter to another function
 - 4) Can be used as the return value from another function

First Class Functions & Higher Order Functions

- First class functions:
 - NOT ONLY declared and called, but CAN also be used in every segment of the language as any other data type.
 - Everything a variable can do, a function can do.
 - 1) Created in literal form without ever having been assigned an identifier
 - 2) Can be stored in a container such as a variable
 - 3) Can be used as a parameter to another function
 - 4) Can be used as the return value from another function
 - All functions are first class functions by default in Scala.
- Higher order functions either:
 - Use other functions as parameters
 - Use functions as return values

First Class Functions & Higher Order Functions - Example

Examples from: <https://docs.scala-lang.org/tour/higher-order-functions.html>

- 1) Created in literal form without ever having been assigned an identifier

First Class Functions & Higher Order Functions - Example

Examples from: <https://docs.scala-lang.org/tour/higher-order-functions.html>

- 1) Created in literal form without ever having been assigned an identifier

$$(x: Int) \Rightarrow x * 2$$

Known as literal/anonymous function

First Class Functions & Higher Order Functions - Example

2) Can be stored in a container such as a variable



First Class Functions & Higher Order Functions - Example

2) Can be stored in a container such as a variable

$$\textit{val double} = (x: \textit{Int}) \Rightarrow x * 2$$

First Class Functions & Higher Order Functions - Example

3) Can be used as a parameter to another function



First Class Functions & Higher Order Functions - Example

3) Can be used as a parameter to another function

```
val salaries = List(10, 20 50)
```

```
val double = (x: Int) => x * 2
```

```
val newSalaries = salaries.map(double)
```


First Class Functions & Higher Order Functions - Example

3) Can be used as a parameter to another function

```
val salaries = List(10, 20 50)
```

```
val double = (x: Int) => x * 2
```

```
val newSalaries = salaries.map(double)
```

Can be rewritten as:

```
val salaries = List(10, 20, 50)
```

```
val newSalaries = salaries.map(x => x * 2)
```

First Class Functions & Higher Order Functions - Example

3) Can be used as a parameter to another function

```
val salaries = List(10, 20 50)
```

```
val double = (x: Int) => x * 2
```


```
val newSalaries = salaries.map(double)
```

Can be rewritten as:

```
val salaries = List(10, 20, 50)
```

```
val newSalaries = salaries.map(x => x * 2)
```

Anonymous function



First Class Functions & Higher Order Functions - Example

4) Can be used as the return value from another function



First Class Functions & Higher Order Functions - Example

4) Can be used as the return value from another function

```
def urlBuilder (use_ssl: Boolean, domainName: String): (String,  
String) => String = {  
    val ssl = if (use_ssl) "https://" else "http://"  
    (endpoint: String, query: String) => ssl + domainName + "/"  
        + endpoint + "?" + query  
}
```

First Class Functions & Higher Order Functions - Example

4) Can be used as the return value from another function

```
val domainName = "www.example.com"  
def getURL = urlBuilder(true, domainName)  
val endpoint = "users"  
val query = "id=1"  
val url = getURL(endpoint, query)  
println("url: " + url) //url: https://www.example.com/users?id=1
```

Functional Programming concepts

- Pure functions & side effects
- Referential transparency
- First class functions & higher order functions
- Immutability
- Recursion & tail-recursion
- Lambda functions
- Strict and lazy evaluation
- Pattern matching