



# *Programming Languages – Functional Languages*

---

Mahmoud Abdelsalam

# Functional Programming concepts

- Pure functions & side effects
- Referential transparency
- First class functions & higher order functions
- Immutability
- Recursion & tail-recursion
- Lambda functions
- Strict and lazy evaluation
- Pattern matching

# Functional Programming concepts – Lambda Functions

- Lambda function is a function literal (anonymous function) – Recall Previous lecture.

# Functional Programming concepts – Lambda Functions

- Lambda function is a function literal (anonymous function) – Recall Previous lecture.

*val add = (a: Int, b: Int) => a + b*

# Functional Programming concepts – Lambda Functions

- Lambda function is a function literal (anonymous function) – Recall Previous lecture.

*val add = (a: Int, b: Int) => a + b*

*val add: (Int, Int) => Int = (a, b) => a + b*

# Functional Programming concepts – Lambda Functions

- Lambda function is a function literal (anonymous function) – Recall Previous lecture.

*val add = (a: Int, b: Int) => a + b*

*val add: (Int, Int) => Int = (a, b) => a + b*

Even Better:

*val add: (Int, Int) => Int = \_ + \_*

*//Each underscore stands for a new  
unnamed parameter*

# Functional Programming concepts

- Pure functions & side effects
- Referential transparency
- First class functions & higher order functions
- Immutability
- Recursion & tail-recursion
- Lambda functions
- Strict and lazy evaluation
- Pattern matching

# Functional Programming concepts – Strict and Lazy Evaluation

- Strict evaluation:
  - Used by most traditional programming languages





# Functional Programming concepts – Strict and Lazy Evaluation

- Strict evaluation:
  - Used by most traditional programming languages
  - Evaluates an expression as soon as it is bound to a variable

# Functional Programming concepts – Strict and Lazy Evaluation

- Strict evaluation:
  - Used by most traditional programming languages
  - Evaluates an expression as soon as it is bound to a variable, for example:

*val x = 1 + 2 // x = 3 at this line*

# Functional Programming concepts – Strict and Lazy Evaluation

- Strict evaluation:
  - Used by most traditional programming languages
  - Evaluates an expression as soon as it is bound to a variable, for example:

*val x = 1 + 2 // x = 3 at this line*

*val x = add(1, 2) // x = 3*

# Functional Programming concepts – Strict and Lazy Evaluation

- Strict evaluation:
  - Used by most traditional programming languages
  - Evaluates an expression as soon as it is bound to a variable, for example:

*val x = 1 + 2 // x = 3 at this line*

*val x = add(1, 2) // x = 3*

*val date = new java.util.Date //Data is determined at this line*

# Functional Programming concepts – Strict and Lazy Evaluation

- Lazy evaluation:
  - Delays the evaluation of an expression until its value is needed



# Functional Programming concepts – Strict and Lazy Evaluation

- Lazy evaluation:
  - Delays the evaluation of an expression until its value is needed, for example:

*val x = 1 + 2 // x is NOT 3 at this line*  
*println(x) // x = 3 at this line*

# Functional Programming concepts – Strict and Lazy Evaluation

- Lazy evaluation:
  - Delays the evaluation of an expression until its value is needed, for example:

***lazy** val x = 1 + 2 // x is NOT 3 at this line  
println(x) // x = 3 at this line*

# Functional Programming concepts – Strict and Lazy Evaluation

- Lazy evaluation:
  - Delays the evaluation of an expression until its value is needed, for example:

*lazy val x = 1 + 2 // x is NOT 3 at this line*  
*println(x) // x = 3 at this line*

*lazy val x = add(1, 2) // x is NOT 3 at this line*  
*println(x) // x = 3 at this line*



# Functional Programming concepts – Strict and Lazy Evaluation

*val date = new java.util.Date //Data is NOT determined at this line*

*println(date) //data is set at this point*

Note: might have a delay between the time it is defined and the time it is needed (used)

# Functional Programming concepts – Strict and Lazy Evaluation

- Example:

*val date = new java.util.Date*

*lazy val lazy\_date = new java.util.Date*

*Thread.sleep(5000) //Sleep for 5 seconds*

*println(date)*

*println(lazy\_date) //Print time with 5*

*seconds after “date”*

# Functional Programming concepts – Strict and Lazy Evaluation

- Another Example:

```
lazy val lazy_add: (Int, Int) => Int =  
    {println("Lazy"); _ + _}
```

```
val add: (Int, Int) => Int =  
    {println("Strict"); _ + _}
```

```
lazy val l = lazy_add(1, 2)
```

```
val s = add(1, 2)
```

```
println(l)
```

**Output:**

Strict

Lazy

3

# Functional Programming concepts

- Pure functions & side effects
- Referential transparency
- First class functions & higher order functions
- Immutability
- Recursion & tail-recursion
- Lambda functions
- Strict and lazy evaluation
- Pattern matching