

GalSim Library Quick Reference

1. Overview

The GalSim Library provides a number of Python classes and methods for simulating astronomical images. The typical work flow will normally be something like the following:

- Construct a representation of your desired astronomical object as an instance of the `GObject` class. Multiple components can be combined or in combination using the special `Add` and `Convolve` `GObjects` — see Section 2.
- Apply transformations such as shears, shifts or magnification using the methods of the `GObject` — see Section 3.
- Draw the object into a GalSim `Image`, representing a postage stamp image of your astronomical object. This can be done using the `obj.draw(...)` or `obj.drawShoot(...)` methods carried by all `GObjects` for rendering images — see Section 3.
- Add noise to the `Image` using one of the GalSim random deviate classes — see Section 4.
- Add the postage stamp `Image` to a subsection of a larger `Image` instance, or to a list of `Image` instances multiple `Image` instances in preparation for output — see Section 5.
- Save the `Image(s)` to file in FITS (Flexible Image Transport System) format — see Section 5.

There are many examples of this workflow in the directory `GalSim/examples/`, showing most of the GalSim library in action, in the scripts named `demo1.py` – `demo8.py`.

We now provide a brief, reference description of the GalSim classes and methods which can be used in this workflow. Where possible in the following Sections this document has been hyperlinked to the online GalSim documentation generated by *doxygen* where a more detailed description can be found.

2. The GSOBJects

There are currently 12 types of GSOBJect. The first ten listed are ‘simple’ GSOBJects that can be initialized by providing values for their required or optional parameters. The last two are ‘compound’ classes used to represent combinations of GSOBJects. They are summarized in the following hyperlinked list, in the order in which the classes appear in `GalSim/galsim/base.py`:

- Gaussian — *a 2D Gaussian light profile.*
- Moffat — *a Moffat profile, used to approximate ground-based telescope PSFs.*
- AtmosphericPSF — *currently an image-based implementation of a Kolmogorov PSF (see below), but expected to evolve to use an image of a stochastically modelled atmospheric PSF in the near future.*
- Airy — *an Airy PSF for ideal diffraction through a circular aperture, with optional obscuration.*
- Kolmogorov — *the Kolmogorov PSF for long-exposure images through a turbulent atmosphere.*
- OpticalPSF — *a simple model for non-ideal (aberrated) propagation through circular or square apertures, with optional obscuration.*
- Pixel — *used for integrating light onto square or rectangular pixels.*
- Sérsic — *the Sérsic family of galaxy light profiles.*
- Exponential — *the Exponential galaxy disc profile, a Sérsic with index $n = 1$.*
- DeVaucouleurs — *the De Vaucouleurs galaxy bulge profile, a Sérsic with index $n = 4$.*
- RealGalaxy — *models galaxies using real data, including a correction for the original PSF. Requires the download of external data for full functionality.*
- Add — *a compound object used for summing multiple GSOBJects.*
- Convolve — *a compound object used for convolving multiple GSOBJects.*

For more information and initialization details for each GSOBJect, the Python docstring for each class is available by typing

```
>>> print galsim.<GSOBJectName>.__doc__
```

within the Python interpreter, for example `print galsim.Sérsic.__doc__`. Alternatively follow the hyperlinks on the class names above to view the *doxygen* documentation based on the Python docstrings.

3. Important GSOBJECT methods

A number of methods are shared by all the GSOBJECTS of Section 2, and are also to be found in `GalSim/galsim/base.py` within the definition of the GSOBJECT base class. In what follows, we assume that a GSOBJECT labelled `obj` has been instantiated using one of the calls described in the documentation linked above. For example,

```
>>> obj = galsim.Sersic(n=3.5, half_light_radius=1.743).
```

Some of the most important and commonly-used methods for such an instance are:

- `obj.copy()` — *return a copy of the GSOBJECT.*
- `obj.centroid()` — *return the (x,y) centroid of the GSOBJECT as a PositionD (see Section 6).*
- `obj.getFlux()` — *get the flux of the GSOBJECT.*
- `obj.scaleFlux(flux_ratio)` — *multiply the flux of the GSOBJECT by flux_ratio.*
- `obj.setFlux(flux)` — *set the flux of the GSOBJECT to flux.*
- `obj.applyTransformation(ellipse)` — *apply an Ellipse transformation represented by ellipse to the GSOBJECT (see Ellipse; Section 6).*
- `obj.applyDilation(scale)` — *change of the linear size of the GSOBJECT by a factor scale, conserving flux.*
- `obj.applyMagnification(scale)` — *dilate linear size by scale and multiply total flux by scale², conserving surface brightness.*
- `obj.applyShear(*args, **kwargs)` — *apply a shear to the GSOBJECT, handling a number of different input conventions (see also Shear; Section 6).*
- `obj.applyRotation(theta)` — *apply a rotation of theta (positive direction anti-clockwise) to the GSOBJECT, where theta is an Angle instance (see Section 6).*
- `obj.applyShift(dx, dy)` — *apply a (dx,dy) position shift to the GSOBJECT centroid.*
- `obj.draw(...)` — *draw an image of the GSOBJECT using Discrete Fourier Transforms and interpolation to perform the image rendering.*
- `obj.drawShoot(...)` — *draw an image of the GSOBJECT by shooting a finite number of photons to perform the image rendering. The resulting image therefore contains stochastic noise, but the rendering is otherwise very close to exact.*

Once again, for more information regarding each `GSObject` method, the Python docstring is available

```
>>> print obj.<methodName>.__doc__
```

within the Python interpreter. Alternatively follow the hyperlinks on the class names above to view the *doxygen* documentation based on the Python docstrings. You will see that many of the `GSObject` instances also have their own specialized methods, often for retrieving parameter values. Examples are `obj.getSigma()` for the Gaussian, or `obj.getHalfLightRadius()` for many of the `GSObjects`.

4. Random deviate classes and methods

A short summary of the 8 random deviates currently implemented in GalSim, with a short description of their distributions:

- `UniformDeviate` — *uniform distribution in the interval $[0, 1)$.*
- `GaussianDeviate` — *Gaussian distribution with mean and standard deviation σ .*
- `BinomialDeviate` — *Binomial distribution for N trials each of probability p .*
- `PoissonDeviate` — *Poisson distribution with a single mean rate.*
- `CCDNoise` — *a basic detector noise model, parameterized by gain and read noise.*
- `WeibullDeviate` — *Weibull distribution family (includes Rayleigh and Exponential) with shape parameters a and b .*
- `GammaDeviate` — *Gamma distribution with parameters α and β .*
- `Chi2Deviate` — *χ^2 distribution with degrees-of-freedom parameter n .*

Unfortunately the random deviate classes are not yet fully integrated within the *doxygen* documentation, due to their being C++ with compiled Python wrappers. This means that the class names above and methods below are not yet hyperlinked.

However, the full docstrings are available in `galsim/random.py`, so please refer there for more information, or type

```
>>> print galsim.<RandomDeviateName>.__doc__
```

within the Python interpreter.

We now illustrate the most commonly-used methods of the random deviates, assuming that some random deviate instance `dev` has been instantiated, for example by

```
>>> dev = galsim.GaussianDeviate(sigma=3.9, mean=50.).
```

The two most important and commonly-used methods for such an instance are:

- `dev.applyTo(image)` — *adds a random number, distributed according to the distribution represented by `dev`, to each element in a supplied `Image` instance `image` (see Section 5).*
- `dev()` — *returns a new random number drawn from the distribution represented by `dev`.*

5. Image classes and methods

The GalSim `Image` classes store array data, along with a figure for the pixel separation in physical units and image bounds information (origin, extent). The `ImageView` provides a mutable view into `Image` instance data, and `ConstImageView` an immutable view into `Image` instance data. The full docstrings are available in `galsim/image.py` with a description of the differences between these fundamental types.

They are used to store the rendered output of the `GSObject` `obj.draw(...)` and `obj.drawShoot(...)` methods. They can also be operated on to add stochastic noise simulating real astronomical images (see Section 4), and have methods for writing to FITS format output.

There are four types of GalSim `Image`, one for each of four supported array data types:

- `ImageS`; `ImageViewS`; `ConstImageViewS` — *for short integers (typically 16 bit).*
- `ImageI`; `ImageViewI`; `ConstImageViewI` — *for integers (typically 32 bit).*
- `ImageF`; `ImageViewF`; `ConstImageViewF` — *for single precision (typically 32 bit) floats.*
- `ImageD`; `ImageViewD`; `ConstImageViewD` — *for double precision (typically 64 bit) floats.*

Unfortunately the `Image` classes are not yet fully integrated within the *doxygen* documentation, due to their being in C++ with compiled Python wrappers. This means that the class names above and methods below are not hyperlinked.

However, the full docstrings are available in `galsim/image.py`, so please refer there for more information, or type

```
>>> print galsim.<ImageName>.__doc__
```

within the Python interpreter.

We now illustrate the most commonly-used methods of `Image` class instances. We will assume that some image `img` has been instantiated, for example by

```
im = obj.draw(dx=1.).
```

The most important and commonly-used methods for such an instance are:

- `img.addNoise(dev)` — (see `galsim/noise.py`) *this adds stochastic noise, distributed as represented by the random deviate instance dev, to each element of the data array in img. This therefore has the same effect as `dev.applyTo(img)` (see Section 4).*
- `img.write(image, fits, ...)` — (see `galsim/fits.py`) *write the image to a FITS file or object as determined by the fits input parameter.*
- `img.writeMulti(image_list, fits, ...)` — (see `galsim/fits.py`) *write multiple images stored in a Python list object image_list to a Multi-Extension FITS file or object as determined by the fits input parameter.*
- `img.writeCube(image_list, fits, ...)` — (see `galsim/fits.py`) *write multiple images stored in a Python list object image_list to a three-dimensional FITS datacube object as determined by the fits input parameter.*

6. Miscellaneous classes and methods

A summary of miscellaneous GalSim library objects:

- `Angle` — (see `galsim/angle.py`) *class to represent angles and handle multiple unit types.*
- `PositionI` & `PositionD` — (see `galsim/position.py`) *classes to represent 2D positions on the plane.*
- `Ellipse` — (see `galsim/ellipse.py`) *class to represent ellipses and thus ellipse-type transformations. The class can be initialized using a variety of different parameter conventions.*
- `Shear` — (see `galsim/shear.py`) *class to represent shears in a variety of ways. Like the Ellipse, this class can be initialized using a variety of different parameter conventions.*

As ever docstrings for the class strings above can be accessed via

```
>>> print galsim.<ClassName>.__doc__
```

within the Python interpreter.