

GalSim Quick Reference

1. Overview

The GalSim package provides a number of Python classes and methods for simulating astronomical images. The package is imported into Python with

```
>>> import galsim
```

and the typical work flow will normally be something like the following:

- Construct a representation of your desired astronomical object as an instance of the `GSObject` class. Multiple components can be combined or in combination using the special `Add` and `Convolve` classes — see Section 2.
- Apply transformations such as shears, shifts or magnification using the methods of the `GSObject` — see Section 3.
- Draw the object into a GalSim `Image`, representing a postage stamp image of your astronomical object. This can be done using the `obj.draw(...)` or `obj.drawShoot(...)` methods carried by all `GSObjects` for rendering images — see Section 3.
- Add noise to the `Image` using one of the GalSim random deviate classes — see Section 4.
- Add the postage stamp `Image` to a subsection of a larger `Image` instance, or to a list of `Image` instances multiple `Image` instances in preparation for output — see Section 5.
- Save the `Image(s)` to file in FITS (Flexible Image Transport System) format — see Section 5.

There are many examples of this workflow in the directory `GalSim/examples/`, showing most of the GalSim library in action, in the scripts named `demo1.py` – `demo8.py`.

We now provide a brief, reference description of the GalSim classes and methods which can be used in this workflow. Where possible in the following Sections this document has been hyperlinked to the online GalSim documentation generated by *doxygen* where a more detailed description can be found.

2. The GSOBJECTS

There are currently 12 types of `GSOBJECT`. The first ten listed are ‘simple’ `GSOBJECTS` that can be initialized by providing values for their required and optional parameters. The last two are ‘compound’ classes used to represent combinations of `GSOBJECTS`.

They are summarized in the following hyperlinked list, in which we also give the required parameters for initializing each class in parentheses after the class name. For more information and initialization details for each `GSOBJECT`, the Python docstring for each class is available by typing

```
>>> print galsim.<GSOBJECTName>.__doc__
```

within the Python interpreter, for example `print galsim.Sersic.__doc__`. Alternatively follow the hyperlinks on the class names to view the *doxygen* documentation based on the Python docstrings.

In the order in which the classes appear in `GalSim/galsim/base.py`:

- `galsim.Gaussian(...)`
a 2D Gaussian light profile.
- `galsim.Moffat(beta, ...)`
a Moffat profile with slope parameter beta, used to approximate ground-based telescope PSFs.
- `galsim.AtmosphericPSF(...)`
currently an image-based implementation of a Kolmogorov PSF (see below), but expected to evolve to use an image of a stochastically modelled atmospheric PSF in the near future.
- `galsim.Airy(lam_over_diam, ...)`
an Airy PSF for ideal diffraction through a circular aperture, parameterized by the wavelength-aperture diameter ratio lam_over_diam, with optional obscuration.
- `galsim.Kolmogorov(...)`
the Kolmogorov PSF for long-exposure images through a turbulent atmosphere.
- `galsim.OpticalPSF(lam_over_diam, ...)`
a simple model for non-ideal (aberrated) propagation through circular or square apertures, parameterized by the wavelength-aperture dimension ratio lam_over_diam, with optional obscuration.
- `galsim.Pixel(xw, ...)`
used for integrating light onto square or rectangular pixels, requires at least one side dimension xw.
- `galsim.Sersic(n, ...)`
the Sérsic family of galaxy light profiles, parameterized by an index n.
- `galsim.Exponential(...)`
the Exponential galaxy disc profile, a Sérsic with index n=1.

- `galsim.DeVaucouleurs(...)`
the De Vaucouleurs galaxy bulge profile, a Sérsic with index $n=4$.
- `galsim.RealGalaxy(real_galaxy_catalog, ...)`
models galaxies using real data, including a correction for the original PSF. Requires the download of external data, stored and input in `real_galaxy_catalog`, for full functionality.
- `galsim.Add(...)`
a compound object used for summing multiple `GSOBJECTS`.
- `galsim.Convolve(...)`
a compound object used for convolving multiple `GSOBJECTS`.

3. Important GSOBJECT methods

A number of methods are shared by all the `GSOBJECTS` of Section 2, and are also to be found in `Galsim/galsim/base.py` within the definition of the `GSOBJECT` base class. In what follows, we assume that a `GSOBJECT` labelled `obj` has been instantiated using one of the calls described in the documentation linked above. For example,

```
>>> obj = galsim.Sersic(n=3.5, half_light_radius=1.743).
```

Some of the most important and commonly-used methods for such an instance are:

- `obj.copy()`
return a copy of the `GSOBJECT`.
- `obj.centroid()`
return the (x,y) centroid of the `GSOBJECT` as a `PositionD` (see Section 6).
- `obj.getFlux()`
get the flux of the `GSOBJECT`.
- `obj.scaleFlux(flux_ratio)`
multiply the flux of the `GSOBJECT` by `flux_ratio`.
- `obj.setFlux(flux)`
set the flux of the `GSOBJECT` to `flux`.
- `obj.applyTransformation(ellipse)`
apply an `Ellipse` transformation represented by `ellipse` to the `GSOBJECT` (see `Ellipse`; Section 6).

- `obj.applyDilation(scale)`
change of the linear size of the `GSOBJect` by a factor `scale`, conserving flux.
- `obj.applyMagnification(scale)`
dilate linear size by `scale` and multiply total flux by $scale^2$, conserving surface brightness.
- `obj.applyShear(...)`
apply a shear to the `GSOBJect`, handling a number of different input conventions (see also `Shear`; Section 6).
- `obj.applyRotation(theta)`
apply a rotation of `theta` (positive direction anti-clockwise) to the `GSOBJect`, where `theta` is an `Angle` instance (see Section 6).
- `obj.applyShift(dx, dy)`
apply a (dx, dy) position shift to the `GSOBJect` centroid.
- `obj.draw(...)`
draw an image of the `GSOBJect` using Discrete Fourier Transforms and interpolation to perform the image rendering.
- `obj.drawShoot(image, ...)`
draw an image of the `GSOBJect` by shooting a finite number of photons into a user-supplied `Image` instance, `image`, which unlike for `draw()` is a required input. The resulting rendering therefore contains stochastic noise, but uses few approximations.

Once again, for more information regarding each `galsim.GSOBJect` method, the Python docstring is available

```
>>> print obj.<methodName>.__doc__
```

within the Python interpreter. Alternatively follow the hyperlinks on the class names above to view the *doxygen* documentation based on the Python docstrings. You will see that many of the `GSOBJect` instances also have their own specialized methods, often for retrieving parameter values. Examples are `obj.getSigma()` for the Gaussian, or `obj.getHalfLightRadius()` for many of the `GSOBJects`.

4. Random deviate classes and methods

A short summary of the 8 random deviates currently implemented in GalSim, with a short description of their distributions, parameterizations and default parameter values:

- `galsim.UniformDeviate(...)`
uniform distribution in the interval $[0, 1)$.

- `galsim.GaussianDeviate(..., mean=0., sigma=1.)`
Gaussian distribution with mean and standard deviation `sigma`.
- `galsim.BinomialDeviate(..., N=1, p=0.5)`
Binomial distribution for `N` trials each of probability `p`.
- `galsim.PoissonDeviate(..., mean=1.)`
Poisson distribution with a single mean rate.
- `galsim.CCDNoise(..., gain=1., read.noise=0.)`
a basic detector noise model, parameterized by `gain` and `read.noise`.
- `galsim.WeibullDeviate(..., a=1., b=1.)`
Weibull distribution family (includes Rayleigh and Exponential) with shape parameters `a` and `b`.
- `galsim.GammaDeviate(..., alpha=1., beta=1.)`
Gamma distribution with parameters `alpha` and `beta`.
- `galsim.Chi2Deviate(..., n=1.)`
 χ^2 distribution with degrees-of-freedom parameter `n`.

Unfortunately the random deviate classes are not yet fully integrated within the *doxygen* documentation, due to their being C++ with compiled Python wrappers. This means that the class names above and methods below are not yet hyperlinked.

However, the full docstrings are available in `galsim/random.py`, so please refer there for more information, or type

```
>>> print galsim.<RandomDeviateName>.__doc__
```

within the Python interpreter.

We now illustrate the most commonly-used methods of the random deviates, assuming that some random deviate instance `dev` has been instantiated, for example by

```
>>> dev = galsim.GaussianDeviate(sigma=3.9, mean=50.).
```

The two most important and commonly-used methods for such an instance are:

- `dev.applyTo(image)`
*adds a random number, distributed according to the distribution represented by `dev`, to each element in in a supplied *Image* instance `image` (see Section 5).*
- `dev()`
returns a new random number drawn from the distribution represented by `dev`.

5. Image classes and methods

The GalSim Image classes store array data, along with a figure for the pixel separation in physical units and image bounds information (origin, extent). The `ImageView` provides a mutable view into Image instance data, and `ConstImageView` an immutable view into Image instance data. The full docstrings are available in `galsim/image.py` with a description of the differences between these fundamental types.

They are used to store the rendered output of the `obj.draw(...)` and `obj.drawShoot(...)` methods. They can also be operated on to add stochastic noise simulating real astronomical images (see Section 4), and have methods for writing to FITS format output.

There are four types of GalSim Image, one for each of four supported array data types:

- `galsim.ImageS(...); galsim.ImageViewS(...); galsim.ConstImageViewS(...)`
for short integers (typically 16 bit).
- `galsim.ImageI(...); galsim.ImageViewI(...); galsim.ConstImageViewI(...)`
for integers (typically 32 bit).
- `galsim.ImageF(...); galsim.ImageViewF(...); galsim.ConstImageViewF(...)`
for single precision (typically 32 bit) floats.
- `galsim.ImageD(...); galsim.ImageViewD(...); galsim.ConstImageViewD(...)`
for double precision (typically 64 bit) floats.

Unfortunately the Image classes are not yet fully integrated within the *doxygen* documentation, due to their being in C++ with compiled Python wrappers. This means that the class names above and methods below are not hyperlinked.

However, the full docstrings are available in `galsim/image.py`, so please refer there for more information, or type

```
>>> print galsim.<ImageName>.__doc__
```

within the Python interpreter.

We now illustrate the most commonly-used methods of Image class instances. We will assume that some image `img` has been instantiated, for example by

```
image = obj.draw(dx=1.).
```

The most important and commonly-used methods for such an instance are:

- `image.addNoise(dev)`
this adds stochastic noise, distributed as represented by the random deviate instance `dev`, to each element of the data array in `image`. This therefore has the same effect as `dev.applyTo(image)` (see Section 4; also `galsim/noise.py`).
- `image.write(fits, ...)`
write the `image` to a FITS file or object as determined by the `fits` input parameter (see `galsim/fits.py`).

6. Miscellaneous classes and functions

A summary of miscellaneous GalSim library objects:

- `galsim.Angle(value, angle_unit)`
class to represent angles and handle multiple unit types, which can be initialized using a numerical value and an `AngleUnit` instance `angle_unit` (see `galsim/angle.py`).
- `galsim.AngleUnit(radians)`
class for holding angular unit definitions, specified on initialization in radians.
- `galsim.PositionI(x, y)` & `galsim.PositionD(x, y)`
classes to represent 2D positions on the x-y plane (see `galsim/position.py`).
- `galsim.Ellipse(...)`
class to represent ellipses and thus ellipse-type transformations. The class can be initialized using a variety of different parameter conventions (see `galsim/ellipse.py`).
- `galsim.Shear(...)`
class to represent shears in a variety of ways. Like the `galsim.Ellipse`, this class can be initialized using a variety of different parameter conventions (see `galsim/shear.py`).
- `galsim.fits.writeMulti(image_list, fits, ...)`
write multiple `Image` instances stored in a Python list object `image_list` to a Multi-Extension FITS file or object as determined by the `fits` input parameter (see `galsim/fits.py`).
- `galsim.fits.writeCube(image_list, fits, ...)`
write multiple `Image` instances stored in a Python list object `image_list` to a three-dimensional FITS datacube object as determined by the `fits` input parameter (see `galsim/fits.py`).

As ever docstrings for the classes and functions above can be accessed via

```
>>> print galsim.<Name>.__doc__
```

within the Python interpreter.