

Data Manipulation

Irfan Emrah Kanat, Arianna Sammarchi

2023-02-01

In this document, I will try to walk you through some simple data manipulation examples. As one might guess, data manipulation is sometimes more of an art, than science. Thus, what I can effectively teach you will be limited. We will learn some basic manipulations with dplyr package and vanilla R. dplyr provides a set of sensible functions to throw data around.

```
library(dplyr)
```

We will conduct our exercise on Worldbank GDP figures and continent information.

The GDP figures data is in GDP.csv. Let us read in the file.

```
GDP<-read.csv("GDP.csv")
head(GDP)
```

```
##      Country ISO2      X2003      X2004      X2005      X2006      X2007      X2008
## 1      Aruba  AW          NA          NA          NA          NA          NA          NA
## 2      Andorra AD          NA          NA          NA          NA          NA          NA
## 3 Afghanistan AF  1096.756  1066.685  1145.717  1173.001  1297.821  1310.717
## 4      Angola AO  3818.663  4086.858  4667.346  5444.890  6452.560  7102.870
## 5      Albania AL  6286.205  6699.225  7119.290  7537.454  8055.857  8747.208
## 6 Arab World <NA> 11595.944 12407.232 12856.602 13434.034 13860.418 14377.830
##      X2009      X2010      X2011      X2012
## 1      NA      NA  36016.484      NA
## 2      NA      NA      NA      NA
## 3  1547.539  1637.297  1695.153  1893.076
## 4  7038.957  7047.052  7094.084  7230.497
## 5  9129.176  9559.157  9897.180 10157.164
## 6 14354.814 14759.051 14825.910 15342.795
```

As you can see, the data is in what we call the wide format. Each row is a country and observations over time are in columns.

Let us also get the second data set: Continents and country codes.

```
Continents<-read.csv("continent.csv")
head(Continents)
```

```
##  ISO2 Continent
## 1   AD        EU
## 2   AE        AS
## 3   AF        AS
## 4   AG        AN
## 5   AI        AN
## 6   AL        EU
```

Combine Two Datasets

The most basic operation you can do with two datasets is to combine them. If you want to append new observations to an existing dataset, use `rbind`. If you want to append new variables to an existing dataset, use `cbind`. Note that the columns/rows need to be compatible in such combinations.

```
# Append one dataset to another
# Append rows
rbind(Continents[1:3,] ,Continents[231:233,])
```

```
##      ISO2 Continent
## 1      AD          EU
## 2      AE          AS
## 3      AF          AS
## 231    UA          EU
## 232    UG          AF
## 233    UM          OC
```

```
# Append columns
cbind(Continents[1:3,] ,Continents[231:233,])
```

```
##      ISO2 Continent ISO2 Continent
## 1      AD          EU    UA          EU
## 2      AE          AS    UG          AF
## 3      AF          AS    UM          OC
```

If you want to combine two datasets based on the values of a common column however, you will need to do a merge. Merging is similar to a join operation in SQL if you are familiar with it.

Below is the syntax for `merge()`

```
merge(x, y, by = intersect(names(x), names(y)), by.x = by, by.y = by, all = FALSE, all.x = all, all.y = all,
sort = TRUE, suffixes = c("x", "y"))
```

As you can see, a lot of the parameters are optional (have default values). Let us use `merge` to join `Continents` dataset to `GDP` dataset.

```
cData <- merge(Continents, GDP)
head(cData)
```

```
##      ISO2 Continent      Country      X2003      X2004      X2005
## 1      AD          EU      Andorra          NA          NA          NA
## 2      AE          AS United Arab Emirates 110549.415 111543.925 103139.799
## 3      AF          AS      Afghanistan   1096.756   1066.685   1145.717
## 4      AG          AN Antigua and Barbuda 19566.329 20395.483 21414.230
## 5      AL          EU      Albania    6286.205   6699.225   7119.290
## 6      AM          AS      Armenia    4181.720   4635.303   5296.814
##      X2006      X2007      X2008      X2009      X2010      X2011      X2012
## 1          NA          NA          NA          NA          NA          NA          NA
## 2 96399.737 83655.038 73611.390 61725.280 57379.972 56376.770 57044.578
## 3 1173.001 1297.821 1310.717 1547.539 1637.297 1695.153 1893.076
## 4 24016.311 26007.825 25736.016 22388.957 20567.359 19987.924 20577.292
## 5 7537.454 8055.857 8747.208 9129.176 9559.157 9897.180 10157.164
## 6 6019.860 6877.382 7382.525 6357.829 6507.914 6812.352 7290.639
```

I did not need to specify which column to merge on as `by` has a default value of `intersect(names(x), names(y))`. This means, if there are common column names between two datasets the two will be merged on common column names.

Let us go over some of the more commonly used parameters.

by, by.x, by.y: column name to merge on between quotation marks. If the two datasets have different names, use by.x and by.y to separately specify the column names.

```
merge(Continents, GDP, by = "IS02")
```

all, all.x, all.y: It determines what to do with rows that can not be matched in both datasets. From an SQL perspective, the all parameters specify the type of join operation. all.x = TRUE left join (keep rows from left table even if not matched), all.y = TRUE left join, and all = TRUE for an outer join.

Subset Rows Based on Column Values

If you want to select certain rows of output based on a column, this is what you do. When we wanted to filter certain observations in the first session we used indexing with logical operations before.

Let us select observations in Oceania first.

First let us see how this is done in R:

```
# displaying the first 6 columns to conserve space
# !is.na bit is required due to how R matches the == with NA's
cData[cData$Continent == "OC" & !is.na(cData$Continent),1:6]
```

##	IS02	Continent	Country	X2003	X2004	X2005
## 9	AS	OC	American Samoa	NA	NA	NA
## 11	AU	OC	Australia	37035.053	38129.815	38840.241
## 60	FJ	OC	Fiji	6804.258	7149.390	7168.896
## 61	FM	OC	Micronesia, Fed. Sts.	3320.158	3220.141	3301.392
## 75	GU	OC	Guam	NA	NA	NA
## 98	KI	OC	Kiribati	1801.492	1825.938	1791.892
## 123	MH	OC	Marshall Islands	3182.515	3183.256	3271.808
## 129	MP	OC	Northern Mariana Islands	NA	NA	NA
## 138	NC	OC	New Caledonia	NA	NA	NA
## 145	NZ	OC	New Zealand	29754.461	30355.860	30984.473
## 149	PF	OC	French Polynesia	NA	NA	NA
## 150	PG	OC	Papua New Guinea	1756.367	1760.134	1779.310
## 157	PW	OC	Palau	14695.686	15798.908	15837.395
## 165	SB	OC	Solomon Islands	1509.057	1543.241	1587.110
## 189	TO	OC	Tonga	4955.380	4973.058	5059.245
## 192	TV	OC	Tuvalu	3189.964	3128.561	2995.404
## 203	VU	OC	Vanuatu	2508.348	2542.075	2609.884
## 204	WS	OC	Samoa	4969.090	5166.430	5347.258

A better way is to subset the data (subset is part of the base package):

```
subset(cData[,1:6], Continent == "OC")
```

##	IS02	Continent	Country	X2003	X2004	X2005
## 9	AS	OC	American Samoa	NA	NA	NA
## 11	AU	OC	Australia	37035.053	38129.815	38840.241
## 60	FJ	OC	Fiji	6804.258	7149.390	7168.896
## 61	FM	OC	Micronesia, Fed. Sts.	3320.158	3220.141	3301.392
## 75	GU	OC	Guam	NA	NA	NA
## 98	KI	OC	Kiribati	1801.492	1825.938	1791.892
## 123	MH	OC	Marshall Islands	3182.515	3183.256	3271.808
## 129	MP	OC	Northern Mariana Islands	NA	NA	NA
## 138	NC	OC	New Caledonia	NA	NA	NA
## 145	NZ	OC	New Zealand	29754.461	30355.860	30984.473
## 149	PF	OC	French Polynesia	NA	NA	NA

## 150	PG	OC	Papua New Guinea	1756.367	1760.134	1779.310
## 157	PW	OC	Palau	14695.686	15798.908	15837.395
## 165	SB	OC	Solomon Islands	1509.057	1543.241	1587.110
## 189	TO	OC	Tonga	4955.380	4973.058	5059.245
## 192	TV	OC	Tuvalu	3189.964	3128.561	2995.404
## 203	VU	OC	Vanuatu	2508.348	2542.075	2609.884
## 204	WS	OC	Samoa	4969.090	5166.430	5347.258

With dplyr:

```
filter(cData[,1:6], Continent == "OC")
```

##	ISO2	Continent	Country	X2003	X2004	X2005
## 1	AS	OC	American Samoa	NA	NA	NA
## 2	AU	OC	Australia	37035.053	38129.815	38840.241
## 3	FJ	OC	Fiji	6804.258	7149.390	7168.896
## 4	FM	OC	Micronesia, Fed. Sts.	3320.158	3220.141	3301.392
## 5	GU	OC	Guam	NA	NA	NA
## 6	KI	OC	Kiribati	1801.492	1825.938	1791.892
## 7	MH	OC	Marshall Islands	3182.515	3183.256	3271.808
## 8	MP	OC	Northern Mariana Islands	NA	NA	NA
## 9	NC	OC	New Caledonia	NA	NA	NA
## 10	NZ	OC	New Zealand	29754.461	30355.860	30984.473
## 11	PF	OC	French Polynesia	NA	NA	NA
## 12	PG	OC	Papua New Guinea	1756.367	1760.134	1779.310
## 13	PW	OC	Palau	14695.686	15798.908	15837.395
## 14	SB	OC	Solomon Islands	1509.057	1543.241	1587.110
## 15	TO	OC	Tonga	4955.380	4973.058	5059.245
## 16	TV	OC	Tuvalu	3189.964	3128.561	2995.404
## 17	VU	OC	Vanuatu	2508.348	2542.075	2609.884
## 18	WS	OC	Samoa	4969.090	5166.430	5347.258

You can also filter based on multiple columns. Let us say we are interested in countries in Oceania that are rich (GDP greater than 3rd quartile).

```
cData[cData$Continent == "OC" & !is.na(cData$Continent) & cData$X2011 > 23000 & !is.na(cData$X2011),]
```

##	ISO2	Continent	Country	X2003	X2004	X2005	X2006	X2007
## 11	AU	OC	Australia	37035.05	38129.81	38840.24	39416.04	40643.45
## 145	NZ	OC	New Zealand	29754.46	30355.86	30984.47	31182.26	31953.38
##	X2008	X2009	X2010	X2011	X2012			
## 11	41311.94	41170.05	41329.95	41706.00	42529.87			
## 145	31058.21	31398.28	31227.55	31683.45	32281.25			

I believe you would agree that, it is not very convenient. Filter to the rescue.

```
filter(cData, Continent == "OC" & X2011 > 23000)
```

##	ISO2	Continent	Country	X2003	X2004	X2005	X2006	X2007
## 1	AU	OC	Australia	37035.05	38129.81	38840.24	39416.04	40643.45
## 2	NZ	OC	New Zealand	29754.46	30355.86	30984.47	31182.26	31953.38
##	X2008	X2009	X2010	X2011	X2012			
## 1	41311.94	41170.05	41329.95	41706.00	42529.87			
## 2	31058.21	31398.28	31227.55	31683.45	32281.25			

Selecting Certain Columns

Let us say we are interested only in the GDP figures and not in any of the country identifiers. We would want to select only certain columns.

Traditional R ways:

```
# Limiting number of rows to 3 to conserve space
cData[1:3,4:13] # Indexing by column numbers
```

```
##           X2003      X2004      X2005      X2006      X2007      X2008      X2009
## 1           NA         NA         NA         NA         NA         NA         NA
## 2 110549.415 111543.925 103139.799 96399.737 83655.038 73611.390 61725.280
## 3   1096.756   1066.685   1145.717   1173.001   1297.821   1310.717   1547.539
##           X2010      X2011      X2012
## 1           NA         NA         NA
## 2 57379.972 56376.770 57044.578
## 3  1637.297  1695.153  1893.076
```

```
cData[1:3,-(1:3)] # Negative indexing
```

```
##           X2003      X2004      X2005      X2006      X2007      X2008      X2009
## 1           NA         NA         NA         NA         NA         NA         NA
## 2 110549.415 111543.925 103139.799 96399.737 83655.038 73611.390 61725.280
## 3   1096.756   1066.685   1145.717   1173.001   1297.821   1310.717   1547.539
##           X2010      X2011      X2012
## 1           NA         NA         NA
## 2 57379.972 56376.770 57044.578
## 3  1637.297  1695.153  1893.076
```

```
cData[1:3,grep("X", colnames(cData))] # Another way based on partial matching column name
```

```
##           X2003      X2004      X2005      X2006      X2007      X2008      X2009
## 1           NA         NA         NA         NA         NA         NA         NA
## 2 110549.415 111543.925 103139.799 96399.737 83655.038 73611.390 61725.280
## 3   1096.756   1066.685   1145.717   1173.001   1297.821   1310.717   1547.539
##           X2010      X2011      X2012
## 1           NA         NA         NA
## 2 57379.972 56376.770 57044.578
## 3  1637.297  1695.153  1893.076
```

subset can also handle this:

```
subset(cData[1:3,], select = -c(IS02, Continent, Country)) # Drop these columns
```

```
##           X2003      X2004      X2005      X2006      X2007      X2008      X2009
## 1           NA         NA         NA         NA         NA         NA         NA
## 2 110549.415 111543.925 103139.799 96399.737 83655.038 73611.390 61725.280
## 3   1096.756   1066.685   1145.717   1173.001   1297.821   1310.717   1547.539
##           X2010      X2011      X2012
## 1           NA         NA         NA
## 2 57379.972 56376.770 57044.578
## 3  1637.297  1695.153  1893.076
```

dplyr way:

```
select(cData[1:3,], X2003:X2012) # All columns between X2003 and X2012
```

```
##           X2003      X2004      X2005      X2006      X2007      X2008      X2009
## 1           NA         NA         NA         NA         NA         NA         NA
```

```
## 2 110549.415 111543.925 103139.799 96399.737 83655.038 73611.390 61725.280
## 3 1096.756 1066.685 1145.717 1173.001 1297.821 1310.717 1547.539
## X2010 X2011 X2012
## 1 NA NA NA
## 2 57379.972 56376.770 57044.578
## 3 1637.297 1695.153 1893.076
```

```
select(cData[1:3,], ~(IS02:Country))
```

```
## X2003 X2004 X2005 X2006 X2007 X2008 X2009
## 1 NA NA NA NA NA NA NA
## 2 110549.415 111543.925 103139.799 96399.737 83655.038 73611.390 61725.280
## 3 1096.756 1066.685 1145.717 1173.001 1297.821 1310.717 1547.539
## X2010 X2011 X2012
## 1 NA NA NA
## 2 57379.972 56376.770 57044.578
## 3 1637.297 1695.153 1893.076
```

Aggregating based on Groups

Let us say we want to calculate the average GDP per continent in 2011 and the number of countries in each continent.

R way:

```
Cont1 <- aggregate(cData$X2011 ~ cData$Continent, FUN=function(x) mean(x, na.rm=T))
Cont1
```

```
## cData$Continent cData$X2011
## 1 AF 5098.267
## 2 AN 18527.820
## 3 AS 23932.691
## 4 EU 29737.968
## 5 OC 9593.810
## 6 SA 12191.071
```

```
Cont2 <- aggregate(cData$X2011 ~ cData$Continent, FUN=function(x) length(x))
Cont2
```

```
## cData$Continent cData$X2011
## 1 AF 51
## 2 AN 26
## 3 AS 46
## 4 EU 40
## 5 OC 13
## 6 SA 11
```

```
Cont <- merge(Cont1, Cont2, by='cData$Continent')
Cont
```

```
## cData$Continent cData$X2011.x cData$X2011.y
## 1 AF 5098.267 51
## 2 AN 18527.820 26
## 3 AS 23932.691 46
## 4 EU 29737.968 40
## 5 OC 9593.810 13
## 6 SA 12191.071 11
```

```
rm(Cont1, Cont2)
```

dplyr way:

```
# Create grouped data
```

```
contiData <- group_by(cData, Continent)
```

```
contiData
```

```
## # A tibble: 208 x 13
```

```
## # Groups:   Continent [6]
```

```
##   IS02 Continent Country      X2003  X2004  X2005  X2006  X2007  X2008  X2009
##   <chr> <chr>      <chr>      <dbl>  <dbl>  <dbl>  <dbl>  <dbl>  <dbl>  <dbl>
##  1 AD    EU        Andorra      NA     NA     NA     NA     NA     NA     NA
##  2 AE    AS        United A~ 110549. 111544. 103140. 96400. 83655. 73611. 61725.
##  3 AF    AS        Afghanis~  1097.   1067.   1146.   1173.   1298.   1311.   1548.
##  4 AG    AN        Antigua ~ 19566.  20395.  21414.  24016.  26008.  25736.  22389.
##  5 AL    EU        Albania    6286.   6699.   7119.   7537.   8056.   8747.   9129.
##  6 AM    AS        Armenia    4182.   4635.   5297.   6020.   6877.   7383.   6358.
##  7 AO    AF        Angola     3819.   4087.   4667.   5445.   6453.   7103.   7039.
##  8 AR    SA        Argentina   NA     NA     NA     NA     NA     NA     NA
##  9 AS    OC        American~   NA     NA     NA     NA     NA     NA     NA
## 10 AT    EU        Austria    39733.  40555.  41142.  42311.  43674.  44157.  42336.
## # ... with 198 more rows, and 3 more variables: X2010 <dbl>, X2011 <dbl>,
## #   X2012 <dbl>
```

```
# Create variables on the fly
```

```
summarise(contiData, count=n(), GDP2012 = mean(X2012, na.rm = T))
```

```
## # A tibble: 6 x 3
```

```
##   Continent count GDP2012
##   <chr>      <int>  <dbl>
##  1 AF         52   5425.
##  2 AN         31  17796.
##  3 AS         49  24344.
##  4 EU         46  29655.
##  5 OC         18   9795.
##  6 SA         12  12542.
```

Save dataset for later use.

```
```r
```

```
write.csv(contiData, file="contiData.csv", row.names=F)
```



How I Learned to Stop Worrying and Love the R Console by Irfan E Kanat is licensed under a Creative Commons Attribution 4.0 International License. Based on a work at <http://github.com/iek/anat/rworkshop>.