



Henry Thermal Engineering Team
Jimmy Zhang
Tel: +86 13961477111
Email: jimmy@henryref.com// jimmy@hcooler.com
web: www.henryref.com/www.hcooler.com

Customer	Date	2026/6/24
To the k. a. of	Our Offer	HC34326003Q
Your Reference	Description	ZA_SG096

HEATING COIL

HDVD2691-2923EC

Capacity	2923.28	kW
Exchange Surface	20896.16	m2
Global Exchange Coefficient	34	W/(m2 K)
DTML	4.1	ï C

AIR SIDE

Atmospheric Pressure / Altitude	1.01 / 0.00	bar A / m
Volumetric Air Flow	818058.2	m3/h
Mass Air Flow	901073	kg/h
Face Velocity on the Coil	2.39	m/s
Inlet Air Density	1.10	kg/m3
Inlet Air Temperature	44.0	ï C
Inlet Air Relative Humidity	30.00	%
Inlet Air Specific Humidity	17.2	g/kg DA
Inlet Air Enthalpy	88.72	kJ / kg
Outlet Air Temperature	55.3	ï C
Outlet Air Relative Humidity	17.12	%
Outlet Air Specific Humidity	17.2	g/kg DA
Outlet Air Enthalpy	100.40	kJ / kg
Pressure Drop	165	Pa
Fouling Factor	0.000000	(m2 K)/W
Partial Exchange Coefficient	70	W/(m2 K)

FLUID SIDE

Fluid	WATER (1 bar A)	
Volumetric Fluid Flow	318.8	m3/h
Mass Fluid Flow	314392	kg/h
Fluid Velocity	0.76	m/s
Inlet Fluid Temperature	58.0	ï C
Outlet Fluid Temperature	50.0	ï C
Total Pressure Drop Fluid Side	26.44	kPa
Partial Exchange Coefficient	4724	W/(m2 K)
Fouling Factor	0.000000	(m2 K)/W

GEOMETRICAL DETAILS	Manifolds	Vertical	In: 4 x 139x5 [5"]	Out: 4 x 139x5 [5"]
---------------------	-----------	----------	--------------------	---------------------