

Code	XXXXA(80+80)061100021WXX(80+80+80+80)		
Fin type	38.1 X 33 Staggered		
Type of tube	15.32 Smooth C		
Fluid	Water		

Utilized tubes	960	HxLxP [mm]	6096 x 11000 x 198
Non utilized tubes	0	Outer area [m2]	11038
Inner volume [l]	2111	Frontal area [m2]	67.1
Headers	8 x 133 mm CU	Inner area [m2]	508
Tubes per circuit	3		

AIR SIDE		SIDE -Water	
Temp. ingresso [癈]	44	Entering temp. [癈]	58
U.R. entering [%]	50	Outlet temp. [癈]	52
Temp. uscita [癈]	55.9	Mass flow [kg/h]	438395
U.R. outlet [%]	27.6	Volumetric flow [l/h]	444332
Flow [m3/h]	820000	Flow per circuit [l/h]	1389
Flow [kg/s]	242	Velocity [m/s]	2.09
Frontal velocity [m/s]	3.4	Coil pressure drop [kPa]	110
Pressure drop [Pa]	215		
		Total pres. drop [kPa]	134
Barometric pres. [kPa]	101.325		
Altitude [m]	0		

Type of calculation	Countercurrent	Total capacity [kW]	3065
Corrective factor	1	Sensible capacity [kW]	3065
Additional equivalent lenght	0	Condensed water [l/h]	0

Fin		Tube	
Thickness [mm]	0.12	Thickness [mm]	0.41
Material	Aluminium	Material	Copper
Conduktivita[W/mK]	200	Conduktivita[W/mK]	330