

# Locality-Sensitive Hashing (LSH)

Mining Massive Datasets

Prof. Carlos Castillo


Topic 09

# Source for this deck

- Mining of Massive Datasets 2<sup>nd</sup> edition (2014) by Leskovec et al. (Chapter 3) [[slides ch3](#)]

# Locality-sensitive hashing

# Final step: locality-sensitive hashing



# LSH: first idea

- **Goal:** Find documents with Jaccard similarity at least  $s$  (for some similarity threshold, e.g.,  $s=0.8$ )
- **LSH – General idea:** Use a function  $f(x,y)$  that tells whether  $x$  and  $y$  is a **candidate pair**: a pair of elements whose similarity must be evaluated
- **For Min-Hash matrices:**
  - 1) Hash columns of signature matrix  $M$  to many buckets
  - 2) Each pair of documents that hashes into the same bucket is a **candidate pair**

Signature matrix  $M$

d1	d2	d3	d4
2	1	4	1
1	2	1	2
2	1	2	1

# Selecting candidates

- **Pick a similarity threshold  $s$  ( $0 < s < 1$ )**
- Columns  $x$  and  $y$  of  $M$  are a **candidate pair** if their signatures agree ( $M(i, x) = M(i, y)$ ) on at least fraction  $s$  of their rows
- We expect documents  $x$  and  $y$  to have the same (Jaccard) similarity as their signatures

Signature matrix  $M$

d1	d2	d3	d4
2	1	4	1
1	2	1	2
2	1	2	1


# Creating buckets of similar documents

- **Big idea: hash columns of signature matrix  $M$**
- Arrange that (only) **similar columns** are likely to **hash to the same bucket**, with high probability
- **Candidate pairs are those that hash to the same bucket**

Signature matrix  $M$

d1	d2	d3	d4
2	1	4	1
1	2	1	2
2	1	2	1

# Partition $M$ into $b$ bands of size $r$






# Partition $M$ into $b$ bands of size $r$ (cont.)

- Partition matrix  $M$  into  $b$  bands of  $r$  rows
- For each band, hash its portion of each column to a hash table with  $k$  buckets
  - Make  $k$  as large as possible
- **Candidate** column pairs are those that hash to the same bucket for  $\geq 1$  band
- Tune  $b$  and  $r$  to catch most similar pairs, but few non-similar pairs

Signature matrix  $M$

d1	d2	d3	d4
2	1	4	1
1	2	1	2
2	1	2	1

# Hashing bands



# Simplifying assumption: no collisions (no false positives)

- We will assume there are **enough buckets** that columns are unlikely to hash to the same bucket unless they are **identical** in a particular band
- Hereafter, we assume that “**same bucket**” means “**identical in that band**”
- Assumption needed only to simplify analysis, not for correctness of algorithm

# Example of bands

## Assume the following case:

- Suppose 100,000 columns of  $\mathbf{M}$  (100k docs)
- Signatures of 100 integers (rows)
  - Therefore, signatures take 40Mb
- Choose  $b = 20$  bands of  $r = 5$  integers/band
- **Goal:** Find pairs of documents that are at least  $s = 0.8$  similar

# Suppose $\text{sim}(C_1, C_2) = 0.8$

- **Find pairs of  $s=0.8$  similarity, set  $b=20, r=5$**
- Since  $\text{sim}(C_1, C_2) = s$ , we want  $C_1, C_2$  to be a **candidate pair**
  - We want them to hash to **at least 1 common bucket**  
(at least one band is identical)
- **Probability  $C_1, C_2$  identical in one particular band:  $(0.8)^5 = 0.328$**
- **Probability  $C_1, C_2$  are *not* similar in all of the 20 bands:**  
 $(1-0.328)^{20} = 0.00035$ 
  - i.e., about 1/3000th of the 80%-similar column pairs are **false negatives**  
(we will miss them)
- **We would find 99.965% pairs of truly similar documents**

# Suppose $\text{sim}(C_1, C_2) = 0.3$

- Find pairs of  $s=0.8$  similarity, set  $b=20$ ,  $r=5$
- Since  $\text{sim}(C_1, C_2) < s$ , we **do not** want  $C_1, C_2$  to be a **candidate pair**
- **Probability  $C_1, C_2$  identical in one particular band:**

$$(0.3)^5 = 0.00243$$

- Probability  $C_1, C_2$  identical in at least 1 of 20 bands:

$$1 - (1 - 0.00243)^{20} = 0.0474$$

- In other words, approximately 4.74% pairs of docs with similarity 0.3% end up becoming **candidate pairs**
  - They are **false positives** since we will have to examine them (they are candidate pairs) but then it will turn out their similarity is below threshold  $s$

# LSH summary

- Tune ***K (permutations), b (bands), r (permutations/band)*** to get almost all pairs with similar signatures, but eliminate most pairs that do not have similar signatures
- After finding candidates, check in main memory that **candidate pairs** really do have **similar signatures**

# Summary



# Things to remember

- **Locality-Sensitive Hashing**: Focus on pairs of signatures likely to be from similar documents
  - We used hashing to find **candidate pairs** of similarity **s**

# Exercises for TT08-TT09

- Mining of Massive Datasets 2<sup>nd</sup> edition (2014) by Leskovec et al.
  - Exercises 3.1.4 (Jaccard similarity)
  - Exercises 3.2.5 (Shingling)
  - Exercises 3.3.6 (Min hashing)
  - Exercises 3.4.4 (Locality-sensitive hashing)