

Data Streams: Bloom Filters

Mining Massive Datasets

Prof. Carlos Castillo

Topic 24

Sources

- Mining of Massive Datasets (2014) by Leskovec et al. (chapter 4)
 - Slides [part 1](#), [part 2](#)
- Tutorial: [Mining Massive Data Streams](#) (2019) by Michael Hahsler

Bloom filters

Filtering a data stream


- Suppose we have a large set S of keys
- We want to filter a stream $\langle \text{key}, \text{data} \rangle$ to let pass only the elements for which $\text{key} \in S$
- Example: key is an e-mail address, we have a total of $|S|=10^9$ allowed e-mail addresses

Naïve solution?

Filtering a data stream

- Suppose we have a large set S of keys
- We want to filter a stream $\langle \text{key}, \text{data} \rangle$ to let pass only the elements for which $\text{key} \in S$
- Example: key is an e-mail address, we have a total of $|S|=10^9$ allowed e-mail addresses
- Naïve solution? Hash table won't work, too big!

Bloom Filter (1-bit case)

- Given a set of keys S
- Create a bit array $B[]$ of n bits
 - Initialize to all 0s
- Pick a hash function h with range $[0, n)$
 - For each member of s  S
 - Hash to one of n buckets
 - Set that bit to 1, i.e., $B[h(s)] \leftarrow 1$
- For each element a of the stream
 - Output a if and only if $B[h(a)] == 1$

Bloom filter creation

Stream processing

Bloom Filter is an approximate filter

- Can it output an element with a key not in S ?
- Can it not output an element with a key in S ?

Bloom Filter is an approximate filter

- Can it output an element with a key not in S ?

Yes, due to hash collisions $h(x)=h(y)$ when $x \neq y$

- Can it not output an element with a key in S ?

No, because $h(x)$ is always the same for x

Bloom filters are *permissive* (not *strict*)

Bloom filter

- A bloom filter is:
 - An array of n bits, initialized as 0
 - A collection of hash functions h_1, h_2, \dots, h_k
 - A set S of m key values
- The purpose of the bloom filter is to allow all stream items whose key is in S

Bloom filter initialization


For all positions i in $[0, n-1]$

$B[i] \leftarrow 0$

For all keys K in S :

For every hash function h_1, h_2, \dots, h_k

$B[h_i(K)] \leftarrow 1$



Bloom filter usage


For each input element $\langle \text{key}, \text{data} \rangle$

$\text{allow} \leftarrow \text{TRUE}$

For every hash function h_1, h_2, \dots, h_k

$\text{allow} \leftarrow \text{allow} \wedge B[h_i(K)] == 1$

output element if $\text{allow} == \text{TRUE}$



Characteristics of Bloom Filters

- Are lax (not strict) and let some items pass
 - May require a second-level check to make filter strict, for instance store output on disk files and then check against hash tables (slower)
- Implementations can be very fast
 - E.g., use hardware words for the bit table

Preliminaries for the analysis: targets and darts

- Suppose we throw y darts at x targets
 - All darts will hit one of the targets
- After throwing the darts, how many distinct targets can we expect to hit at least once?
 - Prob. that a given dart will not hit a given target is $(x-1)/x = 1-1/x$
 - Prob. none of the y darts will hit a given target is $(1-1/x)^y = (1-1/x)^{x(y/x)}$
 - Using $(1-\varepsilon)^{1/\varepsilon} \simeq 1/e$ for small ε
 - Prob. none of the y darts will hit a given target is $(1/e)^{y/x}$

Analysis of the 1-bit Bloom Filter

- Each element of S is a dart $|S|=y$
- Each bit in the array is a target $n=x$
- Suppose $y=|S|=10^9$ (1 G) and $x=n=8 \times 10^9$ (8 GB)
- Prob. that a given bit is NOT set to 1 (dart does not hit the target) is $(1/e)^{y/x} = (1/e)^{1/8}$
- Prob. bit is set to 1 is $1 - (1/e)^{1/8} = 0.1175$

About 12% of bits are set to one in this Bloom Filter
this is also the false-hit probability in this case

General case

- $|S|=m$ keys, array has n bits
- k hash functions
- Targets $x=n$, darts $y=km$
- Probability that a bit remains 0 is $e^{-km/n}$
- Example:
We can pick $k=n/m$ to obtain collision probability $1/e = 37\%$

Analysis of a 2-bit Bloom Filter

- Suppose $|S|=10^9$ (1 G) and $n=8 \times 10^9$ (8 GB)
- Suppose we use two hash functions
- Prob. that a given bit is NOT set to 1 (dart does not hit the target) is $(1/e)^{y/x} = (1/e)^{1/4}$
- Prob. a bit is set to 1 is $1 - (1/e)^{1/4}$
- Prob. two bits are set to 1 is $(1 - (1/e)^{1/4})^2 = 0.0493$
- We have a false hit probability of about 5% with two hash functions, while the probability was about 12% with only one

How many hash functions to use?


Too few: test is too unspecific. Too many: table becomes too crowded.

- **$m = 1$ billion, $n = 8$ billion**

$$k = 1: (1 - e^{-1/8}) = 0.1175$$

$$k = 2: (1 - e^{-1/4})^2 = 0.0493$$

- **What happens as we keep increasing k ?**
 - “Optimal” value of k : $n/m \ln(2)$
 - **In our case:** Optimal $k = 8 \ln(2) = 5.54 \approx 6$
 - Error at $k = 6$: $(1 - e^{-1/6})^2 = 0.0235$



Summary

Things to remember

- How to initialize a Bloom filter
- How to use a Bloom filter
- Proofs for 1-bit, 2-bit case

Exercises for TT22-T26

- Mining of Massive Datasets (2014) by Leskovec et al.
 - Exercises 4.2.5
 - Exercises 4.3.4
 - Exercises 4.4.5
 - Exercises 4.5.6