From data to evidence: the complete story

BRCA MODEL GUIDE

From actual records to the model, calculations and limits of the evidence

For students starting without prior knowledge of genetics, statistics or programming.

> **This guide explains the existing work. No new patient analysis, hypothesis test, model fitting or calculator change was performed.**

Three distinct parts of the work

1. Archive: link files, specimens, people and families, and establish which data are usable.
2. Prediction: explain the calculations and evaluation of the model developed in the original 1,295 people.
3. Biological research: understand existing comparisons between genetic and clinical features and their uncertainty.

Reading route

Biology → archive → development patients → encoding and missing data → learning → coefficients → manual calculation → points card → statistics → laboratory trade-offs → biological finding → independent validation → software and sources.

Guide date: 3 November 2026. Archive and validation counts come from the existing 24 October audit. The separate research report retains its 25 October date. Stored model version: 2026-10-04-8cc48aa58b.

Open the model details page

1 · The language of biology and genetics

Our bodies consist of cells. DNA (deoxyribonucleic acid) carries genetic information used to make proteins. A gene is a section associated with a particular function. Proteins perform many of the cell's jobs.

BRCA1 and BRCA2 are genes associated with proteins that help repair damaged DNA. A genetic change is called a variant. An inherited variant can be passed through a family. A somatic change acquired in a tumour is a different concept.

Term	Meaning
P / Pathogenic	A disease-related harmful effect is established.
LP / Likely Pathogenic	Strong evidence suggests a harmful effect.
VUS / Variant of Uncertain Significance	Its significance is not sufficiently understood.
B / LB	Benign / likely benign: harmless or likely harmless.
CNV / Copy Number Variant	A change in the copy number of a DNA segment.
NGS / Next-Generation Sequencing	Sequencing methods examining many DNA regions in parallel.
MLPA / Multiplex Ligation-dependent Probe Amplification	A method assessing copy-number losses or gains in selected regions.

> **Not every variant is harmful. Carrying a disease-related BRCA variant does not mean cancer is inevitable.**

Our prediction question is not whether someone will develop cancer in the future. It is whether existing clinical information can help predict the recorded BRCA test result.

2 · The actual archive: files, rows, people and families

We did not start with one clean table. Drive contained individual patient folders, genetic reports, variant workbooks and clinical files from years including 2019, 2020 and 2022. The same person can appear in different versions or with repeat specimens.

Record level	Count
Patient folders	2,259
Established operational genetic patient entities	2,148
Rows across clinical source versions	7,939
Genetic entities with accepted clinical links	1,445
Consistently recorded family IDs	1,989
Conservatively retained variant-call rows	84,492

These are different counting units, not a single flow from which all exclusions can be subtracted. The 2,148 entities are not a certified unique-patient total for the entire archive. Clinical-only components without an accepted genetic link cannot automatically be counted as additional people. Different recorded family IDs do not exclude undocumented relatedness.

84,492 rows do not mean 84,492 unique variants. A variant can recur in different people. Absence from a table does not establish adequate examination and a negative result for that region; complete callability masks are unavailable.

Identity linkage considers patient code, name, date of birth, family number, protocol ID and original reports together. Forcing a conflicting link can assign genetic or clinical information to the wrong person.

> **Files ≠ rows ≠ specimens ≠ people ≠ independent families.**

3 · Development patients and clinical fields

The calculator was developed using the original 1,295-person group, not the entire expanded archive. Diagnosis years range from 1988 to 2020. The first four breast-related categories total 1,088 people; 207 are ovarian-only.

Diagnosis	People	Positive
Unilateral breast	978	104
Bilateral breast	75	17
Breast and ovarian	22	10
Male breast	13	2
Ovarian only	207	34
Total	1295	167

The target y is 1 when BRCA_status_v3_strict is exactly Positive, and 0 for other labels. We do not treat all 1,128 other labels as established complete, up-to-date clinical negatives.

$$\pi = \frac{167}{1295} \approx 0.12896 = 12.9\%$$

Here π is the positive-label proportion in the development group, not general-population carrier frequency or the geometric constant pi.

Field	Explanation
Age at diagnosis	Age when diagnosed, not current age.
Family history	Relationship degree, cancer type, diagnosis age and relative counts.
Grade	Microscopic abnormality; not the same as stage.
Stage	Anatomical extent; not used by this calculator.
Origin region	Recorded geographical category, not measured genetic ancestry.

First-degree relatives include parents, siblings and children; second-degree relatives include grandparents, aunts and uncles. Not every archive field is a model input: tumour size and lymph-node status are not used here.

4 · Encoding, tumour markers and missing information

Term	Full name and meaning
ER	Estrogen Receptor.
PR	Progesterone Receptor.
HER2	Human Epidermal Growth Factor Receptor 2. A receptor/protein assessed in tumours.
TNBC	Triple-Negative Breast Cancer. Breast cancer classified as negative for ER, PR and HER2.
Ki-67	A proliferation-related marker, usually recorded as a percentage.
IHC	Immunohistochemistry. Staining-based assessment of proteins in tissue.
ISH / FISH	In Situ Hybridization / Fluorescence In Situ Hybridization. Methods assessing selected DNA/RNA targets in tissue.

Encoding uses numbers such as age 38, counts such as one relative, and indicators such as TNBC present = 1 or absent = 0. Diagnosis, grade and region are categorical. Unilateral breast, g2 and Marmara are reference categories with no additional category coefficient.

The development package records 87 missing ages, 16 unrecorded regions and 464 recorded Ki-67 measurements. Filling missing values for calculation is called imputation.

Historical processing: missing family counts became 0; missing age used the diagnosis-group median plus an indicator; missing region became Marmara; missing Ki-67 used 30 plus an indicator set to 1. Grades other than 1 or 3 map to g2. The live panel does not give a personal result for blank age. Ovarian-only selection clears TNBC and sets Ki-67 to missing.

> **Unknown information is not a known zero. Unknown Ki-67 differs from measured 30%. These are existing model rules, not newly established clinical facts.**

5 · Learning: how were the coefficients obtained?

The method is logistic regression, not a deep neural network. The computer predicts using coefficients, compares predictions with recorded outcomes y, and searches for coefficients reducing error. Finding the coefficients is called training or fitting.

Because positives are the smaller class, class weights give an error on a positive record more influence during fitting than an error on an other-labelled record. This does not create new patients.

$$w_+ = \frac{1295}{2 \times 167} \approx 3.877246, \qquad w_- = \frac{1295}{2 \times 1128} \approx 0.574025$$

L2 regularisation penalises squared coefficients to discourage excessively large coefficients. C is the inverse penalty-strength setting: smaller C gives stronger penalisation. Overfitting means adapting too specifically to development examples and performing poorly on new ones.

Candidate C values: 0.01, 0.03, 0.1, 0.3 and 1. The main script uses five outer folds × five repeats. Three inner folds select C by AUC within each outer training set. The modal selection is 0.3; the final model is fitted on the complete development data. max_iter = 5000 is an iteration limit; seed = 2020 is a reproducibility setting, not a quality guarantee.

Standardisation puts differently scaled inputs such as age and Ki-67 on a common scale for fitting. Exported coefficients were converted back to raw units, so the live panel does not standardise again.

In the main path, repeated out-of-fold raw probabilities are averaged per person and their logits used to learn Platt calibration. A separate queue-evaluation script learns scaling on outer training data, calibrates using inner out-of-fold predictions and counts outer-test outcomes. These are distinct evaluation pipelines.

6 · The 26 learned coefficients and intercept

A coefficient β determines an input's contribution to the linear score z. Positive coefficients raise the score; negative coefficients lower it. These are not percentage-point or causal effects. Values are rounded here; the app uses full precision.

Input	Coefficient
Intercept	-1.608284
Age at diagnosis	-0.029742
First-degree breast <40	1.617774
First-degree breast ≥40	0.675359
Second-degree breast <40	0.612541
Second-degree breast ≥40	0.566324
Third/fourth-degree breast	0.386057
First-degree ovarian	0.865623
Second–fourth-degree ovarian	0.741728
First-degree other cancer	0.212743
Age-missing indicator	1.067055
TNBC	0.809504
Ki-67, per percentage unit	0.025036
Ki-67-missing indicator	0.377173
Bilateral breast	0.817837
Breast and ovarian	1.184748
Male breast	0.498472
Ovarian only	0.317136
Grade 1	0.089786
Grade 3	0.643779
Black Sea	-0.092277
Eastern Anatolia	-0.215376
Central Anatolia	0.160451
Balkans	0.405355
Southeastern Anatolia	-0.384251
Aegean	0.347375
Mediterranean	-0.631471

References: unilateral breast, g2 and Marmara. Not every indicator is active in one patient. Some adjustment variables used in biological research, such as ethnicity, are not inputs to this prediction model.

7 · Worked patient: inputs and contributions

This is a synthetic teaching profile, not an identifiable real patient.

Feature	Value
Age at diagnosis	38
Diagnosis / grade / region	Unilateral breast / 2 / Marmara
TNBC	1
First-degree breast <40	1
Other family counts	0
Ki-67	Unknown
Urgency boxes	Unchecked

$$z = \beta_0 + \sum_{j=1}^{26} \beta_j x_j$$

x_j: patient input j. β_j: its coefficient. β_0: intercept. j: input index. Σ: sum the contributions. z: linear score, not a percentage.

$$\begin{aligned} z = & -1.608283515050 \\ & + 38(-0.029741519309) \\ & + 1(1.617774083556) \\ & + 1(0.809503755804) \\ & + 30(0.025035821777) \\ & + 1(0.377172660529) \end{aligned}$$

$$\begin{aligned} z = & -1.608283515050 - 1.130177733759 \\ & + 1.617774083556 + 0.809503755804 \\ & + 0.751074653320 + 0.377172660529 \\ = & \, 0.817063904400 \end{aligned}$$

Unknown Ki-67 activates both the imputed 30 and the missingness indicator. Measured 30% would not activate the missingness contribution. The other category and family indicators contribute zero here.

8 · From score to percentage: sigmoid and calibration

The sigmoid converts a linear score to a number between 0 and 1. e ≈ 2.71828 is Euler's number; the superscript is an exponent. p means probability, raw means uncalibrated, and cal means calibrated.

$$\sigma(t) = \frac{1}{1 + e^{-t}}$$

$$p_{\text{raw}} = \frac{1}{1 + e^{-0.817063904400}} \approx 0.693612733313$$

Approximately 69.4% is not the final displayed result. Calibration concerns agreement between predicted probabilities and observed frequencies. The class-weighted model's raw probability is not used directly as the final percentage.

$$\eta = a + bz, \quad a = -1.824095746896, \quad b = 0.939227549588$$

$$\begin{aligned} \eta &= -1.824095746896 + 0.939227549588(0.817063904400) \\ &= -1.824095746896 + 0.767408928786 \\ &= -1.056686818109 \end{aligned}$$

$$p_{\text{cal}} = \frac{1}{1 + e^{-\eta}} = \frac{1}{1 + e^{1.056686818109}} = 0.257943116995$$

$$100p_{\text{cal}} = 25.7943116995\% \approx \boxed{25.8\%}$$

η (eta) is the adjusted linear score; a is the intercept correction and b the slope correction. Apply calibration once. Substituting the raw probability instead of z into a+bz is incorrect. The logit is the inverse sigmoid: log[p/(1−p)]. Odds = p/(1−p); OR (Odds Ratio) is a ratio of odds, not a percentage-point difference. On the calibrated log-odds scale the coefficient is bβ.

Changing only age from 38 to 48

$$\Delta z = 10(-0.029741519309) = -0.297415193094$$

$$z_{\text{new}} = 0.519648711306, \qquad p_{\text{new}} \approx 0.208164117 = 20.8\%$$

The decrease is about 4.98 percentage points. This is not a protective effect of becoming ten years older; it is the frozen model's conditional response to a different input. Previous-value arrows let students follow quantities affected by the last edit.

9 · The separate points card and queue rules

The card comes from a separate class-balanced L2 model with 16 candidate features and C = 0.3. Coefficients were divided into 0.5 log-odds units and rounded; removing zero-point rows left 14 items. It is not a rounding of the main model's β coefficients.

Item	Points
Age at diagnosis < 40	1
Triple-negative tumour	2
Grade 3	1
Ki-67 ≥ 30%	1
1st-degree relative, breast cancer < 40 (each, max 2)	3
1st-degree relative, breast cancer ≥ 40 (each, max 2)	1
2nd-degree relative, breast cancer (each, max 2)	1
3rd–4th-degree relative, breast cancer (each, max 2)	1
1st-degree relative, ovarian cancer (each, max 2)	1
2nd–4th-degree relative, ovarian cancer (each, max 2)	1
Bilateral breast cancer	2
Both breast and ovarian cancer	2
Ovarian cancer	2
Male breast cancer	1

Example: age <40 gives 1, TNBC gives 2, first-degree breast <40 gives 3: total 6. Unknown Ki-67 earns no high-Ki-67 card point. Each family card row caps at two; the panel allows model counts up to six.

Lane	Model	Card
Normal	<10%	0–3
Priority	10%–<20%	4
Urgent	≥20%	≥5

$$A = \max(s_{\text{card}}, s_{\text{model}}, u), \qquad B = \max(s_{\text{model}}, u)$$

s values are lane codes: 0 normal, 1 priority, 2 urgent; max takes the highest. u=2 if a treatment decision awaits the result; otherwise u=1 for documented familial P/LP, else 0. B remains a proposal. A's urgent lane triggers the rapid package; B uses model ≥20%. Familial P/LP does not change the β sum, but suppresses the personal probability headline because that information is absent from the model.

10 · Other displayed numbers and performance measures

Do not confuse different numbers for one patient

$$N = \text{round}(1/p) = \text{round}(3.876824) = 4$$

“Approximately one in four” is a rounded description, not four observed people. Round chooses the nearest integer; exact halves go to the even integer in the code.

$$\text{Position} = \text{round}\left[5\left(17 + \frac{0.257943117 - 0.2133526175}{0.2763791363 - 0.2133526175}\right)\right] = 89$$

The score is near the 89th percentile: a position in the development-score distribution, not an 89% carrier probability. 17 is the zero-based lower-knot index; the denominator is the gap between adjacent knots.

$$\text{Fill} = \min\left(100, \frac{p}{0.40} \times 100\right) \approx 64.5\%$$

Fill is the visual bar fill; min takes the smaller value. This 64.5% is not another medical probability.

Stored performance estimates

Metric	Value
Nested cross-validation AUC	0.776
AUC confidence interval	0.733–0.817
Apparent / optimism-corrected AUC	0.815 / 0.784
PR-AUC	0.404
Temporal-test AUC	0.788
Recalibrated Brier	0.095
Base-rate Brier	0.112

AUC: Area Under the Receiver Operating Characteristic Curve. It measures ranking of a positive record above an other-labelled record; 0.776 does not mean 77.6% of individual answers are correct. ROC plots sensitivity against false-positive rate. PR-AUC is the area under the Precision–Recall curve, focusing on positive-class retrieval.

11 · Validation, thresholds and the error table

$$\text{Brier} = \frac{1}{n}\sum_{i=1}^{n}(p_i - y_i)^2$$

n is the number evaluated, p_i the prediction and y_i the recorded outcome. Brier measures probability error; lower is better. Calibration asks whether groups predicted at, for example, 20% have observed rates near that value. Good ranking does not guarantee good calibration.

An out-of-fold prediction is made while that person is excluded from the relevant fitting step. However, some imputation and scaling in the main script preceded the outer split, creating leakage concerns. StratifiedKFold balances classes but does not group families; relatives can enter different folds. The AUC interval uses 2,000 person-level bootstrap samples, and optimism correction uses 200. Bootstrap resamples observations with replacement.

The temporal table records 796 training and 477 test patients, with 52 positives in the test period. A later period at the same centre is not independent external validation. Denominators and processing paths from different evaluation tables are not interchangeable.

Historical approximately 3.5% threshold example

	Positive	Other	Total
Above threshold	TP 159	FP 978	1,137
Below threshold	FN 8	TN 150	158
Total	167	1,128	1,295

$$\text{Sensitivity} = \frac{TP}{TP+FN} = \frac{159}{167} = 95.21\%$$

$$\text{Specificity} = \frac{TN}{TN+FP} = \frac{150}{1128} = 13.30\%$$

$$\text{NPV} = \frac{TN}{TN+FN} = \frac{150}{158} = 94.94\%, \quad \text{PPV} = \frac{159}{1137} = 13.98\%$$

TP/FP: True/False Positive; TN/FN: True/False Negative, relative to the recorded labels. Sensitivity captures positives; specificity keeps others below threshold; NPV (Negative Predictive Value) is the other-label proportion below threshold; PPV (Positive Predictive Value) is the positive proportion above threshold. High sensitivity alone is insufficient. This is not the current 10%/20% queue boundary; one threshold table cannot give AUC.

12 · Laboratory capacity: workload and yield

Two decisions are distinct: who is prioritised in the queue, and who receives the narrow rapid first-test package? The package covers BRCA1 deletions/duplications by MLPA plus c.5266dupC. It is not complete testing for all BRCA variants. A negative rapid result does not exclude a carrier; full testing continues.

Strategy	Packages	Detectable targets
Model ≥20%	212.6	26.6
Card-or-model A trigger	280.0	29.4

These are means over five repeats, not fractional patients. A detectable target is a selected carrier with a target covered by the narrow package; it is not the same denominator as all BRCA positives.

$$\Delta N = 212.6 - 280 = -67.4, \qquad \Delta T = 26.6 - 29.4 = -2.8$$

$$\text{Yield} = \frac{26.6}{212.6} \times 100 = 12.511759\%$$

$$\text{Packages/target} = \frac{212.6}{26.6} = 7.992481$$

Δ means difference; here N is package count and T detectable-target count. Fewer packages trade off against fewer detectable targets. The mean of repeat-specific ratios is about 8.013; the ratio of means is about 7.992. These are different operations.

The capacity panel reads aggregate results for six stored strategies; it performs no new patient analysis. The temporal option concerns 477 people and 52 carriers. Extra workload from urgency overrides was not measured. In the equal-workload comparison, the card showed no added advantage; its manual and explanatory value is separate.

> **Improvements in waiting time, cost or treatment outcomes were not measured. The hypothetical test-reduction panel is not an instruction to omit tests.**

The hypothetical reduction policy excludes card ≥4, ovarian cancer, male breast cancer, TNBC, ovarian family history, urgency and, in the strict option, age <45. Its generating script is absent from this package, so the stored aggregate reduction results are not independently regenerated here.

13 · The biological finding and statistical uncertainty

Prediction asks which information combinations predict an outcome. Biological association research might ask whether tumour sizes differ between variant classes. Useful prediction does not establish causation.

The existing comparison uses 87 family representatives: 20 stop-gain and 67 frameshift families. Stop-gain introduces an early stop in protein production; frameshift shifts the three-letter reading frame. The recorded-size ratio below adjusts for age, year, gene, recorded ethnicity, region and genotype source.

$$R = 0.649, \qquad \text{interval: } 0.421 \text{ to } 1.001$$

The point estimate corresponds to about 35% smaller recorded size. The interval includes 1, meaning no difference. The primary empirical p is about 0.0504; the cumulative multiple-testing-adjusted q is about 0.527. This is not a validated difference and was not added to the calculator.

Term	Meaning
Effect size	Magnitude of the association; here a size ratio.
Confidence interval	Describes sampling uncertainty, not a probability that this one interval is correct.
p-value	Probability of a result at least this extreme under the null and assumptions; not the probability the hypothesis is false.
Confounder	A variable related to group and outcome that can distort the comparison.
Selection bias	Systematic differences between included and excluded people.
Power	Probability of detecting a specified true effect with a specified design.
FDR / False Discovery Rate	An approach controlling false discoveries across multiple comparisons.

Many comparisons create more opportunities for chance findings. Statistical adjustment does not eliminate missingness, selection or measurement bias. These issues remain unresolved for this observation; independent validation is absent.

14 · Why are the additional records not yet a validation set?

An expanded archive does not mean the model has been retrained or independently validated. A person used in development, or from the same family, may not be eligible for an independent test. Recorded family separation is not genomic proof of unrelatedness.

Existing audit stage	Count
Clinically linked people outside development	206
Excluded for known development-family overlap	20
Without an eligible cancer record	1
Remaining candidate people / family groups	185 / 184
Family representatives with complete core inputs	111
Report-supported, core-complete representatives	91
Remaining without historical-VUS dependency	51
Positive / negative in the 51 candidates	14 / 37
Diagnosis year available / missing	41 / 10
Complete dated pre-result profile / eligible validation	0 / 0

Forty of the 91 report-supported representatives depended on historical variant classification and were excluded from the more conservative 51-person review. Diagnosis year is not a model input, but its absence limits chronology checks. Even the 41 with a year lacked adequate dated evidence that the complete clinical profile preceded the BRCA result.

> **Genetic reports exist in Drive. What is missing is dated clinical documentation of the full input profile at the prediction time. Zero eligible patients does not mean zero performance; performance could not be estimated.**

Needed: dated pre-result clinical assessment covering model inputs; traceable genetic outcomes and report dates; reliable identity/family links; enough independent positive and negative outcomes. Archive size alone does not justify new coefficients, recalibration or threshold changes.

15 · Software, sources and the complete story

An input edit does not retrain the model. The app reads inputs, applies encoding/missingness rules, calculates z with stored coefficients, a percentage with stored calibration, a separate card score and A/B queue lanes. The teaching page uses synthetic profiles only.

The 54 synthetic examples and 47 stored self-tests check arithmetic agreement. Automated tests and live desktop/mobile checks can establish intended software behaviour. Language switches should retain inputs; reset should restore the selected profile. These are not evidence of clinical performance in new patients.

A SHA-256 checksum verifies a file version, not data correctness or scientific validity. Original genetic reports and private identity/family linkage lists remain in authorised Drive records; this guide contains no patient identifiers.

Explain the complete work in one paragraph

We linked scattered genetic and clinical records, separating files, specimens, people and families. We explain the logistic model developed in the original 1,295 people: weighted sum, calibration and probability. The points card and queue rules are separate layers. Internal evaluation suggests useful ranking, but preprocessing and family-independence limitations remain. The 87-family biological observation is not a validated discovery. The expanded archive has not yet supplied a dated, independent validation set. We have an explainable research prototype and explicit data needs; reliability in new patients requires independent validation.

Traceable existing sources

- Frozen coefficients, development counts and stored performance
- Calculation, card and A/B rules
- Existing methods audit and symbols
- Archive census
- 87-family result
- Validation candidate selection
- Prediction-date audit of 51 candidates
- Rapid-test capacity

Links lead to the aggregate records used here; they do not replace original patient-level document review. This guide introduces no new clinical classification or testing recommendation.

16 · Where does our calculator fit within AI?

Artificial intelligence (AI) is the broad field of making computers perform tasks such as learning and problem solving. Machine learning (ML) includes methods that learn patterns from data rather than relying only on hand-written rules. Deep learning (DL) uses artificial neural networks with many layers and is one part of machine learning.

> **AI → machine learning → supervised learning → our logistic regression model. Deep learning is another family of machine-learning methods; our calculator does not use a deep neural network.**

In supervised learning, training examples have recorded outcome labels. Our inputs include diagnosis age, family history and selected tumour features; the target is the recorded BRCA result. We know the outcome during training. For a new prediction, the inputs must be available before the result. Treating information recorded afterwards as if it had been known earlier does not faithfully test intended use.

Different questions in the same field

Question	Input → output	Our calculator?
BRCA-result probability	Clinical features → probability of a recorded positive result	Yes; a research model
Variant calling	Sequencing reads → DNA variant call	No; DeepVariant is an example of a separate task
Variant interpretation	A variant and supporting evidence → clinical classification	No; this model does not reclassify a VUS
Future cancer / treatment response	Suitable baseline data and follow-up → a future outcome	No; a different target and validation are required

Complexity does not guarantee accuracy. Logistic regression assigns a coefficient to each input; a decision tree branches through questions; K-nearest neighbours (KNN) looks at similar training examples; a support vector machine (SVM) learns a separating boundary; neural networks learn transformations through layers. These descriptions are not the results of an algorithm competition. Establishing which works better for our data would require a fair comparison using the same patients and family-separated evaluation. No new comparison was performed here.

DeepVariant: original variant-calling study

17 · How does the computer learn the coefficients?

> **The numbers below are a fictional classroom example only. They are not a real patient, an actual training iteration or a new performance estimate. The calculator's stored coefficients were not changed.**

The learning cycle is: predict using coefficients → compare with the recorded label → calculate loss → update coefficients together → repeat. Performance on examples held outside fitting matters as well as training error. Chapter 5 describes the settings and limitations of how the historical work did this.

Loss measures how far a prediction is from its recorded label during training. Logarithmic loss (log loss) strongly penalises confident wrong predictions. Here y is the recorded label: 1 for Positive, 0 for other labels. p is the raw positive probability during training, not the final calibrated percentage on screen. ℓ (lower-case L) is one example's loss; ln is the natural logarithm.

$$\ell = -\left[y \ln(p) + (1-y) \ln(1-p)\right]$$

One fictional example labelled positive

For an example labelled positive, predicting a raw probability of 20% gives a loss of about 1.609. Predicting 80% for that same example gives about 0.223. Assigning only 1% to a positive example gives about 4.605: a larger penalty for a confident wrong prediction.

$$-\ln(0.20) \approx 1.609$$

$$-\ln(0.80) \approx 0.223$$

$$-\ln(0.01) \approx 4.605$$

Training does not simply increase one example's percentage: errors on other examples also matter. Class weights give more influence to errors on the smaller positive class. The L2 penalty counterbalances excessively large coefficients. Lower loss can mean a better fit to the training data; it does not by itself establish better performance in new patients.

For a coefficient β, the squared-penalty contribution is 1 when β=1 and 9 when β=3; total penalty strength also depends on its setting. This illustrates only the shape of the penalty. Under our stored parameterisation, smaller C means stronger regularisation. C is not a patient-specific risk control to adjust manually.

$$1^2 = 1, \qquad 3^2 = 9$$

Training and use are different activities

During training, labels help determine coefficients; calibration and decision rules are then evaluated. During live use, the stored coefficients are fixed: editing an input only recomputes the existing formulas. Your entries are not stored as new training examples. Changing a fictional profile's percentage does not measure model performance or a biological effect.

The web lesson lets you follow learning step by step with eight fictional examples. Go back to compare weights, errors and new predictions. This small classroom experiment is not a record of the actual model's training.

Watch learning with fictional data

Log loss: method explanation

Logistic regression and regularisation: method documentation

18 · The earlier publication and today's calculator

The 2023 book chapter by Adibi and Yazıcı, "Artificial Intelligence and Machine Learning Applications in Precision Medicine and Genomic Diagnostics", reviews applications in the field. It is not an independent validation report for today's calculator. Its BRCA example on printed page 72 cites Yazıcı and colleagues' 2020 study. For algorithm and performance details, we use the original paper linked below.

Aspect	2020 publication	Today's calculator
Data group	2,070 high-risk breast cancer patients; initially 125 features	Original development group: 1,295 people
Target	Identification of BRCA1/2 negativity	Probability of a recorded positive result and separate test-priority rules
Method	Comparisons involving KNN, decision trees and SVM; highlights a nine-feature dataset	Class-balanced L2 logistic regression + stored calibration; a separate points card
Reported measure	92.88% accuracy	Stored internal cross-validation AUC: 0.776; methodological limitations in chapter 11
Independent validation	This publication does not validate today's model	The expanded archive has not yet supplied an eligible, dated independent set

> **The published 2,070, the development group of 1,295 and the archive's 2,148 describe different record scopes. They cannot be added or subtracted to infer new or independent patients. Counts alone do not establish patient or family overlap between the publication and today's data.**

Accuracy is the proportion classified correctly at a particular decision threshold. AUC summarises ranking across thresholds. A reported accuracy of 92.88% and an AUC of 0.776 are not two success rates on the same scale and cannot be directly ranked. Data group, outcome labels, class balance, patient/family separation and evaluation design also matter.

Shared research interests, authors or archives do not establish that two tools are the same fitted model. A calculation taking under two minutes does not establish replacement of genetic testing, safe test reduction, cost savings or measured treatment benefit. Our site does not present those outcomes as established clinical benefits.

2020 original paper: PubMed record and full-text link

2020 original paper: DOI

2023 review chapter: Istanbul University publisher source

These additions are educational. No new patient analysis or algorithm comparison was performed; the clinical model was not retrained and the calculator's arithmetic was not changed.