SI No	Terminologies	Clustering (Un - Supervised)		Dimension Reduction
	reminologies	K-Means Clustering	Hierarchial Clustering	Principal Component Analysis
	Key Concepts	Centroid Convergence based on Eucledian Distance Elbow Curve (WSS - Within Sum of Squares> No of Clusters vs WSS)	Dendrogram: Hierarchy created from the smallest to largest distance. It's of 2 types: Agglomerative: Bottoms up / Smallest to Largest distance (preferred) Divisive: Top Down	Dimension Reduction Technique
1	Category	No Target Variable	No Target Variable	No Target Variable
2	Linear/Non-Linear	Linear Data Only. Spectral Clustering for Non Linear Data	Linear Data Only	Linear Data Preferred
3	Method	Distance Based	Distance (proximity) Based	
4	Scaling	Required	Required	Required
5	Correlation Check	Recommended	Recommended	Not Needed
6	Outlier Treatment	Required	Required	Required
7	H/W Requirement	Low	High	
8	Reliability	Data cannot be interpreted due to complexity		
9	Comments	# Works well with Large Datasets # Results are not scalable and not reproducible as centroids are created randomly	# Works only with small datasets but results are scalable and reproducible # High Time Complexity of order n^2 # Rarely Used	# Used for vast datasets # Used in Preprocessing before applying ML Model
10	Use Cases	Market Segmentation, Document Clustering	Hard Disk Organization, Social Network Data Storage	Image Compression, Facial Expression Data
		1	Agglomerative Step 0 Step 1 Step 2 Step 3 Step 4 Leaf a a b c de Root Leaf C de Step 4 Step 3 Step 2 Step 1 Step 0 Divisive (DIANA)	0.0014- 0.0012- 0.0008- 0.0008- 0.0008- 0.0004- 0.0004- 0.00015 0.002 0.0025 0.0003