Comprehensive Algorithm Categories for WTA

Five major categories of solution approaches

Exact

- Optimal solutions
- Exponential time
- Small instances

Approximation

- Provable bounds
- Polynomial time
- Large instances

Randomized

- Probabilistic
- Quality $\propto$ samples
- Baseline approach

Heuristic

Fast, problem-specific, near-optimal

Metaheuristic

General-purpose, exploration/exploitation balance

Category 1: Exact Exponential Algorithms

Guarantee Optimal Solutions with Proven Bounds

These algorithms guarantee finding the optimal solution but have exponential time complexity.

Algorithm	Description	Complexity	Solution Quality
Branch-and-Bound (B&B)	Uses LP/IP relaxations with branching on weapon-target assignments. Employs maximum marginal return for branching strategy and network flow for lower bounds.	Worst-case: $O(2^{mn})$ nodes	Optimal; handles up to 80×80 instances
Branch-Price-and-Cut (BPC)	Reformulates WTA for column generation with efficient pricing problem solver. Uses clique cuts and power cone optimization for tight relaxations.	Polynomial per iteration; $O(nm \cdot K)$	Optimal; solves 10000+ in seconds
Branch-and-Adjust	Specialized B&B using compact piecewise linear convex under-approximation of objective. Built on MILP solvers with custom callbacks.	Exponential worst; poly approx	Optimal; 2% gap for 1500×1000 in 2h

Trade-off

Pro: Optimal solutions with proven bounds **Con:** Only practical for instances < 1000 variables

Category 2: Approximation Algorithms

Provable Bounds with Polynomial Time Complexity

These algorithms provide theoretical guarantees on solution quality while running in polynomial time.

Algorithm	Description	Complexity	Solution Quality
Piecewise Linear Approximation	Approximates nonlinear survival probability using piecewise linear convex functions with breakpoints. Based on logarithmic transformation — $\log(1-p_{ij})$.	$O(mn \cdot B)$ where $B =$ breakpoints	Provable δ-error bounds; suboptimal but efficient
LP Relaxation + Rounding	Relaxes integer constraints to LP, solves continuous problem, then rounds to feasible integer solution using various rounding schemes.	$O(\text{poly}(m, n))$ (interior point)	No approximation guarantee; may violate constraints
Lagrangian Relaxation	Relaxes weapon constraints via Lagrangian multipliers, decomposes into independent target subproblems. Uses subgradient method for multiplier updates.	$O(T \cdot nm)$ where $T =$ iterations	Provides lower bounds; typically 5-15% gap

Instance Size Capability

Can handle $>$ 10000 variables efficiently

Category 3: Randomized Algorithms

Probabilistic Methods for Solution Space Exploration

These algorithms use randomness to explore the solution space.

Algorithm	Description	Complexity	Solution Quality
Monte Carlo Sampling	Generates multiple random weapon-target assignments, evaluates each using survival probability function, selects best assignment.	$O(S \cdot mn)$ where S = samples	Baseline; expected value $\rightarrow$ optimal as $S \rightarrow \infty$
Randomized Constructive Heuristic	Builds solutions by probabilistically selecting weapon-target pairs based on marginal returns with added randomness to escape local optima.	$O(R \cdot mn)$ where R = restarts	Variable ($\pm$10-20%); depends on random seed

Category 4: Heuristic Algorithms

Problem-Specific Knowledge for Fast Good Solutions

Heuristics use domain knowledge to quickly find good (but not necessarily optimal) solutions.

Algorithm	Description	Complexity	Solution Quality
Maximum Marginal Return (MMR)	Greedy algorithm that sequentially assigns each weapon to target yielding maximum reduction in survival probability. Based on $\Delta_{ij} = V_j(q_j - q_j \cdot q_{ij})$.	$O(mn)$	Near-optimal; optimal when p_{ij} uniform; typically <5% from optimal
Very Large-Scale Neighborhood (VLSN)	Explores exponentially large neighborhoods via improvement graphs. Uses multi-exchange moves to escape local optima.	$O(m^2n^2)$ per iteration	High quality; improves MMR by 2-5%; effective for 200×200
MRBCH	Iteratively selects weapon-target-sensor triplets based on dynamic marginal return calculation. Updates threat values after each assignment.	$O(mn \log(mn))$	Fast; within 3-8% of optimal for sensor-WTA

Category 5: Metaheuristic Algorithms

General-Purpose Optimization Frameworks

Metaheuristics are adaptable frameworks that balance exploration and exploitation.

Algorithm	Description	Complexity	Solution Quality
Genetic Algorithm (GA)	Population-based evolution with crossover (weapon reassignment between parents) and mutation operators. Uses tournament selection and elitism.	$O(G \cdot P \cdot mn)$ G=gens, P=pop	Good for medium-large; 5-10% gap; may converge prematurely
Ant Colony Optimization (ACO)	Pheromone-based probabilistic construction. Transition probability: $P_{ij} = \frac{[\tau_{ij}]^\alpha [\eta_{ij}]^\beta}{\sum [\tau]^\alpha [\eta]^\beta}$	$O(I \cdot A \cdot mn)$ I=iters, A=ants	Competitive; avoids premature convergence; elite ant effective
Modified Pareto ACO (MPACO)	Multi-objective ACO for bi-objective WTA. Uses dynamic heuristic info, improved movement probability, dynamic evaporation rate, boundary mutation.	$O(I \cdot A \cdot mn \cdot K)$ K=objectives	Superior Pareto front; outperforms NSGA-II and SPEA-II

Complexity Comparison Summary

When to Use Each Category?

The choice depends on instance size, time constraints, and solution quality requirements.

Category	Typical Complexity	Instance Size Limit	Use Case
Exact	$O(2^{mn})$ - Exponential	< 1000 variables	When optimality required
Approximation	$O(\text{poly}(m, n))$	> 10000	Need theoretical bounds
Randomized	$O(S \cdot mn)$	Any (quality $\propto S$)	Baselines, diversity
Heuristic	$O(mn)$ - $O(m^2 n^2)$	> 1000	Real-time systems
Metaheuristic	$O(I \cdot P \cdot mn)$	> 10000	Large-scale optimization