

NOMEX SUIT

DUPONT FIRE FIGHTING NOMEX SUIT



DuPont™ Nomex® is a revolutionary heat and flame-resistant fiber, providing protection Nomex® III A - innovative fiber is a blend of 93% Nomex® with 5% Kevlar® and 2% anti-static fiber. This fiber forms a protective guard to skin.

- NOMEX® 3 LAYER
- Construction
- Outer Shell : Nomex® rip stop construction for greater abrasion resistance
- Moisture barrier : Resistant to water penetration and liquid chemicals
- Thermal liner : FR felt attached to FR face cloth
- Reflective Tape : Tested to EN 471
- Standard : EN 469
- Fireman helmet as per EN443
- Fireman hand gloves, waterproof and fire resistant
- Fireman boots as per EN345-2

Flame Retardant Suit



- Material : Proban[®] treated 100% cotton fabric
- Weight : 350 ± 5% g/m² (10.32 ± 5% Oz/Yd²) or custom weight
- Sizes : Small, medium, large and extra large or custom size
- Style : Single piece coverall with or without reflective tapes Jacket and pant with or without reflective tapes
- Long coat
- Standard:Bib type apron
- Flame resistance : NFPA 2112, ASTM F1506-2010a, ATPV 12 CAL/CM2
- Application: Metal industries, electrical industries, chemical manufacturing or anywhere there is a risk of fire.

Cotton Boiler Suit with Reflective strips.



-
- Material : Proban ® treated 100% cotton fabric
 - Weight : 350 ± 5% g/m² (10.32 ± 5% Oz/Yd²) or custom weight
 - Sizes : Small, medium, large and extra large or custom size
 - Style : Single piece coverall with or without reflective tapes Jacket and pant with or without reflective tapes
 - Long coat
 - Standard: Bib type apron
 - Flame resistance : NFPA 2112, ASTM F1506-2010a, ATPV 12 CAL/CM²
 - Application: Metal industries, electrical industries, chemical manufacturing or anywhere there is a risk of fire.

Chemical Suit

TYCHEM® C SUIT



Dupont™ Tychem® C, hooded coverall is available in bright yellow for high visibility and with elasticated face, wrists, waist and ankles for an optimal fit, thumb loops prevent sleeves from riding up. Made from a lightweight and durable fabric (<450g per garment), Tychem® C garments utilise the strength of Tyvek® and a polymeric barrier coating to offer good permeation barrier protection against a wide range of inorganic chemicals and biological hazards (even under pressure).

- EN 14126 (barrier to infective agents), en 1073-2 (protection against radioactive contamination)
- Anti-static treatment (EN 1149-5) - on inside
- Stitched and over-taped seams with barrier tape for protection and strength
- Self-adhesive double zipper flap closure system for higher protection
- Also available in two piece - jacket and pant

DUPONT TYVEK 400 SUIT



DuPont™ Tyvek® 400, model TY198S WH. Hooded coverall available in white, in sizes SM to 3XL. Stitched external seams. Robust yet lightweight (<180g per garment). 3-piece hood for optimal fit to head and face when turning. Elasticated face, wrists and ankles as well as glued-in waist elastic. Ample crotch area for freedom of movement. Tyvek® garments are composed of flash spun high density polyethylene, providing an ideal balance of protection, durability and comfort. Tyvek® is permeable to both air and water vapour, yet repels water-based liquids and aerosols. It offers an excellent barrier against fine particles and fibres (down to 1 micron in size), is ultra-low-linting, antistatically treated. Silicon non added. Applications for Tyvek® 400 garments include pharmaceutical handling, chemical protection, oil and gas industry, general maintenance/operations, spray painting, general clean-up, amongst many others

- Limited-Use protective clothing, Type 5 and 6 Protection
- EN 1073-2 (protection against radioactive contamination)
- Antistatic treatment (EN 1149-5) - on both sides
- Stitched external seams for enhanced protection against penetration from the outside to the inside of the garment
- Tyvek® zipper and zipper flap for enhanced protection

DUPONT TYVEK 600 SUIT



Tyvek® 600 garments are composed of flash spun high density polyethylene which creates a unique, nonwoven material available only from DuPont. Tyvek® garments provide an ideal balance of protection, durability and comfort. They are now available with serged and over-taped seams that provides the performance of Type 4/5/6 garments, which have been tested to standards against heavy liquid aerosols and airborne solid particles. The coveralls provide an effective barrier against many water-based inorganic chemicals in low concentration and particles (down to 1.0 micron in size). Tyvek® 600 coveralls are suitable for applications such as pharmaceutical manufacturing, medical applications, research and biosecurity laboratories, nuclear and maintenance. Tyvek® 600 Type 4/5/6 coveralls offer the following safety and comfort

- Chemical protective clothing, Category III, Type 4-B, 5-B and 6-B
- EN 1073-2 (protection against radioactive contamination)
- Protection against infective agents (EN 14126) including resistance to penetration by blood and body fluids using synthetic blood (ISO 16603)
- Antistatic treatment (EN 1149-5) - on both sides
- Fabric and seams offer chemical permeation barrier to low concentration water-based inorganic chemicals
- Serged and over-taped seams for protection and strength
- Self-adhesive chin flap for tight seal of suit to the mask
- Elastic face, wrists and ankles as well as glued-in waist elastic
- Elastic thumb loops keep sleeves in place
- Packaged Individually

PVC SUIT /APRON

PVC Suit



-
- Material : Soft non-toxic PVC .
 - Design : Coat, Pant & Hood OR Coverall type
 - Electrically welded instead of conventional stitching making it leak proof, tough and durable.
 - Acrylic visor fitted in the Hood to give unrestricted clear vision.
 - Generously cut for ease of movements, construction of Hood permits easy breathing.
 - Acid/Alkali resistant Temperature withstanding capacity with hot
 - Acid/alkali is 60 Deg. C Safe limit
 - Color : yellow
 - Applications : Used for splash protection in a variety of industrial environments, including pulp and paper manufacturing, food processing,
 - chemical processing and pharmaceutical manufacturing.

PVC APRON WITH BUCKLE



LEATHER APRON



-
- Leather Grade: AB
 - With Kevlar Thread Stitching

PRESSURE SUIT



-
- PRESSURE SUIT WITH AIRLINE ADAPTOR
 - Colour - yellow, grey , white which is readily available as per lot.

FIRE PROXIMITY ALUMINISED SUIT



-
- Three layer tested to EN1486:2008 and is made from multilayer assembly
 - Outer Shell: Aluminum fabric with fiber glass backing
 - 2nd Layer: Thermal Liner Heat resistant FR non woven
 - 3rd layer: FR face cloth

- High resistance to heat impacts
- The Aluminised suits is available in coverall (or) Jacket and Trouser, has a provision for housing a BA set
- Certified EN166 High tech polymer. Helmet adjustable internally in accordance with safety requirements
- Over Boots : Insulated quilted fabric FR compound. FR Zipper at side for easy wear and removal. It has HR Nitrile rubber antiskid sole
- Hood: Full face cover with space for mask dispensing unit. Panoramic visor golden polycarbonate FR toughened glass
- Gloves: A pair of five fingers, made from the same by 3 layers. Velcro® FR fastening strap on the forearm
- Size: S to XXXL
- Color: Silver