

UDYOGI 6220 GI SAFETY SHOWER



-
- Safety Shower and eyewash operates independently by pull rod, hand push lever and foot lever
 - Pipe : ISI marked GI pipe with powder coating for anti-corrosion
 - Valve : SS stay open ball valve with yellow ABS push plate
 - Bowl : Receptor bowl made of ABS and highly resistant to acid, alkali and oil among others.
 - Activation : Push plate and foot paddle
 - Water inlet and drain: 1/2 inches BSP inlet and 1¼ inches BSP drain
 - Standard : IS: 10592:1982
 - Automiser heads : Twin soft flow automiser head which has aerators to control the stream straightness and diameter, thus reducing splash by aerating the stream. It also controls to save water and reduce energy costs. The twin flow has cover which protects from dust and opens with water pressure.

UDYOGI 6250 GI SAFETY SHOWER



-
- Safety Shower and eyewash operates independently by pull rod, hand push lever and foot lever
 - Pipe : ISI marked GI pipe with powder coating for anti-corrosion
 - Valve : SS stay open ball valve with yellow ABS push plate
 - Bowl : Receptor bowl made of ABS and highly resistant to acid, alkali and oil among others.
 - Activation : Push plate and foot paddle
 - Water inlet and drain: 1/2 inches BSP inlet and 1¼ inches BSP drain
 - Standard : IS: 10592:1982
 - Automiser heads : Twin soft flow automiser head which has aerators to control the stream straightness and diameter, thus reducing splash by aerating the stream. It also controls to save water and reduce energy costs. The twin flow has cover which protects from dust and opens with water pressure.

UDYOGI 4220 GI EMERGENCY EYE/FACE WASH FOUNTAIN



-
- Emergency eye/face wash fountain operates independently by push lever and foot paddle
 - Pipe : ISI marked GI pipe with powder coating for anti-corrosion
 - Valve : SS stay open ball valve with yellow ABS push plate
 - Bowl : Receptor bowl made of ABS and highly resistant to acid, alkali and oil among others.
 - Activation : Push plate and foot paddle
 - Water inlet and drain: 1/2 inches BSP inlet and 1¼ inches BSP drain
 - Standard : IS: 10592:1982
 - Automiser heads : Twin soft flow automiser head which has aerators to control the stream straightness and diameter, thus reducing splash by aerating the stream. It also controls to save water and reduce energy costs. The twin flow has cover which protects from dust and opens with water pressure.

UDYOGI 4710 GI EMERGENCY EYE/FACE WASH FOUNTAIN



-
- Emergency eye/face wash fountain operates independently by push lever and foot paddle
 - Pipe : ISI marked GI pipe with powder coating for anti-corrosion
 - Valve : SS stay open ball valve with yellow ABS push plate
 - Bowl : Receptor bowl made of ABS and highly resistant to acid, alkali and oil among others.
 - Activation : Push plate and foot paddle
 - Water inlet and drain: 1/2 inches BSP inlet and 1¼ inches BSP drain
 - Standard : IS: 10592:1982
 - Automiser heads : Twin soft flow automiser head which has aerators to control the stream straightness and diameter, thus reducing splash by aerating the stream. It also controls to save water and reduce energy costs. The twin flow has cover which protects from dust and opens with water pressure.

UDYOGI 6220 SS SAFETY SHOWER



-
- Safety Shower and eyewash operates independently by pull rod, hand push lever and foot lever
 - Shower : Extra large drench shower head made of stainless steel
 - Pipe : SS 304 pipe
 - Valve : SS stay open ball valve with push plate
 - Bowl : Receptor bowl made of SS and highly resistant to acid, alkali and oil among others.
 - Activation : For shower - Pull rod; For eyewash – Push plate/ Foot paddle
 - Water inlet and drain : 1-1/4 inches BSP
 - Standard : IS: 10592:1982
 - Automiser heads : Twin soft flow automiser head which has aerators to control the stream straightness and diameter, thus reducing splash by aerating the stream. It also controls to save water and reduce energy costs. The twin flow has cover which protects from dust and opens with water pressure

UDYOGI 6250 SS SAFETY SHOWER



-
- Safety Shower and eyewash operates independently by pull rod, hand push lever and foot lever
 - Shower : Extra large drench shower head made of stainless steel
 - Pipe : SS 304 pipe
 - Valve : SS stay open ball valve with push plate
 - Bowl : Receptor bowl made of SS and highly resistant to acid, alkali and oil among others.
 - Activation : For shower - Pull rod; For eyewash – Push plate/ Foot paddle
 - Water inlet and drain : 1-1/4 inches BSP
 - Standard : IS: 10592:1982
 - Automiser heads : Twin soft flow automiser head which has aerators to control the stream straightness and diameter, thus reducing splash by aerating the stream. It also controls to save water and reduce energy costs. The twin flow has cover which protects from dust and opens with water pressure

UDYOGI 4710 SS EMERGENCY EYE/FACE WASH FOUNTAIN



-
- Emergency eye/face wash fountain operates independently by push lever
 - Pipe : SS 304 pipe
 - Valve : SS stay open ball valve with push plate
 - Bowl : Receptor bowl made of SS and highly resistant to acid, alkali and oil among others.
 - Activation : Push plate and foot paddle
 - Water inlet and drain : 1/2 inches BSP inlet and 1¼ inches BSP drain
 - Standard : IS: 10592:1982
 - Automiser heads : Twin soft flow automiser head which has aerators to control the stream straightness and diameter, thus reducing splash by aerating the stream. It also controls to save water and reduce energy costs. The twin flow has cover which protects from dust and opens with water pressure

UDYOGI 4810 GI



-
- Wall Mounted Eye/Face Wash
 - Valve : SS stay open ball valve with yellow ABS push plate
 - Bowl : Receptor bowl made of ABS and highly resistant to acid, alkali and oil among others.
 - Automiser heads : Twin soft flow automiser head which has aerators to control the stream straightness and diameter, thus reducing splash by aerating the stream. It also controls to save water and reduce energy costs. The twin flow has cover which protects from dust and opens with water pressure.
 - Activation : Push plate
 - Water inlet and drain : 1/2 inches BSP inlet and 1 1/4 inches BSP drain
 - Standard : IS: 10592:1982

Portable Eyewash fountain with Handle



- 34 liters capacity