

Fire Fighting Nozzle



The selectable flow rate multipurpose nozzle. This Product is very light in weight and easy to handle. The calibrated flow rates are easily selectable through an indexed ring and the maximum rate is indicated by a raised lug. The stream patterns are also changed by rotating the diffuser head ring with tactile marking (Straight jet, Spray and Fog) These Nozzles are used by large number of firefighters across the globe.

- MATERIAL : Aluminum Alloy
- WEIGHT : 2.5 KG
- BODY TYPE : Cut in to Bars
- PISTOL GRIP : Single.
- INLET : Instantaneous Coupling.
- WORKING PRESSURE : PN 16
- SELECTABLE FLOW RATE : 150-250-350-500 LPM .
- SHUTOFF : Ball Valve
- OPENING : Operating Handle
- FLUSH POSITION : Yes

FIRE FOSE



-
- PREMIER EXTRA brand, all synthetic fiber circular woven
 - Jacketted EPDM synthetic rubberised externally synthetic elastomer
 - Coated / covered fire delivery hose With Coupling with binding ISI mark as per IS 636 Type A
 - Dia : 63mm dia 15mtr length

FIRE FOSE PYROPROTECT



“PYROPROTECT” Brand non percolating flexible fire fighting delivery hose, three layered synthetic jacketed with elastomeric outer covering resistant to liquid, chemicals, acids, alkalies, solvents, ozone, abrasion & heat having 42 kg/cm² burst pressure, 25kg/cm² proof pressure, 18kg/ cm² working pressure, With Coupling with binding bearing IS : 636 –1988 Type B mark. Having UL /Lloyds approval. Length : 15mtr. Dia : 63mm

FIRE HOSE BOX



Fire Hose Box Mounting Type, Made Out Of 18 Gauge Mild Steel, 30' X 24" X 10" Size To Accommodate, glass Fronted Double Door. Painted Red Outside And White Inside. fitting Should Be By Metal Strip.

HOSE REEL DRUM



SRI fire hose reels are tested and approved to European Standard EN671 by British Standards Institution and to Australian Standards AS1221 by QAS Australia. These approvals require the certification authority to carry out regular inspection of our hose reels manufacturing facility, testing of hose reels and auditing of quality system. With rigorous inspection and testing of our fire hose reels during production the performance and reliability is at the highest standard. SRI manufactures a wide selection of fire hose reel, 3/4" and 1", swing and fixed type, manual and

automatic. Swing type hose reel has double 180° rotating hinge, which allows hose reel to be mounted in a recessed wall and fixed type hose reel is complete with hose guide which allows the hose withdrawal in all directions

- Side Plate powder painted finish red
- Automatic hose reel has integrated automatic stop valve which will open after 2 revolution of the reel
- Threaded Inlet connection
- Outlet connection for hose can be rotated for left and right direction
- Waterways made from non ferrous metals which ensure corrosion free*
- Maximum working pressure 15Bar, test pressure 20bar
- Side plate available in stainless steel

GUN METAL FIRE HYDRANT VALVE 63MM ISI MARKED



-
- Item Description : 63mm Fire Hydrant Valve Right Angle, having 63mm NB inlet & 63mm Female Inst. outlet.
 - Ref. Standard : BS:336
 - Material of construction : Gunmetal
 - Inlet : Flanged
 - Outlet : Generally Female Instantaneous (Male Inst. Outlet available on request) Size : 63mm
 - Ordering Details :Material : GM
 - ISI marked

DOUBLE HEADED HYDRANT VALVE



-
- Double Headed Hydrant Valve are designed and manufactured as per IS:5290-1993.
 - Highly Durable and Corrosion Resistant.
 - Excellent Flow Characteristics

WATER FOAM MONITOR



Water foam type monitor. Stand Post Type Water Foam Monitor Body having 75mm Barrel size having Body Carbon Steel, having 100mm N.B. flanged inlet with Ball bearing and swivel joints with locking flow capacity of 2580LPM@7Kgf/cm² as per IS:- 8442 type "I", ISI marked with Aluminum Aqua Foam Nozzle with 3 mtr. Length PVC Pick up tube and SS strainer. ISI mark

FB 5X Foam Branch



- Low expansion foam branch with 225 LPM flow at 7 bar with expansion ratio of 1:2 to 1:10.
- With in-built foam inductor along with pick-up tube and dip pipe.
- Built-in foam proportioning valve from 0 to 6% induction.
- Built-in shut off valve

FRP Mobile Foam Unit



FRP Mobile Foam Unit (MFU), Aero dynamic shape Consisting of liter capacity, corrosion resistant FRP 100 Ltrs. Tank Complete with One , Inline Inductor, MOC: Al. Alloy, with connection to foam tank and One Foam making Branch Pipe with 63mm male inst. Inlet, Unit mounted on a rubber-tyred trolley with a handle & 6" castor wheel With 2 length of fire hoses type A 63mm X 15 Mtr. Length fire hose pipe as per IS: 636 Type 'B', ISI marked with "SS 63mm male & female coupling, as per IS: 903, ISI marked duly binded with Copper Wire

Short Branch Pipe



-
- Short Branch Pipe SS/GM Metal 63mm with Detachable Hexagonal Nozzle as per IS:903 with ISI Mark



Fire bucket



Fire Bucket Stand



Fireman Beater



Fireman axe with handle

FIRE EXTINGUISHER

ABC Fire Extinguisher



-
- Dry Chemical Powder (Stored Pressure Type) Mono Ammonium Phosphate 50% concentration powder confirming to 'IS 14609' , Nitrogen Pressurized, Controllable Discharge Mechanism, Pressure Gauge, Discharge Hose & Nozzle Epoxy Polyester Powder Coated As per 'IS 15683' ISI Mark Fire Extinguishers.
 - Operating Temperature: - (-) 20°C to (+) 55°C Suitable for 'A' 'B' 'C' Class of FIRE.

DCp Fire Extinguisher



-
- Dry Chemical Powder (Stored Pressure Type) Sodium Bi-Carbonate powder confirming to 'IS 4308', Nitrogen Pressurized, Controllable Discharge Mechanism, Pressure Gauge, Discharge Hose & Nozzle Epoxy Polyester Powder Coated As per 'IS 15683' ISI mark Fire Extinguishers.
 - Operating Temperature: - (-) 20°C to (+) 55°C Suitable for 'A' 'B' 'C' Class of FIRE.

Water/foam Based Fire Extinguisher



-
- Water Based(Stored Pressure Type) ,Nitrogen Pressurized, Controllable Discharge Mechanism, Pressure Gauge, Discharge Hose & Nozzle Epoxy Polyester Powder Coated As per 'IS 15683' ISI mark Fire Extinguishers.
 - Operating Temperature:- (+)50C to (+)550C.
 - Suitable for 'A' Class of FIRE (for WATER) & 'A' 'B' Class of FIRE(for AFFF 6% FOAM confirming to IS 4989)

Co2 Fire Extinguisher



-
- Carbon Di-oxide Type , Gas Confirming to IS '15222' , Cylinder Confirming to 'IS 7285' & PESO approved ,Controllable Discharge Mechanism, Discharge Hose & Horn As per 'IS 15683' & 'IS 2878' ISI mark Fire Extinguishers (Wheel Type or Squeeze Grip Type)

- Operating Temperature :- (-)20oC to (+)55oC Suitable for 'B' 'C' Class of FIRE

D Class Fire Extinguisher



- TEC Based Stored pressure type 4Kg capacity with Squeeze grip Valve, pressure Gauge, Discharge hose applicator tube with dome type nozzle made as per IS 15683 Fire Extinguisher Suitable for D Class of fire For Metal(NON ISI)

Modular ABC Type Fire Extinguisher



- Modular Automatic Fire Detection working pressure 30kgf/cm²
- discharge time 10 seconds,
- heat ensitive glass bulb sprinkler head range 68 degree filled with ABC Dry Chemical Powder50% ABC Modular

Modular Clean Agent Type Fire Extinguisher



-
- Modular Clean Agent HFC236fa Extinguishers 68° C
 - Modular Type Automatic Fire Extinguisher 68° C with Clean Agent HFC236fa, UL Listed Ceiling Mounted Type Capacity

Fire Ball



-
- Easy To Use : No Training required, just throw the ball with one Hand into the Fire
 - Self Activating : It Works Automatically When in contact with Fire (Install it within 30 Centimeters Over any Fire Hazard)
 - Fire Extinguishing Agent : Non-Toxic Mono Ammonium Phosphate

- Alarm : When It Explodes, The Built-In Alarm Goes OFF Releasing an Approximately 138 Decibel Noise
- Weight : 1.3 KG (Un-Packed)
- Safe : Don't have to get too close to fire, just Roll into Fire from a Distance for ActivationActivates
- Fast And Effective : ActivationActivates within 3 Seconds after getting in contact of Fire
- Colour : Red
- Dimension : Diameter : 14.5 cm
- Covering Area : 5 meters
- fire Rating : Class A, B, C
- container : Outer Layer Of Pent Foam, About 11 Mm Thick Shield By Pvc Film