

Udyogi Di Electric Harness



-
- Anchor point: One dorsal D-ring and Two textile chest attachment loop and two lateral D-ring.
 - Special features: Integrated work positioning, built-in dual colour webbing for easy orientation, waist pad, sit-strap positioned for extended comfort
 - Materials: Fray proof dope: dyed polyester webbing. All metal components high class polymer coated, electrically insulated
 - Stitching: High-strength polyester stitching
 - Adjustability: Chest, Thigh & Shoulder
 - Standard: Conforms to EN 361:2002 & EN 358:1998

Udyogi Fr Jacket With Fr Harness



-
- Anchor point: One dorsal D-ring and Two textile chest attachment loop
 - Special features: High visibility jacket harness made of 100% FR fluorescent fabric, 3M Scotchlite tape in front and back for easy visibility
 - Material: Flame retardant webbing to withstand upto 7000F / 3710C
 - Stitching: High-strength polyester stitching
 - Adjustability: Size adjustment strong at chest & thighs
 - Standard: EN 361:2002 & as per ISO 15025:2005

UDYOGI Eco 1



-
- Anchor point: : One dorsal D-ring and Two textile chest attachment loop.

- Special features: Ideally positioned sit-strap for extended comfort Built-in dual colour webbing for easy orientation.
- Material: Fray-proof dope-dyed polyester webbing Metal buckles of high strength alloy steel.
- Stitching: High-strength polyester stitching.
- Adjustability: Size adjustment straps only at chest and thighs.
- Standard: IS 3521: 2005 ISI Marked, DGMS Approved.

UDYOGI UB 102



-
- Anchor point One dorsal D-ring and Two textile chest attachment loop.
 - Special features Ideally positioned sit-strap for extended comfort Built-in dual colour webbing for easy orientation.
 - Materials Fray-proof dope-dyed polyester webbing Metal buckles of high strength alloy steel.
 - Stitching High-strength polyester stitching.
 - Adjustability Size adjustment straps only at chest and thighs.
 - Standard EN 361 CE Marked.

UDYOGI Ultratek



- Anchor point: : One dorsal D-ring, Two chest attachment textile loop, One ventral loop, Two lateral D-ring
- Special features: Multipurpose harness, ideal for professional use and rescue One external attachment point for rescue & descending Ergonomic Horizontal H-shaped thigh straps
- Material: Fray-proof dope-dyed polyester webbing Metal quick buckles of high strength alloy steel
- Stitching: High-strength polyester computer-controlled stitching ensures consistency
- Adjustability: Adjustment straps at shoulder, waist, thighs
- Standard: Conforms to EN 361, EN 358 and EN 813

UDYOGI Easy Absorb RL 22



- Energy Absorbing Double Polyamide Rope Lanyard With EASY 308 Karabiner and on other side two EASY SH 60 Scaffolding Hooks
- Rope: diameter 12 mm
- Strength: 23 kN
- Standard: Conforms to EN 355:2002 and 354:2010

USP 15 with DOUBLE USP 210 2mtr PP



Full Body Harness With Double Link Connecting Polypropylene Rope Lanyard, One Side Loop & Other Side Scaffold Hook H-10

USP 16 with DOUBLE USP 210 2mtr PP



Full Body Harness With Two Front Textile Loops With Link Connecting Polypropylene Rope Lanyard, One Side Loop & Other Side Scaffold Hook H-10

Suraksha-1 with DOUBLE USP 210 (2mtr.)PA WITH ENERGY ABSORBER



Full Body Harness With Double Link Connecting Polyamide Rope Lanyard, One Side Loop & Other Side Scaffolding Hook H-10 With Energy Absorber

Suraksha-2 with DOUBLE USP 210 (1.8mtr.)PA WITH ENERGY ABSORBER



Full Body Harness With Two Front D-ring With Link Connecting Polyamide Rope Lanyard, One Side Loop & Other Side Scaffolding Hook H-10. Adjustable Shoulder Strap And Thigh Straps Incorporated Waist Belt And H-type Thigh Strap.

USP 27 with DOUBLE USP 210 (1.8mtr.)PA and USP 888



USP 27 Adjustable shoulder & thigh strap with dual colour scheme for differentiation 44 mm Polyester Webbing with Min. Breaking Strength 23 kN Two Chest attachment D-Rings for fall arrest. Automatic stitching pattern with strength Metal type chest strap with easy handling Adjustable dorsal high strength forged D-ring, Min. Breaking Strength 23 kN Finished Webbing Ends with web holder. Special design & high resistant polyethylene Back Plate for holding D-Ring even after the fall. Conforms To EN: 361:2002 WITH DOUBLE LINK CONNECTING POLYAMIDE ROPE LANYARD, ONE SIDE LOOP & OTHER SIDE SCAFFOLD HOOK

USP 116 without lanyard



Fully adjustable with comfort padded waist belt. Shoulder & adjustable thigh strap with dual colour scheme for differentiation. 44mm Polyester Webbing with Min. Breaking Strength 25kN Automatic stitching pattern with strength Metal type chest strap with easy handling. Adjustable dorsal high strength forged D-Ring, Min. Breaking Strength 25kN Two lateral D-Rings for work

positioning Suitable for fall arrest and work positioning Special design & high resistant polyethylene Back Plate for holding D-Ring even after the fall. Conforms to EN: 361:2002, EN: 358 USP 160 without lanyard



Fully adjustable with comfort padded waist belt, thigh strap and Shoulder Strap. 44 mm Polyester Webbing with Min. Breaking Strength 23 kN Automatic stitching pattern with strength Metal type chest strap with easy handling Adjustable dorsal high strength forged D-ring, Min. Breaking Strength 23 kN Two lateral D-Rings for work positioning, one sternal D-Ring for fall arrest & one ventral D-Ring for rescue. Suitable for fall arrest, work positioning, descent & ascent & rescue service. Special design & high resistant polyethylene Back Plate for holding D-Ring even after the fall. Conforms To EN: 361: 2002, EN: 358 & EN: 813

USP JH21 without lanyard



Made of Polycotton Consists of Dorsal D-ring with two front attachment textile loops for fall arrest. Has Adjustable chest, shoulder & Thigh Straps. This Comfortable Vest Harness also has Velcro stitched on the D-Ring window provided at the back of the vest for preventing it from slipping into the vest. Has double durable zipper for snug fit. Reflective tapes are stitched on to the vest for increased visibility.