

Vertical Lifeline System

Vertical Lifeline System USP-1000



Features

- System is made of SS 316 Grade Stainless Steel.
- Brackets are designed for ladder rungs but can be easily adapted to most structures.
- Note : System must be used only with VL-50 Rope Grab
- Length : From 3mt to desired length.
- Conform to : EN 353-1:2014

Vertical Lifeline System USP-1000A



Features

- System is made of SS 316 Grade Stainless Steel.
- Brackets are designed for ladder rungs but can be easily adapted to most structures.
- This systems comes with an extended top bracket which can be used by the user to detach itself safely on the roof after connecting to a horizontal lifeline systems.
- Note : System must be used only with VL-50 Rope Grab
- Length : From 3mt to desired length.
- Conform to : EN 353-1:2014

Vertical Lifeline System USP-2000

**Features**

- System is made of SS 316 Grade Stainless Steel.
- Brackets are designed for ladder rungs but can be easily adapted to most structures.
- Note : System must be used only with VL-50A Rope Grab
- Length : From 3mt to desired length.
- Conform to : EN 353-1:2014

Vertical Lifeline System USP-2000A



Features

- System is made of SS 316 Grade Stainless Steel.
- Brackets are designed for ladder rungs but can be easily adapted to most structures.
- This systems comes with an extended top bracket which can be used by the user to detach itself safely on the roof after connecting to a horizontal lifeline systems.
- Note : System must be used only with VL-50A Rope Grab
- Length : From 3mt to desired length.
- Conform to : EN 353-1:2014

Vertical Lifeline System USP-5000



Features

This vertical fall arrest anchorage system is an integrated fall arrest solution made of an Aluminum Alloy Guide Vertical Rail over which glides a Guided- Type Fall Arrest Trolley. Conforming to EN353-1:2014, the line is constructed by attaching the aluminum rail Intermediate of length 3mts. In series using a junction to connect them to each other, and Rung Clamps to affix them to the ladder rungs. The trolley moves up and down on the line accompanying the user who is connected to it with an Auto- locking steel Carabiner.

Vertical Lifeline System USP-6000



Features

This is a complete Fall Protection Ladder System which consists of Hot dipped galvanized Steel Ladder Rungs over which is fixed the Vertical Anchorage Rail made of Aluminum Alloy. This system is an ideal choice for use where there are no pre-fabricated ladders or climbing structures available for climbing and can be fitted over various structures using different types of fasteners. The system conforms to EN 353-1:2014. The Rungs of the Ladder, made of Galvanized Steel, are fitted at a suitable distance from the underlying structure/profile to allow enough foot space. The rungs also have a grooved surface that allows a slip-free grip while climbing. The Aluminum Anchorage Rail fitted on to the center of the Rungs of the ladder is smooth and allows the Guided type Fall-Arrest Trolley to glide effortlessly over its length. This trolley moves up and down accompanying the user who is connected to it with the help of an Auto-locking Carabiner. The Trolley is made of Stainless Steel and has wheels made of Brass, making the system highly corrosion resistant and extremely smooth in working.

Vertical Lifeline System Components



Features

UFS Horizontal Line provide permanent anchorage to a user who has to constantly move along in horizontal track. It is attached with 08 MM SS 316 wire rope all along the horizontal track it is installed at the ends using roof top anchor post Extremity. Roof top intermediate post hold the wire rope in position all along the length of life line.

Intermediates are installed at an interval of 5 to 15Mtr. distance. Wire rope maintains the tension with the help of tensioner at one end and has a Swag less termination on the other end.

Horizontal Lifeline System

Horizontal Lifeline System USP 11000 (Over The Head)



Features

UFS Horizontal Line provide permanent anchorage to a user who has to constantly move along in horizontal track. It is attached with 08 MM SS 316 wire rope all along the horizontal track it is installed at the ends using roof top anchor post Extremity. Roof top intermediate post hold the wire rope in position all along the length of life line.

Intermediates are installed at an interval of 5 to 15Mtr. distance. Wire rope maintains the tension with the help of tensioner at one end and has a Swag less termination on the other end.

Stainless steel Horizontal skater connects the user to the life line with the help of a lanyard and runs smoothly without any interruption along the entire length of the Horizontal life line and also through the intermediate post its ensuring 100% anchorage of the user at all time.

The line also has a Shock absorber at one end which reduces the impact on the user as well as on the extreme ends of the systemThe system is versatile and it can be easily installed on any building roof.

Conforms to EN 795:2012 Type C, TS 16415:2013

Horizontal Lifeline System USP 12000 (Over The Head)



Features

UFS Horizontal Line provide permanent anchorage to a user who has to constantly move along in horizontal track. It is attached with 08 MM SS 316 wire rope all along the horizontal track it is installed at the ends using roof top anchor post Extremity. Roof top intermediate post hold the wire rope in position all along the length of life line.

Intermediates are installed at an interval of 5 to 15Mtr. distance. Wire rope maintains the tension with the help of tensioner at one end and has a Swag less termination on the other end.

Stainless steel Horizontal skater connects the user to the life line with the help of a lanyard and runs smoothly without any interruption along the entire length of the Horizontal life line and also through the intermediate post its ensuring 100% anchorage of the user at all time.

The line also has a Shock absorber at one end which reduces the impact on the user as well as on the extreme ends of the system The system is versatile and uniquely designed to be installed on walls and ceilings.

Horizontal Lifeline System Components



Features

UFS Horizontal Line provide permanent anchorage to a user who has to constantly move along in horizontal track. It is attached with 08 MM SS 316 wire rope all along the horizontal track it is installed at the ends using roof top anchor post Extremity. Roof top intermediate post hold the wire rope in position all along the length of life line.

Intermediates are installed at an interval of 5 to 15Mtr. distance. Wire rope maintains the tension with the help of tensioner at one end and has a Swag less termination on the other end.

Temporary Life Line USP-14010-30



Features

UFS offers a temporary lifeline system that extends safety to the user while working in areas where a permanent lifeline system cannot be installed or may not require due to the temporary nature of work. UFS Temporary Lifeline includes a 30-meter webbing horizontal lifeline, having minimum breaking strength of 2kN. It can be adjusted from 2-meters to 30-meters and includes 2 steel snap hooks.

- Secures an operator throughout travel.
- Horizontal lifeline in 30mm webbing.
- Steel ratchet to put the system into tension after adjusting the required length.
- Supplied with 2 steel snap hooks.
- Adjustable length from 2 mtrs to 30 mtrs.
- Minimum breaking strength 25 kN.

Forked ends in order to : Either anchor to a structure without the need to add anchorage sling, or hang directly on adapted anchorage point.

Tripod USP-TP700



Features

- Tripod Head : Robust Aluminium Alloy cast head with two integral pulleys for smooth operation of the Winch.
- Stainless Steel Eye Bolts : Tested to sustain a force of more than 12 kN static force as per EN 795 CLASS B.
- Telescopic Legs : Fully Adjustable Aluminium Telescopic Legs for use on level surfaces.
- Sturdy Rubber Shoes : Sturdy Rubber Shoes provided With High Abrasion Resistant Sole to increase friction and impart more stability to the Tripod.
- Compliance EN 795:2012 TYPE B

Winch USP-WN710



Features

- Winch - Galvanized Steel wire rope of dia 4.5mm
- Length of cable - 20mtrs
- Connector - Steel screw locking karabiner USP-H9
- Compatibility - Can be mounted on Tripods with the help of their fastener.
- Compliance - EN 1496:2017 (Class A)