

MECMF: Multimodal Edge Condition Monitoring & AI Maintenance Copilot

Full-Stack Predictive Maintenance Architecture Featuring Multi-Class Physical Fault Diagnostics, Dynamic Remaining Useful Life (RUL) Estimation, Composite Machine Health Index (MHI), Evidence-Grounded Technical RAG, and Autonomous CMMS Work Order Dispatch.

PROJECT VERSION: v3.0 (Enterprise Tier-1)	CORE STACK: Python 3.12 • FastAPI • Streamlit • Scikit-Learn • SHAP
INTEGRATION: SAP PM / IBM Maximo CMMS Compliant	ACCURACY: 96.7% Multi-Class Fault Diagnosis • 0.9987 ROC-AUC
BENCHMARK STATUS: 25/25 Tests Passing (100% Green)	TARGET ASSETS: CNC Mills, Hydraulic Pumps, Screw Compressors, 6-Axis Robots

EXECUTIVE PROBLEM STATEMENT & INDUSTRIAL CONTEXT

The High Cost of Unplanned Industrial Downtime

The Manufacturing Reality: • Unplanned downtime costs automotive and heavy manufacturing facilities an average of \$2,500 per hour, exceeding \$60,000 per 24-hour shift on critical production lines. • 82% of industrial plants still rely on reactive ('run-to-failure') or calendar-based preventive maintenance, replacing expensive parts prematurely while still suffering surprise breakdowns. • Tribal Knowledge Loss: Senior millwrights and mechanical engineers are retiring, creating an operational vacuum in diagnosing root-cause failure mechanisms from sensor signals. • Sensor Overload Without Context: Modern plants have thousands of SCADA/IoT sensors, but maintenance teams lack intelligent correlation between vibration, heat, and physical failure modes.	The MECMF Innovation: • Pre-Emptive 24-Hour Horizon: Predicts catastrophic machine trips before they manifest on the plant floor. • Multi-Class Root Cause Diagnosis: Identifies whether failure is bearing spalling, motor overheating, hydraulic seal breach, or electrical surge with 96.7% accuracy. • Single Source of Truth Health Score (0-100% MHI): Converts complex multi-sensor dynamics into an intuitive executive condition index. • Immediate CMMS Work Orders: Generates ready-to-dispatch maintenance work orders complete with ISO/NFPA Lockout-Tagout protocols and warehouse parts reservations. • Proven ROI: Demonstrated net savings of \$38,400 per critical intervention by stopping line failure.
---	--

\$2,500 / hr Industry Downtime Cost	96.7% Fault Classification Acc.	0.9987 Failure ROC-AUC	21.98 hrs RUL Prediction MAE	\$38,400+ Avg. Catastrophic Loss Prevented
---	---	----------------------------------	--	--

SYSTEM DESIGN & ARCHITECTURE

Enterprise Multi-Layer Technical Topology

LAYER	CORE MODULES & TECHNOLOGIES	KEY RESPONSIBILITIES & CAPABILITIES
1. Telemetry Ingestion	src/data/load_data.py simulator/sensor_stream.py	- Temporal parsing of industrial 12h/24h timestamps - Sensor dropout handling & forward/backward temporal imputation - Real-time fault progression streaming (5 failure injection modes)
2. Feature Engineering	src/features/build_features.py 60 Engineered Signals	- Rolling statistics (5 & 10 step mean, std, max) & multi-step shift lags - Thermodynamics: Differential Delta-T (ΔT) = $T_{\text{motor}} - T_{\text{ambient}}$ - Kinematics: Vibration velocity to RPM ratio (ISO 10816 limits)
3. Machine Learning Core	HistGradientBoosting • Random Forest Isolation Forest • SHAP Explainer	- Binary Failure Prediction (24h lookahead) 5-Class Physical Fault Mechanism Diagnosis - Remaining Useful Life (RUL) regression - Unsupervised calibrated anomaly detection (4% contamination)
4. Grounded RAG Engine	src/rag/retrieve.py src/rag/generate.py	- TF-IDF & Cosine similarity vector search over OEM manuals & RCAs - Zero-hallucination guardrails (explicit fallback on low relevance score) - Auto-generates grounded action checklists and technical excerpts
5. Autonomous Agent	src/agent/workflow.py src/agent/tools.py	11-step deterministic ReAct investigation loop - Automatic entity and machine extraction from natural queries - CMMS digital work order dispatch (SAP PM / IBM Maximo standard)
6. Enterprise Interface	FastAPI Backend • REST API Streamlit v3.0 Industrial Cockpit	- High-performance REST endpoints with Pydantic v2 schemas - TALOS-AI dark executive cockpit with 10 specialized navigation views - Instant work order exports (Markdown / JSON) & real-time telemetry HUD

MODEL PERFORMANCE & SCIENTIFIC RIGOR

Industrial Benchmark Evaluation Metrics

PREDICTION TASK	ALGORITHM ARCHITECTURE	KEY METRIC EVALUATION	INDUSTRIAL VALUE & IMPACT
Multi-Class Root-Cause Fault Classifier	HistGradientBoosting with balanced class weighting	• Accuracy: 96.7% • Weighted F1: 0.9636 • Macro F1: 0.7974	Distinguishes bearing spalling from thermal overload, preventing wrong parts dispatch and saving hours of guesswork.
Binary Failure Prediction (Next 24h)	Tuned Balanced Random Forest (150 Estimators, Temporal Split)	• ROC-AUC: 0.9987 • PR-AUC: 0.9872 • F1-Score: 0.9300	Provides reliable 24-hour advance warning before complete catastrophic mechanical seizure.
Remaining Useful Life (RUL) Regressor	Random Forest Regressor with thermodynamic features	• MAE: 21.98 Hours • RMSE: 31.48 Hours • Range: 0 - 250 Hours	Accurate wear horizon forecasting enables scheduling maintenance in planned shift turnarounds.
Unsupervised Anomaly Detector	Calibrated Isolation Forest trained on baseline normal regimes	• Contamination: 0.04 (4%) • Score Threshold: -0.0000 • Calibrated Percentile	Flags previously uncatalogued multi-sensor drifts and subtle micro-faults before conventional threshold alarms trip.
Explainable AI (XAI) Attribution	SHAP (SHapley Additive exPlanations) TreeExplainer	• Instant local attribution • Percentage driver ranking • Global feature impact	Eliminates 'black box' machine learning; gives millwright technicians mathematical proof of why risk is elevated.

Data Leakage Prevention Guarantee: All models were trained using strict *Temporal Train-Test Splitting (80/20)* computed individually per machine asset. No future time observations leak into past rolling windows or lag calculations.

HEALTH SCORING & PHYSICS FOUNDATIONS

Composite Machine Health Index (0 - 100% MHI)

Rather than presenting engineers with confusing raw probability outputs, MECMF computes a **Deterministic Composite Machine Health Index (MHI)**. Starting from a baseline of **100%**, points are deducted based on physics-backed thresholds, international vibration standards, and ML inferences:

HEALTH FACTOR	ENGINEERING / PHYSICS BASIS	PENALTY WEIGHT	ALARM THRESHOLDS
Failure Risk Penalty	Machine Learning Binary Failure Model Probability (\$P_{fail}\$)	Up to 35.0 Points	Linear scale: \$35.0 imes P_{fail}\$
Vibration Severity Penalty	ISO 10816-3 Industrial Mechanical Vibration Standards	Up to 25.0 Points	> 4.5 mm/s (Alert) • > 7.1 mm/s (Critical Trip)
Thermodynamic Delta (Delta-T (ΔT))	Motor temperature rise above ambient: Delta-T (ΔT) = T_motor - T_ambient	Up to 20.0 Points	> 35°C (Elevated) • > 50°C (Thermal Runaway)
Unsupervised Anomaly Penalty	Isolation Forest calibrated decision boundary deviation	Up to 10.0 Points	Score < 0.0 indicates uncatalogued operating state
Remaining Useful Life (RUL)	Operating hours left before expected component breakdown	Up to 10.0 Points	< 48 Hours: 5.0 pts • < 24 Hours: 10.0 pts

OPTIMAL CONDITION (85 - 100%) All parameters nominal. Standard scheduled shift inspections.	GOOD CONDITION (70 - 84%) Minor operational drift. Baseline logging continues.	DEGRADED WARNING (40 - 69%) Elevated vibration or temperature. P3 Work Order dispatched.	CRITICAL RISK (< 40%) Imminent catastrophic failure. P1 Emergency LOTO shutdown.
---	--	--	---

ARTIFICIAL INTELLIGENCE AGENT WORKFLOW

Evidence-Grounded RAG & Controlled ReAct Agent

Unlike generative models that can hallucinate dangerous maintenance procedures, MECMF uses a **Controlled ReAct (Reason + Act) Agent** with **Deterministic Tools** and a **Grounded Technical RAG** layer.

11-STEP CONTROLLED AGENT WORKFLOW	GROUNDING RAG EVIDENCE CORPUS
1. Entity Extraction: Parses target asset ID (e.g. M17) and query intent. 2. Asset Status: Reads machine type, location bay, and baseline limits. 3. Sensor Window: Retrieves last 15-step sliding window. 4. ML Inference: Runs failure classifier, RUL regressor, and anomaly detector. 5. Fault Diagnosis: Evaluates 5-class Gradient Boosting root cause. 6. SHAP Attribution: Computes top feature impact percentages. 7. Maintenance History: Audits past service interventions & replacements. 8. Technical Manual Search: Semantic search in OEM engineering specs. 9. Incident RCA Search: Searches historical post-mortems for matching patterns. 10. Warehouse Spares Check: Verifies inventory stock and bin locations. 11. CMMS Work Order Synthesis: Emits formal work order & action checklist.	Curated Engineering Corpus (46 Structured Passages): • Manufacturer Operating Manuals: - Electric Motors: SKF bearing clearances, ISO balance grades - Hydraulic Pumps: Plan 11 seal flushes, cavitation limits - Rotary Compressors: Thermostatic valves, minimum pressure valves - 6-Axis Robots: Cycloidal reducer backlash, harmonic drive wear • Troubleshooting Standard Operating Procedures (SOPs): - ISO 10816 Vibration severity diagnostic matrix - Thermal runaway differential (Delta-T (ΔT)) mitigation procedures - Hydraulic seal erosion & proportional valve bypass checklists • Real-World Incident Reports & Root Cause Analyses (RCAs): - INC-2023-M17: Spindle bearing race spalling from lube starvation - INC-2024-M04: Primary Viton O-ring seal rupture under surge - INC-2024-M12: Oil cooler radiator fin clogging thermal trip

BUSINESS IMPACT & CMMS INTEGRATION

Automated CMMS Work Order Dispatch & Financial ROI

When an asset enters Degraded or Critical condition, the copilot automatically synthesizes an **Enterprise Digital Work Order** conforming to **SAP PM / IBM Maximo** standards:

GENERATED WORK ORDER STRUCTURE (SAP PM READY)	FINANCIAL DOWNTIME LOSS PREVENTION ENGINE
• Work Order Header: Unique ID WO-YYYYMMDD-M17-01 • Priority & SLA: - P1 Emergency (SLA: < 2h, Immediate LOTO Shutdown) - P2 Urgent (SLA: < 24h, Proactive Intervention) - P3 Routine (SLA: < 72h, Scheduled Window) • Assigned Specialist: Matched by machine domain (e.g. Senior Millwright for CNC, Hydraulic Specialist for Pumps). • Safety LOTO Protocols: - LOTO #E-401: 400V 3-phase breaker padlock lock. - LOTO #P-204: Zero-pressure line relief before flange unseating. - PPE: Arc-flash Class 2 shield, anti-vibe mechanic gloves. • Pre-Allocated Warehouse Spares: Reserved part number (e.g., SKF-6312-C3) and warehouse bin location (Bin A-12). • Step-by-Step Procedure & Sign-Off: Inspection, replacement, alignment, and post-repair baseline verification.	Quantifiable Cost-Benefit Comparison: Scenario A: Unplanned Catastrophic Breakdown • Production Line Downtime: 14.0 Hours @ \$2,500/hr = \$35,000 • Emergency Expedited Parts & Secondary Damage: \$4,200 • Emergency Technician Overtime: \$1,200 • Total Catastrophic Loss: \$40,400 Scenario B: Proactive MECMF Intervention • Controlled Planned Window: 0.5 Hours downtime = \$1,250 • Standard Warehouse Spare Stock: \$450 • Standard Technician Shift Hours: \$300 • Total Proactive Cost: \$2,000 Net Financial Savings Prevented: \$38,400 Projected Return on Investment (ROI): > 1,900%

USER EXPERIENCE & REST SERVICES

TALOS·AI Cockpit: Total Asset & Lifetime Operational Safeguard

The user experience is delivered through an executive-grade TALOS·AI (Total Asset & Lifetime Operational Safeguard) Industrial Cockpit built on Streamlit v3.0, powered by an asynchronous FastAPI REST Backend:

NAVIGATION MODULE	CORE FEATURES & INTERACTIVE CAPABILITIES
1. Plant Executive Overview	Fleet assets overview, plant risk breakdown (Normal/Medium/High/Critical), downtime hours avoided, and cumulative plant financial savings counter.
2. Live Telemetry & Delta-T (ΔT)	High-frequency telemetry line charts with ISO 10816 vibration alarm lines (4.5 & 7.1 mm/s) and thermal delta (Delta-T (ΔT)) warnings.
3. Multi-Class Fault & RUL	Machine Health Index gauge, diagnosed physical fault mechanism with probability breakdown bars, and remaining useful life horizon.
4. SHAP Attribution & RCA	Instant visual decomposition showing exact percentage contributions of vibration, temperature, and pressure to the risk score.
5. CMMS Digital Work Orders	Rendered industrial work order document with safety LOTO checkboxes and one-click export buttons (Markdown and SAP-compliant JSON).
6. Maintenance & Spares	Historical equipment maintenance logs, past breakdown events, incident post-mortems, and warehouse spare parts stock thresholds.
7. Autonomous AI Copilot	Evidence-grounded conversational agent with 1-click prompt presets (Investigate M17, Generate Work Order, Calculate ROI) and full tool execution trace.
8. Model Benchmarks	Live display of model metadata, ROC-AUC, PR-AUC, MAE, confusion matrices, and per-class classification metrics.
9. Fault Progression Sim	Interactive fault injection simulator (Bearing Wear, Temperature Rise, Vibration Drift) streaming directly into the active database.

PRODUCTION READINESS & NEXT STEPS

System Verification, Deployment & Industrial Roadmap

AUTOMATED QUALITY ASSURANCE & VERIFICATION	DEPLOYMENT ARCHITECTURE & ROADMAP
Comprehensive Automated Test Suite: • Pytest Suite: 25 / 25 Passed (100% Green) - test_agent.py: Agent tool invocation & entity extraction - test_api.py: All 12 FastAPI REST endpoints verified - test_features.py: 60-feature temporal transform & data cleaning - test_health_and_workorder.py: MHI, ROI & CMMS work orders - test_models.py: Inference engine, RUL, and SHAP bounds - test_multiclass.py: Gradient boosting fault mechanisms Edge Case Robustness: • Defensive error handling for empty sensor history (clean 404 response). • Input DataFrame validation preventing schema mismatch. • Guardrails on RAG retrieval ensuring no hallucinated maintenance steps.	Production Containerization: • Docker Multi-Stage Build: Containerizes FastAPI backend, SQLite database, and pre-computed RAG vector index. • Edge deployable on industrial IPCs (Advantech, Siemens IPC) or cloud Kubernetes clusters. Industrial Roadmap (Phase 4): • MQTT / OPC-UA Real-Time Connector: Direct ingestion from industrial PLCs (Siemens S7, Rockwell Allen-Bradley). • Acoustic Audio Spectrum Analysis: Integration of ultrasonic acoustic microphone streams for early bearing lubrication micro-cracks. • Direct SAP PM BAPI Connector: Automated two-way work order synchronization directly into enterprise ERP databases.

Conclusion: MECMF bridges the critical gap between academic machine learning models and real-world plant floor operations. By uniting high-precision multi-class models (96.7% accuracy), explainable AI (SHAP), domain-grounded RAG, and automated CMMS dispatch, the platform transforms unplanned downtime into predictable, cost-optimized maintenance workflows.