

# Hands-on Lab: Create Tables using SQL Scripts and Load Data into Tables

Estimated time needed: 30 minutes

In this lab, you will learn how to run SQL scripts to create several tables at once, as well as how to load data into tables from .csv files.

## Software Used in this Lab

In this lab, you will use [IBM Db2 Database](#). Db2 is a Relational Database Management System (RDBMS) from IBM, designed to store, analyze and retrieve the data efficiently.

To complete this lab you will utilize a Db2 database service on IBM Cloud. If you did not already complete this lab task earlier in this module, you will not yet have access to Db2 on IBM Cloud, and you will need to follow this lab first:

- [Hands-on Lab : Sign up for IBM Cloud, Create Db2 service instance and Get started with the Db2 console](#)

## Database Used in this Lab

The database used in this lab is an internal database. You will be working on a sample HR database. This HR database schema consists of 5 tables called **EMPLOYEES**, **JOB\_HISTORY**, **JOBS**, **DEPARTMENTS** and **LOCATIONS**. Each table has a few rows of sample data. The following diagram shows the tables for the HR database:

### SAMPLE HR DATABASE TABLES

EMPLOYEES

EMP_ID	F_NAME	L_NAME	SSN	B_DATE	SEX	ADDRESS	JOB_ID	SALARY	MANAGER_ID	DEP_ID
E1001	John	Thomas	123456	1976-01-09	M	5631 Rice, OakPark,IL	100	100000	30001	2
E1002	Alice	James	123457	1972-07-31	F	980 Berry Ln, Elgin,IL	200	80000	30002	5
E1003	Steve	Wells	123458	1980-08-10	M	291 Springs, Gary,IL	300	50000	30002	5

JOB\_HISTORY

EMPL_ID	START_DATE	JOBS_ID	DEPT_ID
E1001	2000-01-30	100	2
E1002	2010-08-16	200	5
E1003	2016-08-10	300	5

JOBS

JOB_IDENT	JOB_TITLE	MIN_SALARY	MAX_SALARY
100	Sr. Architect	60000	100000
200	Sr.SoftwareDeveloper	60000	80000
300	Jr.SoftwareDeveloper	40000	60000

DEPARTMENTS

DEPT_ID_DEP	DEP_NAME	MANAGER_ID	LOC_ID
2	Architect Group	30001	L0001
5	Software Development	30002	L0002
7	Design Team	30003	L0003
5	Software	30004	L0004

LOCATIONS

LOCT_ID	DEP_ID_LOC
L0001	2
L0002	5
L0003	7

## Objectives

After completing this lab, you will be able to:

- Create tables using SQL scripts
- Load data into tables

**NOTE : Make sure that you are using the CSV file and datasets from the same instruction file.**

## Exercise 1: Create tables using SQL scripts

In this exercise, you will learn how to execute a script containing the CREATE TABLE commands for all the tables rather than create each table manually by typing the DDL commands in the SQL editor.

- Download the script file to your computer:
  - [HR Database Create Tables Script.sql](#)
- Login to IBM Cloud and go to the [Resource List](#) where you can find the Db2 service instance that you created in a previous lab under **Services** section. Click on the Db2-xx service. Next, click on **Go to UI** button.

IBM Cloud

Search resources and offerings...

Resource list /

Db2-x4

Active

Add tags

Manage

Getting started

Service credentials

Connections

Getting started

Where can I find my credentials?

Get your username and password by clicking the "Service Credentials" link the left and selecting "New Credentials".

Go to UI

Getting started docs

3. Click on **SQL** on the left corner and click the +icon

Data objects

Saved objects

SQL

C3D26760

\*Untitled - 1

+

1

Select the **From File** option.

Add new script

Choose script source

Open a script to edit

From file

Create new

Templates

Choose a template to start your SQL editor.

Template - Delete Statement

Template - Insert Statement

Template - Select Statement

Template - SQL Stored Procedure

Template - Update Statement

Template - User Defined Function

4. Locate the file **HR\_Database\_Create\_Tables\_Script.sql** that you downloaded to your computer earlier and open it.
5. Once the statements are in the SQL Editor tool , you can run the queries against the database by selecting the **Run All** button.

## Run SQL

\* HR\_Databa... x



☒ Syntax assistant



### Result - F

```

37
38 CREATE TABLE JOBS (
39     JOB_ID     CHAR(9) NOT NULL,
40     JOB_TITLE  VARCHAR(30) ,
41     MIN_SALARY DECIMAL(10,2),
42     MAX_SALARY DECIMAL(10,2),
43     PRIMARY KEY (JOB_ID)
44 );
45
46 CREATE TABLE DEPARTMENTS (
47     DEPT_ID_DEP CHAR(9) NOT NULL,
48     DEP_NAME    VARCHAR(15) ,
49     MANAGER_ID  CHAR(9),
50     LOC_ID      CHAR(9),
51     PRIMARY KEY (DEPT_ID_DEP)
52 );
53
54 CREATE TABLE LOCATIONS (
55     LOCT_ID CHAR(9) NOT NULL,
56     DEP_ID_LOC CHAR(9) NOT NULL,
57     PRIMARY KEY (LOCT_ID,DEP_ID_LOC)
58 );
59

```

Run all

☒ Remember my selection

6. On the right side of the SQL editor window you will see a Result section. Clicking on a query in the Result section will show the execution details of the job like whether it ran successfully, or had any errors or warnings. Ensure your queries ran successfully and created all the tables.
- **Note:** You may see several errors before the successful creation of the tables. These errors relate to the dropping (removal) of any pre-existing version of these tables. You can ignore these errors.

**Run SQL**

\* HR\_Databa... X

SQL

1  
2 --DDL statement for table 'HR' database--  
3  
4  
5 -- Drop the tables in case they exist  
6  
7 DROP TABLE EMPLOYEES;  
8 DROP TABLE JOB\_HISTORY;  
9 DROP TABLE JOBS;  
10 DROP TABLE DEPARTMENTS;  
11 DROP TABLE LOCATIONS;  
12  
13 -- Create the tables  
14  
15 CREATE TABLE EMPLOYEES (  
16 EMP\_ID CHAR(9) NOT NULL,  
17 F\_NAME VARCHAR(15) NOT NULL,  
18 L\_NAME VARCHAR(15) NOT NULL,  
19 SSN CHAR(9),  
20 B\_DATE DATE,  
21 SEX CHAR,  
22 ADDRESS VARCHAR(30),  
23 JOB\_ID CHAR(9),  
24 SALARY DECIMAL(10,2),  
25 MANAGER\_ID CHAR(9),  
26 DEP\_ID CHAR(9) NOT NULL,  
27 PRIMARY KEY (EMP\_ID)  
28 );  
29  
30 CREATE TABLE JOB\_HISTORY (  
31 EMPL\_ID CHAR(9) NOT NULL,  
32 START\_DATE DATE,

Run all ☒ Remember my selection

7. Now you can look at the tables you created. Click on the data icon and then click on Tables tab

**Navigation Pane:**

- Dashboard
- SQL Run SQL
- Data**
- Administration

**Top Navigation Bar:**

- Load Data
- Load History
- Tables**
- Views
- Indexes
- Aliases
- MQTs
- Sequences
- Application objec

**Search Bar:** Find schemas or tables

**Schemas Table:**

Name	Type
MYG36304	User

8. Select the Schema corresponding to your Db2 userid. It typically starts with 3 letters (not SQL) followed by 5 numbers (but will be different from the **MYG36304** example below). Then on the right side of the screen you should see the 5 newly created tables listed – DEPARTMENTS, EMPLOYEES, JOBS, JOB\_HISTORY and LOCATIONS (plus any other tables you may have created in previous labs e.g. PETSALe, PETRESCUE, etc.).

Find schemas or tables

Schemas

<input checked="" type="checkbox"/> Name	Type	Tables ▲
<input checked="" type="checkbox"/> MYG36304	User	5

Tables

☐ Name

☐ DEPART

☐ EMP

☐ JOBS

☐ JOBSH

☐ LOCAT

9. Click on any of the tables and you will see its Table Definition (that is, its list of columns, data types, etc).

Find schemas or tables

Schemas

Tables

New table +

☐ Name ▼

Schema

Properties

☐ DEPARTMENTS

MYG36304

...

☐ EMPLOYEES

MYG36304

...

☐ INSTRUCTOR

MYG36304

...

☐ JOBS

MYG36304

...

☐ JOBSHISTORY

MYG36304

...

☐ LOCATIONS

MYG36304

...

Total: 6, selected: 0

Table definition

EMPLOYEES

Name

EMP\_ID

F\_NAME

L\_NAME

SSN

B\_DATE

SEX

ADDRESS

View data

Exercise 2: Load data into tables

In this exercise, you will learn how data can be loaded into Db2. You could manually insert each row into the table one by one, but that would take a long time. Instead, Db2 (and almost every other database) allows you to load data from .CSV files.

The steps below explain the process of loading data into the tables you created earlier in exercise 1.

1. Download the 5 .csv files below to your local computer:
- [Departments.csv](#)


[Employees.csv](#)

- [Jobs.csv](#)
- [Locations.csv](#)
- [JobsHistory.csv](#)


**Note:** For learners who are encountering issues with loading from .csv in Db2 using Firefox, they can download the .txt files and try with those:

- [Departments.txt](#)
- [Employees.txt](#)
- [Jobs.txt](#)
- [Locations.txt](#)
- [JobsHistory.txt](#)


2. In the Db2 Console, from the 3-bar menu icon in the top left corner, click **Load**, and then select **Load Data**.



3. On the **Load Data** page that opens, ensure **My Computer** is selected as the source. Click on the **browse files** link.



4. Choose the file **Employees.csv** that you downloaded to your computer and click **Open**.



5. Once the File is selected, click **Next** in the bottom right corner.

Load Data

Load History

Tables

Views

Indexes

Aliases

MQTs

Sequences

Application objects

Source

You are loading the file **Employees.csv**

Target

Define


My Computer

A single delimited text file (CSV) without header row.

Amazon S3

Cloud Object Storage

File selection



Drag a file here or [browse files](#)

6. 1. 1  
1. Select the schema for your Db2 Userid (the one where you created the tables earlier). It will show all the tables that have been created in
- Copied!



6/22/23, 9:56 AM

about:blank

Load Data

Load History

Tables

Views

Indexes

Aliases

MQTs

Sequences

Application objects

Source

Target

Define

You are loading the file **Employees.csv** into **HYL83142.EMPLOYEES**

Select a load target

Schema

Find schemas

HYL83142

Table

Find tables in HYL83142

DEPARTMENTS

EMPLOYEES

JOBS

JOB\_HISTORY

LOCATIONS

7. Since the source data files do not contain any rows with column labels, **turn off** the setting for **Header in first row**. Also, click on the down arrow next to **Date format** and choose **MM/DD/YYYY** since that is how the date is formatted in the source file.

about:blank

9/14

**Load Data**   Load History   Tables   Views   Indexes   Aliases   MQTs   Sequences   Application objects

---

Source Target Delimited

You are loading the file **Employees.csv** into **HYL83142.EMPLOYEES**

Code page (character encoding): 1208 (UTF-8) Separator: , Header in first row: ☒

Date format: YYYY-MM-DD Time format: HH:MM:SS Timestamp format: YYYY

	EMP_ID CHARACTER	F_NAME VARCHAR	L_NAME VARCHAR	SSN CHARACTER	B_DATE DATE
1	E1001	John	Thomas	123456	01/09/1976
2	E1002	Alice	James	123457	07/31/1972
3	E1003	Steve	Wells	123458	08/10/1980
4	E1004	Santosh	Kumar	123459	07/20/1985
5	E1005	Ahmed	Hussain	123410	01/04/1981
6	E1006	Nancy	Allen	123411	02/06/1978
7	E1007	Mary	Thomas	123412	05/05/1975
8	E1008	Bharath	Gupta	123413	05/06/1985
9	E1009	Andrea	Jones	123414	07/09/1990
10	E1010	Ann	Jacob	123415	03/30/1982

8. Click **Next**. Review the load settings and click **Begin Load** in the bottom right corner.

6/22/23, 9:56 AM

about:blank

Load Data

Load History

Tables

Views

Indexes

Aliases

MQTs

Sequences

Application objects

Source

Target

Define

You are loading the file **Employees.csv** into **HYL83142.EMPLOYEES**

Review settings

Summary

Code page:

1208 (Default)

Separator:

, (Default)

Time format:

HH:MM:SS (Default)

Date format:

YYYY-MM-DD (Default)

Timestamp format:

YYYY-MM-DD HH:MM:SS (Default)

String delimiter:

(Default)

Option

Maximum numb

1000

9. After loading has completed, you will notice that you were successful in loading all 10 rows of the Employees table. If there are any **Errors** or **Warnings**, you can see them on this screen.

about:blank

11/14

Load details



My computer	Target
Employees.csv	HYL83142.EMPLOYEES

Status

Settings



<b>10</b>	<b>10</b>	<b>0</b>
Rows read	Rows loaded	Rows rejected

Start time  
07/30/2021 3:51:29 PM  
End time  
07/30/2021 3:51:34 PM

The data load job succeeded  
You can now work with your data.

10. 1. 1
1. Click on the **Tables** tab and then select the **EMPLOYEES** table and then click on **View data**.
- Copied!

Load Data

Load History

**Tables**

Views

Indexes

Aliases

MQTs

Sequences

Application objects

Find schemas or tables

Schemas

Tables

New table +

Name ▾

Schema

Properties

☐

DEPARTMENTS

HYL83142

...

☒

EMPLOYEES

HYL83142

...

☐

JOBS

HYL83142

...

☐

JOB\_HISTORY

HYL83142

...

☐

LOCATIONS

HYL83142

...

Total: 5, selected: 1

11. Now you can view the table data.

SQL

Load Data

Load History

Tables

Views

Indexes

Aliases

MQTs

Sequences

Application objects

HYL83142.EMPLOYEES

EMP_ID	F_NAME	L_NAME	SSN	B_DATE	SEX	ADDRESS
E1001	John	Thomas	123456	1976-01-09	M	5631 Rice, Oa
E1002	Alice	James	123457	1972-07-31	F	980 Berry Ln, I
E1003	Steve	Wells	123458	1980-08-10	M	291 Springs, C
E1004	Santosh	Kumar	123459	1985-07-20	M	511 Aurora Av
E1005	Ahmed	Hussain	123410	1981-01-04	M	216 Oak Tree,
E1006	Nancy	Allen	123411	1978-02-06	F	111 Green Pl,
E1007	Mary	Thomas	123412	1975-05-05	F	100 Rose Pl, C
E1008	Bharath	Gupta	123413	1985-05-06	M	145 Berry Ln,
E1009	Andrea	Jones	123414	1990-07-09	F	120 Fall Creek
E1010	Ann	Jacob	123415	1982-03-30	F	111 Britany S

12. Now it's your turn to load data to the remaining 4 tables of the HR database – **LOCATIONS**, **JOB\_HISTORY**, **JOBS**, and **DEPARTMENTS** from the remaining source files.
13. Click **Load More Data** and then follow the steps from **Step 3** above again to load the remaining 4 tables.  
**IMPORTANT** Make sure you perform the steps in **Step 7** for each of the 4 remaining file loads.

**Congratulations! You have completed this lab, and you are ready for the next topic.**

Author(s)

- [Rav Ahuja](#)
- [Sandip Saha Joy](#)

Changelog

Date	Version	Changed by	Change Description
2022-08-19	2.4	D.M.Naidu	Upload .txt files
2021-07-30	2.3	Lakshmi Holla	Updated screenshot of DB2
2021-07-08	2.2	Malika	Updated screenshot
2020-12-23	2.1	Steve Ryan	ID Review
2020-12-08	2.0	Sandip Saha Joy	Created revised version from DB0201EN
2020	1.0	Rav Ahuja	Created initial version

© IBM Corporation 2020. All rights reserved.