

1. strlen()

Purpose: Returns the length of a string.

Example:

```
echo strlen("Hello"); // 5
```

2. str_word_count()

Purpose: Counts the number of words in a string.

Example:

```
echo str_word_count("PHP is easy"); // 3
```

3. str_contains()

Purpose: Checks whether a string contains another string.

Example:

```
echo str_contains("I love PHP", "PHP"); // 1 (true)
```

4. strpos()

Purpose: Returns the position of the first occurrence of a substring.

Example:

```
echo strpos("Hello World", "World"); // 6
```

5. strtoupper()

Purpose: Converts a string to uppercase.

Example:

```
echo strtoupper("hello"); // HELLO
```

6. strtolower()

Purpose: Converts a string to lowercase.

Example:

```
echo strtolower("HELLO"); // hello
```

7. str_replace()

Purpose: Replaces text inside a string.

Example:

```
echo str_replace("World", "PHP", "Hello World");
```

```
// Hello PHP
```

8. strrev()

Purpose: Reverses a string.

Example:

```
echo strrev("abc"); // cba
```

9. trim()

Purpose: Removes whitespace from the beginning and end of a string.

Example:

```
echo trim(" hello "); // hello
```

10. explode()

Purpose: Converts a string into an array.

Example:

```
$arr = explode(",", "apple,mango,banana");  
print_r($arr);
```

11. implode()

Purpose: Converts an array into a string.

Example:

```
$arr = ["apple", "mango", "banana"];  
echo implode(" - ", $arr);  
  
// apple - mango - banana
```

12. substr()

Purpose: Returns part of a string.

Example:

```
echo substr("Hello World", 0, 5); // Hello
```

13. is_int()

Purpose: Checks whether a value is an integer.

Example:

```
var_dump(is_int(10)); // true
```

14. is_float()

Purpose: Checks whether a value is a floating-point number.

Example:

```
var_dump(is_float(10.5)); // true
```

15. is_nan()

Purpose: Checks whether a value is NaN (Not a Number).

Example:

```
var_dump(is_nan(acos(2))); // true
```

16. is_numeric()

Purpose: Checks whether a value is numeric.

Example:

```
var_dump(is_numeric("123")); // true
```

17. round()

Purpose: Rounds a number.

Example:

```
echo round(3.75); // 4
```

18. define()

Purpose: Creates a constant.

Example:

```
define("SITE", "My Website");  
  
echo SITE;
```

19. date()

Purpose: Formats a date or time.

Example:

```
echo date("Y-m-d");
```

20. strtotime()

Purpose: Converts a date string into a timestamp.

Example:

```
echo strtotime("2026-08-15");
```

21. time()

Purpose: Returns the current Unix timestamp.

Example:

```
echo time();
```

22. date_default_timezone_set()

Purpose: Sets the default timezone.

Example:

```
date_default_timezone_set("Asia/Dhaka");
```

23. date_default_timezone_get()

Purpose: Gets the current default timezone.

Example:

```
echo date_default_timezone_get();
```

24. include

Purpose: Includes another PHP file. A warning is shown if the file is missing.

Example:

```
include "header.php";
```

25. require

Purpose: Includes another PHP file. A fatal error occurs if the file is missing.

Example:

```
require "config.php";
```

26. json_encode()

Purpose: Converts a PHP array or object to JSON.

Example:

```
$arr = ["name" => "Asif", "age" => 22];
```

```
echo json_encode($arr);
```

27. json_decode()

Purpose: Converts JSON into a PHP array or object.

Example:

```
$json = '{"name": "Asif"}';  
  
$data = json_decode($json, true);  
  
echo $data["name"];
```

28. array()

Purpose: Creates an array.

Example:

```
$colors = array("red", "green", "blue");
```

29. array_keys()

Purpose: Returns all keys of an array.

Example:

```
$arr = ["a" => 10, "b" => 20];  
  
print_r(array_keys($arr));
```

30. array_merge()

Purpose: Merges two or more arrays.

Example:

```
$a = [1, 2];  
  
$b = [3, 4];  
  
print_r(array_merge($a, $b));
```

31. array_push()

Purpose: Adds elements to the end of an array.

Example:

```
$arr = [1, 2];  
  
array_push($arr, 3);
```

32. array_reverse()

Purpose: Reverses an array.

Example:

```
print_r(array_reverse([1, 2, 3]));
```

33. sizeof()

Purpose: Returns the number of elements in an array.

Example:

```
echo sizeof([1, 2, 3]); // 3
```

34. count()

Purpose: Counts array elements.

Example:

```
echo count(["a", "b", "c"]); // 3
```

35. sort()

Purpose: Sorts an array in ascending order.

Example:

```
$arr = [4, 2, 1, 3];
```

```
sort($arr);
```

```
print_r($arr);
```