

Cisco Packet Tracer Activity: VLSM and DHCP Configuration with Routing set - 1

Objective

Design a multi-department network using VLSM and DHCP based on the provided topology.

Do not click on Cluster0.

Given Information

- Base Network Address: 192.168.20.15/24
 - CSE: 120 hosts
 - ECE: 60 hosts
 - BME: 30 hosts
 - net 4: 2 hosts (gig0/0 1st ip)
 - net 5: 2 hosts (router1 - gig0/1 2nd ip)
 - CSE and ECE obtain IP addresses from the dedicated DHCP Server.
 - Use the first usable IP address of each subnet as the default gateway.
 - Exclude the first 10 addresses from DHCP allocation.
 - Give 2nd ip to PC6 of that network.
 - Give IP to other pcs using DHCP.
 - Apply OSPF routing
 - process id 10
 - area 1
- Base Network Address: 192.168.30.0/24
 - ME: 120 hosts
 - ESE: 60 hosts
 - IPE: 30 hosts
 - net 4: 2 hosts (gig0/1 1st ip)
 - net 5: 2 hosts (router4 - gig0/1 2nd ip)
 - ME and ESE obtain IP addresses from the Router0..
 - Use the first usable IP address of each subnet as the default gateway.
 - Exclude the first 10 addresses from DHCP allocation.
 - Give 2nd ip to DHCP server of that network.
 - Give IP to other pcs using DHCP.
 - Apply RIPv2 routing.