PRODUCTION ENGINEERING

Stopping Duplicate Charges at High Scale

How high-throughput payment rails prevent double-settlement and ledger leakage when upstream switches fail mid-flight.

Ariya Sarrafzadeh
linkedin.com/in/ariya-sarrafzadeh

SWIPE →

FAILURE STATE

Network drops are inevitable. Double charges are not.

When a core banking switch drops an ISO 8583 acknowledgement or an SMS OTP times out, naive payment systems write double balances or trigger aggressive mobile client retries.

```
// The Failure State:
1. Client sends checkout request.
2. Banking switch approves hold.
3. Webhook drops due to 504 Gateway Timeout.
4. Client retries → Balance debited twice.
```

Ariya Sarrafzadeh
Technical Product Owner & Solutions Architect

LOCKING ARCHITECTURE

Distributed Idempotency Locks

Every checkout request must carry a unique client UUID, locked at the ingress gateway using Redis SETNX before reaching internal services.

```
key = "idemp:" + request.uuid
acquired = redis.set(key, "LOCKED", nx=True, ex=30)
if not acquired:
  return HTTP 409 Conflict ("In-Flight Transaction")
```

Ariya Sarrafzadeh
Technical Product Owner & Solutions Architect

SWIPE →

TIMEOUT HANDLING

Asynchronous State Fallbacks

Never let mobile clients hang waiting on third-party banking switches. If an upstream host takes over 3,500ms, cut the connection and queue automated resolution.

```
// Fast-Fail Invariant:
- Threshold: 3,500ms max switch wait.
- Action: Return pending status to app.
- Background: Queue automated inquiry query.
- Outcome: Zero blocked user threads.
```

Ariya Sarrafzadeh
Technical Product Owner & Solutions Architect

DYNAMIC ROUTING

Automated Circuit Breakers

When an upstream acquirer error rate exceeds 2% over a 60-second sliding window, dynamically divert traffic to backup rails in under 200ms.

```
if acquirer.error_rate_60s() > 0.02:
  circuit.trip(acquirer_id)
  traffic.reroute(backup_psp_switch)
  telemetry.alert("PSP Switch Diverted")
```

Ariya Sarrafzadeh
Technical Product Owner & Solutions Architect

SWIPE →

LEDGER INTEGRITY

Real-Time 3D State Locks

Kill midnight batch comparisons. Match the banking switch state, internal wallet balance, and settlement clearing queue simultaneously on every transaction.

```
Dimension 1: Acquirer Switch Auth State
Dimension 2: Internal Double-Entry Ledger
Dimension 3: Settlement Queue Clearing File
Result: 100% discrepancy resolution in real time.
```

Ariya Sarrafzadeh
Technical Product Owner & Solutions Architect

TAKEAWAY BLUEPRINT

The High-Scale Ingress Stack

- ✓ **Idempotency UUIDs:** Block duplicate app retries via Redis locks.
- ✓ **3.5s Hard Cap:** Asynchronously decouple third-party latency.
- ✓ **Ingress Circuit Breakers:** Auto-divert traffic when errors hit 2%.
- ✓ **3D Ledger Matching:** Stop relying on 24-hour midnight batch runs.
- ✓ **Grok Deep-Log Tracing:** Spot settlement gaps in under 3 minutes.

Ariya Sarrafzadeh
Technical Product Owner & Solutions Architect

LET'S CONNECT

Scaling high-throughput payment rails or ledger architecture?

Building zero-defect transaction systems across 45M+ accounts. Open to senior technical product leadership mandates in Dubai and remote.

Ariya Sarrafzadeh
Email: ariasg2002@gmail.com
LinkedIn: linkedin.com/in/ariya-sarrafzadeh