


```
#-----
# Copyright (c) Bentley Systems, Incorporated. All rights reserved.
# See COPYRIGHT.md in the repository root for full copyright notice
#-----
from .openStaadHelper import *
from comtypes import automation
from comtypes import client
from comtypes import CoInitialize
import comtypes.client as cc
```

```
class OSDesign:
    CoInitialize()
```

[\[docs\]](#)

```
def __init__(self, staadObj):
    self._staad = staadObj
    self._design = self._staad.Design

    self._functions= [
        "CreateDesignBrief",
        "AssignDesignParameter",
        "AssignDesignCommand",
        "AssignDesignGroup",
        "GetDesignBriefCode"
    ]

    for function_name in self._functions:
        self._design._FlagAsMethod(function_name)
```

[\[docs\]](#)

```
## Design FUNCTIONS
```

```
def CreateDesignBrief(self, design_code: int):
    """
    Create a new design brief with the specified design code.

    Parameters
    -----
    design_code : int
        Design code index.

    Returns
    -----
    int
        Reference ID of the created design brief.

    Example
    -----
    >>> from openstaadpy import os_analytical
    >>> staad_obj = os_analytical.connect()
```

[\[docs\]](#)

```

>>> ref_id = staad_obj.Design.CreateDesignBrief(1001)
"""
return self._design.CreateDesignBrief(design_code)

```

[\[docs\]](#)

```

def AssignDesignParameter(self, design_ref_id: int, design_param: str, design_value: str)
"""
    Assign design parameters to a specified design brief.

    Parameters
    -----
    design_ref_id : int
        Design brief reference ID.
    design_param : str
        Name of the design parameter.
    design_param_value : str
        Value for the design parameter.
    member_ids : list of int or int
        List of member numbers.

    Returns
    -----
    int
        0 if successful, -1 otherwise.

    Examples
    -----
    >>> from openstaadpy import os_analytical
    >>> staad_obj = os_analytical.connect()
    >>> ref_id = staad_obj.Design.CreateDesignBrief(1001)
    >>> result = staad_obj.Design.AssignDesignParameter(ref_id, "BEAM", "1")
    """
    if isinstance(member_ids, int):
        member_ids = [member_ids]
    safe_members = make_safe_array_long_input(member_ids)
    members_variant = make_variant_vt_ref(safe_members, automation.VT_ARRAY)
    return self._design.AssignDesignParameter(design_ref_id, design_param, design_value)

```

[\[docs\]](#)

```

def AssignDesignCommand(self, design_ref_id: int, design_command_name: str, design_command_value: str)
"""
    Assign a design command to specified members in a design brief.

    Parameters
    -----
    design_ref_id : int
        Design brief reference ID.
    design_command_name : str
        Name of the design command.
    design_command_value : str

```

Value for the design command.
 member_ids : list of int
 List of member numbers.

Returns

int

0 if successful, -1 otherwise.

Examples

```
>>> from openstaadpy import os_analytical
>>> staad_obj = os_analytical.connect()
>>> ref_id = staad_obj.Design.CreateDesignBrief(1001)
>>> result = staad_obj.Design.AssignDesignCommand(ref_id, "CHECK CODE",
"""
if isinstance(member_ids, int):
    member_ids = [member_ids]
safe_members = make_safe_array_long_input(member_ids)
members_variant = make_variant_vt_ref(safe_members, automation.VT_ARRAY
return self._design.AssignDesignCommand(design_ref_id, design_command_na
```

[\[docs\]](#)

```
def AssignDesignGroup(self, design_ref_id: int, design_group_name: str, des:
"""
```

Assign physical members to a design group using a design command.

Parameters

design_ref_id : int
 Design brief reference ID.
 design_group_name : str
 Name of the design group.
 design_group_value : str
 Value for the design group.
 same_as_member : int
 Reference member for the group.
 member_ids : list of int
 List of member numbers.

Returns

int

0 if successful, -1 otherwise.

Examples

```
>>> from openstaadpy import os_analytical
>>> staad_obj = os_analytical.connect()
>>> ref_id = staad_obj.Design.CreateDesignBrief(1001)
>>> result = staad_obj.Design.AssignDesignGroup(ref_id, "scSteelGroup",
"""
if isinstance(member_ids, int):
```

```

        member_ids = [member_ids]
    safe_members = make_safe_array_long_input(member_ids)
    members_variant = make_variant_vt_ref(safe_members, automation.VT_ARRAY)
    return self._design.AssignDesignGroup(design_ref_id, design_group_name,

```

[\[docs\]](#)

```

def GetDesignBriefCode(self, design_ref_id: int):
    """
    Get the design code for a specified design brief.

    Parameters
    -----
    design_ref_id : int
        Design brief reference ID.

    Returns
    -----
    int
        Design code.

    Examples
    -----
    >>> from openstaadpy import os_analytical
    >>> staad_obj = os_analytical.connect()
    >>> ref_id = staad_obj.Design.CreateDesignBrief(1001)
    >>> result = staad_obj.Design.GetDesignBriefCode(ref_id)
    """
    return self._design.GetDesignBriefCode(design_ref_id)

```

[\[docs\]](#)

```

def GetMemberDesignParameters(self, design_ref_id: int, member_no: int):
    """
    Get the design parameters for a specified member in a design brief.

    Parameters
    -----
    design_ref_id : int
        Design brief reference ID.
    member_no : int
        Member number.

    Returns
    -----
    dict
        Dictionary containing:

        status : int
            Return code from COM (0 success, -1 failure or other).
        count : int | None
            Number of parameters available for the member (from COM object's

```

```

_raw : COM object
    Original COM object (StaadPro.MembSteelDgnParams).
parameters : dict[str, list]
    Mapping of parameter name -> [value, unit, description, default]
    unavailable it is set to None. Parameter names are returned exact

```

Examples

```

-----
>>> from openstaadpy import os_analytical
>>> staad_obj = os_analytical.connect()
>>> brief_id = 1
>>> params = staad_obj.Design.GetMemberDesignParameters(brief_id, 1)
"""

design_params = cc.CreateObject("StaadPro.MembSteelDgnParams")
status = self._design.GetMemberDesignParameters(design_ref_id, member_no)

# Attempt to read count (number of parameters for the member)
try:
    count = getattr(design_params, "Count")
except Exception:
    count = None

def _get_attr(name):
    try:
        return getattr(design_params, name)
    except Exception:
        return None

# Raw COM attributes (may be SAFEARRAY, sequence, or callable indexer)
raw_names = _get_attr("Name")
raw_values = _get_attr("Value")
raw_units = _get_attr("Unit")
raw_descriptions = _get_attr("Description")
raw_defaults = _get_attr("Default")

def _materialize(obj):
    """Turn a COM collection or callable indexer into a Python list."""
    if obj is None:
        return []
    # Avoid splitting a single string into characters
    if isinstance(obj, str):
        return [obj]
    # Already a list/tuple
    if isinstance(obj, (list, tuple)):
        return list(obj)
    # Callable indexer pattern (obj(i)) if count known
    if callable(obj) and count is not None:
        result = []
        for i in range(int(count)):
            try:
                result.append(obj(i))
            except Exception:
                result.append(None)
        return result
    # Generic sequence protocol
    if hasattr(obj, "__len__") and hasattr(obj, "__getitem__"):

```

```
try:
    return [obj[i] for i in range(len(obj))]
except Exception:
    return []
# Fallback: wrap scalar
return [obj]

names_list = _materialize(raw_names)
values_list = _materialize(raw_values)
units_list = _materialize(raw_units)
descriptions_list = _materialize(raw_descriptions)
defaults_list = _materialize(raw_defaults)

parameters = {}
for i, nm in enumerate(names_list):
    if nm is None:
        continue
    if isinstance(nm, str) and nm.strip() == "":
        continue
    parameters[str(nm)] = [
        values_list[i] if i < len(values_list) else None,
        units_list[i] if i < len(units_list) else None,
        descriptions_list[i] if i < len(descriptions_list) else None,
        defaults_list[i] if i < len(defaults_list) else None,
    ]

return {
    "status": status,
    "count": count,
    "_raw": design_params,
    "parameters": parameters,
}
```