

# Tables

## Functions

|                 |   |
|-----------------|---|
| afx_msg VARIANT | <b>OSTableUI::CreateReport</b> (const VARIANT FAR &szReportTitle)<br>Creates a report with the specified title.   |
| afx_msg void    | <b>OSTableUI::SaveReport</b> (const VARIANT FAR &ReportNo)<br>Saves the specified report along with all its tables.   |
| afx_msg void    | <b>OSTableUI::SaveReportAll</b> ()<br>Saves all the reports created.  |
| afx_msg VARIANT | <b>OSTableUI::GetReportCount</b> ()<br>Returns the number of reports created.   |
| afx_msg VARIANT | <b>OSTableUI::AddTable</b> (const VARIANT FAR &ToReportNo, const VARIANT FAR &szTableName, const VARIANT FAR &RowNos, const VARIANT FAR &ColNos)<br>Add or create a report data table and returns the table no for a specified table. |
| afx_msg void    | <b>OSTableUI::RenameTable</b> (const VARIANT FAR &ReportNo, const VARIANT FAR &TableNo, const VARIANT FAR &szTableName)<br>Rename an existing report table.   |
| afx_msg void    | <b>OSTableUI::DeleteReport</b> (const VARIANT FAR &FromReportNo)<br>Delete an existing report.  |
| afx_msg void    | <b>OSTableUI::DeleteTable</b> (const VARIANT FAR &FromReportNo, const VARIANT FAR &TableNo)<br>Delete an existing table from report data.   |
| afx_msg void    | <b>OSTableUI::ResizeTable</b> (const VARIANT FAR &ReportNo, const VARIANT FAR &TableNo, const VARIANT FAR &RowNos, const VARIANT FAR &ColNos)<br>Resize existing table by increasing numbers of rows and columns from report data.    |
| afx_msg void    | <b>OSTableUI::SaveTable</b> (const VARIANT FAR &ReportNo, const VARIANT FAR &TableNo)<br>Save a report table.   |
| afx_msg VARIANT | <b>OSTableUI::GetTableCount</b> (const VARIANT FAR &OfReportNo)<br>Get table count in a specified report..  |
| afx_msg void    | <b>OSTableUI::GetCellValue</b> (const VARIANT FAR &ReportNo, const VARIANT FAR &TableNo, const VARIANT FAR &IRow, const VARIANT FAR &ICol, VARIANT FAR &varValueStr)<br>Get cell values for a specified table.                        |
| afx_msg void    | <b>OSTableUI::SetCellValue</b> (const VARIANT FAR &ReportNo, const VARIANT FAR &TableNo, const VARIANT FAR &IRow, const VARIANT FAR &ICol, const VARIANT FAR &varValue)<br>Set cell values for a specified table.                     |
| afx_msg void    | <b>OSTableUI::SetColumnHeader</b> (const VARIANT FAR &ReportNo, const VARIANT FAR &TableNo, const VARIANT FAR &ICol, const VARIANT FAR &varHeader)  |

Sets column header for a specified table.

afx\_msg void **OSTableUI::SetColumnUnitString** (const VARIANT FAR &ReportNo, const VARIANT FAR &TableNo, const VARIANT FAR &ICol, const VARIANT FAR &varUnitString)

Sets unit for the specific column of a specified table.

afx\_msg void **OSTableUI::SetRowHeader** (const VARIANT FAR &ReportNo, const VARIANT FAR &TableNo, const VARIANT FAR &IRow, const VARIANT FAR &varHeader)

Sets row header for the specific row of a specified table.

afx\_msg void **OSTableUI::SetCellTextColor** (const VARIANT FAR &ReportNo, const VARIANT FAR &TableNo, const VARIANT FAR &IRow, const VARIANT FAR &ICol, const VARIANT FAR &IRedValue, const VARIANT FAR &IGreenValue, const VARIANT FAR &IBlueValue)

Sets the color of the text to be displayed in a particular cell. By default, the color is always set to black.

afx\_msg void **OSTableUI::SetCellTextBold** (const VARIANT FAR &ReportNo, const VARIANT FAR &TableNo, const VARIANT FAR &IRow, const VARIANT FAR &ICol)

Sets the text in a given row and column to bold.

afx\_msg void **OSTableUI::SetCellTextItalic** (const VARIANT FAR &ReportNo, const VARIANT FAR &TableNo, const VARIANT FAR &IRow, const VARIANT FAR &ICol)

Italicizes the text in a given row and column.

afx\_msg void **OSTableUI::SetCellTextUnderline** (const VARIANT FAR &ReportNo, const VARIANT FAR &TableNo, const VARIANT FAR &IRow, const VARIANT FAR &ICol)

Underlines the text in a given row and column.

afx\_msg void **OSTableUI::SetCellTextHorzAlignment** (const VARIANT FAR &ReportNo, const VARIANT FAR &TableNo, const VARIANT FAR &IRow, const VARIANT FAR &ICol, const VARIANT FAR &IAlign)

Sets the text in a particular row and column to a specified horizontal alignment. By default, all the text is right justified.

afx\_msg void **OSTableUI::SetCellTextVertAlignment** (const VARIANT FAR &ReportNo, const VARIANT FAR &TableNo, const VARIANT FAR &IRow, const VARIANT FAR &ICol, const VARIANT FAR &IAlign)

Sets the text in a particular row and column to a specified vertical alignment. By default, all the text is top justified.

afx\_msg void **OSTableUI::SetCellTextSize** (const VARIANT FAR &ReportNo, const VARIANT FAR &TableNo, const VARIANT FAR &IRow, const VARIANT FAR &ICol, const VARIANT FAR &dSize)

Sets the text in a particular row and column to a certain font size. The font sizes are equivalent to the ones used in Microsoft Word.

afx\_msg void **OSTableUI::SetCellTextSizeAll** (const VARIANT FAR &ReportNo, const VARIANT FAR &TableNo, const VARIANT FAR &dSize)

Sets the text in the entire table to FontSize. The font sizes are equivalent to the ones used in

## Detailed Description

---

These functions are related to setting Report Tables.

## Function Documentation

---

◆ AddTable()

```
VARIANT OSTableUI::AddTable ( const VARIANT FAR & ToReportNo,
                              const VARIANT FAR & szTableName,
                              const VARIANT FAR & RowNos,
                              const VARIANT FAR & ColNos )
```

private

Add or create a report data table and returns the table no for a specified table.

### Parameters

- [in] **ToReportNo** Report number(Type: int), It can be obtained by calling **OSTableUI::CreateReport**.
- [in] **szTableName** Report Table Name(Type: String).
- [in] **RowNos** row count of the specified table(Type: long).
- [in] **ColNos** column count of the specified table(Type: long).

### Return values

- 0** Create table error.
- Other** Table number.

### C++ Syntax

```
// Create a report "Table1" of #10 rows and #5 columns.
VARIANT TableNo = OSTableUI::AddTable(1, "Table1", 10, 5);
```

### VBA Syntax

```
Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject(, "StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
        MsgBox "Bad"
        Set objOpenStaad = Nothing
        Exit Sub
    End If
    Dim reportnameStr As String
    reportnameStr = "testreport"
    Dim nReportNum As Long
    nReportNum = objOpenStaad.Table.CreateReport(reportnameStr)
    Dim nTableNum As Long
    Dim tablenameStr As String
    tablenameStr = "testtable"
    nTableNum = objOpenStaad.Table.AddTable(nReportNum, tablenameStr, 2, 2)
End Sub
```

CreateReport()

Loading [MathJax]/extensions/MathZoom.js

## VARIANT OSTableUI::CreateReport ( const VARIANT FAR & szReportTitle )

private

Creates a report with the specified title.

### Parameters

[in] **szReportTitle** A null terminated string containing the title of the report.

### Return values

**0** Create Report error.

**Other** Report number.

### C++ Syntax

```
// Return value containing the reference number for the report created to be used to
// access the report.
VARIANT RetVal = OSTableUI::CreateReport("My Report");
```

### VBA Syntax

```
Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject(,"StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
        MsgBox "Bad"
        Set objOpenStaad = Nothing
        Exit Sub
    End If
    Dim reportnameStr As String
    reportnameStr = "testreport"
    Dim nReportNum As Long
    nReportNum = objOpenStaad.Table.CreateReport(reportnameStr)
End Sub
```

## ◆ DeleteReport()

void OSTableUI::DeleteReport ( const VARIANT FAR & **FromReportNo** )

private

Delete an existing report.

### Parameters

[in] **FromReportNo** Report number(Type: int), It can be obtained be calling **OSTableUI::CreateReport**.

### C++ Syntax

```
// Delete an existing table from report data.
OSTableUI::DeleteReport(1);
```

### VBA Syntax

```
Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject(,"StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
        MsgBox"Bad"
        Set objOpenStaad = Nothing
        Exit Sub
    End If
    Dim reportnameStr As String
    reportnameStr = "testreport"
    Dim nReportNum As Long
    nReportNum = objOpenStaad.Table.CreateReport(reportnameStr)
    Dim nTableNum As Long
    Dim tablenameStr As String
    tablenameStr = "testtable"
    nTableNum = objOpenStaad.Table.AddTable(nReportNum, tablenameStr, 2, 2)
    objOpenStaad.Table.DeleteReport(nReportNum)
End Sub
```

## ◆ DeleteTable()

```
void OSTableUI::DeleteTable ( const VARIANT FAR & FromReportNo,
                             const VARIANT FAR & TableNo )
```

private

Delete an existing table from report data.

### Parameters

[in] **FromReportNo** Report number (Type: int), It can be obtained by calling **OSTableUI::CreateReport**.

[in] **TableNo** Table number in specified report (Type: long), It can be obtained by calling **OSTableUI::AddTable**.

### C++ Syntax

```
// Delete an existing table from report data.
OSTableUI::DeleteTable(1, 2);
```

### VBA Syntax

```
Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject(,"StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
        MsgBox"Bad"
        Set objOpenStaad = Nothing
        Exit Sub
    End If
    Dim reportnameStr As String
    reportnameStr = "testreport"
    Dim nReportNum As Long
    nReportNum = objOpenStaad.Table.CreateReport(reportnameStr)
    Dim nTableNum As Long
    Dim tablenameStr As String
    tablenameStr = "testtable"
    nTableNum = objOpenStaad.Table.AddTable(nReportNum, tablenameStr, 2, 2)
    objOpenStaad.Table.DeleteTable(nReportNum, nTableNum)
End Sub
```

## ◆ GetCellValue()

```
void OSTableUI::GetCellValue ( const VARIANT FAR & ReportNo,
                              const VARIANT FAR & TableNo,
                              const VARIANT FAR & IRow,
                              const VARIANT FAR & ICol,
                              VARIANT FAR & varValueStr )
```

private

Get cell values for a specified table.

### Parameters

- [in] **ReportNo** Report number(Type: int), It can be obtained by calling **OSTableUI::CreateReport**.
- [in] **TableNo** Table number in specified report (Type: long), It can be obtained by calling **OSTableUI::AddTable**.
- [in] **IRow** row number for specified table, Start from 1(Type: long).
- [in] **ICol** column Number for specified table, Start from 1(Type: long).
- [out] **varValueStr** Get cell value for specified cell in the table (Type: String).

### C++ Syntax

```
// Get cell values for a specified table.
OSTableUI::GetCellValue(1, TableNo, 10, 5, &varValueStr);
```

### VBA Syntax

```
Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject("StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
        MsgBox "Bad"
        Set objOpenStaad = Nothing
        Exit Sub
    End If
    Dim reportnameStr As String
    reportnameStr = "testreport"
    Dim nReportNum As Long
    nReportNum = objOpenStaad.Table.CreateReport(reportnameStr)
    Dim nTableNum As Long
    Dim tablenameStr As String
    tablenameStr = "testtable"
    nTableNum = objOpenStaad.Table.AddTable(nReportNum, tablenameStr, 2, 2)
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 1, "abc")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 2, "efg")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 1, "xyz")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 2, "mno")
    objOpenStaad.Table.SaveTable(nReportNum, nTableNum)
    Dim RowNum As Long
    Dim ColumnNum As Long
```

Loading [MathJax]/extensions/MathZoom.js<sup>ng</sup>



```

ColumnNum = 1
objOpenStaad.Table.GetCellValue(nReportNum, nTableNum, RowNum, ColumnNum, strValue)
MsgBox strValue
End Sub

```

## ◆ GetReportCount()

VARIANT OSTableUI::GetReportCount ( )

private

Returns the number of reports created.

### C++ Syntax

```

// Returns the number of reports created.
VARIANT RetVal = OSTableUI::GetReportCount();

```

### VBA Syntax

```

Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject("StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
        MsgBox "Bad"
        Set objOpenStaad = Nothing
        Exit Sub
    End If
    Dim reportCount As Long
    reportCount = objOpenStaad.Table.GetReportCount()
End Sub

```

## ◆ GetTableCount()

VARIANT OSTableUI::GetTableCount ( const VARIANT FAR & OfReportNo )

private

Get table count in a specified report..

### Parameters

[in] **OfReportNo** Report number(Type: int), It can be obtained be calling **OSTableUI::CreateReport**.

### C++ Syntax

```
// Get report table count
VARIANT TableCount = OSTableUI::GetTableCount(1);
```

### VBA Syntax

```
Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject("StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
        MsgBox"Bad"
        Set objOpenStaad = Nothing
        Exit Sub
    End If
    Dim reportnameStr As String
    reportnameStr = "testreport"
    Dim nReportNum As Long
    nReportNum = objOpenStaad.Table.CreateReport(reportnameStr)
    Dim nTableNum As Long
    Dim tablenameStr As String
    tablenameStr = "testtable"
    nTableNum = objOpenStaad.Table.AddTable(nReportNum, tablenameStr, 2, 2)
    Dim tableCount As Long
    tableCount = objOpenStaad.Table.GetTableCount(nReportNum)
End Sub
```

## ◆ RenameTable()

```
void OSTableUI::RenameTable ( const VARIANT FAR & ReportNo,
                             const VARIANT FAR & TableNo,
                             const VARIANT FAR & szTableName )
```

private

Rename an existing report table.

### Parameters

- [in] **ReportNo** Report number(Type: int), It can be obtained be calling **OSTableUI::CreateReport**.
- [in] **TableNo** Table number in specified report (Type: long), It can be obtained be calling **OSTableUI::AddTable**.
- [in] **szTableName** Report Table Name(Type: String).

### C++ Syntax

```
// Rename an existing report table from "Table1" to "Table2".
OSTableUI::RenameTable(1, 2, "Table2");
```

### VBA Syntax

```
Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject(,"StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
        MsgBox"Bad"
        Set objOpenStaad = Nothing
        Exit Sub
    End If
    Dim reportnameStr As String
    reportnameStr = "testreport"
    Dim nReportNum As Long
    nReportNum = objOpenStaad.Table.CreateReport(reportnameStr)
    Dim nTableNum As Long
    Dim tablenameStr As String
    tablenameStr = "testtable"
    nTableNum = objOpenStaad.Table.AddTable(nReportNum, tablenameStr, 2, 2)
    objOpenStaad.Table.RenameTable(nReportNum, nTableNum, "testtable2")
End Sub
```

## ◆ ResizeTable()

```
void OTableUI::ResizeTable ( const VARIANT FAR & ReportNo,
                             const VARIANT FAR & TableNo,
                             const VARIANT FAR & RowNos,
                             const VARIANT FAR & ColNos )
```

private

Resize existing table by increasing numbers of rows and columns from report data.

### Parameters

[in] **ReportNo** Report number(Type: int), It can be obtained be calling **OTableUI::CreateReport**.

[in] **TableNo** Table number in specified report (Type: long), It can be obtained be calling **OTableUI::AddTable**.

[in] **RowNos** row count for specified table(Type: long).

[in] **ColNos** column count for specified table(Type: long).

### C++ Syntax

```
// Resize an existing report table by increasing numbers of rows and columns.
OTableUI::ResizeTable(1, 2, 12, 6);
```

### VBA Syntax

```
Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject(,"StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
        MsgBox"Bad"
        Set objOpenStaad = Nothing
        Exit Sub
    End If
    Dim reportnameStr As String
    reportnameStr = "testreport"
    Dim nReportNum As Long
    nReportNum = objOpenStaad.Table.CreateReport(reportnameStr)
    Dim nTableNum As Long
    Dim tablenameStr As String
    tablenameStr = "testtable"
    nTableNum = objOpenStaad.Table.AddTable(nReportNum, tablenameStr, 2, 2)
    objOpenStaad.Table.ResizeTable(nReportNum, nTableNum, 12, 12)
End Sub
```

## ◆ SaveReport()

void OSTableUI::SaveReport ( const VARIANT FAR & ReportNo )

private

Saves the specified report along with all its tables.

### Parameters

[in] **ReportNo** Providing the report number identifying the STAAD report which is to be saved(Type: Int).

### C++ Syntax

```
// Saves the specified report along with all its tables.
OSTableUI::SaveReport(ReportNo);
```

### VBA Syntax

```
Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject("StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
        MsgBox"Bad"
        Set objOpenStaad = Nothing
        Exit Sub
    End If
    Dim reportnameStr As String
    reportnameStr = "testreport"
    Dim nReportNum As Long
    nReportNum = objOpenStaad.Table.CreateReport(reportnameStr)
    Dim nTableNum As Long
    Dim tablenameStr As String
    tablenameStr = "testtable"
    nTableNum = objOpenStaad.Table.AddTable(nReportNum, tablenameStr, 2, 2)
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 1, "abc")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 2, "efg")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 1, "xyz")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 2, "mno")
    objOpenStaad.Table.SaveTable(nReportNum, nTableNum)
    objOpenStaad.Table.SaveReport(nReportNum)
End Sub
```

## ◆ SaveReportAll()

```
void OTableUI::SaveReportAll ( )
```

private

Saves all the reports created.

### C++ Syntax

```
// Saves all the reports created.
OTableUI::SaveReportAll();
```

### VBA Syntax

```
Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject("StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
        MsgBox"Bad"
        Set objOpenStaad = Nothing
        Exit Sub
    End If
    Dim reportnameStr As String
    reportnameStr = "testreport"
    Dim nReportNum As Long
    nReportNum = objOpenStaad.Table.CreateReport(reportnameStr)
    Dim nTableNum As Long
    Dim tablenameStr As String
    tablenameStr = "testtable"
    nTableNum = objOpenStaad.Table.AddTable(nReportNum, tablenameStr, 2, 2)
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 1, "abc")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 2, "efg")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 1, "xyz")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 2, "mno")
    objOpenStaad.Table.SaveTable(nReportNum, nTableNum)
    objOpenStaad.Table.SaveReportAll()
End Sub
```

### ◆ SaveTable()

```
void OSTableUI::SaveTable ( const VARIANT FAR & ReportNo,
                           const VARIANT FAR & TableNo )
```

private

Save a report table.

### Parameters

[in] **ReportNo** Report number (Type: int), It can be obtained by calling **OSTableUI::CreateReport**.

[in] **TableNo** Table number in specified report (Type: long), It can be obtained by calling **OSTableUI::AddTable**.

### C++ Syntax

```
// Save a report table.
OSTableUI::SaveTable(1, 2);
```

### VBA Syntax

```
Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject(,"StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
        MsgBox"Bad"
        Set objOpenStaad = Nothing
        Exit Sub
    End If
    Dim reportnameStr As String
    reportnameStr = "testreport"
    Dim nReportNum As Long
    nReportNum = objOpenStaad.Table.CreateReport(reportnameStr)
    Dim nTableNum As Long
    Dim tablenameStr As String
    tablenameStr = "testtable"
    nTableNum = objOpenStaad.Table.AddTable(nReportNum, tablenameStr, 2, 2)
    objOpenStaad.Table.SaveTable(nReportNum, nTableNum)
End Sub
```

## ◆ SetCellTextBold()

```
void OSTableUI::SetCellTextBold ( const VARIANT FAR & ReportNo,
                                   const VARIANT FAR & TableNo,
                                   const VARIANT FAR & IRow,
                                   const VARIANT FAR & ICol )
```

private

Sets the text in a given row and column to bold.

### Parameters

- [ in] **ReportNo** Report number(Type: int), It can be obtained be calling **OSTableUI::CreateReport**.
- [ in] **TableNo** Table number in specified report (Type: long), It can be obtained be calling **OSTableUI::AddTable**.
- [ in] **IRow** row number for specified table, start from 1(Type: long).
- [ in] **ICol** column number for specified table, start from 1(Type: long).

### C++ Syntax

```
// Sets the text in a given row and column to bold.
OSTableUI::SetCellTextBold(1, TableNo, 10, 5);
```

### VBA Syntax

```
Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject("StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
        MsgBox"Bad"
        Set objOpenStaad = Nothing
        Exit Sub
    End If
    Dim reportnameStr As String
    reportnameStr = "testreport"
    Dim nReportNum As Long
    nReportNum = objOpenStaad.Table.CreateReport(reportnameStr)
    Dim nTableNum As Long
    Dim tablenameStr As String
    tablenameStr = "testtable"
    nTableNum = objOpenStaad.Table.AddTable(nReportNum, tablenameStr, 2, 2)
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 1, "abc")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 2, "efg")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 1, "xyz")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 2, "mno")
    objOpenStaad.Table.SetCellTextBold(nReportNum, nTableNum, 2, 2)
End Sub
```



```
void OSTableUI::SetCellTextColor ( const VARIANT FAR & ReportNo,
                                   const VARIANT FAR & TableNo,
                                   const VARIANT FAR & IRow,
                                   const VARIANT FAR & ICol,
                                   const VARIANT FAR & IRedValue,
                                   const VARIANT FAR & IGreenValue,
                                   const VARIANT FAR & IBlueValue )
```

private

Sets the color of the text to be displayed in a particular cell. By default, the color is always set to black.

### Parameters

- [in] **ReportNo** Report number(Type: int), It can be obtained be calling **OSTableUI::CreateReport**.
- [in] **TableNo** Table number in specified report (Type: long), It can be obtained be calling **OSTableUI::AddTable**.
- [in] **IRow** row number for specified table, start from 1(Type: long).
- [in] **ICol** column number for specified table, start from 1(Type: long).
- [in] **IRedValue** An integer between 0 and 255 that represents the intensity of red in the color for the text(Type: long).
- [in] **IGreenValue** An integer between 0 and 255 that represents the intensity of green in the color for the text(Type: long).
- [in] **IBlueValue** An integer between 0 and 255 that represents the intensity of blue in the color for the text(Type: long).

### C++ Syntax

```
// An integer between 0 and 255 that represents the intensity of red, green or blue in
// the color for the text.
// A value of 0 for a particular color indicates that no shade of that color will be
// mixed into the final color.
// Sets the color (Green) of the text to be displayed in a particular cell.
OSTableUI::SetCellTextColor(1, TableNo, 10, 5, 0, 255, 0);
```

### VBA Syntax

```
' An integer between 0 and 255 that represents the intensity of red, green or blue in
' the color for the text.
' A value of 0 for a particular color indicates that no shade of that color will be
' mixed into the final color.
Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject(,"StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
```

Loading [MathJax]/extensions/MathZoom.js  
aad = Nothing  
Exit Sub

```
End If
Dim reportnameStr As String
reportnameStr = "testreport"
Dim nReportNum As Long
nReportNum = objOpenStaad.Table.CreateReport(reportnameStr)
Dim nTableNum As Long
Dim tablenameStr As String
tablenameStr = "testtable"
nTableNum = objOpenStaad.Table.AddTable(nReportNum, tablenameStr, 2, 2)
objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 1, "abc")
objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 2, "efg")
objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 1, "xyz")
objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 2, "mno")
objOpenStaad.Table.SetCellTextColor(nReportNum, nTableNum, 1, 2, 240, 0, 0)
End Sub
```

## ◆ SetCellTextHorzAlignment()

```
void OSTableUI::SetCellTextHorzAlignment ( const VARIANT FAR & ReportNo,
                                           const VARIANT FAR & TableNo,
                                           const VARIANT FAR & IRow,
                                           const VARIANT FAR & ICol,
                                           const VARIANT FAR & IAlign )
```

private

Sets the text in a particular row and column to a specified horizontal alignment. By default, all the text is right justified.

### Parameters

- [in] **ReportNo** Report number(Type: int), It can be obtained be calling **OSTableUI::CreateReport**.
- [in] **TableNo** Table number in specified report (Type: long), It can be obtained be calling **OSTableUI::AddTable**.
- [in] **IRow** row number for specified table, start from 1(Type: long).
- [in] **ICol** column number for specified table, start from 1(Type: long).
- [in] **IAlign** Sets the text in a particular row and column to a specified horizontal alignment(Type: long). The possible values are:0 = left; 1 = center; 2 = right

### C++ Syntax

```
// Containing the type of horizontal alignment to apply.
// The possible values are:0 = left; 1 = center; 2 = right
OSTableUI::SetCellTextHorzAlignment(1, TableNo, 10, 5, 1);
```

### VBA Syntax

```
Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject("StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
        MsgBox"Bad"
        Set objOpenStaad = Nothing
        Exit Sub
    End If
    Dim reportnameStr As String
    reportnameStr = "testreport"
    Dim nReportNum As Long
    nReportNum = objOpenStaad.Table.CreateReport(reportnameStr)
    Dim nTableNum As Long
    Dim tablenameStr As String
    tablenameStr = "testtable"
    nTableNum = objOpenStaad.Table.AddTable(nReportNum, tablenameStr, 2, 2)
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 1, "abc")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 2, "efg")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 1, "xyz")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 2, "mno")
    objOpenStaad.Table.SetCellTextHorzAlignment(nReportNum, nTableNum, 2, 2, 0)
```

Loading [MathJax]/extensions/MathZoom.js

End Sub

◆ SetCellTextItalic()

```
void OSTableUI::SetCellTextItalic ( const VARIANT FAR & ReportNo,
                                   const VARIANT FAR & TableNo,
                                   const VARIANT FAR & IRow,
                                   const VARIANT FAR & ICol )
```

private

Italicizes the text in a given row and column.

### Parameters

- [ in ] **ReportNo** Report number (Type: int), It can be obtained by calling **OSTableUI::CreateReport**.
- [ in ] **TableNo** Table number in specified report (Type: long), It can be obtained by calling **OSTableUI::AddTable**.
- [ in ] **IRow** row number for specified table, start from 1 (Type: long).
- [ in ] **ICol** column number for specified table, start from 1 (Type: long).

### C++ Syntax

```
// Italicizes the text in a given row and column.
// Italicize the text in row 10 and column 5
OSTableUI::SetCellTextItalic(1, TableNo, 10, 5);
```

### VBA Syntax

```
Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject("StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
        MsgBox "Bad"
        Set objOpenStaad = Nothing
        Exit Sub
    End If
    Dim reportnameStr As String
    reportnameStr = "testreport"
    Dim nReportNum As Long
    nReportNum = objOpenStaad.Table.CreateReport(reportnameStr)
    Dim nTableNum As Long
    Dim tablenameStr As String
    tablenameStr = "testtable"
    nTableNum = objOpenStaad.Table.AddTable(nReportNum, tablenameStr, 2, 2)
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 1, "abc")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 2, "efg")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 1, "xyz")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 2, "mno")
    objOpenStaad.Table.SetCellTextItalic(nReportNum, nTableNum, 2, 2)
End Sub
```

```
void OSTableUI::SetCellTextSize ( const VARIANT FAR & ReportNo,
                                   const VARIANT FAR & TableNo,
                                   const VARIANT FAR & IRow,
                                   const VARIANT FAR & ICol,
                                   const VARIANT FAR & dSize )
```

private

Sets the text in a particular row and column to a certain font size. The font sizes are equivalent to the ones used in Microsoft Word.

### Parameters

- [in] **ReportNo** Report number(Type: int), It can be obtained be calling **OSTableUI::CreateReport**.
- [in] **TableNo** Table number in specified report (Type: long), It can be obtained be calling **OSTableUI::AddTable**.
- [in] **IRow** row number for specified table, start from 1(Type: long).
- [in] **ICol** column number for specified table, start from 1(Type: long).
- [in] **dSize** Containing the size of the font to set the text to(Type: Double).

### C++ Syntax

```
// The text in a particular row and column to a certain font size.
OSTableUI::SetCellTextSize(1, TableNo, 10, 5, 16.0);
```

### VBA Syntax

```
Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject("StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
        MsgBox"Bad"
        Set objOpenStaad = Nothing
        Exit Sub
    End If
    Dim reportnameStr As String
    reportnameStr = "testreport"
    Dim nReportNum As Long
    nReportNum = objOpenStaad.Table.CreateReport(reportnameStr)
    Dim nTableNum As Long
    Dim tablenameStr As String
    tablenameStr = "testtable"
    nTableNum = objOpenStaad.Table.AddTable(nReportNum, tablenameStr, 2, 2)
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 1, "abc")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 2, "efg")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 1, "xyz")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 2, "mno")
    objOpenStaad.Table.SetCellTextSize(nReportNum, nTableNum, 2, 2, 16.0)
End Sub
```

Loading [MathJax]/extensions/MathZoom.js

## ◆ SetCellTextSizeAll()

```
void OSTableUI::SetCellTextSizeAll ( const VARIANT FAR & ReportNo,
                                     const VARIANT FAR & TableNo,
                                     const VARIANT FAR & dSize )
```

private

Sets the text in the entire table to FontSize. The font sizes are equivalent to the ones used in Microsoft Word.

### Parameters

[in] **ReportNo** Report number (Type: int), It can be obtained by calling **OSTableUI::CreateReport**.

[in] **TableNo** Table number in specified report (Type: long), It can be obtained by calling **OSTableUI::AddTable**.

[in] **dSize** Containing the size of the font to set the entire table to (Type: Double).

### C++ Syntax

```
// The text in the entire table to FontSize.
OSTableUI::SetCellTextSizeAll(1, TableNo, 16.0);
```

### VBA Syntax

```
Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject("StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
        MsgBox "Bad"
        Set objOpenStaad = Nothing
        Exit Sub
    End If
    Dim reportnameStr As String
    reportnameStr = "testreport"
    Dim nReportNum As Long
    nReportNum = objOpenStaad.Table.CreateReport(reportnameStr)
    Dim nTableNum As Long
    Dim tablenameStr As String
    tablenameStr = "testtable"
    nTableNum = objOpenStaad.Table.AddTable(nReportNum, tablenameStr, 2, 2)
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 1, "abc")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 2, "efg")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 1, "xyz")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 2, "mno")
    objOpenStaad.Table.SetCellTextSizeAll(nReportNum, nTableNum, 22.0)
End Sub
```

```
void OSTableUI::SetCellTextUnderline ( const VARIANT FAR & ReportNo,
                                       const VARIANT FAR & TableNo,
                                       const VARIANT FAR & IRow,
                                       const VARIANT FAR & ICol )
```

private

Underlines the text in a given row and column.

### Parameters

- [ in] **ReportNo** Report number(Type: int), It can be obtained be calling **OSTableUI::CreateReport**.
- [ in] **TableNo** Table number in specified report (Type: long), It can be obtained be calling **OSTableUI::AddTable**.
- [ in] **IRow** row number for specified table, start from 1(Type: long).
- [ in] **ICol** column number for specified table, start from 1(Type: long).

### C++ Syntax

```
// Underlines the text in a given row and column.
OSTableUI::SetCellTextUnderline(1, TableNo, 10, 5);
```

### VBA Syntax

```
Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject("StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
        MsgBox"Bad"
        Set objOpenStaad = Nothing
        Exit Sub
    End If
    Dim reportnameStr As String
    reportnameStr = "testreport"
    Dim nReportNum As Long
    nReportNum = objOpenStaad.Table.CreateReport(reportnameStr)
    Dim nTableNum As Long
    Dim tablenameStr As String
    tablenameStr = "testtable"
    nTableNum = objOpenStaad.Table.AddTable(nReportNum, tablenameStr, 2, 2)
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 1, "abc")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 2, "efg")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 1, "xyz")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 2, "mno")
    objOpenStaad.Table.SetCellTextUnderline(nReportNum, nTableNum, 2, 2)
End Sub
```



```
void OSTableUI::SetCellTextVertAlignment ( const VARIANT FAR & ReportNo,
                                           const VARIANT FAR & TableNo,
                                           const VARIANT FAR & IRow,
                                           const VARIANT FAR & ICol,
                                           const VARIANT FAR & IAlign )
```

private

Sets the text in a particular row and column to a specified vertical alignment. By default, all the text is top justified.

### Parameters

- [in] **ReportNo** Report number(Type: int), It can be obtained be calling **OSTableUI::CreateReport**.
- [in] **TableNo** Table number in specified report (Type: long), It can be obtained be calling **OSTableUI::AddTable**.
- [in] **IRow** row number for specified table, start from 1(Type: long).
- [in] **ICol** column number for specified table, start from 1(Type: long).
- [in] **IAlign** Sets the text in a particular row and column to a specified vertical alignment(Type: long). The possible values are:0 = top; 4 = center; 8 = bottom

### C++ Syntax

```
// Sets the text in a particular row and column to a specified vertical alignment.
// The possible values are:0 = top; 4 = center; 8 = bottom
OSTableUI::SetCellTextVertAlignment(1, TableNo, 10, 5, 0);
```

### VBA Syntax

```
' Sets the text in a particular row and column to a specified vertical alignment.
' The possible values are:0 = top; 4 = center; 8 = bottom
Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject("StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
        MsgBox"Bad"
        Set objOpenStaad = Nothing
        Exit Sub
    End If
    Dim reportnameStr As String
    reportnameStr = "testreport"
    Dim nReportNum As Long
    nReportNum = objOpenStaad.Table.CreateReport(reportnameStr)
    Dim nTableNum As Long
    Dim tablenameStr As String
    tablenameStr = "testtable"
    nTableNum = objOpenStaad.Table.AddTable(nReportNum, tablenameStr, 2, 2)
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 1, "abc")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 2, "efg")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 1, "xyz")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 2, "mno")
```

Loading [MathJax]/extensions/MathZoom.js

```
objOpenStaad.Table.SetCellTextVertAlignment(nReportNum, nTableNum, 2, 2, 8)  
End Sub
```

## ◆ SetCellValue()

```
void OSTableUI::SetCellValue ( const VARIANT FAR & ReportNo,
                              const VARIANT FAR & TableNo,
                              const VARIANT FAR & IRow,
                              const VARIANT FAR & ICol,
                              const VARIANT FAR & varValue )
```

private

Set cell values for a specified table.

### Parameters

- [in] **ReportNo** Report number (Type: int), It can be obtained by calling **OSTableUI::CreateReport**.
- [in] **TableNo** Table number in specified report (Type: long), It can be obtained by calling **OSTableUI::AddTable**.
- [in] **IRow** row number for specified table, start from 1 (Type: long).
- [in] **ICol** column number for specified table, start from 1 (Type: long).
- [in] **varValue** set cell value for specified cell in the table (Type: String).

### C++ Syntax

```
// Set cell values for a specified table.
OSTableUI::SetCellValue(1, TableNo, 10, 5, varValue);
```

### VBA Syntax

```
Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject("StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
        MsgBox "Bad"
        Set objOpenStaad = Nothing
        Exit Sub
    End If
    Dim reportnameStr As String
    reportnameStr = "testreport"
    Dim nReportNum As Long
    nReportNum = objOpenStaad.Table.CreateReport(reportnameStr)
    Dim nTableNum As Long
    Dim tablenameStr As String
    tablenameStr = "testtable"
    nTableNum = objOpenStaad.Table.AddTable(nReportNum, tablenameStr, 2, 2)
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 1, "abc")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 1, 2, "efg")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 1, "xyz")
    objOpenStaad.Table.SetCellValue(nReportNum, nTableNum, 2, 2, "mno")
End Sub
```

## ◆ SetColumnHeader()

```
void OTableUI::SetColumnHeader ( const VARIANT FAR & ReportNo,
                                const VARIANT FAR & TableNo,
                                const VARIANT FAR & ICol,
                                const VARIANT FAR & varHeader )
```

private

Sets column header for a specified table.

### Parameters

- [in] **ReportNo** Report number(Type: int), It can be obtained be calling **OTableUI::CreateReport**.
- [in] **TableNo** Table number in specified report (Type: long), It can be obtained be calling **OTableUI::AddTable**.
- [in] **ICol** column number for specified table, start from 1(Type: long).
- [in] **varHeader** Column header for a specified column in table(Type: String).

### C++ Syntax

```
// Sets column header for a specified table.
OTableUI::SetColumnHeader(1, TableNo, 5, varHeader);
```

### VBA Syntax

```
Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject(,"StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
        MsgBox"Bad"
        Set objOpenStaad = Nothing
        Exit Sub
    End If
    Dim reportnameStr As String
    reportnameStr = "testreport"
    Dim nReportNum As Long
    nReportNum = objOpenStaad.Table.CreateReport(reportnameStr)
    Dim nTableNum As Long
    Dim tablenameStr As String
    tablenameStr = "testtable"
    nTableNum = objOpenStaad.Table.AddTable(nReportNum, tablenameStr, 2, 2)
    Dim headerStr As String
    headerStr = "Header1"
    objOpenStaad.Table.SetColumnHeader(nReportNum, nTableNum,1,headerStr)
End Sub
```

## ◆ SetColumnUnitString()

```
void OTableUI::SetColumnUnitString ( const VARIANT FAR & ReportNo,
                                     const VARIANT FAR & TableNo,
                                     const VARIANT FAR & ICol,
                                     const VARIANT FAR & varUnitString )
```

private

Sets unit for the specific column of a specified table.

### Parameters

- [in] **ReportNo** Report number(Type: int), It can be obtained be calling **OTableUI::CreateReport**.
- [in] **TableNo** Table number in specified report (Type: long), It can be obtained be calling **OTableUI::AddTable**.
- [in] **ICol** column number for specified table, start from 1(Type: long).
- [in] **varUnitString** set unit for the specific column of a specified table(Type: String).

### C++ Syntax

```
// Sets unit for the specific column of a specified table.
OTableUI::SetColumnUnitString(1, TableNo, 5, varUnitString);
```

### VBA Syntax

```
Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject(,"StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
        MsgBox"Bad"
        Set objOpenStaad = Nothing
        Exit Sub
    End If
    Dim reportnameStr As String
    reportnameStr = "testreport"
    Dim nReportNum As Long
    nReportNum = objOpenStaad.Table.CreateReport(reportnameStr)
    Dim nTableNum As Long
    Dim tablenameStr As String
    tablenameStr = "testtable"
    nTableNum = objOpenStaad.Table.AddTable(nReportNum, tablenameStr, 2, 2)
    Dim unitStr As String
    unitStr = "mm"
    objOpenStaad.Table.SetColumnUnitString(nReportNum, nTableNum,1,unitStr)
End Sub
```

## ◆ SetRowHeader()

```
void OSTableUI::SetRowHeader ( const VARIANT FAR & ReportNo,
                               const VARIANT FAR & TableNo,
                               const VARIANT FAR & IRow,
                               const VARIANT FAR & varHeader )
```

private

Sets row header for the specific row of a specified table.

### Parameters

- [in] **ReportNo** Report number(Type: int), It can be obtained be calling **OSTableUI::CreateReport**.
- [in] **TableNo** Table number in specified report (Type: long), It can be obtained be calling **OSTableUI::AddTable**.
- [in] **IRow** row number for specified table, start from 1(Type: long).
- [in] **varHeader** set header for the specific row of a specified table(Type: String).

### C++ Syntax

```
// Sets row header for the specific row of a specified table.
OSTableUI::SetRowHeader(1, TableNo, 5, varHeader);
```

### VBA Syntax

```
Option Explicit
Sub Main
    Dim objOpenStaad As Object
    Dim stdFile As String
    Set objOpenStaad = GetObject(,"StaadPro.OpenSTAAD")
    objOpenStaad.GetSTAADFile stdFile, "TRUE"
    If stdFile="" Then
        MsgBox"Bad"
        Set objOpenStaad = Nothing
        Exit Sub
    End If
    Dim reportnameStr As String
    reportnameStr = "testreport"
    Dim nReportNum As Long
    nReportNum = objOpenStaad.Table.CreateReport(reportnameStr)
    Dim nTableNum As Long
    Dim tablenameStr As String
    tablenameStr = "testtable"
    nTableNum = objOpenStaad.Table.AddTable(nReportNum, tablenameStr, 2, 2)
    Dim rowHeaderStr As String
    rowHeaderStr = "row1"
    objOpenStaad.Table.SetRowHeader(nReportNum, nTableNum,1,rowHeaderStr)
End Sub
```