

A cartoon ninja character in a black suit with a red gear emblem on the chest, holding two black trident weapons. The character is in a dynamic pose on a green field. In the background, there is a Dutch-style windmill with a grey body and orange lattice sails, a red door, and a blue window. The scene is set in a rural landscape with a blue sky, white clouds, green trees, and a body of water. A black and white cow is grazing in the foreground on the right.

# Azure AD Conditional Access Demystified

Centric Craft – October 2021 edition



# About “Kenneth van Surksun”


## Focus

Modern Workplace Consultant at Insight24, Microsoft Certified Trainer, Co-founder and organizer at Workplace Ninja User Group Netherlands



## From

The Netherlands



## My Blog

<https://www.vansurksun.com>



## Certifications

Microsoft 365 Certified Enterprise Administrator



Microsoft Certified Azure Solutions Architect



## Hobbies

Cooking on my Kamado Joe & Sports



## Contact

[kenneth@vansurksun.com](mailto:kenneth@vansurksun.com)

<https://twitter.com/kennethvs>


<https://www.linkedin.com/in/kennethvansurksun>





# Our topics for Today!

---




- What is Conditional Access?
- How does Conditional Access work?
- Designing Conditional Access
- Implementing Conditional Access
- Troubleshooting Conditional Access



# BACK TO THE FUTURE




# Yesterday's Infrastructure ;)





# Traditional IT environment



1 Personal Computer

Multiple Personal Computers

Network

Authentication

Management via LAN

Internal collaboration, sending documents to each other via email/working of fileshares

Files are stored centrally on fileshares

Printing using print servers


Client/Server applications

Email/Internet


LAN extension (VPN)

Security by using Firewalls

# Tomorrow's Infrastructure



# Tomorrows Workplace



Work anywhere at any time

Internal & external collaboration in a central location

Divers set of Workplaces (Laptops, Desktops, Mobile)

Managed from the Internet

High usage of SaaS offerings (Office 365, Salesforce, Dynamics)


Company data stored in the cloud

Less need to print

Safety provided by the identity




# Cloud Service Types




# Today's Infrastructure = Hybrid

Yesterday



Tomorrow



Identity is the new perimeter





## Microsoft Description:

### What is Conditional Access?

*“With Conditional Access, you can implement automated access control decisions for accessing your cloud apps that are based on conditions.” and “Conditional Access policies are enforced **after** the first-factor authentication has been completed. Therefore, Conditional Access is **not** intended as a first line defense for scenarios like denial-of-service (DoS) attacks, but can utilize signals from these events (e.g. the sign-in risk level, location of the request, and so on) to determine access.”*






## What is Conditional Access?



- Put **conditions** in place to **access** to company data and apps. (Identity and device)
- Can be compared with a Network Firewall but then for your identity
- Resources being accessed must use Azure AD as authentication provider
- Even though you can use it, doesn't mean you are licensed
- When using ADFS, it can become quite complex – ask yourself whether you still need ADFS
- Adds points to your Secure Score



## Prerequisites




- We must block legacy authentication for Conditional Access to work in all scenarios.
  - Azure AD Premium P1 or P2 license (if not you can use Security defaults)
  - Microsoft Endpoint Manager (if you want to leverage compliance)
  - Rethink your reauthentication settings (MFA global settings/KMSI)
  - Make sure that you define 2 break glass accounts - <https://docs.microsoft.com/en-us/azure/active-directory/roles/security-emergency-access>
-


## What is legacy authentication?

When using Basic/Legacy Authentication application sends a username and password with every request to f.e. Exchange Online which either forwards the credentials towards Azure AD or a federated authentication provider like Active Directory Federation Services (ADFS).

Windows PowerShell credential request ? X



Enter your credentials.

User name:  

Password:

OK Cancel

What is the issue  
with legacy  
authentication?



The problem with Basic/Legacy authentication is that it is vulnerable to brute force or password spray attacks.

And therefore:

The Exchange Team announced that effective October 1st, 2022 basic authentication, regardless of usage will be permanently disabled in all tenants.


---



## Some additional reasons



- In order to fully implement Conditional Access we must make sure that the services that we want to protect using Conditional Access make use of Modern Authentication
- If we want to move towards Passwordless we must stop using Legacy Authentication





# Legacy Authentication

Usage within your tenant?

## Signals

User and  
location



Device



Application



Real-time  
risk



## Verify every access attempt



Allow access



Require MFA



Block access

## Apps and data



101010  
010101  
101010





# How does it work?

---

When this happens

Then do this


Conditional access policy

Conditions

Access controls



## How does it really work?



*Access to <provided> Clouds Apps except <provided> Cloud apps by <provided> users and/or <provided> roles and/or <provided> groups except <provided> users and/or <provided> groups using <provided> User Risk and/or <provided> Sign-in Risk and/or <provided> Device Platform except <provided> Device Platform from <provided> Location except <provided> Location using <provided> Client apps with <provided> device state, except <provided> device state Grants, Grants but <provided requirement must be fulfilled> or Blocks access and/or applies Session controls.*

---

The diagram illustrates the Zero Trust Access (ZTA) model. It shows four signals (User and location, Device, Application, Real-time risk) feeding into a central cloud icon with a key. This cloud then feeds into a 'Verify every access attempt' stage, which branches into three outcomes: 'Allow access' (green checkmark), 'Require MFA' (lock icon), and 'Block access' (red X icon). The 'Allow access' path leads to 'Apps and data' (represented by a building, a document, and binary code).



# Important rules

**Grant** ×

Control user access enforcement to block or grant access. [Learn more](#)

☒ Block access  
☐ Grant access

☐ Require multi-factor authentication ⓘ

☐ Require device to be marked as compliant ⓘ

☐ Require Hybrid Azure AD joined device ⓘ

☐ Require approved client app ⓘ  
[See list of approved client apps](#)

☐ Require app protection policy ⓘ  
[See list of policy protected client apps](#)

☐ Require password change ⓘ

☐ I24 Terms of Use

For multiple controls

☐ Require all the selected controls  
☒ Require one of the selected controls

1. All policies are enforced in two phases
  1. In the first phase, all policies are evaluated (in parallel) and all access controls that aren't satisfied are collected.
  2. In the second phase, you are prompted to satisfy the requirements you haven't met.
2. If one of the policies blocks access, you are blocked and not prompted to satisfy other policy controls. If none of the policies blocks you, you are prompted to satisfy other policy controls in the following order:
  - 1. Multi-factor authentication
  - 2. Approved client app/app protection policy
  - 3. Managed device (compliant or hybrid Azure AD join)
  - 4. Terms of use
  - 5. Custom controls
3. Policies are not effective immediately
4. With Continuous Access Evaluation (currently in preview) we will get quicker results




# Conditional Access

Creating your conditional access policy




# Designing a Conditional Access Strategy




- What kind of devices does the customer use to access cloud apps?
  - What kind of applications are used to access cloud apps?
  - Is this a green field implementation, or are the cloud apps already in use without any conditional access policies in action?
  - Does the customer use Intune and which scenarios are built into Intune
    - Mobile Device Management
    - Mobile Application Management
  - Is every user treated equally when it comes to access to the cloud apps, or can we distinct personas with different requirements when it comes to Conditional Access
  - Which licensing is the customer using? My opinion is that you need E5 functionality for administrators or people who are local administrator at least nowadays.
  - How are licenses being assigned to users (groups, directly)
  - Are there any service accounts used that interact with the cloud apps?
  - What are the reauthentication settings for the customer?
  - Is Modern Authentication already enabled for Exchange Online and Skype for Business online?
  - Is the company storing password hashes in Azure Active Directory?
  - Are there cloud apps depending on each other?
-

## Designing a Conditional Access Strategy



- Azure Active Directory Conditional Access Deployment Plan:
  - <https://aka.ms/CADPDownload>
  - How To: Plan your Conditional Access deployment in Azure Active Directory – <https://docs.microsoft.com/en-us/azure/active-directory/conditional-access/plan-conditional-access>
  - Conditional Access documentation spreadsheet - <https://gallery.technet.microsoft.com/Conditional-Access-dc903421>
-

# Define Scenarios



**Scenario 1:** Allow devices managed by Intune access all the cloud apps using Apps and Desktop Clients and Modern Authentication Clients if compliant

- *Access to “All Cloud Apps” by “Users with EMS License” using “Any” device platform” coming from “any location” using “Mobile Apps and Desktop Clients” or “Modern authentication clients” is allowed, but device must be compliant.*
  - **Scenario 2:** Only allow Apps we can manage to access cloud apps when device is not managed.
  - *Allow users with EMS License using devices not managed by intune to access (portion of, t.b.d.) cloud apps, using clients which we can manage using MAM policies (approved clients list)*
  - **Scenario 3:** Allow browser access to all the cloud apps from a trusted location
  - *When users access the cloud apps from a trusted location they can login without using any additional form of authentication*
  - **Scenario 4:** Allow browser access to all the cloud apps from an untrusted location but use MFA and restrict the browser session (when possible)
  - *When users access the cloud apps from a non trusted location they can login but have to use MFA and when possible the browser session is restricted.*
  - **Scenario 5:** Block browser access to all the cloud apps from some geographic areas
  - *Users cannot access cloud apps from regions where the company doesn’t operate.*
-





# Goals


Protect company data hosted in Office 365 and protect identity of users


Access to O365 Company  
Data or Cloud App













# Consequences



- Users on mobile devices must be migrated to either MDM or MAM (Outlook and other Office apps on the approved apps list)
- We must implement Guest user governance
  - Ask yourself if you want to allow full access to Guests from unmanaged devices?
- We must review the usage of non-personal accounts (Service Accounts)








# Additional Notes

- Even though MS recommends less is better when it comes to CA policies, I prefer granularity
  - Conditional Access policy per functionality
  - For each Conditional Access policy there is a specific exclude group (which also includes the Breakglass accounts)
    - Therefore, if exceptions are made, they can be very specific
    - Consider implementing access reviews on those exclude groups if you have Azure AD P2
- Naming convention is very important, follow MS best practices

<SN>- <Cloud app>: <Response> For <Principal> When <Conditions>

- The Conditional Access policies are numbered, **and** versioned
  - CAP = Conditional Access Prerequisite
  - CAU = Conditional Access User
  - CAD = Conditional Access Device
  - CAL = Conditional Access Location
  - CAC = Conditional Access Custom
  - Example: CAD007-O365: Session set Sign-in Frequency for Apps for All users when Modern Auth Clients and Non-Compliant-v1.0





# Some examples

- Prerequisite policies

CAP001-All: Block Legacy Authentication for All users when OtherClients-v 1.0				
Assignments			Access Controls	
Users	Cloud Apps	Conditions	Grant	Session
All Users	All	Client Apps: Other	Block	
Except				
AAD_AA_ConAcc-Breakglass				
AAD_AA_CAP001-Exclude				

CAP002-O365: Grant Exchange ActiveSync Clients for All users when Approved App-v 1.0				
Assignments			Access Controls	
Users	Cloud Apps	Conditions	Grant	Session
All Users	All	Client Apps: Exchange Active	Grant  Require Approved App	
Except				
AAD_AA_ConAcc-Breakglass				
AAD_AA_CAP002-Exclude				



# Some examples

CAU004-Selected: Session route through MCAS for All users when Browser on Non-Compliant-v 1.1

Assignments			Access Controls	
Users	Cloud Apps, User Actions or Authentication Context	Conditions	Grant	Session
All Users	<Selected>	Client Apps: Browser		Use Conditional Access App Control: Block downloads (Preview)
Except		Filter for devices: Exclude		
AAD_AA_ConAcc-Breakglass		isCompliant Equals True		
AAD_AA_CAU004-Exclude				

CAU005-Selected: Session route through MCAS for All users when Browser on Compliant-v 1.1

Assignments			Access Controls	
Users	Cloud Apps, User Actions or Authentication Context	Conditions	Grant	Session
All Users	<Selected>	Client Apps: Browser		Use Conditional Access App Control: Monitor (Preview)
Except		Filter for devices: Include		
AAD_AA_ConAcc-Breakglass		isCompliant Equals True		
AAD_AA_CAU005-Exclude				





# Some examples

CAU006-All: Grant access for High Risk Sign-in for All Users when Browser and Modern Auth Clients require MFA-v 1.0				
Assignments			Access Controls	
Users	Cloud Apps	Conditions	Grant	Session
All Users	All	Client Apps: Browser Mobile Apps and Desktop Clients	Grant  Require multi-factor authentication	
Except		Sign-in Risk: High		
AAD_AA_ConAcc-Breakglass				
AAD_AA_CAU006-Exclude				

CAU007-All: Grant access for High Risk Users for All Users when Browser and Modern Auth Clients require PWD reset-v 1.0				
Assignments			Access Controls	
Users	Cloud Apps	Conditions	Grant	Session
All Users	All	Client Apps: Browser Mobile Apps and Desktop Clients	Grant  Require Password Change	
Except		User Risk: High		
AAD_AA_ConAcc-Breakglass				
AAD_AA_CAU007-Exclude				

**Note:** Disable the policies in Azure AD Identity Protection



# Some examples

CAU011-All: Block access for All users except licensed when Browser and Modern Auth Clients-v 1.0				
Assignments			Access Controls	
Users	Cloud Apps	Conditions	Grant	Session
All Users	All	Client Apps: Browser Mobile Apps and Desktop Clients	Block	
Except				
AAD_AA_ConAcc-Breakglass				
AAD_AA_CAU011-Exclude				
License groups				

**Note:** Be Very Carefull!



# Some examples

CAD002-O365: Grant Windows access for All users when Modern Auth Clients and Compliant-v 1.0				
Assignments			Access Controls	
Users	Cloud Apps	Conditions	Grant	Session
All Users	Office 365	Client Apps: Mobile Apps and Desktop Clients	Grant  Require device to be marked as compliant	
Except		Device Platform: Windows		
Guest and External Users				
And				
AAD_AA_ConAcc-Breakglass				
AAD_AA_CAD002-Exclude				

**Note:** Guest access depending on your design choices



# Some examples

CAD006-O365: Session block download on unmanaged device when All users when Browser-v 1.0				
Assignments			Access Controls	
Users	Cloud Apps	Conditions	Grant	Session
All Users	Office 365	Client Apps: Browser		Use App Enforced Restrictions
Except		Device state: All except Device marked as Compliant		
AAD_AA_ConAcc-Breakglass				
AAD_AA_CAD006-Exclude				

## Notes:

Be careful when setting the SharePoint settings, since that setting will create 2 enabled CA policies without asking

Consider implementing Sensitivity labels if you want more granularity



# Some examples

CAD008-All: Session set Sign-in Frequency for All users when Browser and Non-Compliant-v 1.0

Assignments			Access Controls	
Users	Cloud Apps	Conditions	Grant	Session
All Users	All	Client Apps: Browser		Sign-in Frequency: 1 Days
Except		Device state: All except Device marked as Compliant		
AAD_AA_ConAcc-Breakglass				
AAD_AA_CAD008-Exclude				

CAD0009-All: Session disable browser persistence for All users when Browser and Non-Compliant-v 1.0

Assignments			Access Controls	
Users	Cloud Apps	Conditions	Grant	Session
All Users	All	Client Apps: Browser		Persistent Browser Session
Except		Device state: All except Device marked as Compliant		
AAD_AA_ConAcc-Breakglass				
AAD_AA_CAD009-Exclude				

**Notes: Review your current reauthentication settings**



# Conditional Access

## Implementation





# Browser restrictions

---

OS	Browsers
Windows 10	Microsoft Edge, Internet Explorer, Chrome, <a href="#">Firefox 91+</a>
Windows 8 / 8.1	Internet Explorer, Chrome
Windows 7	Internet Explorer, Chrome
iOS	Microsoft Edge, Intune Managed Browser, Safari
Android	Microsoft Edge, Intune Managed Browser, Chrome
Windows Phone	Microsoft Edge, Internet Explorer
Windows Server 2019	Microsoft Edge, Internet Explorer, Chrome
Windows Server 2016	Internet Explorer
Windows Server 2012 R2	Internet Explorer
Windows Server 2008 R2	Internet Explorer
macOS	Microsoft Edge, Chrome, Safari

# Conditional Access

Browser restrictions





# Authentication Context

---

- Conditional Access Authentication Context can trigger a Conditional Access policy when sensitive content is accessed. With this new functionality new scenarios become available; some examples are:
  - You can require MFA when a SharePoint site with a certain sensitivity label gets accessed on an unmanaged device.
  - You can block the session from a Conditional Access policy when a SharePoint site with a certain sensitivity label gets accessed on a unmanaged device.
  - You can require that Terms of Use must be accepted first before access to a SharePoint site with a certain sensitivity label gets accessed.
  - You can set the sign-in frequency to a low value when a SharePoint site with a certain sensitivity label gets accessed.
  - You can trigger the Authentication Context from within a session control policy defined in MCAS, for example to trigger MFA as defined in the Conditional Access policy. You could for example trigger MFA when a document with a certain sensitivity label gets downloaded, or require the user to accept a Terms of Use first.
  - App developers can leverage the authentication context in their own apps



# Conditional Access examples

CAU012-AuthCon: Require MFA and compliant for sensitivity label confidential-v1.0

Assignments			Access Controls	
Users	Cloud Apps or Actions	Conditions	Grant	Session
All Users Except	Authentication Context: High Authentication Context	Client Apps: Browser Mobile Apps and Desktop Clients	Grant	
AAD_AA_ConAcc-Breakglass			Require multi-factor authentication	
AAD_AA_CAU012-Exclude			And	
All Guest and External Users			Require device to be marked as compliant	

CAU013-AuthCon: Require MFA and Accept TOU for sensitivity label confidential-v1.0

Assignments			Access Controls	
Users	Cloud Apps or Actions	Conditions	Grant	Session
All Guest and External Users Except	Authentication Context: High Authentication Context	Client Apps: Browser Mobile Apps and Desktop Clients	Grant	
AAD_AA_ConAcc-Breakglass			Require multi-factor authentication	
AAD_AA_CAU013-Exclude			And	
			124 - Terms of Use	


# Conditional Access

Authentication Context





# Tips



- Use the **Access Review** functionality if available (Azure AD P2)
  - Define operational procedures to execute when **something out of your control goes down** (f.e. Azure MFA outage)
  - Regularly **review what's new** in Azure AD conditional access and determine if it impacts your environment
    - You can see what's new in Azure Active Directory here: <https://docs.microsoft.com/en-us/azure/active-directory/fundamentals/whats-new> and on the Azure Updates webpage here: <https://azure.microsoft.com/en-in/updates/?product=active-directory&status=all&updatetype=features>
  - Some cloud apps have dependencies with other cloud apps, for example Microsoft Teams has **dependencies** of Exchange Online, SharePoint and Planner and perhaps even more.
    - What are service dependencies in Azure Active Directory Conditional Access? – <https://docs.microsoft.com/en-us/azure/active-directory/conditional-access/service-dependencies>
  - Make sure that you can **test your scenarios** (have equipment available)
    - Android device, Apple Device, Windows 10 device, VPN software....
  - Create Alerts in Log Analytics to notify you when:
    - New Conditional Access policies are created
    - Existing Conditional Access policies are modified
-



# Conditional Access

Troubleshooting Conditional Access policies

## Further Resources

Azure Active Directory @ MSDN –

<https://social.msdn.microsoft.com/Forums/en-US/home?forum=WindowsAzureAD>

Azure Active Directory @ Stack Overflow –

<https://stackoverflow.com/questions/tagged/azure-active-directory>

UserVoice:

<https://feedback.azure.com/forums/169401-azure-active-directory/category/167259-conditional-access>

---



# So much more to tell

---





# References

---

- [Microsoft is going to disable basic/legacy authentication for Exchange Online. What does that actually mean and does that impact me?](#)
- [Understanding and governing reauthentication settings in Azure Active Directory](#)
- [Extending Conditional Access to Microsoft Cloud App Security using Conditional Access App Control](#)
- [Azure AD Identity Protection deep dive](#)
- [Azure AD Continuous access evaluation \(CAE\), a first look](#)
- [Limit Access to Outlook Web Access, SharePoint Online and OneDrive using Conditional Access App Enforced Restrictions](#)
- [Defining more granularity for your Conditional Access App Enforced Restrictions using Sensitivity Labels](#)
- [Mobile Application Management for Mobile Devices with Microsoft Endpoint Manager/Intune deep dive](#)
- [Conditional Access demystified: My recommended default set of policies](#)
- [Defining more granularity for your Conditional Access App Enforced Restrictions using Sensitivity Labels](#)
- [Designing and building your Microsoft Endpoint Manager/Intune environment for Operations](#)