

# Tutorial 1 - An introduction to circular data


Arjan Huizing

2 April 2018

## What is circular data?

Most researchers will be familiar with the concept of measurement levels of variables. The most popular two being continuous data and categorical data. Circular data is another type of measurement with properties that distinguish it from other data types. The main property of circular data is the fact that it is periodical. What this means is that there is no true start or end point, but rather a continuous scale that loops back on itself.


An example would be the time of day as represented on the clock. As time passes the hands on the face of a clock will inevitably be bound to pass the same 12 hours over and over. This also means that distances can not be interpreted as linear. The difference in time between 1 AM and 3 AM is the same as the distance between 11 PM and 1 AM, that is, two hours. Another quality of circular data is that every value can be seen to have an opposite value. When we analyze directions on a compass, we would say that north is the opposite of south, and east is the opposite of west. Circumplex models also use this quality to create a continuum of related values, where opposite values are 180 degrees apart. Examples of this from social and behavioural science are Schwartz' theory of basic values, Russel's mood scale and Leary's interpersonal circumplex. A third measurement that is circular is that of directions, such as those found on a compass.



*Russel's circumplex model of mood (as depicted in in Herbon, Peter, Markert, van der Meer and Voskamp, 2005), a compass and a clock. All examples of circular data.*


Circular data has applications for many disciplines, including the social and behavioural sciences. For example, measuring directions can be used to track eye movement or body movement during an experiment. In a study by Warren et al. (2017), 39 participants were asked to navigate a Euclidian and a non-Euclidian maze using a virtual reality headset. The Euclidian and non-Euclidian mazes were identical except for the presense of two 'wormholes' that would transport participants instantly. The movement of participants through these mazes was tracked for all eight trials. The mazes were designed in a way that the angular error would be higher if participants opted to use wormholes present in the non-Euclidian maze.

The researchers then used this data to test whether participants were capable of learning to navigate a space using these wormholes, which may indicate whether human knowledge on navigation space is Euclidian or not.




The virtual mazes A (Euclidian) and B (non-Euclidian) used in the study by Warren et al. (2017).

### Euclidian maze



### Non-Euclidian maze




A subset of the data is displayed above, containing the angular error found in the standard trials of 20 participants. Here we see a noticeable difference in direction and spread between the Euclidian maze and the non-Euclidian maze. Using circular data models, the researchers were able to - among other things - analyze if there were significant group differences in circular outcomes.


### Circular measurement

Note how the output above indicates the values in degrees. Measuring circular data in degrees is one of the two common measurement types. A second way to express angles on a circle is by using radians. A circle has a total of 360 degrees, or equivalently, a total of  $2\pi \approx 6.28$  radians.

## Degrees



## Radians



Values in degrees are easily converted to radians and vice versa. The formulae for this are

$$\text{degrees}^\circ * (\pi/180) = \text{radians}$$

$$\text{radians}(180/\pi) = \text{degrees}$$

*#Converting degrees into radians*

```
90*(pi/180)
```

```
## [1] 1.570796
```

As we can see  $90^\circ \approx 1.57$ , and  $\pi/2 \approx 1.57$

*#Converting radians into degrees*

```
pi/2*(180/pi)
```

```
## [1] 90
```

So it then follows that  $\pi/2 \text{ rad} = 90^\circ$ .

## Conclusion

Depending on the type of data we want to analyze, we use different methods. For example, if we want to predict a categorical outcome a binomial or multinomial logistic regression is preferred to using a normal linear regression. In the same vein, circular data should be analyzed using methods tailored to the unique attributes of such data. Analyzing circular data as either categorical or continuous data may lead to issues of

validity, as even something as simple as a mean value can result in very different outcomes if analyzed as continuous instead of circular, as we will see in tutorial 2.