




Name: Vanshika
SAP ID: 500069061
Roll number: R171218110

Application Containerization file

Experiment 1

CREATE VM USING VAGRANT

1. Download vagrant



2. After downloading the Vagrant, in order to verify the download, check for its version


```
Administrator: Command Prompt
Microsoft Windows [Version 10.0.18363.1139]
(c) 2019 Microsoft Corporation. All rights reserved.

C:\WINDOWS\system32>vagrant --version
Vagrant 2.2.10
```

3. Now you will need to make a new folder and run the *init* command.

```
C:\WINDOWS\system32>d:
D:\>mkdir first_vagrant
D:\>cd first_vagrant
D:\first_vagrant>vagrant init
A `Vagrantfile` has been placed in this directory. You are now
ready to `vagrant up` your first virtual environment! Please read
the comments in the Vagrantfile as well as documentation on
`vagrantup.com` for more information on using Vagrant.
```

4. open vagrantfile and do the changes in "config.vm.box = "ubuntu/trusty64"




```
# -*- mode: ruby -*-
# vi: set ft=ruby :

# All Vagrant configuration is done below. The "2" in Vagrant.configure
# configures the configuration version (we support older styles for
# backwards compatibility). Please don't change it unless you know what
# you're doing.
Vagrant.configure("2") do |config|
  # The most common configuration options are documented and commented below.
  # For a complete reference, please see the online documentation at
  # https://docs.vagrantup.com.

  # Every Vagrant development environment requires a box. You can search for
  # boxes at https://vagrantcloud.com/search.
  config.vm.box = "ubuntu/trusty64"

  # Disable automatic box update checking. If you disable this, then
  # boxes will only be checked for updates when the user runs
  # 'vagrant box outdated'. This is not recommended.
  # config.vm.box_check_update = false

  # Create a forwarded port mapping which allows access to a specific port
  # within the machine from a port on the host machine. In the example below,
  # accessing "localhost:8080" will access port 80 on the guest machine.
  # NOTE: This will enable public access to the opened port
  # config.vm.network "forwarded port", guest: 80, host: 8080
```



```
Administrator: Command Prompt
D:\first_vagrant>vagrant up
Bringing machine 'default' up with 'virtualbox' provider...
==> default: Box 'ubuntu/trusty64' could not be found. Attempting to find and install...
    default: Box Provider: virtualbox
    default: Box Version: >= 0
==> default: Loading metadata for box 'ubuntu/trusty64'
    default: URL: https://vagrantcloud.com/ubuntu/trusty64
==> default: Adding box 'ubuntu/trusty64' (v20190514.0.0) for provider: virtualbox
    default: Downloading: https://vagrantcloud.com/ubuntu/boxes/trusty64/versions/20190514.0.0/providers/virtualbox.box
Download redirected to host: cloud-images.ubuntu.com
    default:
==> default: Successfully added box 'ubuntu/trusty64' (v20190514.0.0) for 'virtualbox'!
==> default: Importing base box 'ubuntu/trusty64'...
==> default: Matching MAC address for NAT networking...
==> default: Checking if box 'ubuntu/trusty64' version '20190514.0.0' is up to date...
==> default: Setting the name of the VM: first_vagrant default_1604381956405_98417
==> default: Clearing any previously set forwarded ports...
Vagrant is currently configured to create VirtualBox synced folders with
the 'SharedFoldersEnableSymlinksCreate' option enabled. If the Vagrant
guest is not trusted, you may want to disable this option. For more
information on this option, please refer to the VirtualBox manual:

    https://www.virtualbox.org/manual/ch04.html#sharedfolders

This option can be disabled globally with an environment variable:

    VAGRANT_DISABLE_VBOXSYMLINKCREATE=1

or on a per-folder basis within the Vagrantfile:
```

5. run vagrant up command

```

==> default: Checking for guest additions in VM...
default: The guest additions on this VM do not match the installed version of
default: VirtualBox! In most cases this is fine, but in rare cases it can
default: prevent things such as shared folders from working properly. If you see
default: shared folder errors, please make sure the guest additions within the
default: virtual machine match the version of VirtualBox you have installed on
default: your host and reload your VM.
default:
default: Guest Additions Version: 4.3.40
default: VirtualBox Version: 6.1
==> default: Mounting shared folders...
default: /vagrant => D:/first_vagrant

D:\first_vagrant>vagrant SSH
Usage: vagrant [options] <command> [<args>]

-h, --help                Print this help.

```

```

D:\first_vagrant>vagrant ssh
ssh_exchange_identification: read: Connection aborted

```

6. run vagrant SSH

7. check the VM created

