

DCCN ISE 2

Group: 3


Prathamesh Bagekari - 2018130002

Akshat Bhat - 2018130003

Arka Haldi - 2018130014

TASK 1:

Network Topology



PC-A config

PC-A

Physical

Config

Desktop

Programming

Attributes

IP Configuration

InterfaceFastEthernet0

IP Configuration

DHCP

Static

IP Address192.168.1.20

Subnet Mask255.255.255.0

Default Gateway192.168.1.1

DNS Server0.0.0.0

IPv6 Configuration

DHCP

Auto Config

Static

IPv6 Address

Link Local AddressFE80::2D0:D3FF:FE82:3819

IPv6 Gateway

IPv6 DNS Server

802.1X

Use 802.1X Security

AuthenticationMD5

Username

Password

Top

PC-B config

PC-B

Physical

Config

Desktop

Programming

Attributes

IP Configuration

X

InterfaceFastEthernet0

IP Configuration

☐ DHCP

☒ Static

IP Address

192.168.1.21

Subnet Mask

255.255.255.0

Default Gateway

192.168.1.1

DNS Server

0.0.0.0

IPv6 Configuration

☐ DHCP

☐ Auto Config

☒ Static

IPv6 Address

/

Link Local Address

FE80::2E0:F7FF:FE77:EDB1

IPv6 Gateway

IPv6 DNS Server

802.1X

☐ Use 802.1X Security

Authentication

MD5

Username

Password

☐ Top

Gateway g0/0 config

Gateway

Physical Config CLI Attributes

GLOBAL

Settings

Algorithm Settings

ROUTING

Static

RIP

SWITCHING

VLAN Database

INTERFACE

GigabitEthernet0/0

GigabitEthernet0/1

Serial0/0/0

Serial0/0/1

GigabitEthernet0/1

Port Status ☒ On

Bandwidth ☐ 1000 Mbps ☒ 100 Mbps ☐ 10 Mbps ☒ Auto

Duplex ☐ Half Duplex ☒ Full Duplex ☒ Auto

MAC Address 0090.2B37.0602

IP Configuration

IP Address 192.168.1.1

Subnet Mask 255.255.255.0

Tx Ring Limit 10

Equivalent IOS Commands

Gateway(config-if) #
Gateway(config-if) #exit
Gateway(config) #interface GigabitEthernet0/0
Gateway(config-if) #
Gateway(config-if) #exit
Gateway(config) #interface GigabitEthernet0/1
Gateway(config-if) #

☐ Top

Gateway s0/0/1

Gateway

Physical Config CLI Attributes

GLOBAL

Settings

Algorithm Settings

ROUTING

Static

RIP

SWITCHING

VLAN Database

INTERFACE

GigabitEthernet0/0

GigabitEthernet0/1

Serial0/0/0

Serial0/0/1

Serial0/0/1

Port Status ☒ On

Duplex ☐ Full Duplex

Clock Rate 2000000

IP Configuration

IP Address 209.165.201.18

Subnet Mask 255.255.255.252


Tx Ring Limit 10

Equivalent IOS Commands

Gateway(config-if) #
Gateway(config-if) #exit
Gateway(config) #interface Serial0/0/0
Gateway(config-if) #
Gateway(config-if) #exit
Gateway(config) #interface Serial0/0/1
Gateway(config-if) #

☐ Top

ISP serial 0/0/0 config

 ISP

Physical

Config

CLI

Attributes

GLOBAL

Settings

Algorithm Settings

ROUTING

Static

RIP

SWITCHING

VLAN Database

INTERFACE

GigabitEthernet0/0

GigabitEthernet0/1

Serial0/0/0

Serial0/0/1

Serial0/0/0

Port Status ☒ On

Duplex ☐ Full Duplex

Clock Rate 1200

IP Configuration

IP Address 209.165.201.17

Subnet Mask 255.255.255.252


Tx Ring Limit 10

Equivalent IOS Commands

ISP(config-if)#exit
ISP(config)#interface Serial0/0/0
ISP(config-if)#ip address
% Incomplete command.
ISP(config-if)#ip address 209.165.201.17 255.255.255.0
ISP(config-if)#ip address 209.165.201.17 255.255.255.252
ISP(config-if)#

☐ Top

ISP lo0 config



The screenshot shows a window titled "ISP" with a standard Windows-style title bar (minimize, maximize, close buttons). Inside the window, there are four tabs: "Physical", "Config", "CLI", and "Attributes". The "CLI" tab is currently selected and highlighted with a blue underline. Below the tabs, the text "IOS Command Line Interface" is centered. The main area of the window is a text box containing the following text:

```
ISP(config)#
ISP(config)#
ISP(config)#
ISP(config)#
ISP(config)#
ISP(config)#
ISP(config)#
ISP(config)#
ISP(config)#
ISP(config)#
ISP(config)#
ISP(config)#
ISP(config)#
ISP(config)#
ISP(config)#
ISP(config)#
ISP(config)#
ISP(config)#
ISP(config)#
ISP(config)#
ISP(config)#
ISP(config)#
ISP(config)#int lo0
ISP(config-if)#ip add 192.31.7.1 ?
    A.B.C.D  IP subnet mask
ISP(config-if)#ip add 192.31.7.1 255.255.255.255
ISP(config-if)#
```

Below the text box, there is a hint "Ctrl+F6 to exit CLI focus" on the left, and two buttons labeled "Copy" and "Paste" on the right. At the bottom left of the window, there is a checkbox labeled "Top".

Select right clock rate for Routers

Gateway

Physical **Config** CLI Attributes

GLOBAL

Settings

Algorithm Settings

ROUTING

Static

RIP

SWITCHING

VLAN Database

INTERFACE

GigabitEthernet0/0

GigabitEthernet0/1

Serial0/0/0

Serial0/0/1

Serial0/0/1

Port Status ☒ On

Duplex ☒ Full Duplex

Clock Rate 128000

IP Configuration

IP Address 209.165.201.18

Subnet Mask 255.255.255.252

Tx Ring Limit 10

Equivalent IOS Commands

```
Gateway(config-if)#exit
Gateway(config)#interface GigabitEthernet0/1
Gateway(config-if)#
Gateway(config-if)#exit
Gateway(config)#interface Serial0/0/1
Gateway(config-if)#clock rate 128000
Gateway(config-if)#
```

☐ Top

ISP

Physical **Config** CLI Attributes

GLOBAL

Settings

Algorithm Settings

ROUTING

Static

RIP

SWITCHING

VLAN Database

INTERFACE

GigabitEthernet0/0

GigabitEthernet0/1

Serial0/0/0

Serial0/0/1

Serial0/0/0

Port Status ☒ On

Duplex ☒ Full Duplex

Clock Rate 128000

IP Configuration

IP Address 209.165.201.17

Subnet Mask 255.255.255.252


Tx Ring Limit 10

Equivalent IOS Commands


```
ISP(config)#interface Serial0/0/1
ISP(config-if)#
ISP(config-if)#exit
ISP(config)#interface Serial0/0/0
ISP(config-if)#clock rate 128000
This command applies only to DCE interfaces
ISP(config-if)#
```

☐ Top


Gateway config





ISP config






Http error


















Routing Table for Gateway					
Type	Network	Port	Next Hop IP	Metric	
S	0.0.0.0/0	---	209.165.201.17	1/0	
C	192.168.1.0/24	GigabitEthernet0/1	---	0/0	
L	192.168.1.1/32	GigabitEthernet0/1	---	0/0	
C	209.165.201.16/30	Serial0/0/1	---	0/0	
L	209.165.201.18/32	Serial0/0/1	---	0/0	

Routing Table for ISP



Type	Network	Port	Next Hop IP	Metric
C	192.31.7.1/32	Loopback0	---	0/0
S	209.165.200.224/27	---	209.165.201.18	1/0
C	209.165.201.16/30	Serial0/0/0	---	0/0
L	209.165.201.17/32	Serial0/0/0	---	0/0

TASK 2:





Physical

Config

CLI

Attributes

IOS Command Line Interface


```
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#int g0/1
Gateway(config-if)#ip nat inside
Gateway(config-if)#int s0/0/1
Gateway(config-if)#ip nat outside
Gateway(config-if)#ex
Gateway(config)#
```

Ctrl+F6 to exit CLI focus

Copy

Paste

[Top](#)



Q.What is the translation of the Inside local host address?

192.168.1.20 = **209.165.200.225**


Q.The Inside global address is assigned by?

ISP(static) and NAT pool(dynamic)

Q.The Inside local address is assigned by?

System Administrator

Pinging Lo0 interface



The screenshot shows a Packet Tracer configuration window for PC-A. The 'Desktop' tab is selected, displaying a Command Prompt window. The Command Prompt shows the execution of the 'ping 192.31.7.1' command, resulting in four successful replies with 0% loss. The window title is 'PC-A' and it includes tabs for Physical, Config, Desktop, Programming, and Attributes. A 'Top' button is located at the bottom left of the configuration window.

```
PC-A
Physical Config Desktop Programming Attributes
Command Prompt
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>ping 192.31.7.1


Pinging 192.31.7.1 with 32 bytes of data:

Reply from 192.31.7.1: bytes=32 time=2ms TTL=254
Reply from 192.31.7.1: bytes=32 time=1ms TTL=254
Reply from 192.31.7.1: bytes=32 time=1ms TTL=254
Reply from 192.31.7.1: bytes=32 time=1ms TTL=254

Ping statistics for 192.31.7.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 2ms, Average = 1ms

C:\>
```


☐ Top



What port number was used in this ICMP exchange?

4 port nos. were used for 4 ICMP exchanges for 4 pings. They are 13, 14, 15, 16.






What was the protocol used in this translation? **TCP**

What are the port numbers used?

Inside global / local: **1025**

Outside global / local: **23**



Gateway

Physical

Config

CLI

Attributes

IOS Command Line Interface

Gateway#

Gateway#

Gateway#

Gateway#

Gateway#

Gateway#

Gateway#

Gateway#

Gateway#

Gateway#

Gateway#

Gateway#

Gateway#

Gateway#

Gateway#

Gateway#sh ip nat trans

Pro Inside global Inside local Outside local Outside global

icmp 209.165.200.225:1 192.168.1.20:1 209.165.201.17:1 209.165.201.17:1

icmp 209.165.200.225:2 192.168.1.20:2 209.165.201.17:2 209.165.201.17:2

icmp 209.165.200.225:3 192.168.1.20:3 209.165.201.17:3 209.165.201.17:3

icmp 209.165.200.225:4 192.168.1.20:4 209.165.201.17:4 209.165.201.17:4

icmp 209.165.200.225:5 192.168.1.20:5 209.165.201.17:5 209.165.201.17:5

--- 209.165.200.225 192.168.1.20 ---

tcp 209.165.200.225:1025 192.168.1.20:1025 192.31.7.1:23 192.31.7.1:23


Gateway#

Ctrl+F6 to exit CLI focus

Copy


Paste

☐ Top




TASK 3:

Clearing translations and statistics



Assign access-list 1 to range 192.168.1.0 - 192.168.1.255



Show nat statistics

Gateway

Physical Config CLI Attributes

IOS Command Line Interface

```
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#show ip net stats
^
% Invalid input detected at '^' marker.

Gateway(config)#ex
Gateway#
%SYS-5-CONFIG_I: Configured from console by console


Gateway#sh ip nat stat
Total translations: 1 (1 static, 0 dynamic, 0 extended)
Outside Interfaces: Serial0/0/1
Inside Interfaces: GigabitEthernet0/1
Hits: 69 Misses: 14
Expired translations: 13
Dynamic mappings:
Gateway#
```

Ctrl+F6 to exit CLI focus

CopyPaste

☐ Top

Make nat public pool 209.165.200.242 - 209.165.200.254 netmask 255.255.255.224

 Gateway

Physical

Config

CLI

Attributes

IOS Command Line Interface

```
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#ip nat pool public_access 209.165.200.242 209.165.200.254
netmask 255.255.255.224
^
% Invalid input detected at '^' marker.

Gateway#config t
Enter configuration commands, one per line. End with CNTL/Z.
Gateway(config)#ip nat pool public_access 209.165.200.242
209.165.200.254 netmask 255.255.255.224
Gateway(config)#
```


Ctrl+F6 to exit CLI focus

Copy

Paste

☐ Top

Link inside source-list to the outer pool



The screenshot shows a window titled "Gateway" with a tabbed interface. The "CLI" tab is selected, displaying the "IOS Command Line Interface". The interface shows a series of "Gateway(config)#" prompts, followed by the command "ip nat inside source list 1 pool public_access". Below the CLI window, there is a "Ctrl+F6 to exit CLI focus" instruction and "Copy" and "Paste" buttons. At the bottom left, there is a "Top" button.

Gateway

Physical Config **CLI** Attributes

IOS Command Line Interface


```
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#
Gateway(config)#ip nat inside source list 1 pool public_access
Gateway(config)#
```

Ctrl+F6 to exit CLI focus

Copy Paste

☐ Top

Ping Loopback0 from PC-B



The screenshot shows a Packet Tracer configuration window for a PC named 'PC-B'. The 'Desktop' tab is selected, displaying a 'Command Prompt' window. The command prompt shows a series of 'C:\>' prompts, followed by the command 'ping 192.31.7.1'. The output indicates a successful ping with 4 replies, each 32 bytes, with times ranging from 1ms to 7ms and a TTL of 254. The ping statistics show 4 packets sent, 4 received, and 0% loss.

```
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>ping 192.31.7.1

Pinging 192.31.7.1 with 32 bytes of data:


Reply from 192.31.7.1: bytes=32 time=7ms TTL=254
Reply from 192.31.7.1: bytes=32 time=1ms TTL=254
Reply from 192.31.7.1: bytes=32 time=2ms TTL=254
Reply from 192.31.7.1: bytes=32 time=6ms TTL=254

Ping statistics for 192.31.7.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 7ms, Average = 4ms

C:\>
```

☐ Top

Show NAT translation table



The screenshot shows a window titled "Gateway" with tabs for Physical, Config, CLI (selected), and Attributes. The CLI tab displays the "IOS Command Line Interface" with a text area containing the following text:

```
User Access Verification
Password:
Gateway>
Gateway>en
Password:
Gateway#sh ip nat trans
Pro  Inside global      Inside local      Outside local      Outside global
icmp 209.165.200.242:13 192.168.1.21:13   192.31.7.1:13      192.31.7.1:13
icmp 209.165.200.242:14 192.168.1.21:14   192.31.7.1:14      192.31.7.1:14
icmp 209.165.200.242:15 192.168.1.21:15   192.31.7.1:15      192.31.7.1:15
icmp 209.165.200.242:16 192.168.1.21:16   192.31.7.1:16      192.31.7.1:16
--- 209.165.200.225    192.168.1.20      ---                ---
Gateway#
```

Below the text area, there is a status bar with "Ctrl+F6 to exit CLI focus" and two buttons: "Copy" and "Paste". At the bottom left, there is a checkbox labeled "Top".


What is the translation of the Inside local host address for PC-B?

192.168.1.21 = **209.165.200.242**

A dynamic NAT entry was added to the table with ICMP as the protocol when PC-B sent an ICMP message to 192.31.7.1 on ISP. What port number was used in this ICMP exchange?

4 port nos. were used for 4 ICMP exchanges for 4 pings. They are 13, 14, 15, 16.

Removing static NAT from part 2

 Gateway

Physical

Config

CLI

Attributes

IOS Command Line Interface

```
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#config t
Enter configuration commands, one per line.  End with CNTL/Z.
Gateway(config)#no ip nat inside source static 192.168.1.20 209.165.200.225
Gateway(config)#
```


Ctrl+F6 to exit CLI focus

Copy

Paste

☐ Top

Clear NAT and STAT



The screenshot shows a window titled "Gateway" with a tabbed interface. The "CLI" tab is selected, displaying the "IOS Command Line Interface". The terminal shows a series of "Gateway#" prompts. The command "clear ip nat stat" is entered, followed by an invalid input marker (^) and an error message: "% Invalid input detected at '^' marker." The command "clear ip nat trans *" is then entered, followed by another "Gateway#" prompt. Below the terminal, there is a "Ctrl+F6 to exit CLI focus" message and "Copy" and "Paste" buttons. At the bottom left, there is a "Top" link.


Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#
Gateway#clear ip nat stat
^
% Invalid input detected at '^' marker.
Gateway#clear ip nat trans *
Gateway#

Ctrl+F6 to exit CLI focus

Copy Paste

[Top](#)

Ping ISP from both PC's



PC-A

Physical Config **Desktop** Programming Attributes

Command Prompt

```
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>
C:\>telnet 192.31.7.1
Trying 192.31.7.1 ...Open

User Access Verification

Password:
ISP>en
Password:
ISP#

[Connection to 192.31.7.1 closed by foreign host]
C:\>ping 192.31.7.1


Pinging 192.31.7.1 with 32 bytes of data:

Reply from 192.31.7.1: bytes=32 time=1ms TTL=254
Reply from 192.31.7.1: bytes=32 time=1ms TTL=254
Reply from 192.31.7.1: bytes=32 time=23ms TTL=254
Reply from 192.31.7.1: bytes=32 time=1ms TTL=254

Ping statistics for 192.31.7.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 23ms, Average = 6ms

C:\>
```

☐ Top



PC-B

Physical Config **Desktop** Programming Attributes

Command Prompt

```
Reply from 192.31.7.1: bytes=32 time=1ms TTL=254

Ping statistics for 192.31.7.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 7ms, Average = 4ms

C:\>ping 192.31.7.1

Pinging 192.31.7.1 with 32 bytes of data:

Reply from 192.31.7.1: bytes=32 time=1ms TTL=254
Reply from 192.31.7.1: bytes=32 time=1ms TTL=254
Reply from 192.31.7.1: bytes=32 time=1ms TTL=254
Reply from 192.31.7.1: bytes=32 time=1ms TTL=254

Ping statistics for 192.31.7.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 1ms, Average = 1ms

C:\>ping 192.31.7.1

Pinging 192.31.7.1 with 32 bytes of data:


Reply from 192.31.7.1: bytes=32 time=2ms TTL=254
Reply from 192.31.7.1: bytes=32 time=1ms TTL=254
Reply from 192.31.7.1: bytes=32 time=1ms TTL=254
Reply from 192.31.7.1: bytes=32 time=1ms TTL=254

Ping statistics for 192.31.7.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 2ms, Average = 1ms

C:\>
```

☐ Top

Show NAT statistics

 Gateway

Physical Config CLI Attributes

IOS Command Line Interface

```
User Access Verification

Password:

Gateway>en
Password:
Gateway#sh ip nat stat
Total translations: 8 (0 static, 8 dynamic, 8 extended)
Outside Interfaces: Serial0/0/1
Inside Interfaces: GigabitEthernet0/1
Hits: 93 Misses: 38
Expired translations: 29
Dynamic mappings:
-- Inside Source
access-list 1 pool public_access refCount 8
  pool public_access: netmask 255.255.255.224
    start 209.165.200.242 end 209.165.200.254
    type generic, total addresses 13 , allocated 2 (15%), misses 0
Gateway#
```

Ctrl+F6 to exit CLI focus

Copy Paste

☐ Top

Show nat translations

Gateway

Physical Config CLI Attributes

IOS Command Line Interface

User Access Verification

Password:

Gateway>n

Translating "n"

% Unknown command or computer name, or unable to find computer address

Gateway>en

Password:

Gateway#sh ip nat trans

Gateway#

Gateway#sh ip nat trans

Pro	Inside global	Inside local	Outside local	Outside global
icmp	209.165.200.243:25	192.168.1.20:25	192.31.7.1:25	192.31.7.1:25
icmp	209.165.200.243:26	192.168.1.20:26	192.31.7.1:26	192.31.7.1:26
icmp	209.165.200.243:27	192.168.1.20:27	192.31.7.1:27	192.31.7.1:27
icmp	209.165.200.243:28	192.168.1.20:28	192.31.7.1:28	192.31.7.1:28
icmp	209.165.200.244:25	192.168.1.21:25	192.31.7.1:25	192.31.7.1:25
icmp	209.165.200.244:26	192.168.1.21:26	192.31.7.1:26	192.31.7.1:26
icmp	209.165.200.244:27	192.168.1.21:27	192.31.7.1:27	192.31.7.1:27
icmp	209.165.200.244:28	192.168.1.21:28	192.31.7.1:28	192.31.7.1:28

Gateway#

Ctrl+F6 to exit CLI focus

Copy Paste

☐ Top