WisNodeV1.2-LoRa-Arduino Library Use Guide V1.1

Shenzhen Rakwireless Technology Co., Ltd.
www.rakwireless.com
info@rakwireless.com

CONTENTS

1. RAK811 Arduino Library Use Guide

(1) Download

We upload the RAK811 Arduino library code to the official github. You can find this library at github:https://github.com/RAKWireless/WisNode-Arduino-Library



Download the library folder "Arduino-RAK811-Library".

(2) Add to Arduino IDE

①Copy the "Arduino-RAK811-Library" folder to the Arduino library folder.



②And then open the Arduino IDE, you can see the RAK811 sample code in the Arduino example.



(3)Code introduction

On the library contains the available functions, the user can refer to [WisNode_Arduino_Library API Manual V1.1.pdf](), which has a detailed note on the use of each function.

Note:Before compile by Arduino IDE,user should better configure Serial RX and TX buffer size.This must be configured manually in Arduino installation directory.
The following are the minimum recommended sizes.


C:\Program Files (x86)\Arduino\hardware\arduino\avr\cores\arduino
名称 修改日期 类型 大小
abi.cpp 2017/12/11 16:14 C++ Source File 2 KB
Arduino.h 2019/5/16 20:52 H 文件 8 KB
binary.h 2019/5/16 20:52 H 文件 11 KB
CDC.cpp 2019/5/16 20:52 C++ Source File 9 KB
Client.h 2019/5/16 20:52 H 文件 2 KB
HardwareSerial.cpp 2019/5/16 20:52 C++ Source File 9 KB
HardwareSerial.h 2020/1/16 14:48 H 文件 6 KB
HardwareSerial_private.h 2019/5/16 20:52 H 文件 5 KB
HardwareSerial0.cpp 2019/5/16 20:52 C++ Source File 3 KB
HardwareSerial1.cpp 2019/5/16 20:52 C++ Source File 3 KB
HardwareSerial2.cpp 2019/5/16 20:52 C++ Source File 2 KB
HardwareSerial3.cpp 2019/5/16 20:52 C++ Source File 2 KB
hooks.c 2017/11/27 19:21 C 文件 2 KB
IPAddress.cpp 2019/5/16 20:52 C++ Source File 3 KB
IPAddress.h 2019/5/16 20:52 H 文件 3 KB
main.cpp 2019/5/16 20:52 C++ Source File 2 KB
new.cpp 2017/12/11 16:14 C++ Source File 2 KB
new.h 2017/12/11 16:14 H 文件 1 KB
PluggableUSB.cpp 2019/5/16 20:52 C++ Source File 3 KB
PluggableUSB.h 2019/5/16 20:52 H 文件 3 KB
Print.cpp 2019/5/16 20:52 C++ Source File 6 KB
Print.h 2019/5/16 20:52 H 文件 3 KB
Printable.h 2019/5/16 20:52 H 文件 2 KB
Server.h 2019/5/16 20:52 H 文件 1 KB
Stream.cpp 2019/5/16 20:52 C++ Source File 9 KB
Stream.h 2019/5/16 20:52 H 文件 6 KB
Tone.cpp 2019/5/16 20:52 C++ Source File 15 KB
Udp.h 2019/5/16 20:52 H 文件 5 KB
USBAPI.h 2019/5/16 20:52 H 文件 7 KB
USBCore.cpp 2019/5/16 20:52 C++ Source File 20 KB
USBCore.h 2019/5/16 20:52 H 文件 9 KB
USBDesc.h 2019/5/16 20:52 H 文件 2 KB
WCharacter.h 2019/5/16 20:52 H 文件 5 KB
WInterrupts.c 2019/5/16 20:52 C 文件 10 KB
wiring.c 2018/10/29 15:58 C 文件 12 KB
wiring_analog.c 2017/12/18 15:53 C 文件 8 KB
wiring_digital.c 2019/5/16 20:52 C 文件 5 KB


C:\Program Files (x86)\Arduino\hardware\arduino\avr\cores\arduino\HardwareSerial.h - Notepad++ [Administrator]
文件(F) 编辑(E) 搜索(S) 视图(V) 编码(N) 语言(L) 设置(T) 工具(O) 宏(M) 运行(R) 插件(P) 窗口(W) ?
HardwareSerial.h
#include "Stream.h"
// Define constants and variables for buffering incoming serial data. We're
// using a ring buffer (I think), in which head is the index of the location
// to which to write the next incoming character and tail is the index of the
// location from which to read.
// NOTE: a "power of 2" buffer size is reccomended to dramatically
// optimize all the modulo operations for ring buffers.
// WARNING: When buffer sizes are increased to > 256, the buffer index
// variables are automatically increased in size, but the extra
// atomicity guards needed for that are not implemented. This will
// often work, but occasionally a race condition can occur that makes
// Serial behave erratically. See https://github.com/arduino/Arduino/issues/2405
#if !defined(SERIAL_TX_BUFFER_SIZE)
#if ((RAMEND - RAMSTART) < 1023)
#define SERIAL_TX_BUFFER_SIZE 16
#else
#define SERIAL_TX_BUFFER_SIZE 70
#endif
#endif
#if !defined(SERIAL_RX_BUFFER_SIZE)
#if ((RAMEND - RAMSTART) < 1023)
#define SERIAL_RX_BUFFER_SIZE 16
#else
#define SERIAL_RX_BUFFER_SIZE 110
#endif
#endif
#if (SERIAL_TX_BUFFER_SIZE>256)
typedef uint16_t tx_buffer_index_t;
#else
typedef uint8_t tx_buffer_index_t;
#endif
#if (SERIAL_RX_BUFFER_SIZE>256)
typedef uint16_t rx_buffer_index_t;
#else
typedef uint8_t rx_buffer_index_t;
#endif
If the RAM size of Arduino board is enough big,these two buffer size need config better bigger.

2. Hardware connect

This document will use **Arduino Uno + WisNode-LoRa** as an example.






Join NetWorkABP demo
58@qq.com. QQ群：52502449(最新版本)
联系作者 ▲PCB打样降至每款5元顺丰包邮可选杂色！【嘉立创官网】
[16:42:30.719]收←◆Start send data...Firmware Version: RUI v3.0.0.13.L.TO
OK
Start init RAK811 parameters...
[16:42:35.195]收←◆Current work region: CN470
[16:42:44.206]收←◆RAK811 init OK!
Start to join LoRaWAN...
[16:42:46.418]收←◆Join LoRaWAN success
[16:42:48.650]收←◆Start send data...
[16:42:53.799]收←◆[LoRa]: RUI_MCPS_UNCONFIRMED send success
OK
Go to Sleep.
[16:43:04.259]收←◆Start send data...
[16:43:09.408]收←◆[LoRa]: RUI_MCPS_UNCONFIRMED send success
OK
Go to Sleep.
[16:43:19.872]收←◆Start send data...
[16:43:25.021]收←◆[LoRa]: RUI_MCPS_UNCONFIRMED send success
OK
print log by Arduino USB
清除窗口
打开文件
发送文件
停止
清发送区
最前
English
保存参数
扩展
端口号
COM8 Arduino Uno
HEX显示
保存数据
接收数据到文件
HEX发送
定时发送:
80
ms/次
加回车换行
关闭串口
更多串口设置
加时间戳和分包显示,
超时时间:
20
ms
第
1
字节
至
末尾
加校验
None
RTS
DTR
波特率:
115200
at+run
为了更好地发展SSCOM软件
请您注册嘉立创P结尾客户
发 送
【升级到SSCOM5.13.1】★嘉立创PCB打样SMT贴片服务. ★RT-Thread中国人的开源免费操作系统 ★8KM远距离WiFi可自组网 ★新一代WiFi芯片兼容
www.daxia.com
S:0
R:1287
COM8 已打开 115200bps,8,1,None,None

3. Flash firmware

①Flash firmware for RAK811 refer to :Get_Start_with_RAK811_WisNode-LoRa.pdf

RAK811-Firmware:https://github.com/RAKWireless/WisNode-Arduino-Library/tree/master/Documents%20and%20tools/RAK811-Firmware

②Complie and Flash app demo JoinNetworkOTAA.ino through Arduino IDE.



4. Test LoRa Node with LoRaWAN

Serial console log:

TTN log:



If you have any questions, welcome to our forum to ask your question:

http://support.rakwireless.com/.

You can also send your question to this email: ken.yu@rakwireless.com