

# Machine Learning

A. G. Schwing & M. Telgarsky

University of Illinois at Urbana-Champaign, 2018

## L11: Structured Prediction (exhaustive search, dynamic programming)

## **Goals of this lecture**

## **Goals of this lecture**

- Getting to know structured prediction

## **Goals of this lecture**

- Getting to know structured prediction
- Understanding basic structured inference algorithms

## **Goals of this lecture**

- Getting to know structured prediction
- Understanding basic structured inference algorithms

## **Reading material:**

## Goals of this lecture

- Getting to know structured prediction
- Understanding basic structured inference algorithms

## Reading material:

- D. Koller and N. Friedman; Probabilistic Graphical Models: Principles and Techniques;

**Recap:** General framework for learning:

$$\min_{\mathbf{w}} \frac{C}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in \mathcal{D}} \epsilon \ln \sum_{\hat{y}} \exp \frac{L(y^{(i)}, \hat{y}) + F(\mathbf{w}, x^{(i)}, \hat{y})}{\epsilon} - F(\mathbf{w}, x^{(i)}, y^{(i)})$$



**Recap:** General framework for learning:

$$\min_{\mathbf{w}} \frac{C}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in \mathcal{D}} \epsilon \ln \sum_{\hat{y}} \exp \frac{L(y^{(i)}, \hat{y}) + F(\mathbf{w}, x^{(i)}, \hat{y})}{\epsilon} - F(\mathbf{w}, x^{(i)}, y^{(i)})$$

**Attention:**

**Recap:** General framework for learning:

$$\min_{\mathbf{w}} \frac{C}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in \mathcal{D}} \epsilon \ln \sum_{\hat{y}} \exp \frac{L(y^{(i)}, \hat{y}) + F(\mathbf{w}, x^{(i)}, \hat{y})}{\epsilon} - F(\mathbf{w}, x^{(i)}, y^{(i)})$$

**Attention:**

- Scoring function

**Recap:** General framework for learning:

$$\min_{\mathbf{w}} \frac{C}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in \mathcal{D}} \epsilon \ln \sum_{\hat{y}} \exp \frac{L(y^{(i)}, \hat{y}) + F(\mathbf{w}, x^{(i)}, \hat{y})}{\epsilon} - F(\mathbf{w}, x^{(i)}, y^{(i)})$$

**Attention:**

- Scoring function  $F(\mathbf{w}, x^{(i)}, y^{(i)})$

**Recap:** General framework for learning:

$$\min_{\mathbf{w}} \frac{C}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in \mathcal{D}} \epsilon \ln \sum_{\hat{y}} \exp \frac{L(y^{(i)}, \hat{y}) + F(\mathbf{w}, x^{(i)}, \hat{y})}{\epsilon} - F(\mathbf{w}, x^{(i)}, y^{(i)})$$

**Attention:**

- Scoring function  $F(\mathbf{w}, x^{(i)}, y^{(i)})$
- Loss function

**Recap:** General framework for learning:

$$\min_{\mathbf{w}} \frac{C}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in \mathcal{D}} \epsilon \ln \sum_{\hat{y}} \exp \frac{L(y^{(i)}, \hat{y}) + F(\mathbf{w}, x^{(i)}, \hat{y})}{\epsilon} - F(\mathbf{w}, x^{(i)}, y^{(i)})$$

**Attention:**

- Scoring function  $F(\mathbf{w}, x^{(i)}, y^{(i)})$
- Loss function (log-loss, hinge-loss)

**Recap:** General framework for learning:

$$\min_{\mathbf{w}} \frac{C}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in \mathcal{D}} \epsilon \ln \sum_{\hat{y}} \exp \frac{L(y^{(i)}, \hat{y}) + F(\mathbf{w}, x^{(i)}, \hat{y})}{\epsilon} - F(\mathbf{w}, x^{(i)}, y^{(i)})$$

**Attention:**

- Scoring function  $F(\mathbf{w}, x^{(i)}, y^{(i)})$
- Loss function (log-loss, hinge-loss)
- Taskloss  $L$

## **Recap:** General framework for learning:

$$\min_{\mathbf{w}} \frac{C}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in \mathcal{D}} \epsilon \ln \sum_{\hat{y}} \exp \frac{L(y^{(i)}, \hat{y}) + F(\mathbf{w}, x^{(i)}, \hat{y})}{\epsilon} - F(\mathbf{w}, x^{(i)}, y^{(i)})$$

## **Attention:**

- Scoring function  $F(\mathbf{w}, x^{(i)}, y^{(i)})$
- Loss function (log-loss, hinge-loss)
- Taskloss  $L$

How to get to

- Logistic regression

## **Recap:** General framework for learning:

$$\min_{\mathbf{w}} \frac{C}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in \mathcal{D}} \epsilon \ln \sum_{\hat{y}} \exp \frac{L(y^{(i)}, \hat{y}) + F(\mathbf{w}, x^{(i)}, \hat{y})}{\epsilon} - F(\mathbf{w}, x^{(i)}, y^{(i)})$$

## **Attention:**

- Scoring function  $F(\mathbf{w}, x^{(i)}, y^{(i)})$
- Loss function (log-loss, hinge-loss)
- Taskloss  $L$

How to get to

- Logistic regression
- Binary SVM



**Recap:** General framework for learning:

$$\min_{\mathbf{w}} \frac{C}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in \mathcal{D}} \epsilon \ln \sum_{\hat{y}} \exp \frac{L(y^{(i)}, \hat{y}) + F(\mathbf{w}, x^{(i)}, \hat{y})}{\epsilon} - F(\mathbf{w}, x^{(i)}, y^{(i)})$$

**Attention:**

- Scoring function  $F(\mathbf{w}, x^{(i)}, y^{(i)})$
- Loss function (log-loss, hinge-loss)
- Taskloss  $L$

How to get to

- Logistic regression
- Binary SVM
- Multiclass regression

## **Recap:** General framework for learning:

$$\min_{\mathbf{w}} \frac{C}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in \mathcal{D}} \epsilon \ln \sum_{\hat{y}} \exp \frac{L(y^{(i)}, \hat{y}) + F(\mathbf{w}, x^{(i)}, \hat{y})}{\epsilon} - F(\mathbf{w}, x^{(i)}, y^{(i)})$$

## **Attention:**

- Scoring function  $F(\mathbf{w}, x^{(i)}, y^{(i)})$
- Loss function (log-loss, hinge-loss)
- Taskloss  $L$

How to get to

- Logistic regression
- Binary SVM
- Multiclass regression
- Multiclass SVM

**Recap:** General framework for learning:

$$\min_{\mathbf{w}} \frac{C}{2} \|\mathbf{w}\|_2^2 + \sum_{i \in \mathcal{D}} \epsilon \ln \sum_{\hat{y}} \exp \frac{L(y^{(i)}, \hat{y}) + F(\mathbf{w}, x^{(i)}, \hat{y})}{\epsilon} - F(\mathbf{w}, x^{(i)}, y^{(i)})$$

**Attention:**

- Scoring function  $F(\mathbf{w}, x^{(i)}, y^{(i)})$
- Loss function (log-loss, hinge-loss)
- Taskloss  $L$

How to get to

- Logistic regression
- Binary SVM
- Multiclass regression
- Multiclass SVM
- Deep Learning

**Recap:** Inference (how to find the highest scoring configuration):

**Recap:** Inference (how to find the highest scoring configuration):

$$y^* = \arg \max_{\hat{y}} F(\mathbf{w}, x, \hat{y})$$

**Recap:** Inference (how to find the highest scoring configuration):

$$y^* = \arg \max_{\hat{y}} F(\mathbf{w}, x, \hat{y})$$

How to solve it?

**Recap:** Inference (how to find the highest scoring configuration):

$$y^* = \arg \max_{\hat{y}} F(\mathbf{w}, x, \hat{y})$$

How to solve it?

Exhaustive search over all classes (easy for binary/few classes)

**Example:** why is structure/are correlations useful



**Example:** why is structure/are correlations useful



**Example:** why is structure/are correlations useful



V

**Example:** why is structure/are correlations useful



**Example:** why is structure/are correlations useful



|

**Example:** why is structure/are correlations useful



**Example:** why is structure/are correlations useful


**Z**

Z

**Example:** why is structure/are correlations useful



**Example:** why is structure/are correlations useful





**Example:** why is structure/are correlations useful



Q



V



I



Z



**Example:** why is structure/are correlations useful



Q



V



I



Z



Q



U





I




Z

**Example:** why is structure/are correlations useful




Correlations not taken into account

**Example:** why is structure/are correlations useful



Correlations not taken into account



Correlations taken into account

How can we take correlations into account?

How can we take correlations into account?

- Formulate it as prediction of all four letter words (multiclass prediction):

How can we take correlations into account?

- Formulate it as prediction of all four letter words (multiclass prediction):

$$y \in \mathcal{Y} = \{1, \dots, 26^4\}$$

How can we take correlations into account?

- Formulate it as prediction of all four letter words (multiclass prediction):

$$y \in \mathcal{Y} = \{1, \dots, 26^4\}$$

- Problem:



How can we take correlations into account?

- Formulate it as prediction of all four letter words (multiclass prediction):

$$y \in \mathcal{Y} = \{1, \dots, 26^4\}$$


- Problem: Really large **output space**

Example: Disparity map estimation


How big is the output space?

## Example: Disparity map estimation


How big is the output space?



Image



Independent Prediction



**Structured Prediction**

## Example: De-noising

## Example: De-noising



## Example: De-noising



Predictions from neighboring pixel are useful.

**Structured Prediction** estimates a complex object

$$x^{(i)} \rightarrow \mathbf{y}^{(i)} = (y_1^{(i)}, \dots, y_D^{(i)})$$

## Structured Prediction estimates a complex object

- Image segmentation (**estimate a labeling**)

 $x^{(i)}$  $\rightarrow$  $y^{(i)} = (y_1^{(i)}, \dots, y_D^{(i)})$ 




## Structured Prediction estimates a complex object

- Image segmentation (estimate a labeling)
- Sentence parsing (estimate a parse tree)

$$x^{(i)} \rightarrow y^{(i)} = (y_1^{(i)}, \dots, y_D^{(i)})$$

I saw the man with  
the telescope.





## Structured Prediction estimates a complex object

- Image segmentation (estimate a labeling)
- Sentence parsing (estimate a parse tree)
- Protein folding (estimate a protein structure)

$x^{(i)}$

$\rightarrow$

$y^{(i)} = (y_1^{(i)}, \dots, y_D^{(i)})$



## Structured Prediction estimates a complex object

- Image segmentation (estimate a labeling)
- Sentence parsing (estimate a parse tree)
- Protein folding (estimate a protein structure)
- Stereo vision (estimate a disparity map)

$$x^{(i)} \rightarrow y^{(i)} = (y_1^{(i)}, \dots, y_D^{(i)})$$




- “Standard” Prediction: output  $y \in \mathcal{Y}$  is a scalar number

$$\mathcal{Y} = \{1, \dots, K\} \quad \text{or} \quad \mathcal{Y} = \mathbb{R}$$

- “Standard” Prediction: output  $y \in \mathcal{Y}$  is a scalar number

$$\mathcal{Y} = \{1, \dots, K\} \quad \text{or} \quad \mathcal{Y} = \mathbb{R}$$


- “Structured” Prediction: output  $\mathbf{y}$  is a structured output:



- “Standard” Prediction: output  $y \in \mathcal{Y}$  is a scalar number

$$\mathcal{Y} = \{1, \dots, K\} \quad \text{or} \quad \mathcal{Y} = \mathbb{R}$$

- “Structured” Prediction: output  $\mathbf{y}$  is a structured output:



**We can transition between both formulations.  $K$  possibly really large.**

Formally:

$$\mathbf{y} = (y_1, \dots, y_D) \quad y_d \in \{1, \dots, K\}$$

Formally:

$$\mathbf{y} = (y_1, \dots, y_D) \quad y_d \in \{1, \dots, K\}$$

Inference/Prediction:



Formally:

$$\mathbf{y} = (y_1, \dots, y_D) \quad y_d \in \{1, \dots, K\}$$

Inference/Prediction:

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} F(\mathbf{w}, x, \hat{\mathbf{y}}) =$$

Formally:

$$\mathbf{y} = (y_1, \dots, y_D) \quad y_d \in \{1, \dots, K\}$$

Inference/Prediction:

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} F(\mathbf{w}, x, \hat{\mathbf{y}}) = \arg \max_{\hat{\mathbf{y}}} F(\mathbf{w}, x, \hat{y}_1, \dots, \hat{y}_D)$$

Formally:

$$\mathbf{y} = (y_1, \dots, y_D) \quad y_d \in \{1, \dots, K\}$$

Inference/Prediction:

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} F(\mathbf{w}, x, \hat{\mathbf{y}}) = \arg \max_{\hat{\mathbf{y}}} F(\mathbf{w}, x, \hat{y}_1, \dots, \hat{y}_D)$$

How many possibilities do we have to store and explore?

Formally:

$$\mathbf{y} = (y_1, \dots, y_D) \quad y_d \in \{1, \dots, K\}$$

Inference/Prediction:

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} F(\mathbf{w}, x, \hat{\mathbf{y}}) = \arg \max_{\hat{\mathbf{y}}} F(\mathbf{w}, x, \hat{y}_1, \dots, \hat{y}_D)$$

How many possibilities do we have to store and explore?

$$K^D$$

**That's a problem. What can we do?**

## Separate prediction:

If

$$F(\mathbf{w}, x, \hat{y}_1, \dots, \hat{y}_D) = \sum_{d=1}^D f_d(\mathbf{w}, x, \hat{y}_d)$$

$$\max_{\hat{\mathbf{y}}} F(\mathbf{w}, x, \hat{y}_1, \dots, \hat{y}_D) = \max_{\hat{\mathbf{y}}} \sum_{d=1}^D f_d(\mathbf{w}, x, \hat{y}_d) =$$

## Separate prediction:

If

$$F(\mathbf{w}, x, \hat{y}_1, \dots, \hat{y}_D) = \sum_{d=1}^D f_d(\mathbf{w}, x, \hat{y}_d)$$

$$\max_{\hat{\mathbf{y}}} F(\mathbf{w}, x, \hat{y}_1, \dots, \hat{y}_D) = \max_{\hat{\mathbf{y}}} \sum_{d=1}^D f_d(\mathbf{w}, x, \hat{y}_d) = \sum_{d=1}^D \max_{\hat{y}_d} f_d(\mathbf{w}, x, \hat{y}_d)$$

## Separate prediction:

If

$$F(\mathbf{w}, x, \hat{y}_1, \dots, \hat{y}_D) = \sum_{d=1}^D f_d(\mathbf{w}, x, \hat{y}_d)$$

$$\max_{\hat{\mathbf{y}}} F(\mathbf{w}, x, \hat{y}_1, \dots, \hat{y}_D) = \max_{\hat{\mathbf{y}}} \sum_{d=1}^D f_d(\mathbf{w}, x, \hat{y}_d) = \sum_{d=1}^D \max_{\hat{y}_d} f_d(\mathbf{w}, x, \hat{y}_d)$$

Why not predict every variable  $y_d$  from  $\mathbf{y} = (y_1, \dots, y_D)$  separately?

## Separate prediction:

If

$$F(\mathbf{w}, x, \hat{y}_1, \dots, \hat{y}_D) = \sum_{d=1}^D f_d(\mathbf{w}, x, \hat{y}_d)$$

$$\max_{\hat{\mathbf{y}}} F(\mathbf{w}, x, \hat{y}_1, \dots, \hat{y}_D) = \max_{\hat{\mathbf{y}}} \sum_{d=1}^D f_d(\mathbf{w}, x, \hat{y}_d) = \sum_{d=1}^D \max_{\hat{y}_d} f_d(\mathbf{w}, x, \hat{y}_d)$$

Why not predict every variable  $y_d$  from  $\mathbf{y} = (y_1, \dots, y_D)$  separately?

Correlations not explicitly taken into account



Score function decomposes less trivially:

$$F(\mathbf{w}, x, y_1, \dots, y_D) = \sum_{r \in \mathcal{R}} f_r(\mathbf{w}, x, \mathbf{y}_r)$$

Restriction set  $r \subseteq \{1, \dots, D\}$

Set of all restrictions:  $\mathcal{R}$

Score function decomposes less trivially:

$$F(\mathbf{w}, x, y_1, \dots, y_D) = \sum_{r \in \mathcal{R}} f_r(\mathbf{w}, x, \mathbf{y}_r)$$

Restriction set  $r \subseteq \{1, \dots, D\}$

Set of all restrictions:  $\mathcal{R}$

Example:  $r = \{1, 2\}$

$$f_{\{1,2\}}(\mathbf{y}_{\{1,2\}}) = f_{\{1,2\}}(y_1, y_2) = \left[ f_{\{1,2\}}(1, 1), f_{\{1,2\}}(1, 2), \dots \right]$$

Score function decomposes less trivially:

$$F(\mathbf{w}, x, y_1, \dots, y_D) = \sum_{r \in \mathcal{R}} f_r(\mathbf{w}, x, \mathbf{y}_r)$$

Restriction set  $r \subseteq \{1, \dots, D\}$

Set of all restrictions:  $\mathcal{R}$

Example:  $r = \{1, 2\}$

$$f_{\{1,2\}}(\mathbf{y}_{\{1,2\}}) = f_{\{1,2\}}(y_1, y_2) = [f_{\{1,2\}}(1, 1), f_{\{1,2\}}(1, 2), \dots]$$

	Q	U	I	Z	V
Q	0	0.8	0.2	0.1	0.1
U		$\ddots$	$\dots$		
I	$\vdots$				
Z					
V					



Q



U



I



Z

Example:

$$F(\mathbf{w}, x, y_1, \dots, y_4) = f_1(\mathbf{w}, x, y_1) + f_2(\mathbf{w}, x, y_2) + f_3(\mathbf{w}, x, y_3) + f_4(\mathbf{w}, x, y_4) \\ + f_{1,2}(\mathbf{w}, x, y_1, y_2) + f_{2,3}(\mathbf{w}, x, y_2, y_3) + f_{3,4}(\mathbf{w}, x, y_3, y_4)$$



Q



U



I



Z

Example:

$$F(\mathbf{w}, x, y_1, \dots, y_4) = f_1(\mathbf{w}, x, y_1) + f_2(\mathbf{w}, x, y_2) + f_3(\mathbf{w}, x, y_3) + f_4(\mathbf{w}, x, y_4) \\ + f_{1,2}(\mathbf{w}, x, y_1, y_2) + f_{2,3}(\mathbf{w}, x, y_2, y_3) + f_{3,4}(\mathbf{w}, x, y_3, y_4)$$

How many function values need to be stored if  $y_d \in \{1, \dots, 26\} \forall d$ ?



Q



U



I



Z

Example:

$$F(\mathbf{w}, x, y_1, \dots, y_4) = f_1(\mathbf{w}, x, y_1) + f_2(\mathbf{w}, x, y_2) + f_3(\mathbf{w}, x, y_3) + f_4(\mathbf{w}, x, y_4) \\ + f_{1,2}(\mathbf{w}, x, y_1, y_2) + f_{2,3}(\mathbf{w}, x, y_2, y_3) + f_{3,4}(\mathbf{w}, x, y_3, y_4)$$

How many function values need to be stored if  $y_d \in \{1, \dots, 26\} \forall d$ ?


Earlier:  $26^4$       v.s. now:       $3 \cdot 26^2 (+4 \cdot 26)$

Visualization of the decomposition:

$$F(\mathbf{w}, x, y_1, \dots, y_4) = f_1(\mathbf{w}, x, y_1) + f_2(\mathbf{w}, x, y_2) + f_3(\mathbf{w}, x, y_3) + f_4(\mathbf{w}, x, y_4) \\ + f_{1,2}(\mathbf{w}, x, y_1, y_2) + f_{2,3}(\mathbf{w}, x, y_2, y_3) + f_{3,4}(\mathbf{w}, x, y_3, y_4)$$

Visualization of the decomposition:

$$F(\mathbf{w}, x, y_1, \dots, y_4) = f_1(\mathbf{w}, x, y_1) + f_2(\mathbf{w}, x, y_2) + f_3(\mathbf{w}, x, y_3) + f_4(\mathbf{w}, x, y_4) \\ + f_{1,2}(\mathbf{w}, x, y_1, y_2) + f_{2,3}(\mathbf{w}, x, y_2, y_3) + f_{3,4}(\mathbf{w}, x, y_3, y_4)$$



Edges denote subset relationship



## Special cases

- Predicting every variable separately:

## Special cases

- Predicting every variable separately:

$$F(\mathbf{w}, x, y_1, \dots, y_D) = \sum_{d=1}^D f_d(\mathbf{w}, x, y_d)$$

## Special cases

- Predicting every variable separately:

$$F(\mathbf{w}, x, y_1, \dots, y_D) = \sum_{d=1}^D f_d(\mathbf{w}, x, y_d)$$



Markov random field with only unary variables

## Special cases

- Predicting every variable separately:

$$F(\mathbf{w}, x, y_1, \dots, y_D) = \sum_{d=1}^D f_d(\mathbf{w}, x, y_d)$$



Markov random field with only unary variables

- Multi-variate prediction:

$$F(\mathbf{w}, x, y_1, \dots, y_D) = f_{1,\dots,D}(\mathbf{w}, x, \mathbf{y}_{1,\dots,D})$$

## Special cases

- Predicting every variable separately:


$$F(\mathbf{w}, x, y_1, \dots, y_D) = \sum_{d=1}^D f_d(\mathbf{w}, x, y_d)$$




Markov random field with only unary variables

- Multi-variate prediction:

$$F(\mathbf{w}, x, y_1, \dots, y_D) = f_{1,\dots,D}(\mathbf{w}, x, \mathbf{y}_{1,\dots,D})$$



## Example: stereo vision




Markov/Conditional random field:


## Example: stereo vision




## Markov/Conditional random field:



## Example: stereo vision



Markov/Conditional random field:




$$F(\mathbf{w}, x, \mathbf{y}) = \sum_{d=1}^D f_d(\mathbf{w}, x, y_d) + \sum_{i,j} f_{i,j}(\mathbf{w}, x, y_i, y_j)$$



## Example: stereo vision




Markov/Conditional random field:




$$F(\mathbf{w}, x, \mathbf{y}) = \sum_{d=1}^D f_d(\mathbf{w}, x, y_d) + \sum_{i,j} f_{i,j}(\mathbf{w}, x, y_i, y_j)$$

## Example: stereo vision




Markov/Conditional random field:




$$F(\mathbf{w}, x, \mathbf{y}) = \sum_{d=1}^D f_d(\mathbf{w}, x, y_d) + \sum_{i,j} f_{i,j}(\mathbf{w}, x, y_i, y_j)$$

- Unary term:
- Pairwise term:

## Example: stereo vision




Markov/Conditional random field:




$$F(\mathbf{w}, x, \mathbf{y}) = \sum_{d=1}^D f_d(\mathbf{w}, x, y_d) + \sum_{i,j} f_{i,j}(\mathbf{w}, x, y_i, y_j)$$

- Unary term: image evidence
- Pairwise term:

## Example: stereo vision



Markov/Conditional random field:




$$F(\mathbf{w}, x, \mathbf{y}) = \sum_{d=1}^D f_d(\mathbf{w}, x, y_d) + \sum_{i,j} f_{i,j}(\mathbf{w}, x, y_i, y_j)$$

- Unary term: image evidence
- Pairwise term: smoothness prior

## Example: semantic segmentation



Markov/Conditional random field:




$$F(\mathbf{w}, x, \mathbf{y}) = \sum_{d=1}^D f_d(\mathbf{w}, x, y_d) + \sum_{i,j} f_{i,j}(\mathbf{w}, x, y_i, y_j)$$

## Example: semantic segmentation



Markov/Conditional random field:




$$F(\mathbf{w}, x, \mathbf{y}) = \sum_{d=1}^D f_d(\mathbf{w}, x, y_d) + \sum_{i,j} f_{i,j}(\mathbf{w}, x, y_i, y_j)$$

- Unary term:
- Pairwise term:

## Example: semantic segmentation



Markov/Conditional random field:




$$F(\mathbf{w}, x, \mathbf{y}) = \sum_{d=1}^D f_d(\mathbf{w}, x, y_d) + \sum_{i,j} f_{i,j}(\mathbf{w}, x, y_i, y_j)$$

- Unary term: image evidence
- Pairwise term:

## Example: semantic segmentation



Markov/Conditional random field:



$$F(\mathbf{w}, x, \mathbf{y}) = \sum_{d=1}^D f_d(\mathbf{w}, x, y_d) + \sum_{i,j} f_{i,j}(\mathbf{w}, x, y_i, y_j)$$

- Unary term: image evidence
- Pairwise term: smoothness prior



Inference: (how to find the highest scoring configuration)

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\mathbf{w}, x, \hat{\mathbf{y}}_r)$$

Some inference algorithms:

Inference: (how to find the highest scoring configuration)

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\mathbf{w}, x, \hat{\mathbf{y}}_r)$$

Some inference algorithms:

- Exhaustive search

Inference: (how to find the highest scoring configuration)

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\mathbf{w}, x, \hat{\mathbf{y}}_r)$$

Some inference algorithms:

- Exhaustive search
- Dynamic programming

Inference: (how to find the highest scoring configuration)

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\mathbf{w}, x, \hat{\mathbf{y}}_r)$$

Some inference algorithms:

- Exhaustive search
- Dynamic programming
- Integer linear program

Inference: (how to find the highest scoring configuration)

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\mathbf{w}, x, \hat{\mathbf{y}}_r)$$

Some inference algorithms:

- Exhaustive search
- Dynamic programming
- Integer linear program
- Linear programming relaxation

Inference: (how to find the highest scoring configuration)

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\mathbf{w}, x, \hat{\mathbf{y}}_r)$$

Some inference algorithms:

- Exhaustive search
- Dynamic programming
- Integer linear program
- Linear programming relaxation
- Message passing

Inference: (how to find the highest scoring configuration)

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\mathbf{w}, x, \hat{\mathbf{y}}_r)$$

Some inference algorithms:

- Exhaustive search
- Dynamic programming
- Integer linear program
- Linear programming relaxation
- Message passing
- Graph-cut

## Exhaustive Search

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\mathbf{w}, x, \hat{\mathbf{y}}_r)$$



## Exhaustive Search

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\mathbf{w}, x, \hat{\mathbf{y}}_r)$$

Algorithm:

- try all possible configurations  $\hat{\mathbf{y}} \in \mathcal{Y}$
- keep highest scoring element

## Exhaustive Search

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\mathbf{w}, x, \hat{\mathbf{y}}_r)$$

Algorithm:

- try all possible configurations  $\hat{\mathbf{y}} \in \mathcal{Y}$
- keep highest scoring element
  
- **Advantage:**
- **Disadvantage:**

## Exhaustive Search

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\mathbf{w}, x, \hat{\mathbf{y}}_r)$$

Algorithm:

- try all possible configurations  $\hat{\mathbf{y}} \in \mathcal{Y}$
- keep highest scoring element
  
- **Advantage:** very simple to implement
- **Disadvantage:**


## Exhaustive Search

$$\mathbf{y}^* = \arg \max_{\hat{\mathbf{y}}} \sum_r f_r(\mathbf{w}, x, \hat{\mathbf{y}}_r)$$

Algorithm:


- try all possible configurations  $\hat{\mathbf{y}} \in \mathcal{Y}$
- keep highest scoring element
  
- **Advantage:** very simple to implement
- **Disadvantage:** very slow for reasonably sized problems:  $K^D$

## Dynamic Programming




$$\max_{\hat{\mathbf{y}}} F(\mathbf{w}, x, \hat{\mathbf{y}}) = \max_{\hat{y}_1, \hat{y}_2, \hat{y}_3} (f_3(\hat{y}_3) + f_{2,3}(\hat{y}_2, \hat{y}_3) + f_2(\hat{y}_2) + f_1(\hat{y}_1) + f_{1,2}(\hat{y}_1, \hat{y}_2))$$

## Dynamic Programming




$$\begin{aligned} \max_{\hat{\mathbf{y}}} F(\mathbf{w}, \mathbf{x}, \hat{\mathbf{y}}) &= \max_{\hat{y}_1, \hat{y}_2, \hat{y}_3} (f_3(\hat{y}_3) + f_{2,3}(\hat{y}_2, \hat{y}_3) + f_2(\hat{y}_2) + f_1(\hat{y}_1) + f_{1,2}(\hat{y}_1, \hat{y}_2)) \\ &= \max_{\hat{y}_3} \left( f_3(\hat{y}_3) + \max_{\hat{y}_2} \left( f_{2,3}(\hat{y}_2, \hat{y}_3) + f_2(\hat{y}_2) + \max_{\hat{y}_1} \{ f_1(\hat{y}_1) + f_{1,2}(\hat{y}_1, \hat{y}_2) \} \right) \right) \end{aligned}$$

## Dynamic Programming



$$\begin{aligned} \max_{\hat{\mathbf{y}}} F(\mathbf{w}, x, \hat{\mathbf{y}}) &= \max_{\hat{y}_1, \hat{y}_2, \hat{y}_3} (f_3(\hat{y}_3) + f_{2,3}(\hat{y}_2, \hat{y}_3) + f_2(\hat{y}_2) + f_1(\hat{y}_1) + f_{1,2}(\hat{y}_1, \hat{y}_2)) \\ &= \max_{\hat{y}_3} \left( f_3(\hat{y}_3) + \max_{\hat{y}_2} \left( f_{2,3}(\hat{y}_2, \hat{y}_3) + f_2(\hat{y}_2) + \underbrace{\max_{\hat{y}_1} \{f_1(\hat{y}_1) + f_{1,2}(\hat{y}_1, \hat{y}_2)\}}_{\mu_{1,2 \rightarrow 2}(\hat{y}_2)} \right) \right) \end{aligned}$$


## Dynamic Programming



$$\begin{aligned}\max_{\hat{\mathbf{y}}} F(\mathbf{w}, \mathbf{x}, \hat{\mathbf{y}}) &= \max_{\hat{y}_1, \hat{y}_2, \hat{y}_3} (f_3(\hat{y}_3) + f_{2,3}(\hat{y}_2, \hat{y}_3) + f_2(\hat{y}_2) + f_1(\hat{y}_1) + f_{1,2}(\hat{y}_1, \hat{y}_2)) \\ &= \max_{\hat{y}_3} \left( f_3(\hat{y}_3) + \max_{\hat{y}_2} \left( f_{2,3}(\hat{y}_2, \hat{y}_3) + f_2(\hat{y}_2) + \underbrace{\max_{\hat{y}_1} \{f_1(\hat{y}_1) + f_{1,2}(\hat{y}_1, \hat{y}_2)\}}_{\mu_{1,2 \rightarrow 2}(\hat{y}_2)} \right) \right) \\ &= \max_{\hat{y}_3} \left( f_3(\hat{y}_3) + \max_{\hat{y}_2} (f_{2,3}(\hat{y}_2, \hat{y}_3) + f_2(\hat{y}_2) + \mu_{1,2 \rightarrow 2}(\hat{y}_2)) \right)\end{aligned}$$



## Dynamic Programming



$$\begin{aligned}\max_{\hat{\mathbf{y}}} F(\mathbf{w}, \mathbf{x}, \hat{\mathbf{y}}) &= \max_{\hat{y}_1, \hat{y}_2, \hat{y}_3} (f_3(\hat{y}_3) + f_{2,3}(\hat{y}_2, \hat{y}_3) + f_2(\hat{y}_2) + f_1(\hat{y}_1) + f_{1,2}(\hat{y}_1, \hat{y}_2)) \\ &= \max_{\hat{y}_3} \left( f_3(\hat{y}_3) + \max_{\hat{y}_2} \left( f_{2,3}(\hat{y}_2, \hat{y}_3) + f_2(\hat{y}_2) + \underbrace{\max_{\hat{y}_1} \{f_1(\hat{y}_1) + f_{1,2}(\hat{y}_1, \hat{y}_2)\}}_{\mu_{1,2 \rightarrow 2}(\hat{y}_2)} \right) \right) \\ &= \max_{\hat{y}_3} \left( f_3(\hat{y}_3) + \max_{\hat{y}_2} (f_{2,3}(\hat{y}_2, \hat{y}_3) + f_2(\hat{y}_2) + \mu_{1,2 \rightarrow 2}(\hat{y}_2)) \right)\end{aligned}$$

## **Dynamic Programming**

When is this approach suitable:

## Dynamic Programming

When is this approach suitable:

We can reorganize terms whenever the graph is a **tree**.

## **Dynamic Programming**

When is this approach suitable:

We can reorganize terms whenever the graph is a **tree**.

- **Advantage:**
- **Disadvantage:**

## Dynamic Programming

When is this approach suitable:

We can reorganize terms whenever the graph is a **tree**.

- **Advantage:** better complexity than exhaustive search:  $D \cdot K^2$  for pairwise models
- **Disadvantage:**

## Dynamic Programming

When is this approach suitable:

We can reorganize terms whenever the graph is a **tree**.

- **Advantage:** better complexity than exhaustive search:  $D \cdot K^2$  for pairwise models
- **Disadvantage:** only works for trees

## Dynamic Programming

When is this approach suitable:

We can reorganize terms whenever the graph is a **tree**.

- **Advantage:** better complexity than exhaustive search:  $D \cdot K^2$  for pairwise models
- **Disadvantage:** only works for trees

What to do for general loopy graphs?

## Dynamic Programming

When is this approach suitable:

We can reorganize terms whenever the graph is a **tree**.

- **Advantage:** better complexity than exhaustive search:  $D \cdot K^2$  for pairwise models
- **Disadvantage:** only works for trees

What to do for general loopy graphs?

- Integer Linear Programs
- Linear Programming relaxations
- Dynamic programming extensions (message passing)
- Graph cut algorithms



## **Quiz:**

## Quiz:

- Why structured output spaces?

## Quiz:

- Why structured output spaces?
- What makes computation with structured spaces hard?

## Quiz:

- Why structured output spaces?
- What makes computation with structured spaces hard?
- Inference algorithms for structured output spaces?

## **Important topics of this lecture**

- Getting to know structured prediction
- Understood some inference algorithms

## **Up next:**

- More inference algorithms for structured output spaces