

# Comparison of Intrusion Detection Systems for Use in Low-Powered Devices

Pratyay Amrit (140953430)

Under the guidance of

Ms. Ipsita Upasana,  
Assistant Professor  
Department of I & CT  
MIT, Manipal

# Contents

- Introduction
- Problem Definition
- Objective
- Scope
- Methodology
- Results
- Conclusion

# Introduction

- Security in low powered devices
- Rise of IoT and WSN
- Intrusion Detection System (IDS)

# Problem Definition

- Why IDS for low powered devices?
- Signature based IDS
- Anomaly based IDS
- Problems with low powered devices

# Objectives

- To determine useful features in classifying network data.
- To find appropriate measures to score the different models.
- To study the causes of different models performing differently
- To open scope for future studies to improve the given score.

# Scope

- Cyber Security service providers
- People working in IoT/WSN
- Further research

# Methodology: Dataset

- UNSW-NB15 (over 2.5 million records)
- 9 types of attacks:
  - Fuzzers
  - Analysis
  - Backdoor
  - DoS
  - Exploit
  - Generic
  - Reconnaissance
  - Shell Code
  - Worm

# Methodology: Dataset

- 49 features divided into 6 categories:
- Flow Features(5), Basic Features(13), Content Features(8), Time Features(10), Additional Generated Features(11), Labeled Features(2)



# Methodology: Pre-processing

- Import data (python pandas)
- Fill empty values
- Transform nominal to numeric
- Add feature names to Pandas DataFrame

# Methodology: Feature Selection

- Use ExtraTreesClassifier
- Feature Importance Scores (gini impurity)

$$I_g(p) = 1 - \sum_{i=1}^J (p_i^2)$$

# Methodology: K-Nearest Neighbors

- Popular classification algorithm.
- An object is classified as the class of the majority vote from the nearest  $k$  vectors in the feature space.

# Methodology: Naive Bayes

- Popular classification algorithm.
- Assumption that features have no correlation.

$$p(C_k|X)=p(C_k)\prod_{i=1}^n(p(x_i|C_k))$$

# Methodology: Decision Trees

- Generates tree-like model of decisions and their consequences.
- Information gain, gini impurity etc. are used to decide which feature to split at every level in the tree.

# Methodology: Random Forests

- Ensemble Method
- Many small trees formed from random samples of the dataset.
- Decision on the basis of majority vote among individual trees.

# Methodology: Extra Trees

- Ensemble Method
- Similar to Random Forests.
- Split is decided using the entire dataset, instead of a random subset.

# Methodology: Performance Parameters


- True Positive (TP): correctly classified attacks.
- True Negative (TN): correctly classified normal.
- False Positive (FP): incorrectly classified attacks.
- False Negative (FN): incorrectly classified normal.

- $$accuracy = \frac{TP + TN}{TP + TN + FP + FN}$$


- $$TS = \frac{accuracy}{t_{tf}} \quad PS = \frac{accuracy}{t_{tp}}$$




# Results: Feature Selection




# Results: Change in TTF (Table 4.1, 4.2)




# Results: Change in TTP (Table 4.1, 4.2)




# Results: Change in Accuracy (Table 4.1, 4.2)



# Results: Change in TS (Table 4.3)



# Results: Change in PS (Table 4.3)



# Conclusion

- Importance of sttl, dttl and state for IDS.
- Decision Trees

# References

- H. Debar, M. Dacier, and A. Wespi, "A revised taxonomy for intrusion-detection systems," *Annales Des Télécommunications*, vol. 55, no. 7, pp. 361–378, Jul 2000. [Online]. Available: <https://doi.org/10.1007/BF02994844>
- P. V. S. Alpao, J. R. I. Pedrasa, and R. Atienza, "Multilayer perceptron with binary weights and activations for intrusion detection of cyberphysical systems," in *TENCON 2017 - 2017 IEEE Region 10 Conference*, Nov 2017, pp. 2825–2829.
- M. Tavallaee, E. Bagheri, W. Lu, and A. A. Ghorbani, "A detailed analysis of the kdd cup 99 data set," in *2009 IEEE Symposium on Computational Intelligence for Security and Defense Applications*, July 2009, pp. 1–6
- N. Moustafa and J. Slay, "Unsw-nb15: a comprehensive data set for network intrusion detection systems (unsw-nb15 network data set)," in *2015 Military Communications and Information Systems Conference (MilCIS)*, Nov 2015, pp. 1–6.
- N. Moustafa and J. Slay, "The significant features of the unsw-nb15 and the kdd99 data sets for network intrusion detection systems," in *2015 4th International Workshop on Building Analysis Datasets and Gathering Experience Returns for Security (BADGERS)*, Nov 2015, pp. 25–31.



# References

- F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay, “Scikitlearn: Machine learning in Python,” *Journal of Machine Learning Research*, vol. 12, pp. 2825–2830, 2011.
- H. Zhang, “The optimality of naive bayes,” 01 2004.
- T. K. Ho, “Random decision forests,” in *Proceedings of 3rd International Conference on Document Analysis and Recognition*, vol. 1, Aug 1995, pp.278–282 vol.1.
- P. Geurts, D. Ernst, and L. Wehenkel, “Extremely randomized trees,” *Machine Learning*, vol. 63, no. 1, pp. 3–42, Apr 2006. [Online]. Available:<https://doi.org/10.1007/s10994-006-6226-1>