

Mathematics

Systems of equations

Alexandre Quenon

August 2, 2018

- 1 Useful packages
- 2 Functions defined by domain
- 3 Systems of equations

Packages for systems of equations

Some packages very useful for mathematics are listed here below:

- *mathtools* which is mainly an upgrade of the very well-known “amsmath” package (the backbone for mathematics with \LaTeX),
- *cases* which provides the `numcases` command to number all lines of a system of equations, and
- *systeme* which proposes tools to improve the display of the variables of the system.

Functions defined by domain

Tool: `cases` environment, `\\` before starting a new line, maximum one & per line. Must be included inside another mathematical equation environment.

For examples:

$$a = \begin{cases} x^2 + 2 & \text{if } x < 2 \\ \int x - 3 \, dx & \text{if } x \geq 2 \end{cases} \quad (1)$$

$$a = \begin{cases} x^2 + 2 & \text{if } x < 2 \\ \int x - 3 \, dx & \text{otherwise} \end{cases} \quad (2)$$

Extra: a starred version makes the right column *text-mode* instead of *math-mode*. A `dcases` variant makes the environment *displaystyle*. An `rcases` variant creates a closing bracket on the right side.

Systems of equations

One number for the whole system

Tool: cases environment (same as for defined-by-domain function).

Example:

$$\begin{cases} x + 2y - z = 1 \\ x - 3y + 2z = 4 \\ -x + y + z = 0 \end{cases} \quad (3)$$

Issues:

- 1 only one number the whole system but it would be useful to number each line of the system → see the *cases* package,
- 2 there is no alignment between the variables like it is sometimes done in algebra → see the *systeme* package.

Systems of equations

Numbering all lines of the system (1)

Tool: `numcases` environment from the `cases` package, `\|` before starting a new line, maximum one `&` per line.

Examples:

$$\left\{ \begin{array}{l} x + 2y - z = 1 \\ x - 3y + 2z = 4 \\ -x + y + z = 0 \end{array} \right. \quad \begin{array}{l} (4) \\ (5) \\ (6) \end{array}$$

$$a = \left\{ \begin{array}{ll} x^2 + 2 & \text{if } x < 2 \\ \int x - 3 \, dx & \text{otherwise} \end{array} \right. \quad \begin{array}{l} (7) \\ (8) \end{array}$$

Extra: it corresponds to `dcases*` with all lines numbered, which means that:

- it is directly in *displaystyle*,
- the right column is in *text-mode*.

Systems of equations

Numbering all lines of the system (2)

Numbering style: `subnumcases` uses the same number and adds a letter in the equation tag.

Example:

$$\begin{cases} x + 2y - z = 1 & (9a) \\ x - 3y + 2z = 4 & (9b) \\ -x + y + z = 0 & (9c) \end{cases}$$

Systems of equations

Alignment on variables

Tool: `systeme` command from the *systeme* package, commas (,) used to separate equations. Works outside any math environment as well as inside `equation`.

Example:

$$\begin{cases} x + 2y - z = 1 \\ x - 3y + 2z = 4 \\ -x + y + z = 0 \end{cases} \quad (10)$$

Issue: the numbering counter used by the `systeme` command seems to not work properly the \LaTeX 's equation internal counter. Consequently, use it inside an `equation` environment.