

Board notes

Print this and carry it. The deck records what is *projected*; this records what gets *written*, and what gets *typed*.

Three board moments. The ladder at step 6 of the master equation, which is where something disappears. The exponential at step 2 of Gillespie. And the live code, which is the board for five minutes.

Conventions. **ASK:** put it to the room before writing, and the answer to expect. **POINT:** turn and point at the board rather than the screen. **IF ASKED:** the question that always comes.

Before class, left wing: Thursday's two numbers

Leave these up from the start. The first six surfaces finish Thursday and lean on them.

$$g = \frac{nu^n}{1+u^n} = 2, \quad u = \frac{x}{K} \quad \alpha_c = \left(\frac{2}{n-2} \right)^{1/n} \frac{n}{n-2}$$

Session 11 wrote this with x , because its x was already in units of K . Today's x is a molecule count, so the u is not decoration: at a mean of 100 with $K = 100$, $u = 1$ and $g = 1.5$ at $n = 3$, where reading x literally would give 3.

Underneath, smaller: **a clock needs gain and delay.**

Right wing, minutes 25–31: the group answers

Draw a square with its diagonal. Write each group's answer **where it moves a point**: shared causes (polymerase, ribosomes, cell size, LacI) along the diagonal; private causes (which polymerase arrived, when an mRNA decayed) across it.

ASK at 31, before the sorted surface: *which of these would still be there with a perfect microscope?* All of them — but note what the plot cannot do: uncorrelated read noise in the two channels also spreads points across the diagonal and is counted as intrinsic. Nothing on this scatter separates the two, which is why the noise floor has to be measured separately (their supplement). What the main text does report is the prerequisite for the estimator at all: the two reporters gave statistically equivalent intensity distributions (p. 1184).

Centre, at 36: the ladder

The run is projected. **Draw the ladder** beside it, because it is a picture and the slide has it as symbols.

Rungs **0, 1, 2, 3, ...** stacked vertically. Between each pair, an up-arrow labelled **k** and a down-arrow labelled **γn** (with the **n** of the upper rung). Then write, at step 5:

$$J_n = k P_{n-1} - \gamma n P_n$$

At step 6, POINT at the bottom rung. Say: there is nothing below zero, so no traffic can cross the floor.

$J_0 = 0$. Steady state makes every **J** equal, so every **J** is zero. **ASK:** what does **$J_n = 0$** let you do with **P_n** ?

Solve for it from the rung below. Then climb:

$$P_1 = \frac{k}{\gamma} P_0, \quad P_2 = \frac{k}{2\gamma} P_1, \quad P_3 = \frac{k}{3\gamma} P_2 \quad \implies \quad P_n = P_0 \frac{(k/\gamma)^n}{n!}$$

Let the factorial appear on its own. **IF ASKED** why **$P_0 = e^{-k/\gamma}$** : the probabilities sum to one, and **$\sum (k/\gamma)^n / n!$** is the series for **$e^{k/\gamma}$** .

Centre, at 49: the exponential

At Gillespie step 2, write:

$$\Pr(\text{no event in } \tau) = (1 - a_0 dt)^{\tau/dt} \longrightarrow e^{-a_0 \tau}$$

ASK: who has seen this before? Radioactive decay, a Poisson process, a memoryless wait. Then invert it: **$u = e^{-a_0 \tau}$** , so **$\tau = -\ln u / a_0$** .

CHECK out loud: a bigger **a_0** gives a shorter wait. If the code divides by **a_0** where it should, that is what it does.

Live code, at 53: type this

Into a fresh notebook cell, projected. Type it, do not paste it. The room should see it built.

```

import numpy as np
rng = np.random.default_rng(0)
k, gam, T = 10.0, 1.0, 5000.0
t, n = 0.0, 0
ts, ns = [0.0], [0]
while True:
    a = np.array([k, gam * n])
    a0 = a.sum()
    tau = -np.log(rng.random()) / a0
    if t + tau > T:
        break
    t += tau
    n += 1 if rng.random() * a0 < a[0] else -1
    ts.append(t); ns.append(n)
ts, ns = np.array(ts), np.array(ns)
dt = np.diff(np.append(ts, T))          # how long each state was held
keep = ts > 10                          # drop the climb from n = 0
m = np.sum(ns[keep] * dt[keep]) / dt[keep].sum()
v = np.sum((ns[keep] - m) ** 2 * dt[keep]) / dt[keep].sum()
m, v

```

Expect both near 10 (seed 0 gives 10.03 and 9.91, in under a second). **Then run** `ns[keep].mean()` and show it comes out near 10.5 (seed 0: 10.53). **ASK:** *why too high?* A state with more molecules has a higher total rate $k + \gamma n$, so it is left sooner and logged more often per unit time. The event-weighted mean is $\langle n(k + \gamma n) \rangle / \langle k + \gamma n \rangle = 210/20 = 10.5$ exactly.

If late: skip the event-average comparison and say it in one sentence. Do not skip the time weighting.

Centre, at 58: the rule, calibrated

Write the rule before the NAR run uses it, and check it on the case already solved:

$$\sigma^2 = \frac{\text{noise in}}{2 \times \text{return rate}} \quad \text{constitutive:} \quad \frac{k + \gamma n}{2\gamma} = \frac{2k}{2\gamma} = \frac{k}{\gamma} \checkmark$$

Then underneath, for self-repression at the same mean:

$$\frac{2\gamma x}{2\gamma(1+g)} \implies \text{Fano} = \frac{1}{1+g}$$

POINT at the left wing: that g is Thursday's g .

What to cut if you are late

In this order, last first:

1. The Becskei slide's fine print. Keep the threefold — it is the chromosomal control, which is not the transient one — and drop the comparison with our 1.7-fold.

2. The event-average half of the live code.

3. Item 4 on the handout. Items 1–3 cover T31, T35 and T17 — but item 4 is the only student practice on the sum of squares before PS6, so say the identity out of the deck rather than leaving it stated and unused.

Never cut the sweep surface (PS5 Q5a–b is due Thursday), the ladder, or the NAR run (T17 is owed to PS6 and has no other demonstration).