This is a UML class diagram containing the following classes:

com.sterlite.cal.core.base.restclient.BaseRestClient
- ~ public< T > T getForObject (String uri, Map< String, String[]> parameterMap, Class< T > responseType, Map< String, String > requestHeader Parameters)
- ~ public< T > T deleteForObject (String uri, Map< String, String[]> parameterMap, Class < T > responseType, Map< String, String > requestHeaderParameters)
- # final< T > T postForObject (String uri, Object request, Class< T > responseType, Map < String, String > requestHeaderParameters)
- # final< T > T patchForObject (String uri, Object request, Class< T > responseType, Map < String, String > requestHeaderParameters)
- # final< T > T putForObject (String uri, Object request, Class< T > responseType, Map< String, String > requestHeader Parameters)
- # final< T > T deleteForObject (String uri, Object request, Class< T > responseType, Map < String, String > requestHeaderParameters)

JpaRepository< APIConfig, Long >

JpaRepository< QueryConfig, Long >

Environment

com.sterlite.cal.cache.ui.service.IUICacheService
- + String loadCacheSpecific (String type, String value)
- + IMap< Object, Object > getCache(String key)
- + Map< String, String > loadAPIConfigCache()
- + Map< String, String > loadQueryConfigByAliasCache()
- + Map< String, String > loadProductCacheFromBSS()
- + Map< String, String > loadBESystemParamConfig CacheFromBSS()
- + Map< String, String > loadDepositTypeCacheFrom BSS()
- + Map< String, String > loadProductSpecifications CacheFromBSS()
- + Map< String, String > loadCurrencyCacheFromBSS()
- + Map< String, String > loadSystemParameterCache FromBSS()
- + Map< String, String > loadCompanyCacheFromBSS()
- + Map< String, String > loadInstituteMasterCache FromBSS()
- + Map< String, String > loadPaymentModeByAliasCache FromBSS()
- + Map< String, String > loadPaymentModeCacheFrom BSS()
- + Map< String, String > loadTaxCacheFromBSS()

com.sterlite.cal.config.api.repository.APIConfigRepository

com.sterlite.cal.config.query.repository.QueryConfigRepository

com.sterlite.cal.core.base.restclient.BRMRestClient
- + Map< String, String > prePareHeaderMap (String authTypeId, Map < String, String > header)
- ~ public< T > T postForObject (String uri, Object request, Class< T > responseType, String authTypeId, Map< String, String > header)
- ~ public< T > T getForObject (String uri, Map< String, String[]> parameterMap, Class< T > responseType, String authTypeId, Map< String, String > header)
- ~ public< T > T patchForObject (String uri, Object request, Class< T > responseType, String authTypeId, Map< String, String > header)
- ~ public< T > T deleteForObject (String uri, Object request, Class< T > responseType, String authTypeId, Map< String, String > header)
- ~ public< T > T deleteForObject (String uri, Map< String, String[]> parameterMap, Class < T > responseType, String authTypeId, Map< String, String > header)
- ~ public< T > T putForObject (String uri, Object request, Class< T > responseType, String authTypeId, Map< String, String > header)
- # String getURL(String requestURI)

com.sterlite.cal.core.base.util.JsonUtils
- + String getJsonFromObject (Object data)
- ~ public< T > T getObjectFrom Json(String jsonData, Class < T > beanType)
- ~ public< T > T getObjectFrom Json(String jsonData, JavaType javaType)
- ~ public< T > T getObjectFrom Json(String jsonData, TypeReference < T > typeReference)
- ~ public< T > T convertValue (Object fromValue, TypeReference < T > typeReference)

com.sterlite.cal.cache.ui.service.impl.UICacheServiceImpl
- + static final String FINAL_RESP
- + IMap< Object, Object > getCache(String key)
- + String loadCacheSpecific (String type, String value)
- + Map< String, String > loadAPIConfigCache()
- + Map< String, String > loadQueryConfigByAliasCache()
- + Map< String, String > loadProductCacheFromBSS()
- + Map< String, String > loadBESystemParamConfig CacheFromBSS()
- + Map< String, String > loadDepositTypeCacheFrom BSS()
- + Map< String, String > loadProductSpecifications CacheFromBSS()
- + Map< String, String > loadCurrencyCacheFromBSS()
- + Map< String, String > loadTaxCacheFromBSS()
- + Map< String, String > loadSystemParameterCache FromBSS()
- + Map< String, String > loadCompanyCacheFromBSS()
- + Map< String, String > loadInstituteMasterCache FromBSS()
- + Map< String, String > loadPaymentModeByAliasCache FromBSS()
- + Map< String, String > loadPaymentModeCacheFrom BSS()

Relationships/labels:
- ~env
- ~apiConfigRepository
- ~queryConfigRepository
- ~brmRestClient
- ~jsonUtils