problem solving

problem

```
The current branch main has no upstream branch.
To push the current branch and set the remote as upstream, use
git push --set-upstream origin main
```


sloving

```
git pull --rebase origin main
```

```
User@LAPTOP-PCPDTS3V MINGW64 ~/OneDrive/桌面/1101-1A-midproj-id (main)
$ git pull --rebase origin main
From https://github.com/Arlenchunchi/midproject
 * branch            main      -> FETCH_HEAD
Successfully rebased and upda       Focus folder in explorer (ctrl + click)

User@LAPTOP-PCPDTS3V MINGW64 ~/OneDrive/桌面/1101-1A-midproj-id (main)
$ git push origin main
Enumerating objects: 100, done.
Counting objects: 100% (100/100), done.
Delta compression using up to 8 threads
Compressing objects: 100% (92/92), done.
Writing objects: 100% (99/99), 4.17 MiB | 727.00 KiB/s, done.
Total 99 (delta 14), reused 0 (delta 0), pack-reused 0
remote: Resolving deltas: 100% (14/14), done.
To https://github.com/Arlenchunchi/midproject.git
   b092de6..3efad51  main -> main

User@LAPTOP-PCPDTS3V MINGW64 ~/OneDrive/桌面/1101-1A-midproj-id (main)
$ 
```