

1. Algorithms

Name	Worst	Average	Hidden constants	In place
Insertion sort	$\Theta(n^2)$	$\Theta(n^2)$	small	yes
Merge sort	$\Theta(n * \log n)$	$\Theta(n * \log n)$	large	no
Heap sort	$O(n * \log n)$	-	small	yes
Quicksort	$\Theta(n^2)$	$\Theta(n * \log n)$ expected	small	yes
Counting sort	$\Theta(k + n)$	$\Theta(k + n)$	large	no
Radix sort	$\Theta(d * (k + n))$	$\Theta(d * (k + n))$	large	no
Bucket sort	$\Theta(n^2)$	$\Theta(n)$	large	no

Key: k - constant, d - constant

2. Sum

Name	Formula
Arithmetic	$\sum_{k=1}^n k = \frac{n(n+1)}{2}$
Arithmetic	$\sum_{k=0}^n k^2 = \frac{n(n+1)(2n+1)}{6}$
Arithmetic	$\sum_{k=0}^n k^3 = \frac{n^2(n+1)^2}{4}$
Geometric	$\sum_{k=0}^n x^k = \frac{x^{n+1}-1}{x-1}$
Geometric	$\sum_{k=0}^{\infty} x^k = \frac{1}{1-x}$, where $x < 1$
Harmonic	$\sum_{k=1}^n 1/k = \ln(n)$
Integrating	$\sum_{k=0}^{\infty} kx^k = \frac{x}{(1-x)^2}$, where $x < 1$

3. Logs

Exp	Equiv
$\log(\prod_{k=1}^n a_k)$	$\sum_{k=1}^n \log(a_k)$
$\log_b a$	$\frac{\log_c a}{\log_c b}$

4. Finance

- $C(S_t, t) = N(d_1) * S_t - N(d_2) * Ke^{-r(T-t)}$