


Web / BD

Introduction to Web Programming
2025-2026

Gérald Oster <gerald.oster@telecomnancy.eu>



Data Persistence

- Put everything in a database!



SQLite3

- SQLite3 (<https://www.sqlite.org/>):
 - « Public domain » Embedded database / SQL92 compliant (mostly)
- In a Linux (Debian/Ubuntu) machine :

```
$ sudo apt-get install sqlite3
```
- Main commands:
 - .help (your friends ;b)
 - .open (open a database file – sqlite file format)
 - .quit (exit SQLite)
 - .tables (show all tables)
 - .schema (show schema of all tables)

SQLite3

```
$ sqlite3 halloween.db
```

```
SQLite version 3.39.5 2022-10-14 20:58:05
```

```
Enter ".help" for usage hints.
```

```
sqlite> CREATE TABLE monsters(id integer, name varchar, height integer);
```

```
sqlite> .schema
```

```
CREATE TABLE monsters(id integer, name varchar, height integer);
```

```
sqlite> INSERT INTO monsters VALUES (1, 'Cthulhu', 47);
```

```
sqlite> INSERT INTO monsters VALUES (2, 'Nyarlathotep', 100);
```

```
sqlite> SELECT * FROM monsters ORDER BY height ASC;
```

```
1|Cthulhu|47
```

```
2|Nyarlathotep|100
```

```
sqlite> SELECT * FROM monsters ORDER BY height DESC;
```

```
2|Nyarlathotep|100
```

```
1|Cthulhu|47
```

Python / SQLite3

- <https://docs.python.org/3/library/sqlite3.html>

```
import sqlite3
```

```
con = sqlite3.connect('halloween.db')
```

```
cur = con.cursor()
```

```
# print(cur.execute('SELECT * FROM monsters'))
```

```
# print(cur.fetchone())
```

```
# print(cur.fetchall())
```

```
for row in cur.execute('SELECT * FROM monsters ORDER BY height DESC):
```

```
#     print(row)
```

```
    print(f'id: {row[0]}, name: {row[1]}, height: {row[2]}')
```


```
con.commit()
```

```
con.close()
```

Python / SQLite3 (cont.)

- What not to do (security issues: SQL injection):

```
monster_name = 'Cthulhu'  
cur.execute("SELECT * FROM monsters WHERE name = '%s'" % monster_name)  
# or:  
cur.execute(f"SELECT * FROM monsters WHERE name = '{monster_name}'")
```



Python / SQLite3 (cont.)

- How to do it:

either:

```
cur.execute("SELECT * FROM monsters WHERE (?)", ('Cthulhu',))
```

or:

```
cur.execute("SELECT * FROM monsters WHERE name=:mname", {"mname": 'Cthulhu'})
```



Beware! ('Cthulhu') is 'Cthulhu' so it is a string!
but you need to pass a python tuple!
('Cthulhu',) is a tuple in Python

A Simple App using Flask / SQLite3

```
from flask import Flask
from flask import g
import sqlite3
```

```
app = Flask(__name__)
```

```
DATABASE = 'halloween.db'
```

```
def get_db():
    db = getattr(g, '_database', None)
    if db is None:
        db = g._database = sqlite3.connect(DATABASE)
    return db
```

```
@app.teardown_appcontext
def close_connection(exception):
    db = getattr(g, '_database', None)
    if db is not None:
        db.close()
```


A Simple App using Flask / SQLite3 (cont.)

...

```
@app.route('/')  
def status():  
    return 'The server is running!'
```

```
@app.route('/monsters')  
def all_monsters():  
    c = get_db().cursor()  
    c.execute("select * from monsters")  
    return c.fetchall()
```

```
@app.route('/monsters/<int:monster_id>')  
def one_monster(monster_id: str):  
    c = get_db().cursor()  
    c.execute("select * from monsters where id = ?", (monster_id,))  
    return list(c.fetchone())
```

SQLAlchemy

<https://www.sqlalchemy.org/>

```
$ pip install SQLAlchemy
```

```
from sqlalchemy import create_engine, text
```

```
engine = create_engine('sqlite:///halloween.db')
```

```
# engine = create_engine('postgresql://user:password@host/database')
```

```
con = engine.connect()
```

```
rs = con.execute(text('SELECT * FROM book'))
```

```
for row in rs:  
    print(row)
```

```
con.close()
```

SQLAlchemy / PostgreSQL

OPTIONAL

```
from sqlalchemy import create_engine, text
```

```
engine = create_engine('postgresql://postgres:mysecret@localhost/postgres')  
con = engine.connect()
```

```
rs = con.execute(text('SELECT * FROM monsters'))
```

```
for row in rs:  
    print(row)
```

```
con.close()
```

SQLAlchemy (cont.)

```
from sqlalchemy import create_engine, text

engine = create_engine('sqlite:///bookstore.db')
con = engine.connect()

rs = con.execute(text('DROP TABLE IF EXISTS book'))
rs = con.execute(text('CREATE TABLE book (id INTEGER PRIMARY_KEY,
                                title VARCHAR, primary_author VARCHAR)'))

statement = text('INSERT INTO book(id, title, primary_author) VALUES
                (:id, :title, :primary_author)')
rs = con.execute(statement, {'id':1, 'title':'The Silmarillion',
                                'primary_author':'Tolkien' })

for row in con.execute(text('SELECT * FROM book')):
    print(row)
con.close()
```

Flask-SQLAlchemy

<https://flask-sqlalchemy.palletsprojects.com/en/3.1.x/>

```
from flask import Flask
from sqlalchemy import text
from flask_sqlalchemy import SQLAlchemy

app = Flask(__name__)
app.config['SQLALCHEMY_DATABASE_URI'] = 'sqlite:///tmp/halloween.db'
db = SQLAlchemy(app)

@app.route('/')
def status():
    return 'The server is running!'

@app.route('/monsters')
def all_monsters():
    c = db.session
    res = c.execute(text("select * from monsters"))
    return str(res.fetchall())
```

\$ pip install flask_sqlalchemy

PostgreSQL (using Docker ;\$)

```
$ docker pull postgres:16
```

```
$ docker network create mynetwork
```

.SERVER in a container.

```
$ docker run -p 5432:5432 --name postgres-vm --network mynetwork  
--network-alias postgres-srv -e POSTGRES_PASSWORD=mysecret -d postgres
```

```
$ docker ps
```

.CLIENT in a container.

```
$ docker inspect postgres-vm | grep 'IPAddress'
```

```
"IPAddress": "172.17.0.2",
```

```
$ docker run -it --network mynetwork --rm postgres psql -h postgres-srv -U  
postgres
```

```
Password for user postgres:
```

```
psql (13.2 (Debian 13.2-1.pgdg100+1))
```


```
Type "help" for help.
```

```
postgres=# CREATE TABLE monsters(id integer, name varchar, height integer);  
CREATE TABLE
```

```
postgres=# INSERT INTO monsters VALUES (1, 'Cthulhu', 47);
```

```
INSERT 0 1
```

Big Picture 🤔





To go further...

- Me want Cookie!