





## WAGO Installation Connectors



## WAGO 222: CLASSIC Splicing Connectors for All Conductor Types




0.08 ... 4 mm<sup>2</sup>  
0.08 ... 2.5 mm<sup>2</sup>  
400 V / 4 kV / 2  
32 A  
Surrounding air temperature:  
max. 40 °C

## WAGO 2273: COMPACT Junction Box Connectors



0.5 ... 2.5 mm<sup>2</sup>  
450 V / 4 kV / 2  
24 A  
Surrounding air temperature:  
max. 60 °C (T60)

## WAGO 773: SPECIAL Junction Box Connectors



2.5 ... 6 mm<sup>2</sup>  
400 V / 4 kV / 2  
41 A  
Surrounding air temperature:  
max. 60 °C

0.75 ... 2.5 mm<sup>2</sup>  
1.5 ... 2.5 mm<sup>2</sup>  
400 V / 4 kV / 2  
24 A  
Surrounding air temperature:  
max. 60 °C



## Vario-T-BOXX 887-912


High-quality Sortimo® plastic case containing a selection of compact connectors, including WAGO's 221 Series Splicing Connectors

## L-BOXX 887-913

Splicing connector set in new L-BOXX with WAGO 221; the robust L-BOXX is available with WAGO's COMPACT Splicing Connectors for all conductor types.




## WAGO 224: Lighting and Inline Connectors



Installation side: 1 ... 2.5 mm<sup>2</sup>  
Lighting side: 0.5 ... 2.5 mm<sup>2</sup>  
400 V / 4 kV / 2  
24 A  
Surrounding air temperature:  
max. 60 °C (gray and white)  
max. 75 °C (black)

0.5 ... 2.5 mm<sup>2</sup>  
400 V / 4 kV / 2  
24 A  
Surrounding air temperature:  
max. 60 °C

## WAGO 773: Junction Box Connectors up to 4 mm<sup>2</sup>



1.5 ... 4 mm<sup>2</sup>  
400 V / 4 kV / 2  
32 A  
Surrounding air temperature:  
max. 60 °C

## WAGO 243: MICRO Junction Box Connectors



0.6 ... 0.8 mm Ø  
100 V / 1.5 kV / 2  
6 A  
Surrounding air temperature:  
max. 60 °C

When using conductors of the same diameter, Ø 0.5 mm or Ø 1 mm are also possible!

## L-BOXX Mini 887-955

The small assortment box of proven WAGO Splicing Connectors for different conductor types and a broad range cross-sections prepare you for practically any task (e.g., maintenance, lab work and building development).



Other sets available in stores!

# WAGO 221

## COMPACT Splicing Connectors for All Conductor Types













221-613,  
6 mm² variant






221-413,  
4 mm² variant




- Continuous operating temperature: max. 105 °C
- Surrounding air temperature: max. 85 °C (T85)



Carrier			
	Description	Item No.	Pack. Unit
	Strain relief plate, for 221-500 and 221-510 carriers	222-505	50
	Mounting carrier, orange, for 2-, 3- and 5-wire connectors; 4 mm² variant	221-500	50
	Mounting carrier, orange, for 2-, 3- and 5-wire connectors; 6 mm² variant	221-510	50
	Angled DIN-rail adapter, for horizontal mounting of 221-500 carrier on DIN-35 rail	222-510	50
	Mounting carrier, blue, for 2-, 3- and 5-wire connectors, 4 mm² variant	221-500/000-0006	50
	Mounting carrier, blue, for 2-, 3- and 5-wire connectors, 6 mm² variant	221-510/000-006	50
	Mounting carrier, gray-yellow, for 2-, 3- and 5-wire connectors, 4 mm² variant	221-500/000-053	50
	Mounting carrier, gray-yellow, for 2-, 3- and 5-wire connectors, 6 mm² variant	221-510/000-053	50

4 mm² Variant			
0.14 ... 4 mm²		450 V / 4 kV / 2	
0.2 ... 4 mm²		32 A	
	Description	Item No.	Pack. Unit
	2-wire connectors	221-412	100
	3-wire connectors	221-413	50
	5-wire connectors	221-415	25

6 mm² Variant			
0.5 ... 6 mm²		450 V / 4 kV / 2	
		41 A	
	Description	Item No.	Pack. Unit
	2-wire connectors	221-612	50
	3-wire connectors	221-613	30
	5-wire connectors	221-615	15

Carrier			
	Description	Item No.	Pack. Unit
	Mounting carrier, for 2-wire connectors, for screw mounting	221-502	50
	Mounting carrier, for 3-wire connectors, for screw mounting	221-503	50
	Mounting carrier, for 5-wire connectors, for screw mounting	221-505	50



206-1441  
In-socket cable stripper; for Ø  
8 ... 13 mm



206-1442  
Universal cable stripper; for Ø  
8 ... 13 mm



206-1204  
"Variocrimp 4" crimping tool;  
for ferrules; Crimping range: 0.25  
... 4 mm²



206-1216  
"Variocrimp 16" crimping tool;  
for ferrules; Crimping range:  
6 mm², 10 mm², 16 mm²

**WAGO Kontakttechnik GmbH & Co. KG**

Postfach 2880 · 32385 Minden  
Hansastraße 27 · 32423 Minden

**info@wago.com**  
**www.wago.com**

Headquarters	+49 571/887 - 0
Sales	+49 571/887 - 44 222
Orders	+49 571/887 - 44 333
Fax	+49 571/887 - 844 169

WAGO is a registered trademark of WAGO Verwaltungsgesellschaft mbH.

"Copyright – WAGO Kontakttechnik GmbH & Co. KG – All rights reserved. The content and structure of the WAGO websites, catalogs, videos and other WAGO media are subject to copyright. Distribution or modification of the contents of these pages and videos is prohibited. Furthermore, the content may neither be copied nor made available to third parties for commercial purposes. Also subject to copyright are the images and videos that were made available to WAGO Kontakttechnik GmbH & Co. KG by third parties."