1. Description


1.1. Project

Project Name	I02_Stepper
Board Name	I02_Stepper
Generated with:	STM32CubeMX 4.22.0
Date	01/28/2018

1.2. MCU

MCU Series	STM32F0
MCU Line	STM32F0x0 Value Line
MCU name	STM32F030F4Px
MCU Package	TSSOP20
MCU Pin number	20

2. Pinout Configuration




3. Pins Configuration

Pin Number TSSOP20	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
1	BOOT0	Boot		
4	NRST	Reset		
5	VDDA	Power		
10	PA4 *	I/O	GPIO_Output	
11	PA5 *	I/O	GPIO_Output	
12	PA6 *	I/O	GPIO_Output	
13	PA7 *	I/O	GPIO_Output	
15	VSS	Power		
16	VDD	Power		
19	PA13	I/O	SYS_SWDIO	
20	PA14	I/O	SYS_SWCLK	

^{*} The pin is affected with an I/O function

4. Clock Tree Configuration



5. IPs and Middleware Configuration

5.1. SYS

mode: Debug Serial Wire Timebase Source: SysTick

^{*} User modified value

6. System Configuration

6.1. GPIO configuration

IP	Pin	Signal	GPIO mode	GPIO pull/up pull	Max	User Label
				down	Speed	
SYS	PA13	SYS_SWDIO	n/a	n/a	n/a	
	PA14	SYS_SWCLK	n/a	n/a	n/a	
GPIO	PA4	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	
	PA5	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	
	PA6	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	
	PA7	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	

6.2. DMA configuration

nothing configured in DMA service

6.3. NVIC configuration

Interrupt Table	Enable	Preenmption Priority	SubPriority
Non maskable interrupt	true	0	0
Hard fault interrupt	true	0	0
System service call via SWI instruction	true	0	0
Pendable request for system service	true	0	0
System tick timer	true 0 0		0
Flash global interrupt	unused		
RCC global interrupt	unused		

^{*} User modified value

7. Power Consumption Calculator report

7.1. Microcontroller Selection

Series	STM32F0
Line	STM32F0x0 Value Line
мси	STM32F030F4Px
Datasheet	024849_Rev2

7.2. Parameter Selection

Temperature	25
Vdd	3.6

8. Software Project

8.1. Project Settings

Name	Value
Project Name	I02_Stepper
Project Folder	C:\Users\armst\Desktop\STM32\STM32F030F4P6\GCC\I02_Stepper
Toolchain / IDE	TrueSTUDIO
Firmware Package Name and Version	STM32Cube FW_F0 V1.8.0

8.2. Code Generation Settings

Name	Value
STM32Cube Firmware Library Package	Copy only the necessary library files
Generate peripheral initialization as a pair of '.c/.h' files	No
Backup previously generated files when re-generating	No
Delete previously generated files when not re-generated	Yes
Set all free pins as analog (to optimize the power	No
consumption)	