

17CS2009 Database Systems Lab

Ex. No: 6

Date: 12/09/2019

Ex. No. 6 JOINS

Aim

A JOIN clause is used to combine rows from two or more tables, based on a related column between them.

Description

Here are the different types of the JOINS in SQL:

(INNER) JOIN: Returns records that have matching values in both tables

LEFT (OUTER) JOIN: Returns all records from the left table, and the matched records from the right table

RIGHT (OUTER) JOIN: Returns all records from the right table, and the matched records from the left table

FULL (OUTER) JOIN: Returns all records when there is a match in either left or right table.

Questions:

Note: Drop the previously created Manager table and create a new one.

Manager Table:

Ename	mname	City
Anil	Ajay	Nagpur
Shankar	Vijay	Chennai
Jaya	Kiran	Calcutta
Sunil	Jaya	Bombay
Vijay	Rakesh	Calcutta
Prakash	Shankar	Nagpur
Ajay	Sanjay	Coimbatore

1. Write a query to display the name, living city and salary of employee using natural join.

17CS2009 Database Systems Lab

```
SQL> select ename,city,salary from emp_company_cs076 natural join employee_cs076;
```

ENAME	CITY	SALARY
anil	nagpur	1500
shankar	bombay	2000
jaya	chennai	1800
sunil	bombay	1700
vijay	delhi	5000
prakash	calcutta	3000
ajay	chennai	8000

7 rows selected.

- Write a query to display the name, living city and salary of employee using cross(Cartesian) join.

```
SQL> select e.ename,e.city,ec.salary from employee_cs076 e cross join emp_company_cs076 ec;
```

ENAME	CITY	SALARY
anil	nagpur	1500
anil	nagpur	2000
anil	nagpur	1800
anil	nagpur	1700
anil	nagpur	5000
anil	nagpur	3000
anil	nagpur	8000
anil	nagpur	1000
anil	nagpur	30000
shankar	bombay	1500
shankar	bombay	2000
shankar	bombay	1800
shankar	bombay	1700
shankar	bombay	5000
shankar	bombay	3000
shankar	bombay	8000
shankar	bombay	1000
shankar	bombay	30000
jaya	chennai	1500
jaya	chennai	2000
jaya	chennai	1800
jaya	chennai	1700
jaya	chennai	5000
jaya	chennai	3000
jaya	chennai	8000
jaya	chennai	1000
jaya	chennai	30000
sunil	bombay	1500
sunil	bombay	2000
sunil	bombay	1800

- Write a SQL statement to make a cartesian product between manager name and employee name

17CS2009 Database Systems Lab

```
SQL> select e.ename,m.mname from employee_cs076 e cross join manager_cs076 m;
```

ENAME	MNAME
anil	ajay
shankar	ajay
jaya	ajay
sunil	ajay
vijay	ajay
prakash	ajay
ajay	ajay
anil	vijay
shankar	vijay
jaya	vijay
sunil	vijay

ENAME	MNAME
vijay	vijay
prakash	vijay
ajay	vijay
anil	kiran
shankar	kiran
jaya	kiran
sunil	kiran
vijay	kiran
prakash	kiran
ajay	kiran
anil	jaya

ENAME	MNAME
shankar	jaya
jaya	jaya
sunil	jaya
vijay	jaya
prakash	jaya
ajay	jaya
anil	rakesh
shankar	rakesh

4. Display the employee name, manager name and salary of the employees whose salary is greater than 3000.[using where clause]

17CS2009 Database Systems Lab

```
SQL> select m.ename,m.mname,ec.salary from manager_cs076 m cross join emp_company_cs076 ec where ec.salary>30000;
```

ENAME	MNAME	SALARY
anil	ajay	5000
shankar	vijay	5000
jaya	kiran	5000
sunil	jaya	5000
vijay	rakesh	5000
prakash	shankar	5000
ajay	sanjay	5000
anil	ajay	8000
shankar	vijay	8000
jaya	kiran	8000
sunil	jaya	8000

ENAME	MNAME	SALARY
vijay	rakesh	8000
prakash	shankar	8000
ajay	sanjay	8000
anil	ajay	30000
shankar	vijay	30000
jaya	kiran	30000
sunil	jaya	30000
vijay	rakesh	30000
prakash	shankar	30000
ajay	sanjay	30000

21 rows selected.

5. Write a SQL statement to prepare a list with employee names who live and work in the same city.

```
SQL> select distinct e.ename from employee_cs076 e inner join company_cs076 c on e.city=c.city;
```

ENAME

anil
vijay
shankar
jaya
sunil
ajay

6 rows selected.

6. Write a SQL statement to make a list with employee name who live in the city Chennai and whose salary is between 1500 and 10000.

```
SQL> select distinct e.ename from employee_cs076 e inner join emp_company_cs076 ec on ec.salary between 1500 and 10000 where e.city='chennai';
```

ENAME

jaya
ajay

7. Display the names of the employees, company name and salary of the employees who are not assigned any living city.

17CS2009 Database Systems Lab

```
SQL> select emp_company_cs076.ename,emp_company_cs076.cname,emp_company_cs076.salary from emp_company_cs076 left join employee_cs076 on emp_company_cs076.ename=employee_cs076.ename where employee_cs076.city is NULL;
```

ENAME	CNAME	SALARY
kiran	hyundai mobis	30000
amol	acc	1000

8. Display the employee name, manager name and shift of all the employees. [use left outer join]

```
SQL> select m.ename,m.mname,em.shift from manager_cs076 m left outer join emp_shift_cs076 em on m.ename=em.ename;
```

ENAME	MNAME	SH
anil	ajay	a
sunil	jaya	b
vijay	rakesh	b
prakash	shankar	c
jaya	kiran	
ajay	sanjay	
shankar	vijay	

7 rows selected.

9. Display cities of the employees in which a company is not located.[using right outer join]

```
SQL> select employee_cs076.city from company_cs076 right outer join employee_cs076 on employee_cs076.city=company_cs076.city where employee_cs076.city not in(select city from company_cs076);
```

CITY
calcutta

10. Display the employee name, manager name and shift of the employees. [using full outer join]

```
SQL> select m.ename,m.mname,em.shift from manager_cs076 m full outer join emp_shift_cs076 em on m.ename=em.ename;
```

ENAME	MNAME	SH
anil	ajay	a
shankar	vijay	
jaya	kiran	
sunil	jaya	b
vijay	rakesh	b
prakash	shankar	c
ajay	sanjay	
		e

8 rows selected.

11. Display the employee name, manager name and shift of the employees. [using natural join]

17CS2009 Database Systems Lab

```
SQL> select * from manager_cs076 m natural join emp_shift_cs076 em;
```

ENAME	MNAME	CITY	SH
anil	ajay	nagpur	a
sunil	jaya	bombay	b
vijay	rakesh	calcutta	b
prakash	shankar	nagpur	c

12. Display the employee name and cities of the employees who are assigned a manager and live in the same city as that of the manager [Use Inner Join].

```
SQL> select e.ename,e.city from employee_cs076 e inner join manager_cs076 m on e.city=m.city;
```

ENAME	CITY
anil	nagpur
ajay	chennai
jaya	chennai
prakash	calcutta
sunil	bombay
shankar	bombay
prakash	calcutta
anil	nagpur

8 rows selected.

13. Display the ascending list of customers who are either assigned a manager or not.

```
SQL> select * from manager_cs076 order by ename asc;
```

ENAME	MNAME	CITY
ajay	sanjay	coimbatore
anil	ajay	nagpur
jaya	kiran	calcutta
prakash	shankar	nagpur
shankar	vijay	chennai
sunil	jaya	bombay
vijay	rakesh	calcutta

7 rows selected.

Result:

The above queries have been executed and the results have been verified.