

HMM search using eggNOG viral data and parsing of output

LJM

2019-11-25

Contents

1	Searching with HMMs	2
2	Counting number of bins in each fOTU	3
3	Parse delimited files from hmmsearch output files	4
4	Testing new utilities	5
4.1	Utility script for parsing eggNOG output files	5
4.2	Utility script for changing delimiters	5
5	Session info	6
6	References	7

Chapter 1

Searching with HMMs

Essentially the following code will be run in a sbatch script:

```
#ml bioinfo-tools hammer/3.2.1
DATA="../analyses/HMM_scan_using_eggNOG_HMMs/eggNOG_data/HMMs/10239/"
fOTUproteoms_DIR="../analyses/fOTU_proteomes/"
HMMer_OUTPUT_DIR="../analyses/HMM_scan_using_eggNOG_HMMs/hmmsearch_out_viruses/"
TAXID_NO="10239"
read -r -a fOTUproteoms <<< $( find $fOTUproteoms_DIR -name "*.faa" -and -type f -print0 | xargs -0 echo )
echo "fOTUprot" ${#fOTUproteoms[@]}
# Take time of this run
SECONDS=0
read -r -a HMMs <<< $( find $DATA -name "*.hmm" -and -type f -print0 | xargs -0 echo )
for fOTUproteom in "${fOTUproteoms[@]}"; do
    fOTU_FILE=$(echo $(basename "$fOTUproteom"))
    fOTU=$(echo $(basename "$fOTUproteom") | awk -F "." '{print $1}')
    for HMM in "${HMMs[@]}"; do
        HMM_FILE=$(echo $(basename "$HMM"))
        HMM_VARIANT=$(echo $(basename "$HMM") | awk -F "." '{print $1}')
        hmmsearch --cpu 10 --noali --notextw -E 0.1 --domE 0.1 --incE 0.01 --incdome 0.01 "$HMM" "$fOTU_FILE"
    done
done
duration=$SECONDS
echo "$(($duration / 60)) minutes and $(($duration % 60)) seconds elapsed."
```

Chapter 2

Counting number of bins in each fOTU

```
fOTUs="../../data/fOTUs.csv"
SCRIPT="../../scripts/binCounter.awk"
OUTPUT="../../analyses/numBinsfOTU.csv"
cat $fOTUs | awk -F, -v delimiter="," -f $SCRIPT > $OUTPUT
```

Chapter 3

Parse delimited files from hmmsearch output files

```
SCRIPT="../scripts/hmmsearchOutputParser.awk"
eggNOGs="../analyses/HMM_scan_using_eggNOG_HMMs/hmmsearch_out_viruses/"
PARSED="../analyses/HMM_scan_using_eggNOG_HMMs/hmmsearch_out_parsed/"
read -r -a eggNOGarray <<< $( find $eggNOGs -name "*.out" -and -type f -print0 | xargs -0 echo )

SECONDS=0
for eggNOGfile in "${eggNOGarray[@]}; do
    FILE=$(echo $(basename "$eggNOGfile"))
    fOTU=$(echo $FILE | awk -F "-" '{print $2}' | awk -F "." '{print $1}')
    awk -v filename="$FILE" -v delimiter="\t" -v last_col=10 -f "$SCRIPT" "$eggNOGfile" > "$PARSED/$fOTU/$FILE"
done

duration=$SECONDS
echo "$(($duration / 60)) minutes and $((($duration % 60)) seconds elapsed."
```

Chapter 4

Testing new utilities

4.1 Utility script for parsing eggNOG output files

```
OUTPUT="../analyses/HMM_scan_using_eggNOG_HMMs/hmmsearch_out_viruses/"
FILE="10239-with-cogOTU_1165.out"
SCRIPT="../scripts/hmmsearchOutputParser.awk"
#pcr2grep -M -B 19 -A 11 "^      \d.+$\n(.*\n)*?~Internal pipeline statistics summary:" $OUT
SECONDS=0
#pcr2grep -M -B 19 -A 11 "^      \d.+$\n(.*\n)*?~Internal pipeline statistics summary:" $OUT
awk -v filename="$FILE" -v delimiter="\t" -v last_col=10 -f $SCRIPT "$OUTPUT"$FILE
duration=$SECONDS
echo "$(($duration / 60)) minutes and $((($duration % 60)) seconds elapsed."
```

4.2 Utility script for changing delimiters

The changing of delimiters is from space delimited to a user given delimiter

```
SCRIPT="../scripts/eggNOGdelimiter.awk"
TSV_FILE="Fuselloviridae_10474_annotations.tsv"
# A regex for the linus that should be skipped when adding delimiters in the middle
REGEXP="^#.+\"

cat $TSV_FILE | awk -v delimiter=";" -v last_col="4" -v excluded_recs="$REGEXP" -f $SCRIPT
```

Chapter 5

Session info

```
sessionInfo()
```

```
## R version 3.6.1 (2019-07-05)
## Platform: x86_64-pc-linux-gnu (64-bit)
## Running under: Debian GNU/Linux 9 (stretch)
##
## Matrix products: default
## BLAS/LAPACK: /usr/lib/libopenblas-r0.2.19.so
##
## locale:
##  [1] LC_CTYPE=C.UTF-8      LC_NUMERIC=C           LC_TIME=C.UTF-8
##  [4] LC_COLLATE=C.UTF-8    LC_MONETARY=C.UTF-8    LC_MESSAGES=C
##  [7] LC_PAPER=C.UTF-8      LC_NAME=C              LC_ADDRESS=C
## [10] LC_TELEPHONE=C        LC_MEASUREMENT=C.UTF-8 LC_IDENTIFICATION=C
##
## attached base packages:
## [1] stats      graphics  grDevices  utils      datasets  methods    base
##
## loaded via a namespace (and not attached):
##  [1] compiler_3.6.1  magrittr_1.5     bookdown_0.13    tools_3.6.1
##  [5] htmltools_0.3.6 yaml_2.2.0       Rcpp_1.0.2       stringi_1.4.3
##  [9] rmarkdown_1.15  knitr_1.24       stringr_1.4.0    xfun_0.9
## [13] digest_0.6.20   evaluate_0.14
```

Chapter 6

References