

# Spark UI, Optimizer & Internal concepts (PhysicalPlan, Jobs, Stages, Tasks)

arnaud.nauwynck@gmail.com

This document:

https://github.com/Arnaud-Nauwynck/presentations/ /pres-bigdata/12-sparkui-internals-plan-job-stage-task

### Outline


What's visible from Spark-ui

The concepts behinds Dataset/RDD execution: Job, Stage, Task


The architecture of deployment: Client, Driver, Executor

## Spark-ui

# http://localhost:4040



# spark-ui [1/6]: Jobs



1/1

1/1

15 ms

16 ms

2021/12/31 19-53-59

show at <console>:26 show at consoles:26

# Spark-ui [1/6]: Job details DAG



#### **Details for Job 4**

Status: SUCCEEDED


Submitted: 2022/01/02 18:55:23

Duration: 0,2 s

Associated SQL Query: 2 Completed Stages: 2


Event Timeline

**▼** DAG Visualization



→ Completed Stages (2)

## Spark-ui [1/6] detail Job timeline + statistics



# Spark-ui [2/6]: detail Job > Stage > Task



Storage

Environment Executors SQL

Spark shell application UI

#### **Details for Stage 12 (Attempt 0)**

**Resource Profile Id:** 0

Total Time Across All Tasks: 4 ms Locality Level Summary: Process local: 1 Input Size / Records: 450.0 B / 1

Associated Job Ids: 10

- DAG Visualization
- ▶ Show Additional Metrics
- ▶ Event Timeline

#### **Summary Metrics for 1 Completed Tasks**

Metric	Min 25th percentile		Median	75th percentile	Max
Duration	4.0 ms	4.0 ms	4.0 ms	4.0 ms	4.0 ms
GC Time	0.0 ms	0.0 ms	0.0 ms	0.0 ms	0.0 ms
Input Size / Records	450 B / 1	450 B / 1	450 B / 1	450 B / 1	450 B / 1

Showing 1 to 3 of 3 entries

#### **→ Aggregated Metrics by Executor**

#### Tasks (1)



Index 🔺	Task ID	Attempt	Status	Locality level	Executor ID	Host	Logs 🛊	Launch Time	Duration	GC Time	Input Size / Records	Errors
0	12	0	SUCCESS	PROCESS_LOCAL	driver	DESKTOP-2EGCC8R		2021-12-31 19:58:07	4.0 ms		450 B / 1	

Search:

# Spark-ui [3/6] Storage (cache, persist)



Jobs

Stages

Storage

Environment Executors

SQL

Spark shell application UI

#### **Storage**

#### **▼ RDDs**

ID	RDD Name	Storage Level	<b>Cached Partitions</b>	Fraction Cached	Size in Memory	Size on Disk
28	*(1) SerializeFromObject [staticinvoke(class org.apache.spark.unsafe.types.UTF8String, StringType, fromString, input[0, java.lang.String, true], true, false) AS value#30] +- MapPartitions org.apache.spark.sql.Dataset\$\$Lambda\$4450/17435982@68a3d4, obj#29: java.lang.String +- DeserializeToObject value#21.toString, obj#28: java.lang.String +- FileScan text [value#21] Batched: false, DataFilters: [], Format: Text, Location: InMemoryFileIndex[file:/c:/data/loremIpsum.txt], PartitionFilters: [], PushedFilters: [], ReadSchema: struct <value:string></value:string>	Disk Memory Deserialized 1x Replicated	1	100%	952.0 B	0.0 B
40	FileScan text [value#21] Batched: false, DataFilters: [], Format: Text, Location: InMemoryFileIndex[file:/c:/data/loremlpsum.txt], PartitionFilters: [], PushedFilters: [], ReadSchema: struct <value:string></value:string>	Disk Memory Deserialized 1x Replicated	1	100%	960.0 B	0.0 B

# Spark-ui [4/6] Environment: jvm+spark+hadoop+..



Jobs

Stages

Storage

Environment

Executors

SQL

Spark shell application UI

#### **Environment**

- **Runtime Information**
- Spark Properties
- Resource Profiles
- Hadoop Properties
- System Properties
- **→ Classpath Entries**

#### **▼ Spark Properties**

Name	Value
spark.app.id	local-1640975191762
spark.app.name	Spark shell
spark.app.startTime	1640975189843
spark.driver.host	DESKTOP-2EGCC8R
spark.driver.port	57122
spark.executor.id	driver
spark.home	C:\apps\hadoop\spark-3.1.1
spark.jars	
spark.master	local[*]
spark.repl.class.outputDir	C:\Users\arnaud\AppData\Local\Temp\spark-169a28ae-4479-4585-ab47-1e354d2d1347\repl-ff2cda14-38ec-4b1e-9c63-c4f02e84bf14
spark.repl.class.uri	spark://DESKTOP-2EGCC8R:57122/classes
spark.scheduler.mode	FIFO
spark.sql.catalogImplementation	hive
spark.submit.deployMode	client
spark.submit.pyFiles	
spark.ui.showConsoleProgress	true

# Spark-ui [5/6]: Executors / Driver



Stages Storage Environment

Executors

SQL

Spark shell application UI

#### **Executors**

▶ Show Additional Metrics

#### Summary

	RDD Blocks	Storage Memory	Disk Used	Cores	Active Tasks	Failed Tasks	Complete Tasks	Total Tasks	Task Time (GC Time)	Input	Shuffle Read	Shuffle Write	Excluded
Active(1)	0	0.0 B / 413.9 MiB	0.0 B	8	0	0	13	13	0.8 s (18.0 ms)	4.6 KiB	118 B	118 B	0
Dead(0)	0	0.0 B / 0.0 B	0.0 B	0	0	0	0	0	0.0 ms (0.0 ms)	0.0 B	0.0 B	0.0 B	0
Total(1)	0	0.0 B / 413.9 MiB	0.0 B	8	0	0	13	13	0.8 s (18.0 ms)	4.6 KiB	118 B	118 B	0

#### **Executors**

Show 20 ♦ entries


Executor ID	Address	Status	RDD Blocks	Storage Memory	Disk Used	Cores 🍦	Active Tasks	Failed Tasks	Complete Tasks	Total Tasks	Task Time (GC Time)	Input	Shuffle Read	Shuffle Write	Thread Dump
driver	DESKTOP-2EGCC8R:57178	Active	0	0.0 B / 413.9 MiB	0.0 B	8	0	0	13	13	0.8 s (18.0 ms)	4.6 KiB	118 B	118 B	Thread Dump

Showing 1 to 1 of 1 entries



Search:

# Spark-ui [6/6] SQL



#### **SQL**

**Completed Queries:** 3

#### **▼** Completed Queries (3)

Page: 1


1 Pages. Jump to 1 . Show 100 items in a page. Go

ID *	Description	Submitted	Duration	Job IDs
2	count at <console>:26 +details</console>	2022/01/02 18:55:23	0,2 s	[4]
1	count at <console>:26 +details</console>	2022/01/02 18:54:35	0,7 s	[3]
0	reduce at <console>:26 +details</console>	2022/01/02 18:42:06	0,2 s	[2]

Page: 1

1 Pages. Jump to 1 . Show 100 items in a page. Go

# Spark-ui [6/6] Sql detail for query




#### **Details for Query 2**

Submitted Time: 2022/01/02 18:55:23

**Duration:** 0,2 s **Succeeded Jobs:** 4

☐ Show the Stage ID and Task ID that corresponds to the max metric



```
Exchange
shuffle records written: 1
shuffle write time: 7 ms
records read: 1
local bytes read: 59.0 B
fetch wait time: 0 ms
remote bytes read: 0.0 B
local blocks read: 1
remote blocks read: 0
data size: 16.0 B
remote bytes read to disk: 0.0 B
shuffle bytes written: 59.0 B
          WholeStageCodegen (2)
                     duration: 6 ms
HashAggregate
time in aggregation build: 5 ms
number of output rows: 1
```

#### ▼ Details

```
== Physical Plan ==
* HashAggregate (7)
+- Exchange (6)
   +- * HashAggregate (5)
     +- * SerializeFromObject (4)
        +- MapPartitions (3)
           +- DeserializeToObject (2)
              +- Scan text (1)
(1) Scan text
Output [1]: [value#21]
Batched: false
Location: InMemoryFileIndex [file:/c:/data/loremIpsum.txt]
ReadSchema: struct<value:string>
(2) DeserializeToObject
Input [1]: [value#21]
Arguments: value#21.toString, obj#28: java.lang.String
(3) MapPartitions
Input [1]: [obj#28]
Arguments: org.apache.spark.sql.Dataset$$Lambda$4450/17435982@68a3d4, obj#29: java.lang.String
```

```
(4) SerializeFromObject [codegen id : 1]
Input [1]: [obj#29]
(5) HashAggregate [codegen id : 1]
Input: []
Keys: []
Functions [1]: [partial_count(1)]
Aggregate Attributes [1]: [count#35L]
Results [1]: [count#36L]
(6) Exchange
Input [1]: [count#36L]
Arguments: SinglePartition, ENSURE_REQUIREMENTS, [id=#55]
(7) HashAggregate [codegen id : 2]
Input [1]: [count#36L]
Keys: []
Functions [1]: [count(1)]
Aggregate Attributes [1]: [count(1)#32L]
Results [1]: [count(1)#32L AS count#33L]
```

Spark Internals


Logical/PhysicalPlan

Jobs - Stage - Tasks

Sql -> parsed AST -> Dataset + expression API


Optimisation: re-write from LogicalPlan to PhysicalPlan

### SQL / DataSet -> AST -> Catalyst -> Code + RDD



### Compiler chain: Parser -> AST -> ..

### Sql> select (a+1) from ...



```
case class Add(left: Expression, right: Expression) extends BinaryArithmetic {
        override def symbol: String = "+"
111
112
       lazy val numeric = dataType match {
113
          case n: NumericType => n.numeric.asInstanceOf[Numeric[Any]]
114
          case other => sys.error(s"Type $other does not support numeric operations")
115
116
117
        override def eval(input: Row): Any = {
118
         val evalE1 = left.eval(input)
119
         if(evalE1 == null) {
120
            null
121
122
         } else {
            val evalE2 = right.eval(input)
123
            if (evalE2 == null) {
124
              null
125
126
           } else {
              numeric.plus(evalE1, evalE2)
127
128
129
130
131
```

# Catalyst AST -> CodeGenerator

```
apache / spark (Public)
                                                                                  Y Fork 25k
                                                                                                  ☆ Star 31.7k


    Watch 2.1k 
▼

  <> Code
             17 Pull requests 241
                                    Actions
                                                 Projects
                                                               Security
                                                                            ✓ Insights
                    spark / sql / catalyst / src / main / scala / org / apache / spark / sql / catalyst /
  ¥ fedbfc7074 ▼
                                                                                                    Go to file
                    expressions / codegen / CodeGenerator.scala
33
     * A base class for generators of byte code to perform expression evaluation. Includes a set of
34
     * helpers for referring to Catalyst types and building trees that perform evaluation of individual
35
     * expressions.
36
37
38
    abstract class CodeGenerator[InType <: AnyRef, OutType <: AnyRef] extends Logging {</pre>
              case Add(e1, e2) => (e1, e2) evaluate { case (eval1, eval2) => q"$eval1 + $eval2" }
363
364
              case Subtract(e1, e2) => (e1, e2) evaluate { case (eval1, eval2) => q"$eval1 - $eval2" }
              case Multiply(e1, e2) => (e1, e2) evaluate { case (eval1, eval2) => q"$eval1 * $eval2" }
365
 640
 641
```

### Runtime Execution:


Dataset -> RDD -> Dag Scheduler -> Jobs,Stages,Tasks

Spark Application Workers



# Spark-core Internal Concepts... RDD, Job, Stage, Task


using only low-level spark-core "RDD.eval()" => trigger 1 Job, with 1 or several Stages




# Spark-sql Internal Concepts... SQLExecution, Job, Stage, Task

lineage dependency using high-level spark-sql "Dataset.<action>()" DataSet => trigger 1 or Several Jobs, with 1 or several Stages **SQLExecution DataSet** RDD lineage dependency Job **RDD** Stage **RDD** Task **Partition** TaskAttempt 1 (or 2,3?)


# Spark Internal Concepts... SQL, Job, Stage, Task




# DAG Job = list of Stages each Stage = N "narrow" transformations between Stages = Exchange Shuffle ("Wide" transfo.)




# example Word Count DAGs simple -vs- repartition()






**→ Completed Stages (1)** 

# Stage = list of Tasks : 1 per Partition ... each scheduled on an executor




# Tasks may fail, Retry individually



Tasks errors are automatically retryed (rescheduled)

By default, spark.task.maxFailures = 4

## Stage Retry



"Stage" failures, are also retryed


spark.stage.maxConsecutiveAttempts = 4

### Architecture Components

Client-Cluster ... Driver & Executors

program/library/servers

# Cluster Client -> Driver (-> SparkContext) -> Executor



Questions?

... Next Steps?