

Introduction to JavaScript, Json, TypeScript, TSX

Cours Esilv 2024

arnaud.nauwynck@gmail.com

Outline

JavaScript

JSON

TypeScript

TSX

JavaScript

Java Script



Syntax inspired from "Java"
(itself inspired from "C", "C++")

untyped at compile-time,
interpreted at runtime
like "script" shells.

only "string", "numeric", boolean".
no "class" or type declarations !

Birth of JavaScript : 1995



ChatGPT

history of javascript



The History of JavaScript


1. Birth of JavaScript (1995)

JavaScript was created in 1995 by Brendan Eich while he was working at Netscape Communications Corporation. Originally, the language was developed in just 10 days and was initially named Mocha, then renamed to LiveScript, and finally to JavaScript.

Key Points:

- **Creator:** Brendan Eich
- **Initial Name:** Mocha
- **Release Date:** December 1995
- **Initial Purpose:** To add interactivity to web pages

JavaScript Evolution



developed in 10 days by 1 person
... => explain many weird parts of the language

<https://jsisweird.com/>



even for me

← → ↻ 🌐 jsisweird.com 📄 ☆ A

You got 12 out of 25 correct!

1. true + false

Output: 1
You answered: 1

You got it right!

According to the [ECMAScript Language Specification](#), the two boolean values are type coerced into their numeric counterparts.

```
Number(true); // -> 1
Number(false); // -> 0
1 + 0; // -> 1
```

There are (strange) implicit coercions between primitive types...
For exact comparison, use "===" ("==" may introduce conversions)

JavaScript = un-maintanable code !!


NO Type !!

- .. alternative like Google Dart since 2011 (ex in Flutter)
- .. work-around since 2012 via TypeScript

NO Class !

- .. work-around since 2012 via TypeScript
- .. ok since 2015 EcmaScript6

Runtime Implementations



JavaScript Primitive Value Objects

null

undefined

String

Numeric

Boolean

Object Compositions: [Array], {Object}

Array

> [undefined, null, true, 12.3, "text", [], {}, [{}, {}]]

< ▶ (8) [undefined, null, true, 12.3, 'text', Array(0), {...}, Array(2)]

Object

> { a: undefined, b: null, c: 12.3, d: "text", e: [], f: {}, g: [{}, {}] }

< ▶ {a: undefined, b: null, c: 12.3, d: 'text', e: Array(0), ...}

JSON = JavaScript Object Notation

NO code, only Value

Can be integrated directly in JavaScript (or TypeScript)

=> SUPER Easy for Http Rest using JSON as data encoding protocol

in pure JSON, identifier need to have double-quotes
... NOT needed in Js/Ts

JSON Example

```
{  
  "a": null,  
  "b": undefined,  
  "c": 123,  
  "d": true,  
  "e": "text with escaped \" and \\n chars",  
  "f": [ null, undefined, 123, true, [], {} ],  
  "g": { "subField": 1, "b": true }  
}
```


Example Unquoted JSON directly in JavaScript

```
let obj = {  
  a: null,  
  b: undefined,  
  c: 123,  
  d: true,  
  e: "text with escaped \" and \\n chars",  
  f: [ null, undefined, 123, true, [], {} ],  
  g: { subField: 1, b: true }  
};
```

JSON stringify() / parse()... builtin in JavaScript

```
test-json.js x
1 let obj : {...} = { a:null, b:undefined, c:12.3, d:true,
2   e: 'text with ", \' and \n',
3   f:"text with \", ' and \n",
4   g: [1, 2],
5   h: { a:1, b:2}
6 }
7 let objJson : string = JSON.stringify(obj);
8 console.log('json stringify:', objJson);
9
10 let objJsonIndented : string = JSON.stringify(obj, {replacer: null, space: ' '});
11 console.log('json stringify indented:', objJsonIndented);
12
13 let objCopy = JSON.parse(objJson);
14 console.log('objCopy', objCopy)
```

stringify, parse



The screenshot shows the VS Code interface with a debug console. The top bar indicates the file is 'test-json.js'. The 'Debugger Console' tab is active, showing the output of a JavaScript script. The script uses `JSON.stringify` to convert a JavaScript object to a JSON string and `JSON.parse` to convert the string back to a JavaScript object. The output shows the compact stringified JSON and the pretty-printed version with indentation. The bottom of the console shows the resulting object in the `objCopy` variable.

```
Debug: test-json.js x
Debugger Console
json stringify: {"a":null,"c":12.3,"d":true,"e":"text with \", ' and \n","f":"text with \", ', and \n","g":[1,2],"h":{"a":1,"b":2}}
json stringify indented: {
  "a": null,
  "c": 12.3,
  "d": true,
  "e": "text with \", ' and \n",
  "f": "text with \", ', and \n",
  "g": [
    1,
    2
  ],
  "h": {
    "a": 1,
    "b": 2
  }
}
objCopy > Object {a: null, c: 12.3, d: true, e: "text with ", ' and \n", f: "text with ", ', and \n", ...}
```


JavaScript object deep clone


```
let objCopy = JSON.parse(JSON.stringify(obj));
```

Object Creation from variables without repeating "a":a, "b":b, simply {a,b}

```
JS test-object-structuring.js ×
1  "use strict";
2  let a : null = null,
3      b : undefined = undefined,
4      c : number = 123,
5      d : boolean = true,
6      e : string = "text with escaped \" and \\n chars",
7      f : [* , undefined, number, boolean... ] = [ null, undefined, 123, true, [], {} ],
8      g : {b: boolean, subField: number} = { subField: 1, b: true };
9  let obj : {...} = { a,b,c,d,e,f,g};
```

Structured Logging



```
9      let obj : {...} = { a,b,c,d,e,f,g};  
10  
11      console.log('message with structured', obj)  
12  
13      console.log('message with a,b', { a, b})  
14  
15      console.log('message with [a,b]', [ a, b ])
```



Object De-Structuring to variables

```
test-object-structuring.js x
1  "use strict";
2  let obj : {...} = { a:1, b:2, c:3};
3
4  // partial extract by names
5  // let {a} = obj;
6  // let {a,b} = obj;
7  // let {b,a} = obj;
8  // let {b,a,c} = obj;
9  let {b : number, a : number} = obj;
10 console.log('a', a);
11 console.log('b', b);
```

Debug: test-object-structuring.js x

Debugger	Debugger Console
	a 1
	b 2

Objects (~= HashMap<String,*>)

```
> let obj = { }
```

```
obj.x = 1
```

```
obj.x = "changed"
```

```
console.log(obj)
```

```
▶ {x: 'changed'}
```

```
< undefined
```

```
> obj
```

```
< ▶ {x: 'changed'}
```

using field Array notation :

```
> obj['x']
```

```
< 'changed'
```

```
> obj['x'] = true
```

```
< true
```

Undefined Field

```
> let a= { x: 1 }
```

```
< undefined
```

```
> a.y
```

```
< undefined
```

```
> a.y = 2
```

```
< 2
```

```
> a
```

```
< ▶ {x: 1, y: 2}
```

```
> delete a.x
```

```
< true
```

```
> a
```

```
< ▶ {y: 2}
```

get unknown field
=> NO error, return undefined

add new field on first set

set field undefined

```
> a.y = undefined
```

```
< undefined
```

```
> a
```

```
< ▶ {y: undefined}
```

```
> a.y
```

```
< undefined
```

delete field

Syntactic Sugar for Object Creations

```
> let obj1 = { x: 1 }
```

```
< undefined
```

```
> let y = 2
```

```
< undefined
```

```
> let obj2 = { 'x': 1, y }
```

```
< undefined
```

```
> let obj3 = { ...obj2, y: 3 }
```

```
< undefined
```

```
> obj3
```

```
< ► {x: 1, y: 3}
```

can omit quotes, double-quotes,
and even variable name as in 'y': y

object spreading operator

(last value override previous)

```
> { y: 1, y: 2 }
```

```
< ► {y: 2}
```

```
> { y: 3, ...obj2 }
```

```
< ► {y: 2, x: 1}
```

Array

```
> a=[1, 2, 3, 4, 5 ]  
↵ ▶ (5) [1, 2, 3, 4, 5]  
↵ a.push(6)  
↵ 6  
↵ a.splice(3, 1)  
↵ ▶ [4]  
↵ a  
↵ ▶ (5) [1, 2, 3, 5, 6]
```

spreading operator

```
> let a = [ 3, 4 ]  
↵ [ 1, 2, ...a, 5 ]  
↵ ▶ (5) [1, 2, 3, 4, 5]
```


Functions

```
> let f = function(a, b) { console.log('f()', {a,b}); }
```

```
< undefined
```

```
> f(1)
```

```
f() ► {a: 1, b: undefined}
```

```
< undefined
```

```
> f(1, 2, 3)
```

```
f() ► {a: 1, b: 2}
```

```
< undefined
```

Functions are Object

```
> f.x = 1
```

```
< 1
```

```
> f
```

```
< f (a, b) { console.log('f()', {a,b}); }
```

```
> f.x
```

```
< 1
```

Arrow (Lambda) Function

```
> let myFunc = (a,b) => { console.log('myFunc()', {a,b}); }
```

arrow function with code block

```
< undefined
```

```
> myFunc(1, 2)
```

```
myFunc() ▶ {a: 1, b: 2}
```

```
< undefined
```

```
> let myFuncPlus = (a,b) => a+b
```

arrow function with expression

```
< undefined
```

```
> myFuncPlus(1, 2)
```

```
< 3
```

Function used as field ~ method ? this = ??

```
> let myFuncThisX = function() { return this.x; } // strange... see next
< undefined
> let a = { x:1, getX: myFuncThisX }
< undefined
> a.getX()
< 1
```

"this" bounded to function

```
> let axFnc = getX.bind(a)
```

```
< undefined
```

```
> axFnc()
```

```
< 1
```

Function as "Class" Constructor

```
> let MyConstructor = function(x) { this.x = x; this.y = 0; }
```

```
< undefined
```

```
> let pt = new MyConstructor(12);
```

```
< undefined
```

```
> pt
```

```
< ▶ MyConstructor {x: 12, y: 0}
```

prototype

adding field (property / method) to object prototype => adding to all impacted instances

```
> MyConstructor.prototype.getX = function() { return this.x; }
```

```
< f () { return this.x; }
```

```
> MyConstructor.prototype.getY = function() { return this.y; }
```

```
< f () { return this.y; }
```

```
> pt.getX()
```

```
< 12
```

```
> pt.getY()
```

```
< 0
```

```
> MyConstructor.prototype.t = 123
```

```
< 123
```

```
> pt.t
```

```
< 123
```

emulated class with Prototype (before EcmaScript2015)

using Typescript (transpiler to JavaScript)

class are emulated with prototype before EcmaScript2015

looks like class after (but internally, still mutable prototype objects)

Type checking ? at "Compile Time" ??

add optional " : <typeDeclaration>" to variables

TypeScript = superset of JavaScript language

a JavaScript file is a TypeScript file
(valid grammar, but maybe invalid type check)

Edit Js to add ": <type>" to variables

Rename file ".js" to ".ts" TypeScript

": <type>" is not valid JavaScript


```
> let a: string = 'test'
```

✖ Uncaught
SyntaxError: Unexpected token ':'

valid in TypeScript



```
1  
2 let a: string = 'text';  
3 console.log('Hello TypeScript', a);
```



```
1  
2 let a : string = 'text';
```

Types are not supported by current JavaScript version

Change JavaScript language version to Flow Alt+Maj+Entrée More actions... Ctrl+1 Alt+Entrée

Compile Time checking ...

```
TS Hello.ts x
1
2 let err : number = 12; // number
3 err = 'changed to text'; // compile error in TypeScript
```


valid in untyped JavaScript
but not in TypeScript

Problems: File 2 Project Errors 1 Server-Side Analysis Vulnerable Dependencies


TS Hello.ts C:\arn\perso\cours\esilv\web\typescript 2 problems

- TS2322: Type 'string' is not assignable to type 'number'. :3
- Variable initializer is redundant :2


IntelliJ TypeScript : Recompile on changes



Js file generated from Ts file




expand to see
generated file



Transpile TypeScript

= generate JS by mostly removing
": <typeDeclaration>"



The image shows a side-by-side comparison of TypeScript and JavaScript code in a code editor. The left pane, titled 'a.ts', contains TypeScript code with type annotations. The right pane, titled 'a.js', shows the resulting JavaScript code after transpilation, where the type annotations have been removed. A vertical scrollbar is visible between the two panes.

```
1  let a: string = 'text';  
2  console.log('Hello', a);  
3  
4  no usages  
5  let f = function(str: string, x:number): string {  
6      return str + x;  
7  }
```

```
1  "use strict";  
2  var a = 'text';  
3  console.log('Hello', a);  
4  no usages  
5  var f = function (str, x) {  
6      return str + x;  
7  };
```

Tsc (=TypeScript Compiler)

```
$ tsc --help  
tsc: The TypeScript Compiler - Version 5.3.3
```

COMMON COMMANDS

```
tsc
```

Compiles the current project (tsconfig.json in the working directory.)

```
tsc app.ts util.ts
```

Ignoring tsconfig.json, compiles the specified files with default compiler options.

```
tsc -b
```

Build a composite project in the working directory.

```
tsc --init
```

Creates a tsconfig.json with the recommended settings in the working directory.

tsc --init


```
$ tsc --init
```

Created a new tsconfig.json with:

```
target: es2016
module: commonjs
strict: true
esModuleInterop: true
skipLibCheck: true
forceConsistentCasingInFileNames: true
```

You can learn more at <https://aka.ms/tsconfig>


tsconfig.json using ES5 ... ES2023



The image shows a code editor with a file named `tsconfig.json` open. A dropdown menu is displayed over the file, listing various ECMAScript versions. The current selection is `ES5`. The background code is partially visible, showing the `"compilerOptions"` section of the `tsconfig.json` file.

```
2  "compilerOptions": {  
3    /* Visit https://typescriptlang.org for more about this file  
4  
5    /* Project  
6    // "incremental": true, /* Save  
7    // "composite": true, /* Enabl  
8    // "tsBuildInfoFile": "tsbuildinfo", /* Specifi  
9    // "disableSizeOfMemory": true, /* Disab  
10   // "disableSizeOfMemory": true, /* Opt a  
11   // "disableSizeOfMemory": true, /* Reduc  
12  
13   /* Language  
14   "target": "ES5", /* Set the  
15   // "lib": [], /* Specifi  
16   // "jsx": "preserve", /* Specifi  
17   // "experimentalDecorators": true, /* Enabl
```

Example Emulating class with ES5



```
TS a.ts
1
2 class Pt {
3
4     constructor(public x: number, public y: number) {}
5
6
7     toString(): string {
8         return '(' + this.x + ',' + this.y + ')';
9     }
10 }
```

```
JS a.js
1 "use strict";
2 var Pt = /** @class */ (function () {
3     function Pt(x, y) {
4         this.x = x;
5         this.y = y;
6     }
7     Pt.prototype.toString = function () {
8         return '(' + this.x + ',' + this.y + ')';
9     };
10    return Pt;
11 }());
12
```

JavaScript evolve (from TypeScript ESNext) now have class since ES2015

```
TS Pt.ts x
```

```
1 no usages
2 class Pt {
3
4   no usages
5   constructor(public x: number, public y: number) {
6
7   }
8
9   no usages
10  toString(): string {
11    return '(' + this.x + ',' + this.y + ')';
12  }
13 }
```

```
JS Pt.js x
```

```
1 "use strict";
2 no usages
3 class Pt {
4   no usages
5   constructor(x, y) {
6     this.x = x;
7     this.y = y;
8   }
9   no usages
10  toString(): string {
11    return '(' + this.x + ',' + this.y + ')';
12  }
13 }
```

JavaScript has weird "var" visibility

JavaScript has weird "var" visibility

"use strict"; // at first line

But still weird

JavaScript has weird "var" visibility

"use strict"; // at first line

use Immediately Invoked Anonymous Function

But still weird

JavaScript has weird "var" visibility

"use strict"; // at first line

use Immediately Invoked Anonymous Function

use "let" or "const" instead of "var"

use TypeScript

in "Standard Languages"

1/ declare, then 2/ init, then- 3/ use
with scope = enclosing { block }

```
block-decl.js
1  "use strict";
2  console.log('after decl let, in same block');
3  {
4    let a : number = 1;
5    console.log(a); // OK, standard case
6  }
```

Debug: block-decl.js

Debugger Debugger Console Process Console

after decl let, in same block

1

JavaScript has weird "var" visibility



```
1  "use strict";
2  console.log('after decl var, in nested block');
3  {
4      var a : number = 1;
5  }
6  console.log(a);
```

What do you think ??

a/ does not "evaluate" / "run" / "compile"

b/ throws exception

c/ print "undefined"

d/ print "1"

Answer: d/ print 1
the scope of visibility if the enclosing function
(not the enclosing block)

```
JS block-decl.js x
1  "use strict";
2  console.log('after decl var, in nested block');
3  {
4      var a : number = 1;
5  }
6  console.log(a);
```

Debug: JS block-decl.js x

Debugger	Debugger Console	Process Console
	after decl var, in nested block	
	1	

without "use strict" ... NO need to decl "var"

```
block-decl.js x
1 // NO "use strict";
2 console.log('no decl but init, in nested block');
3 {
4     a = 1;
5 }
6 console.log(a);
```

Debug: block-decl.js x block-decl.js x

Debugger Debugger Console Process Console

no decl but init, in nested block

1

with "use strict";

```
block-decl.js x
1  "use strict";
2  console.log('no decl but init, in nested block');
3  try {
4      a = 1;
5  } catch(e) {
6      console.log('err', e)
7  }
```

Debug: block-decl.js x block-decl.js x

Debugger Debugger Console Process Console

no decl but init, in nested block

err

> ReferenceError: a is not defined at Object.<anonymous> (C:\arn\perso\cours\...
(node:internal/modules/cjs/loader:1376:14) at Module._extensions..js (node:i
(node:internal/modules/cjs/loader:1207:32) at Module._load (node:internal/mo
(node:internal/modules/run_main:135:12) at node:internal/main/run_main_modul
node:internal/main/run_main_module:28:49", message: "a is not defined"}

even stranger:
use before declare in nested block

```
block-decl.js
1  "use strict";
2  console.log('before decl var, in nested block');
3  console.log(a);
4  {
5      var a : number = 1;
6  }
```

Debug: block-decl.js

Debugger Debugger Console Process Console

before decl var, in nested block

undefined

other strange "var" visibility

```
block-decl.js x
1  "use strict";
2  console.log('after decl var, in nested block');
3  {
4      var a : number = 1;
5  }
6  console.log(a);
```

Debug: block-decl.js x


Debugger Debugger Console Process Console

after decl var, in nested block

1

JavaScript has weird "var" visibility

```
1  "use strict";
2  console.log('before decl var, in nested block');
3  console.log(a);
4  {
5      var a : number = 1;
6  }
```



declared "ok"
BUT not initialized yet => undefined !

work around for scope :

"Immediately Invoked Anonymous Function"

```
JS immediatly-invoke-func.js x
1  "use strict";
2  (function () {
3      var a = 12;
4  })();
5  console.log(a);
```

Debug: JS immediatly-invoke-func.js x

Debugger Debugger Console Process Console

! > Uncaught ReferenceError: a is not defined

"let" | "const" ... as "var" replacement

```
block-decl.js x
1  "use strict";
2  console.log('after decl let, in nested block');
3  {
4      let a : number = 1;
5  }
6  console.log(a);
```

Debug: block-decl.js x

Debugger Debugger Console Process Console

after decl let, in nested block

Uncaught ReferenceError: a is not defined

```
block-decl.js x
1  "use strict";
2  console.log('before decl let, in nested block');
3  console.log(a);
4  {
5      let a : number = 1;
6  }
```

Debug: block-decl.js x

Debugger Debugger Console Process Console

before decl let, in nested block

Uncaught ReferenceError: a is not defined

"let" (or "const") in same block

```
block-decl.js x
1  "use strict";
2  console.log('before decl let, in same block');
3  {
4      console.log(a);
5      let a : number = 1;
6  }
```


Debug: block-decl.js x

Debugger Debugger Console Process Console


before decl let, in same block

Uncaught ReferenceError: Cannot access 'a' before initialization

not init (ok in JS !)
but does not compile in TypeScript



```
block-decl.js x
1  "use strict";
2  console.log('after decl let, but not init');
3  {
4      let a;
5      console.log(a);
6      a = 1;
7  }
```



```
Debug: block-decl.js x
Debugger  Debugger Console  Process Console
after decl let, but not init
undefined
```

everybody hate JavaScript, for million reasons

100 reasons you need TypeScript
and will probably love it

Spoiler Alert

TypeScript is NOT "more efficient" than JS

... it is just typed-checked at Compile-Time
then translated to JS

at Runtime, you still have poor old
Node.js or Web Browser

TypeScript Types

Primitive Types (for values) : any, null, undefined, boolean, number, string

Composite Types:

" | " Union (choice between types)

" & " combination of type constraint

"**readonly**" type modifier


Array

Interfaces : type constraint on existence of field / partial field in Object

" ? " Optional Field Type (for accepting "undefined")

Function, Class, Templates, etc.

any ?



```
1 {  
2   let a: any;  
3  
4   a = 'text';  
5   console.log(a);  
6   a = 123;  
7   console.log(a);  
8 }
```

any ... as name implies
= No Type checking !

To use TEMPORARILY while porting JS to Ts

Good Ts program(er)s should never use "any"

Union Type


```
test-types.ts x
2  type MyUnionType = (number | string);
3
4  {
5      let a: MyUnionType = 123;
6      a = 'some text';
7
8      console.log('a', a);
9  }
```


Example usages

Type | null

Type | undefined

Force type-check with "!!"



The screenshot shows a VS Code editor with a file named `test-force-defined.ts`. The code defines a function `myFunc` with a parameter `x` of type `(number | undefined)`. Inside the function, there are two lines of code: `let forceAssign : number = x!!;` and `let errorAssign : number = x;`. The first line has a red squiggly line under `x!!`, and the second line has a red squiggly line under `x`. A red box highlights the `x!!` expression in the first line. A tooltip is visible over the `x!!` expression, showing the error message: "TS2322: Type 'number | undefined' is not assignable to type 'number'. Type 'undefined' is not assignable to type 'number'". Below the error message, there are two suggestions: "Remove unused local variable 'errorAssign'" and "More actions...". The second suggestion is selected, and a dropdown menu is open, showing the code `let errorAssign: number`. The file name `test-force-defined.ts` and the file type `typescript` are also visible in the bottom right corner of the editor.

```
no usages
1 function myFunc(x: (number | undefined)) : void {
2   ! let forceAssign : number = x!!;
3   let errorAssign : number = x;
4
5 }
```

TS2322: Type `number | undefined` is not assignable to type `number`.
Type `undefined` is not assignable to type `number`.

Remove unused local variable 'errorAssign' Alt+Maj+Entrée More actions... Ctrl+1 Alt+Entrée

let errorAssign: number

test-force-defined.ts
typescript

Duck Typing

```
TS duck-typing.ts ×  
2 usages  
1 interface Duck { name : string };  
2  
3 {  
4     let obj : {name: string} = { name: 'abc' };  
5  
6     // obj is a Duck !  
7     let duckObj : Duck = obj; // explicit typed, from implicit assign  
8     let duckObj2 : Duck = <Duck> obj; // implicit typed, explicit coerce  
9 }
```

Structural Interface Typing, Combine Partial

```
test-interface.ts x
1  interface Ix { x: number; }
   1 usage
2  interface Iy { y: number; }
3  type Ixy = Ix & Iy;
4  type Pt = { x: number; y: number }; // equivalent to Ix & Iy
5
6  {
7      let objX [ ] = { x: 1 }; // type inferred = { x:number }
8      let objX2 : Ix = objX; // implicit type "cast" ok
9      let objY [ ] = { y: 1 };
10     let obj: Pt = { ...objX, ...objY };
11     console.log(obj);
12 }
```

[] = type inferred (displayed by IntelliJ), NOT edited in file

Type Checking "missing property" in Interface

