BigData Spark – HandsOn 3

SQL, Temporary View
Hive MetaStore, ExternalCatalog, Table Partitions

arnaud.nauwynck@gmail.com

Esilv 2025

Objectives of Hands-On



Reminders:
Local Install, spark-shell
Spark File IO

1/ CreateTempView, use Dataset from SQL


2/ Configure HiveMetastore DB

3/ connect Spark External Catalog to MetaStore


4/ Create Table

5/ (Directory) Partitioned Table

Reminder Hands-On 1



Reminder Hands-On 2



Objectives of Hands-On 3



1/ CreateTempView, use Dataset from SQL

2/ Configure HiveMetastore DB

3/ connect Spark External Catalog to MetaStore

4/ Create Table

5/ (Directory) Partitioned Table

PRE-REQUISITES : Redo from previous TD

```
val df = spark.read.option("header", "true").option("delimiter", ";").
              option("dateFormat", "yyyy/MM/dd").
              schema("""
  uid_adresse STRING,  cle_interop STRING,
  commune_insee STRING,  commune_nom STRING,
  commune_deleguee_insee INT,  commune_deleguee_nom STRING,
  voie_nom STRING,  lieudit_complement_nom STRING,  numero INT,  suffixe STRING,
  position STRING,  x STRING,  y DOUBLE,  long DOUBLE,  lat DOUBLE,  cad_parcelles STRING,
  source STRING,  date_der_maj TIMESTAMP,  certification_commune INT
""").
csv("C:/data/OpenData-gouv.fr/bal-csv-all").
drop("x", "y", "date_der_maj") //   drop big & redundant columns x,y (cf longitude,latitude),  invalid dates


df.repartition(3).
  sortWithinPartitions("commune_insee", "voie_nom", "numero",  "'suffixe", "position").
  write.format("parquet").save("c:/data/OpenData-gouv.fr/bal-parquet")
```

REMINDER..

Columns « x », « y » are big & redundant with « longitude », « latitude » (french coordinate system)

Columns « date_der_maj » contained some invalid dates … some with 1111-01-01
(before year 1534, so invalid in GregorianCalendar system)

Therefore, using « . drop("x", "y", "date_der_maj") »

Saving with both « .repartition() » and « .sortWithinPartitions() » produces better quality parquet files
(same data, but better organized, so better compressed and with better blocks statistics)

ERROR on column "date_der_maj" ("date dernière mise à jour", in english: last update date)

Caused by: org.apache.spark.SparkUpgradeException: [INCONSISTENT_BEHAVIOR_CROSS_VERSION.WRITE_ANCIENT_DATETIME] You may get a different result due to the upgrading to Spark >= 3.0:
writing dates before 1582-10-15 or timestamps before 1900-01-01T00:00:00Z
into Parquet files can be dangerous, as the files may be read by Spark 2.x
or legacy versions of Hive later, which uses a legacy hybrid calendar that
is different from Spark 3.0+'s Proleptic Gregorian calendar. See more
details in SPARK-31404. You can set "spark.sql.parquet.datetimeRebaseModeInWrite" to "LEGACY" to rebase the
datetime values w.r.t. the calendar difference during writing, to get maximum
interoperability. Or set the config to "CORRECTED" to write the datetime
values as it is, if you are sure that the written files will only be read by
Spark 3.0+ or other systems that use Proleptic Gregorian calendar.

at org.apache.spark.sql.errors.QueryExecutionErrors$.sparkUpgradeInWritingDatesError(QueryExecutionErrors.scala:759)
at org.apache.spark.sql.execution.datasources.DataSourceUtils$.newRebaseExceptionInWrite(DataSourceUtils.scala:187)
at org.apache.spark.sql.execution.datasources.DataSourceUtils$.$anonfun$createDateRebaseFuncInWrite$1(DataSourceUtil

Gregorian Calendar Dates : after 1582-10-15 so check invalid dates before

ds.select("date_der_maj").distinct().orderBy($"date_der_maj".asc).show(10)

```
+----------------+
|date_der_maj|
+----------------+
|            NULL|
|  0023-04-12|
|  1111-11-01|
|  1900-01-01|
|  1901-01-01|
|  1904-09-30|
|  1930-02-21|
|  1935-04-17|
|  1936-11-27|
|  1944-10-13|
+----------------+
only showing top 10 rows
```


Alternative to Fix invalid dates, replace by min date (or NULL)

```
val min_date = to_date(lit("1901-01-01"));
val ds_fixdate = ds.withColumn("date_der_maj2", greatest(col("date_der_maj"), min_date));

ds_fixdate.select("date_der_maj2").distinct().orderBy($"date_der_maj2".asc).show(10)

val ds = ds_fixdate.drop("date_der_maj").withColumnRenamed("date_der_maj2", "date_der_maj")
```

Parquet Files … ~3 x 640 Mo



Nom	Modifié le	Type	Taille
._SUCCESS.crc	16/10/2025 22:18	Fichier CRC	1 Ko
.part-00000-9296d159-36a9-4e99-b505-9254b629254c-c000.snappy.parquet.crc	16/10/2025 22:18	Fichier CRC	4 994 Ko
.part-00001-9296d159-36a9-4e99-b505-9254b629254c-c000.snappy.parquet.crc	16/10/2025 22:18	Fichier CRC	4 991 Ko
.part-00002-9296d159-36a9-4e99-b505-9254b629254c-c000.snappy.parquet.crc	16/10/2025 22:18	Fichier CRC	4 992 Ko
_SUCCESS	16/10/2025 22:18	Fichier	0 Ko
part-00000-9296d159-36a9-4e99-b505-9254b629254c-c000.snappy.parquet	16/10/2025 22:18	Fichier PARQUET	639 111 Ko
part-00001-9296d159-36a9-4e99-b505-9254b629254c-c000.snappy.parquet	16/10/2025 22:18	Fichier PARQUET	638 801 Ko
part-00002-9296d159-36a9-4e99-b505-9254b629254c-c000.snappy.parquet	16/10/2025 22:18	Fichier PARQUET	638 883 Ko

If keeping columns x, y, date_der_maj => ~3 x 750 Mo (that is + ~3 x 110M for the 3 useless columns)

part-00000-b6bf06ad-31a5-4e47-a533-5fe51ae6aee2-c000.snappy.parquet	16/10/2025 22:03	Fichier PARQUET	749 378 Ko
part-00001-b6bf06ad-31a5-4e47-a533-5fe51ae6aee2-c000.snappy.parquet	16/10/2025 22:03	Fichier PARQUET	749 413 Ko
part-00002-b6bf06ad-31a5-4e47-a533-5fe51ae6aee2-c000.snappy.parquet	16/10/2025 22:03	Fichier PARQUET	749 439 Ko

Objectives of Hands-On 3



0/ Check spark backward compatibility (spark <=3)

1/ CreateTempView, use Dataset from SQL

2/ Configure HiveMetastore DB

3/ connect Spark External Catalog to MetaStore

4/ Create Table

5/ (Directory) Partitioned Table

Spark Changes version <= 3 … then >= 4

Before version <= 3, you needed to explicitly configure spark for Hive

Since >=4, spark comes with HiveMetastore pre-configured
(using Derby embedded database)

Conclusion: It is easier to use for beginners, without re-configuring

Exercise 1: check spark conf spark.sql.catalogImplementation= « hive » or « in-memory » ?

a/ execute line

scala> **spark.sharedState.sparkContext.getConf.get("spark.sql.catalogImplementation")**

Res1: String = in-memory

b/ expecting for now to have «**in-memory**» .. not « **hive** »


(… to work similarly even on old spark version <=3)

c/ If not correct, relaunch spark-shell using

spark-shell --driver-memory 5g --conf spark.sql.catalogImplementation=in-memory

Check Source Code

https://github.com/apache/spark/blob/master/sql/catalyst/src/main/scala/org/apache/spark/sql/internal/StaticSQLConf.scala#L53




Checking from Spark-UI

a/ Open Spark-UI http://localhost:4040 … more on this later

b/ browse to Environment > Spark Properties >

c/ check spark.sql.catalogImplementation



WRONG for now..

Re-Checking Second Time …

println(spark.sharedState.externalCatalog.unwrapped)

```
scala> println(spark.sharedState.externalCatalog.unwrapped)
org.apache.spark.sql.catalyst.catalog.InMemoryCatalog@50f6eb17
```

Else, even this will fail in spark version <= 3 … but OK in spark version >= 4

```
Caused by: org.apache.hadoop.hive.metastore.api.MetaException: Could not connect to meta store using any of the URIs provided. Most recent failure: org.apach
e.thrift.transport.TTransportException: java.net.ConnectException: Connection refused: connect
        at org.apache.thrift.transport.TSocket.open(TSocket.java:226)
        at org.apache.hadoop.hive.metastore.HiveMetaStoreClient.open(HiveMetaStoreClient.java:478)
        at org.apache.hadoop.hive.metastore.HiveMetaStoreClient.<init>(HiveMetaStoreClient.java:245)
```

Exercise 2: reload address DataSet ensure no OutOfMemoryError

a/ Load the Dataset of addresses from previous hands-on.

scala> **val allAddressDs = spark.read.parquet**("C:/data/OpenData-gouv.fr/bal-parquet")

b/ check the data… using « **.count** » and « **.show**(2, false) »

You must have ~27 Millions rows

```
scala> val allAddressDs = spark.read.parquet("C:/data/OpenData-gouv.fr/bal-parquet")
val allAddressDs: org.apache.spark.sql.DataFrame = [uid_adresse: string, cle_interop: string ... 14 more fields]

scala> allAddressDs.count()
val res7: Long = 26972391
```

Details

OutOfMemoryError ?


if encountering OutOfMemory Error .. Then increase memory (cf next):
« spark-shell --driver-memory 5g »

```
scala> allAddressDs.count
22/09/29 16:11:08 WARN BlockManager: Block rdd_8_1 could not be removed as it was not found on disk or in memory
22/09/29 16:11:08 WARN BlockManager: Block rdd_8_5 could not be removed as it was not found on disk or in memory
22/09/29 16:11:08 WARN BlockManager: Block rdd_8_4 could not be removed as it was not found on disk or in memory
22/09/29 16:11:08 ERROR Executor: Exception in task 5.0 in stage 2.0 (TID 7)
java.lang.OutOfMemoryError: Java heap space
22/09/29 16:11:08 ERROR Executor: Exception in task 1.0 in stage 2.0 (TID 3)
java.lang.OutOfMemoryError: Java heap space
        at java.nio.HeapByteBuffer.<init>(HeapByteBuffer.java:57)
        at java.nio.ByteBuffer.allocate(ByteBuffer.java:335)
        at org.apache.parquet.bytes.HeapByteBufferAllocator.allocate(HeapByteBufferAllocator.java:32)
        at org.apache.parquet.hadoop.ParquetFileReader$ConsecutivePartList.readAll(ParquetFileReader.java:1696)
```

Details

Ensure Memory JVM Argument –Xmx3g
add arg --driver-memory=3g

spark-shell --conf spark.sql.catalogImplementation=in-memory --driver-memory=3g



Exercise 3: createTempView … then SQL

Execute following

```
allAddressDs.createTempView("tmp_address")

spark.sql("SELECT count(*) FROM tmp_address").show()

spark.sql("SELECT * FROM tmp_address").show(2, false)

spark.sql("SELECT * FROM tmp_address WHERE commune_nom='Paris'").show(2, false)
```

Exercise 4: list Tables

```
spark.sql("SHOW TABLES").show()

spark.catalog.listTables().show(false)
```

Exercise 5: Describe Table / printSchema

Execute

spark.sql("select * from tmp_address")**.printSchema()**

spark.sql("**describe table** tmp_address").show(false)

spark.sql("**show create table** tmp_address").show(false)

```
// …. WILL FAIL … no Sql DDL for it
// error: not a « table » (but describe ok!)
```

Exercise 6: stop + restart .. temporary

a/ stop spark-shell

b/ restart spark-shell

c/ list tables …
Check temporary tables have disapeared !

Optional

Optional Exercise 7: createGlobalTemporaryView

https://spark.apache.org/docs/latest/sql-getting-started.html#global-temporary-view

a/ similar to Exercise 3,
« **createGlobalTemporaryView** » from your dataset
instead of a « createTempView »

b/ forget about finding it from default spark catalog (… confusing)
list explicitly from:
spark.catalog.listTables(**« global_temp »**).show(false)

c/ execute SQL query on « **global_temp.**address »
select count(*) from global_temp.address

d/ explain difference between global temp and temp

Objectives of Hands-On



1/ CreateTempView, use Dataset from SQL



2/ Configure HiveMetastore DB


3/ connect Spark External Catalog to MetaStore


4/ Create Table


5/ (Directory) Partitioned Table

Optional

Default hive… using Derby metastore_db
cf next slides if explicitly using Postgresql DB







Optional

Install Hive Standalone Metastore

https://downloads.apache.org/hive/hive-standalone-metastore-3.0.0/

https://downloads.apache.org/hive/

Index of /hive

Name	Last modified
Parent Directory	
hive-1.2.2/	2022-06-17 12:34
hive-2.3.9/	2022-06-17 12:34
hive-3.1.2/	2022-06-17 12:34
hive-3.1.3/	2022-06-17 12:34
hive-4.0.0-alpha-1/	2022-06-17 12:34
hive-standalone-metastore-3.0.0/	2022-06-17 12:34
hive-storage-2.7.3/	2022-06-17 12:34
hive-storage-2.8.1/	2022-06-17 12:34
stable-2/	2022-06-17 12:34
KEYS	2022-03-23 18:19


Index of /hive/hive-standalone-metastore-3.0.0


Name	Last modified	Size	Description
Parent Directory		-	
hive-standalone-metastore-3.0.0-bin.tar.gz	2018-06-07 17:56	25M	
hive-standalone-metastore-3.0.0-bin.tar.gz.asc	2018-06-07 17:56	832	
hive-standalone-metastore-3.0.0-bin.tar.gz.sha256	2018-06-07 17:56	109	
hive-standalone-metastore-3.0.0-src.tar.gz	2018-06-07 17:56	2.3M	
hive-standalone-metastore-3.0.0-src.tar.gz.asc	2018-06-07 17:56	832	
hive-standalone-metastore-3.0.0-src.tar.gz.sha256	2018-06-07 17:56	109	

Optional

Example using Postgres : Create Hive Schema

1/ Open PgAdmin
2/ Create a « Database »
3/ execute SQL script « hive-schema-<dbType>.sql »
copied from <downloadedHiveDir>/scripts/metastore/upgrade/<dbType>






Optional


Copy Jar .. Example using Postgresql

Step 1/ find g:org.postgresql a:postgresql

https://search.maven.org/search?q=g:org.postgresql%20a:postgresql



Step 2/ copy jar to SPARK_HOME/jars



Optional

Configure hive metastore in HADOOP_CONF_DIR (or HADOOP_HOME) /conf/hive-site.xml

hive-site.xml

```
22  <property>
23    <name>hive.metastore.db.type</name>
24    <value>postgres</value>
25  </property>
26  <property>
27    <name>javax.jdo.option.ConnectionDriverName</name>
28    <value>org.postgresql.Driver</value>
29  </property>
30  <property>
31    <name>javax.jdo.option.ConnectionURL</name>
32    <value>jdbc:postgresql://localhost/hivemetastore</value>
33  </property>
34  <property>
35    <name>javax.jdo.option.ConnectionUserName</name>
36    <value>hivemetastore-user</value>
37  </property>
38  <property>
39    <name>javax.jdo.option.ConnectionPassword</name>
40    <!-- <value> ... </value>  -->
41  </property>
42
```

Objectives of Hands-On



1/ CreateTempView, use Dataset from SQL

2/ Configure HiveMetastore DB

3/ connect Spark External Catalog to MetaStore

4/ Create Database, Table

5/ (Directory) Partitioned Table

Restart spark-shell + Check externalCatalog


relaunch spark-shell
spark-shell --driver-memory 5g --conf spark.sql.catalogImplementation=hive

Check in sparkContext
spark.sharedState.sparkContext.getConf.get("spark.sql.catalogImplementation")
res1: String = "hive"

println(spark.sharedState.externalCatalog.unwrapped)

Check in Spark UI

Optional Exercise 8: View/Change spark-defaults.conf



a/ Copy file, and rename without suffix « .template »
Edit to add line

spark.sql.catalogImplementation hive

Check conf can still be overloadded by « --conf key=value »
check conf at runtime:
  spark.sharedState.sparkContext.getConf.get(« key »)
Or in Spark UI

Objectives of Hands-On



1/ CreateTempView, use Dataset from SQL

2/ Configure HiveMetastore DB

3/ connect Spark External Catalog to MetaStore

4/ Create Database, Table

5/ (Directory) Partitioned Table

List Databases

```
scala> spark.catalog.listDatabases().show(false)
+-------+--------------------+--------------------------------------+
|name   |description         |locationUri                           |
+-------+--------------------+--------------------------------------+
|default|Default Hive database|file:/C:/apps/hadoop/spark-warehouse|
+-------+--------------------+--------------------------------------+
```

Exercise 9: Create Database, Create if not exists

Execute:

spark.sql("**CREATE DATABASE** db1").show(false)

spark.sql("**CREATE DATABASE IF NOT EXISTS** db1").show(false)

Then, search created database

10 mn pause

Exercise 10: saveAsTable

Try some variations:

```
// val ds = spark.read.format("parquet").load("C:/data/OpenData-gouv.fr/bal-parquet")

ds.write.saveAsTable("addr")

ds.write.saveAsTable("db1.addr")

ds.write.format("parquet").saveAsTable("db1.addr")
```

Exercise 10 : CTAS
CREATE TABLE <db>.<table> AS SELECT

CREATE TABLE … => STUPID default format « text »

```
scala> spark.sql("CREATE TABLE db1.address_copy AS SELECT * FROM tmp_address LIMIT 100")
22/10/01 15:20:38 WARN ResolveSessionCatalog: A Hive serde table will be created as there is no table provider specified. You can set spark.sql.legacy.create
HiveTableByDefault to false so that native data source table will be created instead.
22/10/01 15:20:38 WARN HiveMetaStore: Location: file:/C:/apps/hadoop/spark-warehouse/db1.db/address_copy specified for non-external table:address_copy
res33: org.apache.spark.sql.DataFrame = []
```

CREATE TABLE … STORED AS PARQUET => OK

```
scala> spark.sql("CREATE TABLE db1.address_copy STORED AS PARQUET AS SELECT * FROM tmp_address LIMIT 100")
22/10/01 15:28:12 WARN HiveMetaStore: Location: file:/C:/apps/hadoop/spark-warehouse/db1.db/address_copy specified for non-external table:address_copy
res40: org.apache.spark.sql.DataFrame = []
```

Anyway… it is only to do next « show create table » ..
CTAS => can NOT create EXTERNAL tables / can NOT create PARTITIONED tables !!!

Exercise 11 : SHOW CREATE TABLE


a/ Execute SQL

```
spark.sql("SHOW TABLES in db1").show(false)
spark.sql("DESCRIBE TABLE db1.addr").show(false)
spark.sql("SHOW CREATE TABLE db1.addr").show(false)
```

b/ check you can RE-Execute the result SQL DDL script
(ensure modify table name)

c/ compare difference with « dataset.printSchema » or Sql « DESCRIBE TABLE »
(ASCII table vs Sql)

Hint Exercise 11: Replacing \\n by \n



SHOW CREATE TABLE

```
CREATE TABLE spark_catalog.db1.addr (
uid_adresse STRING,
cle_interop STRING,  commune_insee STRING,
commune_nom STRING,
commune_deleguee_insee INT,
commune_deleguee_nom STRING,
voie_nom STRING,
lieudit_complement_nom STRING,
numero INT,  suffixe STRING,  position STRING,  x DOUBLE,  y DOUBLE,
long DOUBLE,  lat DOUBLE,  cad_parcelles STRING,  source STRING,
date_der_maj STRING,  certification_commune INT
)
USING parquet
```

Exercise 12: Create « EXTERNAL » TABLE instead of default «MANAGED » Table

a/ Execute Sql « DROP TABLE db1.address »

b/ Verify that it has deleted all Directories and Files !

c/ recreate your table, but using « CREATE EXTERNAL TABLE .. LOCATION .. »

d/ fill your table using « INSERT OVERWRITE … SELECT .. »)

e/ Execute « DROP TABLE » on the external table
Verify that Dir/Files are NOT affected !

f/ RE-Create EXTERNAL TABLE … adding « LOCATION 'c:/data/your-dir' » (cf next slide)
Verify it still has data « select count(*) from .. »

CREATE EXTERNAL TABLE .. STORED AS .. LOCATION ...

```
spark.sql("""
CREATE EXTERNAL TABLE spark_catalog.db1.addr2 (
uid_adresse STRING,
cle_interop STRING,  commune_insee STRING,
commune_nom STRING,  commune_deleguee_insee INT,  commune_deleguee_nom STRING,
voie_nom STRING,  lieudit_complement_nom STRING,  numero INT,  suffixe STRING,
position STRING,  x DOUBLE,  y DOUBLE,  long DOUBLE,  lat DOUBLE,  cad_parcelles STRING,
source STRING,  date_der_maj STRING,  certification_commune INT
)
STORED AS parquet
LOCATION 'C:/data/OpenData-gouv.fr/bal-table-addr2'
""").show()
```

Exercise 13: INSERT INTO ..VALUES … result created File(s)

a/ Execute SQL

```
spark.sql("""
INSERT INTO db1.addr2
   (commune_insee,commune_nom,numero,voie_nom)
    VALUES ('75000', 'PARIS', 1, 'rue de la paix')
""").show()
```

check that it has created 1 new File (containing only 1 line)

b/ .. Repeat 10 times … “for(i <- 0 to 10)”,
check it has created 10 additional files

Exercise 13(next): INSERT INTO SELECT.. … result created File(s)

c/ Execute SQL

```
spark.sql("""
INSERT INTO db1.addr2
   SELECT * FROM db1.addr
""").show()
```

Check how many files are inserted, comparing to the parallelism of the SELECT

```
spark.sql("SELECT * FROM db1.addr").toJavaRDD.getNumPartitions
```

d/ redo with

```
spark.sql("""
INSERT INTO db1.addr2 SELECT /*+REPARTITION(25)*/ * FROM db1.addr
""").show()
```

Exercise 14: INSERT OVERWRITE (difference with INSERT INTO)

a/ Question: if you reapeat several time the same « INSERT INTO »,
do you have duplicate rows ?
Can you have unicity with Primary Key constraint ?
can you do sql “UPDATE” ?

b/ Execute SQL, replacing « INTO » by « OVERWRITE »
INSERT **OVERWRITE** db1.address SELECT * FROM tmp_address

c/ what are the files remaining/created after ?

d/ if you repeat several times « INSERT OVERWRITE »,
what happens ?

Objectives of Hands-On



1/ CreateTempView, use Dataset from SQL

2/ Configure HiveMetastore DB

3/ connect Spark External Catalog to MetaStore

4/ Create Database, Table

5/ (Directory) Partitioned Table

Exercise 15: enrich Dataset / table address by computing column « dept » from column « commune_insee »

We want to partition by department : only 99 values … instead of by 50 000 cities

Use column « commune_insee »: it is a String of 5 chars,
padding with « 0 » on left,
and ignore the 3 chars on right (city code within department)

Create a column to extract the numeric value of dept
Recreate your table (or dataset) with this extra column

HINT: use « .withColumn(« dept », regexp_replace(col(srcCol), pattern, replacement)) »

Example:
« 75100 » => « 75 » => 75
« 01200 » => « 01 » => « 1 » => 1

Exercise 16 : Create PARTITIONED Table

a/ do « show create table » on UN-partitioned table

b/ edit SQL + execute to change to a new table « address_by_dept »,
   partitioned by column « dept Int »

```
//?? allAdressDept.write.writePartitioned("dept").format("parquet").saveAsTable("db1.tmp_a
CREATE EXTERNAL TABLE db1.address_by_dept (
      … <all columns except dept column> … )
  PARTITIONED BY ( dept Int)
  STORED AS PARQUET
  LOCATION ‘file:///c/data/db1/address_by_dept’
allAdressDept.write.format("hive").insertInto("db1.tmp_addr_with_dept")
or..
INSERT OVERWRITE db1.address_by_dept  SELECT * FROM db1. tmp_addr_with_dept
```

Exercise 17: Dirs for Partitioned Table

a/ explore directory / files for partitioned table

b/ check the partitioned column does not exist in the sub-files content, only in directory names

HINT: reload an individual parquet file using « spark.read.parquet(« … »)

10 mn pause

Exercise 18: Query a Partitioned Table … optim « Partition Pruning »

a/ do a SQL query using a « WHERE dept=92 »

b/ do a SQL query using a « WHERE dept in (75, 78, 91, 92) »

c/ do a SQL query without partition column condition

d/ Can you measure that

Query a/ is ~4x faster than Query b/ (1 part << 4 parts)

Query a/ is ~99x faster than Query c/ (1 part << 99 parts)

e/ check that Spark prunes the unnecessary partitions dirs from scanning

Exercise 19: SQL Explain plan: SQL « EXPLAIN select … from .. Where ..»

a/ Execute SQL prefixed by “EXPLAIN”

```
spark.sql("""
EXPLAIN select count(*) FROM db1.address_by_dept WHERE dept=92
""").foreach(println(_))
```

b/ Check that Spark has read ONLY files within directory « …/dept=92/*.parquet »

Exercise 20: Query by condition, NOT by partition column

a/ Execute SQL with any condition but not on column “dept”
SELECT .. WHERE … somethingElse …

b/ Execute SQL:
EXPLAIN SELECT …

b/ Check that Spark has read ALL directories/files
… Check that is is slower than the unpartitioned table

Exercise 21: INSERT OVERWRITE... partitioned

a/ Execute SQL
INSERT OVERWRITE address_by_dept
SELECT .. FROM .. WHERE … commune='Nanterre'

b/ check that ALL files from directory /dept=92/*
have been deleted… and rewritten with partial new results

c/ .. check that all cities != 'Nanterre' from dept=92 have been deleted
(not re-created).
an "INSERT OVERWRITE" can INSERT+UPDATE+DELETE rows !

d/ check that ALL other directories dept != 92 are unmodified

Exercise 22: SAME insert overwrite … on 2 differently partitioned tables

Execute twice the same SQL, on 2 different tables, containing the same data
a/ compare select count(*) on both tables

b/ execute SQL on first (partitioned) table:
INSERT OVERWRITE address_by_dept
SELECT .. FROM .. WHERE … dept=92

c/ execute Same SQL on second (un-partitioned) table
INSERT OVERWRITE address
SELECT .. FROM .. WHERE … dept=92

d/ compare counts, Explain

Exercise 23: INSERT OVERWRITE… for fully « UPDATING » partition(s)

a/ Execute SQL:
INSERT OVERWRITE address_by_dept
SELECT * FROM address WHERE … dept=92

b/ check that counts are same:
  select count(*) from address where dept=92
  select count(*) from address_by_dept where dept=92

c/ Explain that you can replay safely an « UPDATE » batch for any dept
  .. NO duplicate, NO delete
  Update fully the expected result but no side effect elsewhere

Exercise 24: ACID Update / Delete in Spark ?

Questions

a/ Does Spark support SQL Update or Delete per rows?

b/ Can you « insert overwrite » data in Spark ? With which granularity ?

c/ can you emulate applicative updates or deletes on rows
by append-only events ?

d/ Do you know « DeltaLake » or « Iceberg » ? (google it)

Exercise 25: Question on Partition.. What for ?

Questions

a/ Are partitions improving performances ?

b/ is it true that same SQL INSERT OVERWRITE
can have different results on tables with different partitionning ?

c/ Why/How should you use partitions ?

d/ Is is advisable to have deep sub-sub-sub partitioning ?

Optionnal Exercise 26 – DeltaLake / Iceberg …

Have a look to DeltaLake (legacy system, now switching to Iceberg standard)


https://docs.delta.io/latest/quick-start.html

```
spark-shell --packages io.delta:delta-core_2.12:2.2.0 \
 --conf spark.sql.extensions=io.delta.sql.DeltaSparkSessionExtension  \
 --conf spark.sql.catalog.spark_catalog=org.apache.spark.sql.delta.catalog.DeltaCatalog
```

CREATE TABLE … USING DELTA … (instead of STORED AS PARQUET …)

Exercise 27 – Iceberg…

https://iceberg.apache.org/docs/latest/spark-getting-started/



Spark + Iceberg

```
spark-shell --packages org.apache.iceberg:iceberg-spark-runtime-3.5_2.12:1.10.0
```

Self Exploration (or HomeWork)

Create Iceberg Table for your dataset

Execute SQL query on it

Execute an UPDATE Sql query on it !

Check Read-Consistency

Open 2 spark-shells

In terminal 1/ launch spark-shell…. start working (reading) with an Iceberg Table

In Terminal 2/ launch another spark-shell …. Do an UPDATE on the Table

Then, go back on Terminal 1/
do again a Query on Table (or continue a long query)
… Check that it still works, with read isolation (you don’t see the updates & it does not fail ?)

Compare with legacy Hive (Partitioned) Table

On Legacy Hive (Partitioned) Table

You can ONLY fully overwrite (~ « Update ») a partition

If a Table is NOT partitioned => yuo can only fully overwrite the full table

… This is not an Atomic update
And not READ ISOLATED !

Check that 2 concurrent sessions of spark will FAIL :
After an Update, the Spark session that try to read the (old files of) the table FAIL miserably

Exercise 28 : MindMap

Draw a MindMap to summarize
what you did and learn from this Hands-On session

Your MindMap should
start with word « Spark Catalog - Metastore» in the middle
Then draw star edges to other word chapters and sub-chapters

Questions ?

Take-Away

What You learned ?

Next Steps

More Lessons

More Hands-On

Spark concepts:
- Spark UI, DAG, Optimisation, Predicate-Push-Down
- Spark Clustering
- Java binding, UDF, map
- Spark Streaming
- …