

Contradictions in the Evidence

eDurgaPuja pass platform — every point where the three primary sources disagree with each other, or with themselves. Each one is a decision someone must make before it can be built.

COMPILED 8 SEPTEMBER 2026
FROM THREE PRIMARY SOURCES
12 OPEN CONFLICTS

SOURCES				
D Client's <i>Application Features</i> document				
R Admin-portal screen recording				
P Clickable prototype website				
#	ISSUE	ONE SOURCE SAYS	ANOTHER SAYS	WHAT MUST BE DECIDED
01	Is the QR a pass, or a ticket to enter once? BLOCKING	D §7: the QR is part of the pass — “available in-app and optionally as a downloadable/shareable pass”, with pass status <i>Active, Used, Cancelled, Expired, Blocked</i> .	P My Pass mints a fresh code on demand, scoped to one pandal, headed <i>ONE-TIME ENTRY</i> , counting down from 03:00: “Valid once. Expires in 3 mins.”	A code that must be minted at the gate cannot be downloaded, shared or cached; its lifecycle is not the pass’s lifecycle. This single answer sets the gate design, the offline story, the fraud posture and the data model. Settle it before anything else.
02	What level does capacity live at? BLOCKING	D §5: “Capacity controls at Pandal / date / slot / pass-type level” — all four at once.	R Pass Configuration caps passes per <i>row</i> (type + group + date range + time range + price). The pandal master shows one flat <i>Capacity</i> per pandal (2,000 / 3,500 / 2,800).	Three different units of inventory, not obviously nested. Pick the one that holds the count — everything else becomes a derived view. Also unanswered: does a City Pass consume capacity at every pandal it covers? If not, what stops a pandal filling with City Pass holders?
03	Does a City Pass have a date and a time slot? BLOCKING	P <i>CityPassPuja</i> goes straight from pandal selection to <i>Continue to payment</i> — no date, no slot.	P <i>CityVisitDateTimeUpdated</i> gives every selected pandal a visit date, a time slot and a pass-category toggle. Both screens are live in the same click flow.	These are two different products under one name. Is a City Pass an undated roaming right, or an Individual Pass sold as a bundle? The answer changes whether it can be capacity-controlled at all.
04	Three incompatible pass taxonomies HIGH	D §5: General, Preview, VIP, Family, Group — “plus configured special pass types”.	P R Everywhere else: Individual, Group, City. And inside the City flow, a per-pandal category of <i>Family Pass</i> / <i>Sponsor Pass</i> .	Product, category and tier are being used interchangeably. Separate them explicitly: the <i>shape</i> of the pass (how many pandals, whose dates), the <i>tier</i> that prices it, and the <i>channel</i> it came through (retail vs sponsor pool). Naming this wrong will hard-code the confusion.

#	ISSUE	ONE SOURCE SAYS	ANOTHER SAYS	WHAT MUST BE DECIDED
05	How many people does a Group Pass cover? HIGH	P Checkout: “Up to 4 members”, with the order summary line <i>Members covered · Up to 4</i> .	P My Pass: “Shib Mandir Squad — Includes 18 members”. The group picker lists “18 Pujas”, which is a count of pandals .	Both strings sit in the same source file , so this isn’t drift between screens — one flow asserts both. Group size and the group’s pandal list have been conflated . Decide whether party size is a property of the pass, the group, or the price tier.
06	Two separate service catalogs HIGH	P The app Menu offers four <i>platform</i> services with bespoke forms: Curated Tours ₹750, Puja By Your Name ₹501, Special Assistance ₹350, Aarti Slot ₹251.	R Pandal Admin maintains its own catalog — VIP Darshan ₹500, Prasad Delivery ₹150, Photography ₹800, Heritage Walk ₹300 — each with price and available days. The service checkout screens use this catalog.	Are these one thing or two? Platform services need fixed, form-specific schemas; pandal services need a generic price-and-days record. If they are one table, the bespoke forms need a home; if two, the app must show both and the reports must add them up.
07	Manual exception admission HIGH	D Web §11 requires “manual exception handling for authorized staff”, with entry/exit logs and gate-wise reporting.	P R No override control exists anywhere. The gate app offers only Valid / Expired / Duplicate; the admin has no exception queue.	Gates will need this on the night — a dead phone, a flat battery, a code that will not mint. Decide who may override, what they must record, and whether an override still consumes capacity .
08	Sponsor pool arithmetic doesn’t close HIGH	R Sponsor Overview: Purchased 850, Issued 115, Remaining 735. Per-pandal purchases are $500 + 200 + 150 = 850$.	R <i>Distribution by Pass Type</i> prints 735 remaining on every row — Individual, Group and City alike — while issuing 80, 35 and 0.	Either “remaining” is one shared pool rendered once per row, or the figures are decorative. Is a sponsor’s pool one balance or one per pandal, and is it typed by pass? This is the invariant the whole hierarchy rests on — it must hold under concurrent issuance.
09	Sub-sponsor passwords shown in clear text BLOCKING	R The Sub-sponsors table displays a Password column — eDP@4821 — readable by the sponsor and by the Super Admin. The same table appears in the Super Admin portal.	D Web §1 expects secure login, role-based authorisation, password reset and an admin audit trail.	The platform is creating accounts for third parties and then showing their credentials to other tenants. Replace with an invite-and-set-own-password flow . Do not build the screen as drawn.
10	Branding entitlement is exceeded on screen MEDIUM	R Sponsor Branding: “Your Gold Sponsor package includes 2 banner placement(s) · 3 in use.”	D Web §8 explicitly requires the system to “prevent unauthorized benefits by enforcing package entitlements”.	The mockup demonstrates the exact failure the requirement forbids. Decide where the limit bites — refuse the upload, allow it but hold approval, or allow overage and bill it.

#	ISSUE	ONE SOURCE SAYS	ANOTHER SAYS	WHAT MUST BE DECIDED
11	Super Admin navigation is mislabelled MEDIUM	R <i>Groups</i> opens a pandal master — 14 pandals with capacity, visits today, and an Open / “Opens Oct 12” lifecycle, plus + <i>Add Pandal</i> .	R <i>Donations</i> opens a combined passes- and -donations report. Neither label describes its screen.	Cheap to fix now, expensive later. Rename before coding , or these labels leak into routes, endpoints and permissions and stay wrong for the life of the system.
12	Registration channel MEDIUM	D Mobile §1: “Mobile number/ email registration with OTP verification.”	P Sign-up takes a full name and a ten-digit mobile behind a fixed +91. No email field anywhere in the visitor app.	Email is the only channel that survives a lost phone number, and it is the natural receipt address. Decide whether email is an identity or just a contact field — it changes the account model and the OTP provider.

Not listed: the two Pass ID formats (visitor EDP–2026–1842 vs admin UP–10482) — a presentation choice, not a conflict. It matters only that whichever survives is treated as a **reference and never as an authenticator**, so that no “look up by pass ID and admit” path is ever built at a gate. ·

Also unresolved, but not contradictions: whether gates work offline (D calls it “may be considered”); whether the platform settles money it collects; what an eligibility category actually grants; and the absent peak-load, uptime and retention figures.