Bootstrap Modal

- Model is used to display a dialog box.
- You can open and close the dialog dynamically.

Class	Description
.modal	It is a container for dialog. All dialogs are kept inside modal.
.modal-dialog	It configures a dialog box in model.
.modal-content	It defines the content to display in dialog. Content comprises of header, body, footer.
.modal-header	Header content.
.modal-body	Body content.
.modal-footer	Footer content.
.modal-title	Title text.
.modal-dialog-scrollable	It will set overflow to scroll.

.modal-dialog-centered	It keeps the dialog center screen.

Ex:

```html
<!DOCTYPE html>
<html>
  <head>
    <title>Modal</title>
    <link rel="stylesheet"
href="../node_modules/bootstrap/dist/css/bootstrap.css">
  </head>
  <body class="container-fluid">
    <div class="mt-3">
      <button data-bs-toggle="modal" data-bs-target="#login" class="btn btn-primary">Login</button>
      <a href="#register" class="btn btn-link" data-bs-toggle="modal">Register</a>

      <!--Login Modal-->
      <div class="modal fade" id="login">
        <div class="modal-dialog modal-fullscreen ">
          <div class="modal-content">
            <div class="modal-header">
              <h3>User Login</h3>
              <button data-bs-dismiss="modal" class="btn btn-close"></button>
            </div>
            <div class="modal-body">
              <dl>
                <dt>User Name</dt>
                <dd>
                  <input type="text">
                </dd>
                <dt>Password</dt>
                <dd>
                  <input type="password">
                </dd>
              </dl>
            </div>
            <div class="modal-footer">
              <button class="btn btn-primary">Login</button>
              <button data-bs-dismiss="modal" class="btn btn-danger">Cancel</button>
```

```html
                </div>
              </div>
            </div>
          </div>
        <!--Register Modal-->
        <div class="modal fade" id="register">
          <div class="modal-dialog modal-dialog-scrollable">
              <div class="modal-content">
                  <div class="modal-header bg-warning">
                      <h3>Register New User</h3>
                      <button data-bs-dismiss="modal" class="btn btn-
close"></button>
                  </div>
                  <div class="modal-body">
                      <dl>
                        <dt>User Name</dt>
                        <dd><input type="text"></dd>
                        <dt>Password</dt>
                        <dd><input type="text"></dd>
                        <dt>Mobile</dt>
                        <dd><input type="text"></dd>
                        <dt>Email</dt>
                        <dd><input type="text"></dd>
                        <dt>Date of Birth</dt>
                        <dd><input type="text"></dd>
                        <dt>City</dt>
                        <dd><input type="text"></dd>
                        <dt>Postal Code</dt>
                        <dd><input type="text"></dd>
                      </dl>
                  </div>
                  <div class="modal-footer">
                      <button class="btn btn-primary">Register</button>
                  </div>
              </div>
          </div>
        </div>
    </div>
    <script src="../node_modules/jquery/dist/jquery.js"></script>
    <script
src="../node_modules/bootstrap/dist/js/bootstrap.bundle.js"></script>
  </body>
</html>
```