SVKM's NMIMS · Mukesh Patel School of Technology Management & Engineering, Mumbai

Modern Day Robotics & Its Industrial Applications (MDRIIA - 702CO0E012) · B.Tech Computer Science & Business Systems (CSBS), in partnership with TCS · AY 2026–27 Odd Semester

GROUP 03 TECHNICAL DOSSIER

Capstone ICA (20 marks): CDIO Robotics Engineering & MuJoCo Physics 10 · CSBS Techno-Economic Business Systems Analysis 5 · Studio Showcase & Viva Voce 5

Group · project	Group 03 · Autonomous Last-Mile Ground AED Delivery Robot for Sudden Cardiac Arrest
Monorepo folder	https://github.com/sunny-nanade/NMIMS-MPSTME-MDRIIA-2026/tree/main/Group_03_Kashish_Vaishnavi
Submit (3 places)	(1) PDF on MS Teams, turned in by EVERY member · (2) this filled Word file AND its PDF committed to Group_03_Kashish_Vaishnavi/docs/MDRIIA_Group_03_Technical_Dossier.docx / .pdf · (3) LinkedIn video URL in Section 5. Due Monday, 26-Oct-2026, 23:59 IST. Studio Showcase, Expo & Viva Voce: Saturday, 31-Oct-2026.
No slides	There is no PPT for MDRIIA. At the Expo and in your video you present the live MuJoCo simulation, your business sensitivity graphs, and a webcam picture-in-picture of every member.
How to fill this file	Use Microsoft Word (desktop). Choose answers from the 'Select ▾' drop-downs and type into the 'type here' fields. Do not delete or retype them and do not edit this file in Google Docs: the fields are how your answers are read.

Student name	Roll No.	SAP ID	Capstone role(s)	Specialisation (finalised titles sheet / monorepo)
Kashish Praveen Jain	E026	70362400060	Autonomous Navigation / Vision Specialist + CSBS Business & Techno-economic Systems Analyst	Lead Autonomous Navigation & Traffic Congestion Modeling Specialist
Vaishnavi Parashar	E046	70362400074	Lead Robotics Systems Architect + Telemetry QA Lead	MuJoCo Dynamic Chassis Modeler & Path Optimization Engineer

Roll numbers and SAP IDs are from the official student list. Tell Dr. Nanade by Tuesday, 20-Oct-2026 if any name, ID or role is wrong. Groups with fewer than four members combine roles as shown.

SECTION 1 · Problem Bottleneck, Industry Standards & Aalborg Research Title *Component 1 · CDIO Robotics (10)*

Authorised Aalborg title	Can an autonomous last-mile ground AED delivery vehicle simulated in MuJoCo reduce time-to-first-shock below urban ambulance congestion delays (15-20 minutes), given that sudden cardiac arrest survival drops 7-10% for every minute without defibrillation?
Original draft topic	Autonomous ambulance robot for medical emergencies
Why the title changed	The student team identified a critical clinical reality: sudden cardiac arrest (SCA) survival decays exponentially (7-10% per minute delay), whereas dense metropolitan ambulance response routinely exceeds 15-20 minutes. However, the student draft mentioned 'Delhi' specifically without specifying whether the robotic mechanism is an airborne drone or a ground AMR, and did not define the physical MuJoCo simulation environment or vehicle dynamics.

1.1 Baseline friction: claim verification table

Each statement was carried over from your titles sheet or your monorepo scripts. Before you use it anywhere (dossier, video, paper), find the primary source yourself and record it, or correct or delete the claim. Statistics: cite the original study, not a blog or an AI answer.

Claim (as carried over)	Faculty pre-audit note	Primary source you verified (author, year, venue, DOI/URL)	Source type	Keep / Correct / Delete
Sudden cardiac arrest survival drops 7–10% for every minute without defibrillation.	*Widely cited (e.g. Larsen et al., 1993, Annals of Emergency Medicine; resuscitation guidelines). Cite the primary paper, not a secondary web page.*	Kim TY et al. (2026) 2025 Korean CPR Guidelines Part 4, Clin Exp Emerg Med 13:S32-S60, doi:10.15441/ceem.26.073: 7-10 %/min without CPR (a guideline rule of thumb, not a fitted coefficient). Larsen MP et al. (1993) Ann Emerg Med 22(11):1652-1658, doi:10.1016/S0196-0644(05)81302-2: fitted loss 0.023 (CPR) + 0.011 (shock) + 0.021 (ACLS) = 5.5 %/min; the starter value 0.046 for the shock term is not in that model.	Peer-reviewed paper (DOI)	Correct
Sudden cardiac arrest claims over 700,000 lives annually in India, with less than 2% out-of-hospital survival.	*Published estimates vary widely. Find the primary epidemiological study, report its range, or delete.*	No primary source found for 700,000 deaths or <2 % survival. Regional evidence: Telangana WACAR registry (PMC12369094) reports ROSC <10 % and 1.3 % discharge; an Indian Heart Journal 2023 review gives survival <10 %. India has no national arrest registry. The 700,000 figure appears only in an uncited hospital blog.	No source found	Delete
Dense metropolitan ambulance response routinely exceeds 15–20 minutes.	*Find a city-specific source (state emergency-service data or a peer-reviewed study).*	Naess LE et al. (2024) PLOS ONE 19, doi:10.1371/journal.pone.0296308 (Central Norway, n=216,787): urban response median 10.0 min, 90th percentile 17.7 min. Not an Indian city and not 15-20 min as a median; no Mumbai-specific peer-reviewed study was found. 15-20 min is therefore run as a scenario.	Peer-reviewed paper (DOI)	Correct

1.2 Governing industry standards

Decide for each standard whether it governs your system, and name the clause or requirement you design against (cite number, part and year). 'No' is a correct answer when you can say why. The hint is the faculty view; you may disagree with a reason.

Standard	Scope	Faculty hint for your project	Applies?	Clause / requirement you use, or why not
ISO 10218-1/-2	Safety requirements for industrial robots (robot, and robot integration)	*No*	No	Industrial robot-arm cells. The pod is a mobile ground vehicle with no manipulator.
ISO 3691-4	Driverless industrial trucks / AMRs and their systems: safety requirements	*Partly: driverless vehicle safety principles, but it operates on public roads/sidewalks*	Partly	Braking distance s = v^2/(2 mu g) + v t_detect, FOV >= 180 deg, 1.5 m / 0.4 m zones (course manual 2.2). MET: s = 0.26 m at 1.8 m/s, mu = 1.0, t_detect = 50 ms Detection latency: MET: 50 ms modelled reaction time in the safety filter
ANSI/RIA R15.06	US national adoption of ISO 10218 (industrial robot safety)	*No*	No	US adoption of ISO 10218; same reason: no industrial manipulator.
IEC 60601-1	Medical electrical equipment: basic safety and essential performance	*Partly: the AED payload itself is medical electrical equipment*	Partly	The AED is the medical device; the pod only protects it from shock (budget 3 g). On the course vehicle at 3.5 m/s cruise, 250 runs: 96 % stay within 3 g, worst 3.44 g (deviation recorded).
Domain-specific	No standard covers sidewalk delivery robots in India yet: state what your design assumes	*Recommended: check it*	Yes	No standard covers sidewalk delivery robots in India. Design assumes the ISO 3691-4 / ISO 13482 limits above, a 3 g payload budget and an 18 deg roll limit. Recorded deviation: ISO 13482 shared-zone speed 0.8 m/s vs the pod's 1.4 m/s pedestrian cap (analytics/standards_check.csv).

1.3 Documented baseline friction (who struggles, with what, how it is measured today)

Baseline metric and its value today (with unit)	Ambulance response (call to arrival), urban Central Norway: median 10.0 min, p90 17.7 min; survival lost without shock ~1.1 %/min (Larsen shock term). Course scenario 15-20 min is swept, not assumed.
Source of the baseline value (author, year, DOI/URL)	Naess LE et al. 2024, PLOS ONE 19, doi:10.1371/journal.pone.0296308; Larsen MP et al. 1993, doi:10.1016/S0196-0644(05)81302-2
Who carries the cost today (role / stakeholder)	Out-of-hospital cardiac-arrest patient and bystander; EMS dispatchers and ALS crews (ambulance hours)

SECTION 2 · MuJoCo Rigid-Body Physics Modelling & Python Closed-Loop Control *Component 1 · CDIO Robotics (10)*

MuJoCo mechanism (titles sheet)	MuJoCo MJCF Rigid-Body Model with Autonomous Last-Mile Ground AED Delivery Robot for Sudden Cardiac Arrest Physics & Closed-Loop Control
MJCF model	Group_03_Kashish_Vaishnavi/models/aed_delivery_amr.xml
Controller	Group_03_Kashish_Vaishnavi/src/aed_navigation_controller.py
Contact & solver settings in the model today	timestep 0.002 s (500 Hz) · wheel / ground friction 1.1 / 0.01 / 0.005 · 2 motors (drive, steer) · solref default (0.02 1)
Core state machine (FSM)	DISPATCH → ROAD_CRUISE (3.5 m/s) → CURB / SIDEWALK (1.2 m/s) → ARRIVE → AED_HANDOVER; payload acceleration ≤ 3 g in every state
Equations of motion & control	Newton-Euler (rigid body): $m\cdot\dot{v} = \Sigma F$, $I\cdot\dot{\omega} + \omega \times (I\cdot\omega) = \Sigma\tau$; multibody form $M(q)\cdot\ddot{q} + C(q,\dot{q})\cdot\dot{q} + g(q) = \tau + J^T\cdot f_{ext}$ Longitudinal dynamics: $m\cdot a = F_{traction} - F_{roll} - \frac{1}{2}\rho C_d A\cdot v^2$; slip ratio $s = (\omega\cdot r - v) / \max(\omega\cdot r, v)$ TTFS = t_dispatch + d / v̄ + t_handover; survival P(t) from the Larsen model in your ROI script PID tracking: $u(t) = K_p\cdot e(t) + K_i\cdot\int e\,dt + K_d\cdot\dot{e}(t)$ Damped least-squares IK (manipulators): $\Delta q = J^T\cdot(J\cdot J^T + \lambda^2\cdot I)^{-1}\cdot\Delta x$

Faculty code audit: Your CSBS analyst (E057) moved to Group 11. The CSBS role is now shared as listed in the roster; confirm with Dr. Nanade.

Faculty code audit: v_ambulance_kmh = 7.5 is a congested-traffic assumption. Source it (city data) or present it as a scenario in your sensitivity graph.

2.1 Model and controller settings you actually used (from your final code)

MJCF timestep (s) in the final model	0.002 s (500 Hz); implicitfast integrator, pyramidal friction cone
Main contact friction (sliding / torsional / rolling)	course vehicle: tyre 1.1 sliding (the starter MJCF value), 0.005 torsional, 0.0001 rolling; the scenario sampler then draws the sliding coefficient from U(0.7, 1.1), and from U(0.35, 0.6) in the slippery family
solref (timeconst dampratio) and why you chose it	tyre geom solref = 0.1252 s, damping ratio 1.0, calibrated so the effective radial tyre stiffness is the guide's k_t = 30 kN/m (30.0 kN/m measured with sim.validate.tyre_stiffness); the repository default 0.03 s gives ~196 kN/m. Suspension, masses and isolator are the guide's: k_s 4500 N/m, c_s 350 N s/m, 6.5 kg sprung and 2.25 kg unsprung per corner
Controller law used	Potential field / DWA
Final gains (e.g. Kp, Ki, Kd or λ) with units	DWA scoring weights: progress 1.0, centring 0.5, speed 1.0, clearance 1.2, heading 0.2; horizon 2.4 s, dt 0.15 s, a_max 1.6 m/s^2, a_brake 2.0 m/s^2; FSM caps: ROAD_CRUISE 3.5 m/s (the guide's value), CURB_SIDEWALK >= 1.2 m/s, launch 1.0 m/s^2, brake 1.5 m/s^2; kerb friction belief 0.35 and safety-filter reaction time 0.05 s, both chosen on tuning seeds 60000+ (the evaluation seeds start at 70000)
FSM states implemented in code (list)	DISPATCH, ROAD_CRUISE, CURB_SIDEWALK, ARRIVE, AED_HANDOVER (src/aedrover/capstone/fsm.py)
Model loads and runs: python -c "import mujoco; mujoco.MjModel.from_xml_path(...)"	Yes

2.2 Authorship of each script

Several scripts were provided as starter scaffolds. Mark honestly what you wrote, changed, or used as given. Viva questions target the code you claim.

File	Written / Modified / Used as given	Main author (Roll)	What you changed or added (1 line)
models/aed_delivery_amr.xml	Select ▾	Select ▾	type here
src/aed_navigation_controller.py	Select ▾	Select ▾	type here
analytics/cardiac_survival_economics.py	Select ▾	Select ▾	type here
type here	Select ▾	Select ▾	type here
type here	Select ▾	Select ▾	type here

2.3 Key code snippet (≤ 25 lines) implementing your FSM or control law:

```
                        src/aedrover/capstone/fsm.py  (lines 104-127)
                        104      def update(self, obs: dict) -> State:
105          """Advance the state machine from the observation; returns the new state."""
                    106          p, t, x = self.params, obs["t"], obs["x"]
                       107          if self.state is State.AED_HANDOVER:
                                 108              return self.state
                              109          if self._sc.x_goal - x <= p.arrive_m:
        110                      self._go(t, State.ARRIVE, f"goal within {p.arrive_m:.1f} m")
                                111          elif self.state is State.DISPATCH:
                                    112              if t >= p.t_dispatch_s:
   113                              self._go(t, State.ROAD_CRUISE, f"t >= {p.t_dispatch_s:.1f} s")
                                     114          elif self.in_kerb_zone(x):
              115                       self._go(t, State.CURB_SIDEWALK, "kerb edge ahead")
                                 116          elif self.state is State.CURB_SIDEWALK:
```

2.4 Free-body diagram and one equation worked with your own numbers and units:

Free-body diagram: hand sketch to be attached by the team (forces on one wheel: N, F_traction, F_roll, m g; chassis: payload isolator force).

Symbols: TTFS = t_dispatch + d / v_bar + t_handover (section 2, equation 3).

Worked example (run seed 70000, condition free_flow): t_dispatch = collapse-to-call 1.0 + call-to-alert 1.5 = 2.5 min; d = 500 m x 1.54 = 770 m; v_bar = path/time = 36.01 m / 21.00 s = 1.715 m/s; t_handover = 1.0 min.

TTFS = 2.5 + 770 / 1.715 / 60 + 1.0 = 10.983 min (column ttfs_min of analytics/aed_delivery_real_trials.csv).

30-second whiteboard rule: if a team member cannot explain an equation or code block on a whiteboard in 30 seconds without notes, simplify it or remove it. It will be asked in the viva.

SECTION 3 · CSBS Techno-Economic Business Systems Modelling *Component 2 · CSBS Techno-Economic (5)*

Business script	Group_03_Kashish_Vaishnavi/analytics/cardiac_survival_economics.py (rename or add *_roi.py if you restructure it)
CSBS business case (titles sheet)	CSBS Health-Economics Optimization: Sudden cardiac arrest claims over 700,000 lives annually in India, with less than 2% out-of-hospital survival due to traffic gridlock. Deploying micro-hubs of autonomous ground AED pods at 1.5 km radii across high-density metro zones costs a fraction of operating dedicated Advanced Life Support (ALS) ambulances. Every 1-minute reduction in time-to-shock saves tens of thousands of Quality-Adjusted Life Years (QALYs) nationally, presenting an unassailable public-health economic case for municipal smart city tenders.
Constants hard-coded in the script today	dist_km = 1.8, v_ambulance_kmh = 7.5, v_amr_kmh = 22.5, life_expectancy_yrs = 12.0, qol_factor = 0.85, kappa = 0.095 → each one needs a source in 3.1 or must be computed from your simulation.
Owner	CSBS Business & Techno-economic Systems Analyst: E026. Tags in this section carry that roll number.

Keep all money dimensionless: express costs as ratios to the baseline (no rupee or dollar amounts in the title, abstract or video). Every input needs a source or must be a clearly labelled assumption that you vary in the sensitivity graph.

3.1 Business model: formulas, your inputs and your results


Quantity	Formula (define every symbol in your script)	Inputs used, with source or 'assumption'	Result (with unit)
Labour reallocation H_reclaimed	H = ALS-ambulance hours not dispatched for AED-only calls (vehicle-hours/day)	calls/day 3.77 (zone 50 km^2, density 20000/km^2, incidence 55/100k/yr, x2.5 suspected), p_standdown 0.15, 1.5 h/call - all ASSUMPTION	H_reclaimed = 0.848 ALS vehicle-h/day = 0.149 FTE
Payback horizon P_payback (dimensionless)	P_payback = CapEx / (T_life · ΔOpEx_annual); P < 1 ⇒ pays back within life T_life. Also report T_payback = CapEx / ΔOpEx in months.	CapEx 34.6 ALS vehicle-yr (77 pods x 0.35 + 77 hubs x 0.1), life 8.0 yr, dOpEx = C_baseline - C_robot - ASSUMPTION	P_payback = inf (no payback: dOpEx <= 0); T_payback = inf
Normalised Cost Reduction Index NCRI	NCRI = (C_baseline − C_robot) / C_baseline (0–1); cost-parity ratio κ = C_robot / C_baseline = 1 − NCRI	C_robot 10, C_baseline 0.0353 ALS vehicle-yr/yr (pod opex 0.1, hub opex 0.03) - ASSUMPTION	kappa = 283; NCRI = -282 (course target kappa <= 0.25: not met)
Queuing delay	M/M/c: cardiac-arrest calls (λ per hour) served by c AED pods per micro-hub (μ per hour each). ρ = λ / (c·μ) < 1; M/M/1: W_q = ρ / (μ − λ); M/M/c: W_q = C(c, λ/μ) / (c·μ − λ) (Erlang C)	lambda 0.00204/h per hub, mu 2.17/h (service 27.6 min = round trip at measured 2.03 m/s + 0.25 h turnaround), c 1	rho = 0.000939; P(wait) = 0.000939; W_q = 0.026 min
Sensitivity analysis	Vary the most uncertain input ±30 % (or across your scenario range) and plot P_payback and NCRI; report the break-even value.	ohca_incidence_per_100k_yr (no verified national value), swept 0.5x to 400x of 55; +/- 30 % band shaded	break-even kappa=1 (cost parity): 3.96e+04; break-even kappa=0.25 (course target): 2.41e+06

Queuing model used	M/M/c
λ, μ, c values used (with units)	lambda = 0.00204 /h, mu = 2.17 /h, c = 1 per hub
Payback in months (T_payback)	no payback (infinite): the labour lens does not cover pod cost; see docs/CAPSTONE.md for the health lens
Script output reproduces every number above when re-run	Yes

3.2 FMEA: failure modes, effects and risk priority (RPN = S × O × D, each 1–10)

Two failure modes are seeded from your project; add at least two more. Score before and after your mitigation (design change, control limit, sensor, procedure). The post-mitigation RPN must be justified by something you can show in the simulation or the code.

Failure mode	Effect on mission / business	S	O	D	RPN pre	Mitigation (what you changed)	RPN post	Shown in
Wheel slip on wet road / curb climb → late arrival	Injury to a bystander, mission abort, loss of trust	9	10	6	540 (measured rate 54.8 %, baseline_unshielded, n=250)	CBF-style speed-and-separation safety filter on the swept footprint; DWA plans against predicted pedestrian motion	162 (O=6, D=3; measured rate 5.6 %, proposed, n=250)	Both
Payload shock > 3 g damages the AED	AED capacitor or electrodes damaged, device unusable at the scene	9	8	5	360 (measured rate 28.0 %, baseline_fast, n=250)	FSM CURB_SIDEWALK speed cap from the measured kerb table and a dynamic-window planner that slows for the kerb	225 (O=5, D=5; measured rate 3.6 %, proposed, n=250)	Both
Wheel slip or entrapment on a wet kerb	Late arrival or stranded pod: delayed first shock	8	10	5	400 (measured rate 84.0 %, baseline_fast, n=50)	Climb speed from the kerb table at a conservative friction belief; planner replans around the obstruction	400 (O=10, D=5; measured rate 76.0 %, proposed, n=50)	Both
Stall: no forward progress for 15 s	Mission aborted; ambulance remains the only response	7	9	4	252 (measured rate 43.2 %, baseline_fast, n=250)	Dynamic-window planner replaces constant-speed pure pursuit; FSM keeps a creep speed in every state	196 (O=7, D=4; measured rate 19.2 %, proposed, n=250)	Simulation
Rollover on an oblique kerb approach	Loss of vehicle and payload, possible injury	10	1	5	50 (measured rate 0.0 %, baseline_fast, n=250)	Roll-limit monitored as the stability index (18 deg); speed cap in CURB_SIDEWALK	50 (O=1, D=5; measured rate 0.0 %, proposed, n=250)	Simulation




SECTION 4 · Simulation Telemetry, Monte Carlo Testing & Empirical Validation *Component 1 · CDIO Robotics (10)*

Evaluation protocol (titles sheet)	Simulate N = 40 transit scenarios across different urban traffic density levels (free-flow, lane-splitting, pedestrian crowd sidewalk traversal). Track time-to-first-shock (TTFS), wheel slip ratio, payload acceleration (g-force to protect sensitive AED capacitors), and dynamic stability index.
Telemetry standard	Log at 500 Hz (MJCF timestep 0.002 s, or every 2nd step at 0.001 s): time, state (q, q̇ or pose, velocity), reference, tracking error, actuator torques/forces, FSM state, events. One CSV per run or one CSV with a run_id column.
Monte Carlo	N ≥ 30 runs per condition (more if your protocol says so). Randomise disturbances and initial conditions from stated distributions; record every random seed.
Required measures	Tracking RMSE = √(Σ‖p − p_ref‖² / n) on the planned route centreline vs MuJoCo chassis position; control effort E = ∫τ² dt (sum of τ²·Δt over all actuators); your primary task metric from the protocol.
Statistics	Compare the proposed controller with a baseline condition: Student's / Welch's t-test (two-sided, α = 0.05), Cohen's d = (x̄₁ − x̄₂) / s_pooled, and a 95 % confidence interval.
Where real trial data goes	Group_03_Kashish_Vaishnavi/analytics/*_real_trials.csv, produced by your controller. Files named SIMULATED_* are starter targets, never results.
Owner	Telemetry QA Lead: E046.

Baseline condition you compare against	Pure pursuit at constant 1.4 m/s + the same safety filter ('baseline'), on the same course vehicle. FMEA references: the unfiltered run ('baseline_unshielded') and pure pursuit at the 3.5 m/s cruise speed ('baseline_fast')
Monte Carlo runs per condition (N)	50 per condition and controller, 5 conditions (1250 episodes); protocol pool n=150 per controller
Randomised parameters and their distributions	per seed: kerb height U(0.09, 0.15) m, tyre friction U(0.7, 1.1) (slippery: U(0.35, 0.6)), payload mass U(3, 5) kg, obstacle and pedestrian layout and speeds, sensor noise (sim/scenario.py); conditions: free_flow, lane_splitting, crowd (protocol) + kerb, slippery (stress)
Logging rate actually achieved (Hz)	500.0 Hz (min 500.0, max 500.0)
Random seeds recorded for every run	Yes
Real-trials CSV path(s) in the repo	Group_03_Kashish_Vaishnavi/analytics/aed_delivery_real_trials.csv

Measure	N	Baseline mean ± SD	Proposed mean ± SD	Unit	Better? (direction)
Tracking RMSE	68 / 116 successful of 150 runs each	0.0232 +/- 0.0128	0.808 +/- 0.33	m	Lower is better
Control effort $\int \tau^2 dt$	68 / 116 successful of 150 runs each	928.1 +/- 1785	5381 +/- 6455	N^2 m^2 s	Lower is better
Time to first shock (TTFS, from collapse)	68 / 116 successful of 150 runs each	13.8 +/- 2.72	10.5 +/- 2.79	min	Lower is better

Test used	Welch's t-test
t statistic, degrees of freedom, p-value (primary metric)	t = 7.945, df = 143.4, p = 5.19e-13 (successful runs, protocol conditions pooled)
Cohen's d (primary metric)	d = 1.205
95 % confidence interval of the difference	[2.504, 4.162] min (baseline - proposed)



DATA PROVENANCE DECLARATION (mandatory). Reporting generated target numbers as experimental results is research misconduct and scores zero for this component.

Every number in Section 4 comes from MuJoCo runs of OUR controller, logged by our code	Yes
No value comes from SIMULATED_* files, generate_paper_figures.py or any np.random 'target' data	Yes
Our plots re-generate from the *_real_trials.csv files in the repo	Yes
Every input in Section 3 has a source or is labelled as an assumption	Yes

SECTION 5 · LinkedIn Video Showcase, AI Verification Audit & Peer Review *Component 3 · Showcase & Viva (5)*

LinkedIn post URL	type here
Video length (mm:ss)	type here
Video shows the live MuJoCo simulation (not slides)	Select ▾
Video shows our business sensitivity graph	Select ▾
Webcam picture-in-picture: every member appears and speaks	Select ▾

5.1 AI Interaction Audit Log: three cases where AI gave wrong robotics or economic data

Examples: a wrong MuJoCo attribute or API call, an invented statistic, a correct paper given the wrong journal, an economic formula with the wrong units. Show how you checked each one with a textbook, the official documentation or the original paper.

#	AI tool	What we asked & what AI said	How we caught it	What was actually true (with source)	Error type	Verdict
AI-01	Select ▾	type here	Select ▾	type here	Select ▾	Select ▾
AI-02	Select ▾	type here	Select ▾	type here	Select ▾	Select ▾
AI-03	Select ▾	type here	Select ▾	type here	Select ▾	Select ▾

5.2 Peer review: watch both assigned LinkedIn videos and score them (0–2 per criterion)

Group reviewed	Problem	Physics	Business	Data	Clarity	Best moment (mm:ss)	One question for the viva
Group 04: Multi-Arm Robotic Gripper for Non-Cooperative Space Debris Capture in LEO	Select ▾	Select ▾	Select ▾	Select ▾	Select ▾	type here	type here
Group 09: Autonomous Ground Vehicle (UGV) with LiDAR Perception for Hazardous Terrain Reconnaissance	Select ▾	Select ▾	Select ▾	Select ▾	Select ▾	type here	type here

SECTION 6 · Individual Learning Record & Research Consent *unmarked · one row per member · answer honestly*

These answers do not change your marks. They help improve the course and are used in anonymised research only if you consent in the sign-off below. Commit share: your commits ÷ the group's commits in your folder (git shortlog -sn -- <folder>).

Member	Hours I spent (total)	My declared role matched my actual work (1 = not at all, 5 = fully)	I learned a skill outside my role (robotics ↔ business)	Scripts I mainly wrote (file names)	My commit share (%)	Share of my writing first drafted with AI	Wrong AI facts / code I personally caught
Kashish Praveen Jain (E026)	type here	Select ▾	Select ▾	type here	type here	Select ▾	Select ▾
Vaishnavi Parashar (E046)	type here	Select ▾	Select ▾	type here	type here	Select ▾	Select ▾

Member	Before this course I had used a physics simulator	The most valuable thing I learned (one line)	One thing I would change in this course (one line)
Kashish Praveen Jain (E026)	Select ▾	type here	type here
Vaishnavi Parashar (E046)	Select ▾	type here	type here

Track A: how this dossier becomes your 4-page IEEE paper

I. Introduction	Section 1: title, verified baseline friction, governing standards
II. Related work	Section 1.1: verified sources only (5+ with DOIs)
III. System model	Section 2: MJCF model, FSM, equations, control law
IV. Techno-economics & evaluation	Sections 3–4: CSBS model, FMEA, Monte Carlo results, statistics
V. Discussion & limitations	Sim-to-real gap, assumptions in the business model, AI audit lessons
Target venues (titles sheet)	A: IEEE INDICON · B: IEEE/RSJ IROS

Individual Academic Sign-off *every member answers and signs*

Answer each statement for yourself: (1) this work is original and every source and AI use is declared; (2) our model loads and our controller and business scripts run from the repository; (3) I understand our whole project and can explain my own part in the viva voce.

Member (Roll)	(1) Original work	(2) Code runs	(3) Viva-ready	Signature	Optional research consent*
Kashish Praveen Jain (E026)	Select ▾	Select ▾	Select ▾		Select ▾
Vaishnavi Parashar (E046)	Select ▾	Select ▾	Select ▾		Select ▾

**Optional: may Dr. Nanade use anonymised data from this dossier and repository in education research publications? Your answer has no effect on your marks, and you can withdraw until results are published.*