

Denoising-Time Steering Along a Paired Skin-Tone Direction in SDXL:

A Prospectively Frozen Matched-Change Study

Arnav Sharma
The Pennsylvania State University

Abstract

We study whether a linear direction estimated from paired portrait latents can control visible skin tone in Stable Diffusion XL while preserving other image properties. The proposed method computes a paired mean difference in the VAE latent space, applies a spatial Gaussian mask, and distributes the resulting perturbation across denoising steps. We freeze a matched-change evaluation after calibration, estimate the direction from 64 of 96 noise-coupled prompt pairs, validate an image-colour instrument on the remaining 32, and evaluate 570 conditions over 30 held-out seeds. The parent study found no detectable face-embedding advantage, but masking reduced LPIPS relative to unmasked steering by 0.023 lighter and 0.082 darker (Holm-adjusted $p = .012, .002$). We then prospectively fixed an independent-seed replication with new direction data and 30 new seeds. Its LPIPS advantages were again positive: 0.024 ([0.005, 0.041]) lighter and 0.041 ([0.018, 0.065]) darker. The locked decision was nevertheless inconclusive: only 8 and 10 shared matched seeds were available, below the minimum of 12, and the lighter two-test Holm value was .056 (darker .019). The cross-campaign masked-direction cosine was 0.919. The evidence supports a localized perceptual-preservation signal under this SDXL protocol, not strict replication, identity preservation, disentanglement, or bias mitigation. Skin tone is treated only as an apparent visual attribute, never as a proxy for race or ethnicity.

1 Introduction

Latent diffusion models synthesize high-resolution images by denoising in a compressed representation rather than directly in pixel space [9]. SDXL extends this family with a larger U-Net and richer conditioning [8]. These models offer expressive control but also make it difficult to isolate one visual attribute without changing identity, pose, or composition.

Linear semantic directions have been effective in GAN latent spaces [11]. We ask whether an analogous direction, estimated from paired SDXL VAE encodings, can be used during diffusion sampling. Our technical hypothesis is that a denoiser can absorb small perturbations injected throughout sampling more coherently than a single post-hoc edit. Our scientific hypothesis is narrower: at a matched change in measured skin tone, stepwise masked injection will preserve non-target properties better than relevant baselines.

We make three contributions. First, we specify the paired estimator and denoising-time intervention. Second, we provide a prospectively frozen matched-change comparison and a prospectively specified independent-seed replication that separate target response from preservation. Third, we release an auditable research artifact with immutable model and data hashes, measurement validation, seed-level uncertainty, missingness, and failures.

2 Related work

This study does not claim that semantic directions in diffusion models are new. Asyrp identifies a semantic representation space inside frozen diffusion U-Nets and manipulates directions across the reverse process [5]; later work discovers concept-specific internal directions for text-to-image generation [6]. Concept Sliders instead learn low-rank parameter directions for continuous, composable control [1]. Our narrower object of

study is a direction formed directly from paired SDXL VAE encodings, added to scheduler latents throughout sampling without optimization. The empirical question is whether that simple intervention offers a preservation advantage at matched target response, not whether diffusion representations admit semantic control in general.

3 Construct and scope

Race and ethnicity are socially constructed and multidimensional, not fixed one-dimensional visual attributes [3]. The intervention in this study is therefore called a *skin-tone direction*. It must not be interpreted as changing, estimating, or classifying race. Even datasets designed to balance face categories must operationalize a limited set of visual labels, and report performance consequences from category imbalance [4]. The present method is intended for controlled generative-model research and auditing, not profiling or decisions about people.

4 Method

Let $E(x)$ be the deterministic posterior-mode encoding of an image under the SDXL VAE. Given n noise-coupled prompt pairs (x_i^L, x_i^D) generated with the same seed and prompt template but different skin-tone descriptors, the raw direction is

$$v = \frac{1}{n} \sum_{i=1}^n [E(x_i^D) - E(x_i^L)]. \quad (1)$$

Seed reuse controls the initial diffusion noise but does not guarantee the same apparent identity after conditioning changes. Identity, composition, prompt wording, and illumination therefore remain potential training-direction confounders.

We multiply v by a spatial mask $M \in [0, 1]^{H \times W}$ centered on the face:

$$M(p) = w_e + (w_c - w_e) \exp \left[-3 \left(\frac{\|p\|_2}{r} \right)^2 \right], \quad \tilde{v} = M \odot v, \quad (2)$$

where the study uses center weight $w_c = 1$, edge weight $w_e = 0.3$, and radius $r = 1$. For T reverse-diffusion steps and steering magnitude α , the pipeline updates the scheduler latent after each step by

$$z_t \leftarrow z_t + \frac{\alpha}{T} \tilde{v}. \quad (3)$$

All runs use SDXL base 1.0 revision 462165984030 at 1024×1024 resolution. The implementation uses 25 DPM-Solver++ multistep updates [7] with classifier-free guidance 7.5.

5 Evaluation design

The target response and preservation outcomes must be measured separately. The continuous target proxy uses cheek-pixel CIE Lab individual typology angle (ITA). Instrumental ITA decreases as measured pigmentation increases [14], but apparent skin color in images is affected by hue, illumination, and acquisition conditions and is not fully represented by a single light–dark axis [12]. We therefore validate ordering and prespecified illumination perturbations on a held-out split and describe the result only as apparent image color.

The primary preservation outcome is face-embedding similarity, following the general embedding approach of FaceNet [10], at a matched continuous skin-tone change. Secondary outcomes are LPIPS perceptual distance [15], background-only SSIM [13], head-pose drift, face-detection failure, and monotonicity.

The confirmatory design used held-out seeds and four methods: prompt-only generation, post-hoc latent addition, unmasked stepwise injection, and masked stepwise injection. The frozen configuration contains 30 held-out generation seeds and method-specific grids frozen after calibration. Comparisons are paired

Table 1: Held-out validation of the continuous image-colour instrument.

Criterion	Required	Observed
Detection rate	≥ 0.95	1.000
Pair-order accuracy	≥ 0.90	0.969
Median pair gap (ITA)	≥ 8.0	16.67
Median perturbation shift	≤ 2.0	0.40
95th-percentile shift	≤ 5.0	3.06

within seed. We report means, standard deviations, medians, detector failures, and 95% seed-level bootstrap confidence intervals; secondary confirmatory tests use Holm correction. A run cannot pass when a required metric is missing.

After fixing the parent result, we prospectively specified an independent-seed replication with a newly generated 96-pair campaign, 64 pairs for a new direction, 32 for the unchanged validation gates, and evaluation seeds 600000–600029. The model revision, method grids, target, tolerance, outcomes, and bootstrap procedure remained fixed. The locked replication family contains only the lighter- and darker-direction masked-versus-unmasked LPIPS contrasts. Strict replication requires both positive estimates, both ordinary 95% bootstrap intervals above zero, and both two-test Holm-adjusted $p < .05$; either nonpositive estimate is failure, while fewer than 12 shared matched seeds in either direction is inconclusive. Parent and replication samples are reported separately rather than pooled as a 60-seed confirmatory study.

6 Pre-confirmatory validation and calibration

The direction-data campaign generated 96 noise-coupled light/dark prompt pairs. We reserve 64 pairs for direction estimation and 32 pairs for measurement validation. The ITA instrument detected the face and cheek regions in all 32 held-out pairs, ordered the light-descriptor image above the dark-descriptor image in 31 of 32 pairs (96.9%), and produced a median within-pair separation of 16.67 ITA degrees. Across prespecified brightness and white-balance perturbations, the median absolute ITA shift was 0.40 degrees and the 95th percentile was 3.06 degrees. Table 1 shows that every frozen gate passed before confirmatory generation.

Calibration used seeds disjoint from both the direction-data and confirmatory sets. The frozen target was an absolute five-degree ITA change with a three-degree matching tolerance. Prompt-only, unmasked stepwise, and masked stepwise steering achieved both directions for all three calibration seeds. Post-hoc addition achieved the darker target for all three seeds but the lighter target for only one; wider endpoint probes remained non-monotonic and identity-dependent. We therefore froze post-hoc addition as a descriptive feasibility and dose-response baseline, excluding it from the primary matched contrast before confirmatory generation.

7 Confirmatory results

7.1 Completion and target response

The runner produced all 570 prespecified condition rows with 570 unique keys and the frozen configuration fingerprint. All images generated. One post-hoc condition (seed 500019, $\alpha = -1.5$) lacked a detectable edited face/skin region, leaving 569 metric-complete rows (99.8%). The failure remains in the missingness denominator. All 330 conditions in the primary matched-change methods were complete.

Figure 1 shows the mean target response. Mean seed-level Spearman correlations between α and skin-tone change were 0.95 for prompt-only, 0.93 for unmasked stepwise, 0.92 for masked stepwise, and 0.67 for post-hoc addition. The post-hoc median was 0.99 but its mean 95% interval was $[0.43, 0.88]$, confirming substantial seed dependence.

The target was reached within the three-degree tolerance unevenly (Table 2). Masked steering had the highest coverage in both directions. Among successful matches, its mean achieved changes were 5.06 ITA




Figure 1: Confirmatory dose-response curves. Points are seed means and bars are 95% seed-level bootstrap intervals. Dashed lines mark the prespecified ± 5 ITA targets; positive change denotes a darker measured appearance.

Table 2: Prespecified matched-target coverage over 30 seeds.

Method	Lighter	Darker
Prompt-only	7 (23%)	18 (60%)
Stepwise, unmasked	13 (43%)	15 (50%)
Stepwise, masked	19 (63%)	26 (87%)

lighter and 5.23 ITA darker. Low prompt-only lighter coverage constrains that stratum to six seeds shared with the masked reference.

7.2 Preservation at matched change

The primary face-similarity hypothesis was not supported. Masked-stepwise advantages relative to prompt-only were -0.0008 (95% CI $[-0.0035, 0.0016]$, $n = 6$) for lighter edits and 0.0032 ($[-0.0056, 0.0149]$, $n = 17$) for darker edits. Relative to unmasked stepwise steering, the advantages were 0.0020 ($[-0.0014, 0.0056]$, $n = 13$) and 0.0079 ($[-0.0027, 0.0184]$, $n = 14$). All Holm-adjusted p values were 1.0.

Masking nevertheless improved perceptual preservation relative to unmasked steering: the paired LPIPS advantage was 0.0235 ($[0.0128, 0.0360]$, $p_{\text{Holm}} = .012$) for lighter edits and 0.0825 ($[0.0476, 0.1302]$, $p_{\text{Holm}} = .002$) for darker edits. Against prompt-only generation, the darker-direction LPIPS advantage was 0.0812 ($[0.0379, 0.1218]$, $p_{\text{Holm}} = .028$). The corresponding darker-direction improvements were 0.0207 in background SSIM ($[0.0105, 0.0319]$, $p_{\text{Holm}} < .001$) and 1.61 in the pose-difference proxy ($[0.88, 2.36]$, $p_{\text{Holm}} = .007$). Masking also improved background SSIM by 0.0129 versus unmasked darker edits ($[0.0080, 0.0176]$, $p_{\text{Holm}} = .002$). No other secondary contrast survived Holm correction. Figure 2 shows every prespecified matched preservation contrast, including null and adverse estimates.

Figure 3 is illustrative rather than inferential. Its seed was selected by a fixed rule: maximize the number of complete matched rows, then choose the seed closest to the median base ITA, breaking ties by lower seed. The prompt-only example visibly demonstrates why matched image-colour change does not imply matched identity or composition.

8 Post-confirmatory robustness

We performed two explicitly exploratory checks after completing the frozen analysis. First, we repeated matching with one- and two-degree ITA tolerances. The LPIPS advantage retained the same positive di-




Figure 2: Masked-stepwise preservation advantage at matched ± 5 ITA change. Bars are 95% seed-level bootstrap intervals. Positive values favor masked steering after orienting every outcome so that larger is better.

Table 3: Exploratory split-half direction stability. Entries are median cosine similarity with 2.5th–97.5th percentiles over 200 disjoint resamples.

Pairs/half	Raw direction	Masked direction
8	0.42 [0.28, 0.53]	0.53 [0.38, 0.63]
16	0.59 [0.50, 0.66]	0.69 [0.60, 0.75]
32	0.75 [0.69, 0.78]	0.82 [0.77, 0.84]

rection in every estimable stratum, and face-similarity estimates remained compatible with no advantage. However, shared matched samples collapsed to $n = 1\text{--}5$ at one degree and $n = 3\text{--}12$ at two degrees; no secondary contrast survived Holm correction. Thus, the prespecified three-degree results should not be interpreted as evidence of precisely matched effects under stricter tolerances.

Second, we re-encoded all 64 training pairs and confirmed that the resulting direction was exactly equal to the recorded confirmatory tensor (maximum absolute difference zero). We then drew 200 random disjoint split-halves at each pair count. Table 3 reports cosine agreement between independently estimated directions. Stability increased with sample size, and masking improved agreement, but even two disjoint 32-pair estimates had median cosine 0.75 before masking and 0.82 after masking. The direction is therefore reproducible under the fixed 64-pair campaign but not sample-invariant.

9 Prospective independent-seed replication

A fresh 96-pair campaign passed the unchanged held-out measurement gates before outcome generation: detection was 1.000, pair ordering 0.969, the median pair gap 16.08 ITA degrees, and median/95th-percentile perturbation shifts 0.35/3.83 degrees. The new outcome run then completed all 570 frozen conditions over 30 new seeds. All images generated; one post-hoc condition (seed 600020, $\alpha = -1.5$) retained a face/skin-region measurement failure, leaving 569 metric-complete rows and every primary matched method complete.

Masked target coverage was 18/30 lighter and 27/30 darker, versus 10/30 in each direction for unmasked steering and 7/30 lighter and 22/30 darker for prompt-only. The locked masked-versus-unmasked LPIPS effects retained the parent signs and had ordinary bootstrap intervals above zero (Table 4). The formal decision was nevertheless *inconclusive coverage*: only 8 lighter and 10 darker seeds were shared between matched methods, below the prespecified minimum of 12. Even without that override, the lighter two-test




Figure 3: Deterministically selected confirmatory example (seed 500011). Each row reuses the same base image; labels report the selected alpha and achieved ITA change. Prompt-only conditioning can alter apparent identity despite reusing the diffusion seed.

Holm value of .056 missed the strict rule; the darker value was .019. We therefore report a sign-consistent, interval-positive pattern, not strict or directional replication.

The independently estimated raw directions had cosine 0.884; applying the frozen spatial mask raised cross-campaign cosine to 0.919. Their norm ratio was 1.04. Figure 4 compares effects and target coverage without pooling the two campaigns.

10 Limitations

The study evaluates one generator, scheduler, resolution, and model revision; cross-model generalization is unknown. Synthetic direction pairs can encode prompt wording, brightness, age, gender presentation, hair, or facial features alongside skin tone, and seed reuse does not preserve identity. A center Gaussian is not a semantic skin mask. The same generator creates direction and evaluation images, so model-specific artifacts may dominate. ITA is an image-colour proxy, not a complete representation of skin appearance, and its validation uses synthetic prompt pairs rather than calibrated physical colour measurements. Face-recognition systems can exhibit demographic performance differentials [2]; the embedding model, face detector, and cheek heuristic used here were not validated on real demographic groups. Matched-change coverage is incomplete and particularly low for prompt-only lighter edits, reducing paired sample sizes and precision. The post-confirmatory tolerance analysis confirms that stricter matching is too sparse for stable inference, while the split-half analysis shows that the learned direction remains sensitive to which synthetic pairs are sampled. The prospective replication independently reproduced the effect signs and direction geometry but remained formally inconclusive because shared matched coverage was only 8–10 seeds. Both campaigns use the same




Figure 4: Parent and prospective replication reported separately. (a) Locked masked-versus-unmasked LPIPS advantages with ordinary 95% bootstrap intervals. (b) Matched-target coverage; hatching marks replication bars. The formal replication decision is inconclusive because shared matched coverage fell below 12 in both directions.

Table 4: Locked independent-seed replication family. Advantage is unmasked LPIPS minus masked LPIPS; positive values favor masking. $p_{H(2)}$ is Holm adjusted across these two tests.

Direction	n	Advantage	95% CI	$p_{H(2)}$
Lighter	8	0.0238	[0.0049, 0.0415]	.0555
Darker	10	0.0409	[0.0176, 0.0655]	.0192

generator, prompt template, descriptors, and calibration grids, so this is seed-level rather than model- or construct-level independence. The closest-grid matching rule also selects on a noisy measured response; denser grids or prespecified dose-response interpolation would reduce that source of selection and residual mismatch. The pose measure is a five-landmark proxy rather than a full 3D estimator. No human study assesses perceived identity, realism, or social harms. Finally, the additive update is scheduler-dependent and has not been validated across model or library revisions. The study plan and decision scripts were frozen in author-controlled, content-hashed archives before the relevant outcome reviews, but were not deposited with an independent timestamping service. We therefore describe the design as prospectively frozen rather than externally preregistered.

11 Conclusion

In the parent campaign, masked denoising-time injection offered higher target coverage than the tested unmasked grid and improved LPIPS preservation in both directions. A prospectively specified new-seed campaign produced smaller but same-sign LPIPS advantages with intervals above zero and high cross-campaign direction cosine. Its locked decision was inconclusive because only 8–10 shared matched seeds were available, and the lighter multiplicity-adjusted test narrowly missed .05. The prespecified face-similarity hypothesis was not supported in either campaign’s broader corrected family. The result must not be described as strict replication, identity preservation, disentanglement, or bias mitigation. The principal contribution is a bounded empirical signal and an auditable protocol for separating target response, preservation, missingness, and unsupported social claims.

References

- [1] Rohit Gandikota, Joanna Materzynska, Tingrui Zhou, Antonio Torralba, and David Bau. Concept sliders: LoRA adaptors for precise control in diffusion models. In *Computer Vision – ECCV 2024*, volume 15098 of *Lecture Notes in Computer Science*, pages 172–188. Springer, 2024.
- [2] Patrick Grother, Mei Ngan, and Kayee Hanaoka. Face recognition vendor test part 3: Demographic effects. Technical Report NISTIR 8280, National Institute of Standards and Technology, 2019.
- [3] Alex Hanna, Emily Denton, Andrew Smart, and Jamila Smith-Loud. Towards a critical race methodology in algorithmic fairness. In *Proceedings of the 2020 Conference on Fairness, Accountability, and Transparency*, 2020.
- [4] Kimmo Kärkkäinen and Jungseock Joo. FairFace: Face attribute dataset for balanced race, gender, and age for bias measurement and mitigation. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 1548–1558, 2021.
- [5] Mingi Kwon, Jaeseok Jeong, and Youngjung Uh. Diffusion models already have a semantic latent space. In *International Conference on Learning Representations*, 2023.
- [6] Hang Li, Chengzhi Shen, Philip Torr, Volker Tresp, and Jindong Gu. Self-discovering interpretable diffusion latent directions for responsible text-to-image generation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 12006–12016, 2024.
- [7] Cheng Lu, Yuhao Zhou, Fan Bao, Jianfei Chen, Chongxuan Li, and Jun Zhu. DPM-Solver++: Fast solver for guided sampling of diffusion probabilistic models. *arXiv preprint arXiv:2211.01095*, 2022.
- [8] Dustin Podell, Zion English, Kyle Lacey, Andreas Blattmann, Tim Dockhorn, Jonas Müller, Joe Penna, and Robin Rombach. SDXL: Improving latent diffusion models for high-resolution image synthesis. *arXiv preprint arXiv:2307.01952*, 2023.
- [9] Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10684–10695, 2022.
- [10] Florian Schroff, Dmitry Kalenichenko, and James Philbin. FaceNet: A unified embedding for face recognition and clustering. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 815–823, 2015.
- [11] Yujun Shen, Jinjin Gu, Xiaoou Tang, and Bolei Zhou. Interpreting the latent space of GANs for semantic face editing. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9243–9252, 2020.
- [12] William Thong, Przemyslaw Joniak, and Alice Xiang. Beyond skin tone: A multidimensional measure of apparent skin color. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 4903–4913, 2023.
- [13] Zhou Wang, Alan C. Bovik, Hamid R. Sheikh, and Eero P. Simoncelli. Image quality assessment: From error visibility to structural similarity. *IEEE Transactions on Image Processing*, 13(4):600–612, 2004.
- [14] Marcus Wilkes, Caradee Y. Wright, Johan L. du Plessis, and Anthony Reeder. Fitzpatrick skin type, individual typology angle, and melanin index in an african population: Steps toward universally applicable skin photosensitivity assessments. *JAMA Dermatology*, 151(8):902–903, 2015.
- [15] Richard Zhang, Phillip Isola, Alexei A. Efros, Eli Shechtman, and Oliver Wang. The unreasonable effectiveness of deep features as a perceptual metric. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 586–595, 2018.