

timeline Package

Arne Meier
meier@thi.uni-hannover.de

10th June 2020

Abstract

The **timeline** package provides an easy interface to create and maintain timelines. Its macros utilise the **tikzenvironment** and commands from the **pgf** package. The date granularity for entries on a timebar is year and month.

1 License

This package is under the MIT License. Copyright (c) 2018 Arne Meier.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

2 Environment options

The environment **timeline** has five optional arguments:

```
1 \begin{timeline}  
2   [⟨InnerBackgroundColor⟩]  
3   [⟨InnerForegroundColor⟩]  
4   [⟨OuterBackgroundColor⟩]  
5   [⟨OuterForegroundColor⟩]  
6   [⟨ConnectorColor⟩]
```

They define the respective color for the events on the timeline. Default settings are some orange ■ with black text for the inner part and some blueish ■ with white text for the outer part. If the fifth parameter for the connector color is not specified, then the *⟨InnerBackgroundColor⟩* will be used instead. Feel free to change the colours via the parameters.

3 Commands

Inside the **timeline** environment one can use the following commands.

Add a timebar This is done via the 6-parameter command

```
1 \timebar{⟨startsymbol⟩}  
2   {⟨startXcoordinate⟩}  
3   {⟨fromYear⟩}  
4   {⟨toYear⟩}  
5   {⟨stepLength⟩}  
6   {⟨endsymbol⟩}
```

$\langle startSymbol \rangle$ can be any symbol one could put on the left side of ‘-’ at `\draw[-]` in the `tikz`-command.
 $\langle startXcoordinate \rangle$ is the x -coordinate. y is always considered to be 0.
 $\langle fromYear \rangle$ is in YYYY.
 $\langle toYear \rangle$ is in YYYY.
 $\langle stepLength \rangle$ is the length of one year on the timebar.
 $\langle endSymbol \rangle$ can be any symbol one could put on the right side of ‘-’ at `\draw[-]` in the `tikz`-command.

Add a crunched bar part. Used to literally skip some parts in the timebar where nothing happens. Drawn via the command

```
1 \zigzag{\xStartCoordinate}
```

$\langle xStartCoordinate \rangle$ is the x -coordinate where it should start. Usually, when using this command, one has to calculate the x -coordinate by hand from what was executed before. Then length of the zigzag is 0.4.

Entries. An entry has four possible commands, depending on whether it should appear above, below, shifted above, or shifted below. For the unshifted versions the following commands are used.

```
1 \entry{\year}{\what}{\who}
2 \flipentry{\year}{\what}{\who}
```

$\langle year \rangle$ is YYYY or YYYY-MM which has to exist on the timebar. Such labels are automatically created in the process of executing a `timebar`-command. More precisely, you have to execute a `timebar`-command with $\langle fromYear \rangle$ as Y_1 and $\langle toYear \rangle$ as Y_2 and then can use an `entry`/`flipentry`/`entryshift`/`flipentryshift`-command with $\langle year \rangle$ which has to be between Y_1 and Y_2 . Otherwise it will create a missing label error.

$\langle what \rangle$ is the content of the inner (near the timebar) box.

$\langle who \rangle$ is the content of the outer box.

```
1 \entryshift{\year}{\what}{\who}{\distance}
2 \flipentryshift{\year}{\what}{\who}{\distance}
```

$\langle distance \rangle$ is the length (often specified in mm) which shifts the entry to the right (in direction of the x -coordinate).

Regarding all entries, the ‘minimum height’ of a node is automatically set to

$$\max\{\text{height of } \langle who \rangle, \text{height of } \langle what \rangle\} + 1.5\text{mm}$$


that is, the maximum of the font heights of the $\langle who \rangle$ - and $\langle what \rangle$ -values plus an inner sep of 1.5 mm.

4 Example

A small example is provided to demonstrate the commands:

```
1 \begin{timeline}
2   \timebar{}{0}{1959}{1960}{.5}{}
3   \zigzag{1}
4   \entry{1959}{Branching Quantifiers}{Henkin}
5
6   \timebar{}{1.4}{1989}{1990}{.5}{}
7   \zigzag{2.4}
8   \entry{1989}{IF-logic}{Hintikka, Sandu}
9
10  \timebar{}{2.8}{1997}{2018}{.5}{stealth}
11  \entry{1997}{Compositional Semantics for IF}{Hodges}
12  \entry{2003}{IF modal logic}{Tulenheimo}
13  \entry{2007}{Dependence Logic}{Väänänen}
14  \flipentry{2008}{Modal Dependence Logic}{Väänänen}
15  \entry{2011-6}{Inclusion \& Exclusion Logic}{Galliani}
16  \entry{2012-8}{Independence Logic}{Grädel, Väänänen}
17  \flipentry{2011}{Modal Team Logic}{Müller}
18  \entry{2016}{Multiteam Semantics}{Durand et al.}
19  \flipentry{2016}{Propositional Team Logic}{Väänänen Yang}
20  \flipentryshift{2017}{Polyteam Semantics}{Hannula et al.}{3mm}
21 \end{timeline}
```

and produces the following timeline:



5 Acknowledgements

Thanks fly out to: Paul Gaborit, Anthimos Kouroutsidis.