# timeline Package

Arne Meier
meier@thi.uni-hannover.de

30th March 2018

#### Abstract

The timeline package provides an easy interface to create and maintain timelines. It provides macros utilising tikz and pgf.

#### 1 License

This package is under the MIT License. Copyright (c) 2018 Arne Meier.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

## 2 Environment options

The environment timeline has four optional arguments:

```
\begin{timeline}  \{\langle InnerBackgroundColor\rangle\} \\ \{\langle InnerForegroundColor\rangle\} \\ \{\langle OuterBackgroundColor\rangle\} \\ \{\langle OuterForegroundColor\rangle\} \\ \}
```

They define the respective color for the events on the timeline. Default settings are some orange  $\blacksquare$  with black text for the inner part and some blueish  $\blacksquare$  with white text for the outer part.

#### 3 Commands

Inside the timeline environment one can use the following commands.

Add a timebar This is done via the 6-parameter command

```
\label{eq:continuous} $$ \{ \langle startsymbol \rangle \} $$ \{ \langle startXcoordinate \rangle \} $$ \{ \langle from Year \rangle \} $$ \{ \langle to Year \rangle \} $$ \{ \langle stepLength \rangle \} $$ \{ \langle endSymbol \rangle \}$$
```

 $\langle startSymbol \rangle$  can be any symbol one could put on the left side of '-' at  $\draw[-]$  in the tikz-command.  $\langle startXcoordinate \rangle$  is the x-coordinate. y is always considered to be 0.

 $\langle \mathit{from}\, \mathit{Year} \rangle$  is in YYYY.

 $\langle to Year \rangle$  is in YYYY.

 $\langle stepLength\rangle$  is the length of one year on the time bar.

\(\langle endSymbol \rangle \) can be any symbol one could put on the right side of '-' at \draw[-] in the tikz-command.

Add a crunched bar part. Used to literally skip some parts in the timebar where nothing happens. Drawn via the command

```
\zigzar{\langle xStartCoordinate \rangle}
```

 $\langle xStartCoordinate \rangle$  is the x-coordinate where it should start. Usually, when using this command, one has to calculate the x-coordinate by hand from what was executed before.

**Entries.** An entry has four possible commands, depending on whether it should appear above, below, shifted above, or shifted below. The unshifted versions are essentially the same.

```
\entry \{\langle year \rangle\} \{\langle what \rangle\} \{\langle who \rangle\} \\ \entry \{\langle year \rangle\} \{\langle what \rangle\} \{\langle who \rangle\} \\
```

 $\langle year \rangle$  is YYYY which has to exists on the timebar. Otherwise it will create a missing label error.

 $\langle what \rangle$  the content of the inner (near the timebar) box.

 $\langle who \rangle$  the content of the outer box.

```
\entryshift{\langle year \rangle}{\langle what \rangle}{\langle who \rangle}{\langle distance \rangle} \\ \flippedentryshift{\langle year \rangle}{\langle what \rangle}{\langle who \rangle}{\langle distance \rangle}}
```

 $\langle distance \rangle$  is the length (usually in mm) which shiftes the entry to the right (in direction of the x-coordinate).

## 4 Example

A small example is provided:

```
\begin{timeline}
  \timebar{|}{0}{1959}{1960}{.5}{}
  \zigzag{1}
  \entry{1959}{Branching Quantifiers}{Henkin}
  \timebar{}{1.4}{1989}{1990}{.5}{}
  \zigzag{2.4}
  \entry{1989}{IF-logic}{Hintikka, Sandu}
  \timebar{}{2.8}{1997}{2018}{.5}{stealth'}
  \entry{1997}{Compositional Semantics for IF}{Hodges}
  \entry{2003}{IF modal logic}{Tulenheimo}
  \entry{2007}{Dependence Logic}{Väänänen}
  \flipentry{2008}{Modal Dependence Logic}{Väänänen}
  \entry{2011}{Inclusion \& Exclusion Logic}{Galliani}
  \entryshift{2012}{Independence Logic}{Grädel, Väänänen}{2mm}
  \flipentry{2011}{Modal Team Logic}{Müller}
  \entry{2016}{Multiteam Semantics}{Durand et al.}
  \flipentry{2016}{Prop. Team Logic}{Yang, Väänänen}
  \flipentryshift{2017}{Polyteam Semantics}{Hannula et al.}{2mm}
\end{timeline}
```

and produces the following timeline:

